

1. Cree un rol

```
create role logistica login password 'Logistica2026!';
```

6	logistica	false	false
---	-----------	-------	-------

2. Crear Base de Datos

```
create database bd transporte owner logistica;  
> bd_transporte 0 of 3
```

3. Otorgar permisos al usuario logística

```
create table vehiculos (  
    vehiculo_id serial primary key,  
    placa varchar(20) not null,  
    marca varchar(50),  
    modelo varchar(50),  
    capacidad_toneladas decimal  
);
```

parcial_L1.bdii.public

```
create table vehiculos (  
    vehiculo_id serial primary key,  
    placa varchar(20) not null,  
    marca varchar(50),  
    modelo varchar(50),  
    capacidad_toneladas decimal  
);  
  
insert into vehiculos (placa, marca, modelo, capacidad_toneladas) values  
(placa 'p-123abc', marca 'toyota', modelo 'hino 300', capacidad_toneladas 3.5),  
(placa 'p-456def', marca 'isuzu', modelo 'npr', capacidad_toneladas 4.0),  
(placa 'p-789ghi', marca 'freightliner', modelo 'm2', capacidad_toneladas 8.5),  
(placa 'p-321zyx', marca 'hino', modelo 'serie 500', capacidad_toneladas 10.0),  
(placa 'p-654wvu', marca 'chevrolet', modelo 'nkr', capacidad_toneladas 3.0);  
  
select * from vehiculos;
```

Output vehiculos x

vehiculo_id	placa	marca	modelo	capacidad_toneladas
1	1 p-123abc	toyota	hino 300	
2	2 p-456def	isuzu	npr	
3	3 p-789ghi	freightliner	m2	
4	4 p-321zyx	hino	serie 500	
5	5 p-654wvu	chevrolet	nkr	

```
grant select, insert on vehiculos to logistica;
```

```
select grantee, table_name, privilege_type
from information_schema.role_table_grants
where grantee = 'logistica';
```

498 ms

Output parcial_1_bdii.infor...ema.role_table_grants x

grantee	table_name	privilege_type
logistica	vehiculos	INSERT
logistica	vehiculos	SELECT

4. Retirar únicamente el permiso de insert

```
revoke insert on vehiculos from logistica;
```

grantee	table_name	privilege_type
1 logistica	vehiculos	SELECT

5. Escribir una instrucción que permita encriptar

```
create extension if not exists pgcrypto;

create table identificaciones (
    id_registro serial primary key,
    numero_identificacion bytea not null
);

insert into identificaciones (numero_identificacion)
values (pgp_sym_encrypt('1234567890101', 'clave2026'));

select * from identificaciones;
```

```
33 create table identificaciones (
34     id_registro serial primary key,
35     numero_identificacion bytea not null
36 );
37
38 insert into identificaciones (numero_identificacion)
39 values ( numero_identificacion pgp_sym_encrypt('1234567890101', 'clave2026'));
40
41 select * from identificaciones; 502 ms
```

Output identificaciones x

id_registro	numero_identificacion
1	0xc3000407030258827EA0762ED082864D23E01B4C6AD69ABC47DDA0A3...

6. Consulta que muestre permisos del role

```
select grantee, table_name, privilege_type
from information_schema.role_table_grants
where grantee = 'logistica';
```

The screenshot shows a SQL IDE interface. The top panel displays a query being executed, with line numbers 25 through 28. The query is: `select grantee, table_name, privilege_type from information_schema.role_table_grants where grantee = 'logistica';`. The execution time is 545 ms. Below the query editor, there is a toolbar with icons for lightbulb, comment, list, play, and refresh. The bottom panel shows the output of the query, titled "parcial_1_bdii.infor...ema.role_table_grants". It includes a toolbar with icons for table, chart, refresh, clock, stop, zoom in, zoom out, undo, redo, and transaction controls. The results are displayed in a table with three columns: grantee, table_name, and privilege_type. The first row shows the results for the 'logistica' role.

	grantee	table_name	privilege_type
1	logistica	vehiculos	SELECT