

P01 Pacman Game

17341015 Hongzheng Chen

September 30, 2019

Contents


1	Question 1: A* search (3 points)	2
2	Question 2: Corners Problem: Heuristic (3 points)	2
3	Question 3: Eating All The Dots (4 points)	6
4	Question 4: Minimax (5 points)	7
5	Question 5: $\alpha - \beta$ Pruning (5 points)	9

For the codes, please refer to the attached files.

1 Question 1: A* search (3 points)

```
python pacman.py -l bigMaze -z .5 -p SearchAgent -a fn=astar,heuristic=manhattanHeuristic
```

```
def aStarSearch(problem, heuristic=nullHeuristic):
    """Search the node that has the lowest combined cost and heuristic first."""
    start = problem.getStartState()
    queue = util.PriorityQueue()
    queue.push((0,start,[]),0)
    visited = []
    while not queue.isEmpty():
        cost, curr, actions = queue.pop()
        if problem.isGoalState(curr):
            break
        for succ in problem.getSuccessors(curr):
            if succ[0] in visited:
                continue
            priority = cost + succ[2] + heuristic(succ[0],problem)
            queue.push((cost+succ[2],succ[0],actions+[succ[1]]),priority)
            visited.append(succ[0])
    return actions
```



The screenshot shows a Windows command prompt window titled "C:\WINDOWS\system32\cmd.exe". The user has executed the command: `(python27) D:\Assignments\ArtificialIntelligence\P01_Pacman\search>python pacman.py -l bigMaze -z .5 -p SearchAgent -a fn=astar,heuristic=manhattanHeuristic --frameTime 0`. The output shows the SearchAgent using the A* search function and the Manhattan heuristic to solve the bigMaze problem. It reports a path found with a total cost of 210 in 0.1 seconds, 550 search nodes expanded, and a score of 300. The window also displays statistics: Average Score: 300.0, Scores: 300.0, Win Rate: 1/1 (1.00), and Record: Win.

```
C:\WINDOWS\system32\cmd.exe
(python27) D:\Assignments\ArtificialIntelligence\P01_Pacman\search>python pacman.py -l bigMaze -z .5 -p SearchAgent -a fn=astar,heuristic=manhattanHeuristic --frameTime 0
[SearchAgent] using function astar and heuristic manhattanHeuristic
[SearchAgent] using problem type PositionSearchProblem
Path found with total cost of 210 in 0.1 seconds
Search nodes expanded: 550
Pacman emerges victorious! Score: 300
Average Score: 300.0
Scores:      300.0
Win Rate:    1/1 (1.00)
Record:      Win
(python27) D:\Assignments\ArtificialIntelligence\P01_Pacman\search>
```

2 Question 2: Corners Problem: Heuristic (3 points)

```
python pacman.py -l mediumCorners -p SearchAgent -a fn=aStarSearch,prob=CornersProblem,heuristic
```

We represent the state as below

pacmanx, pacmany, 0, 0, 0, 0

where the last four numbers indicating whether there is food in the corner. And the goal state is

*, *, 1, 1, 1, 1

We design a heuristic that calculates the total Manhattan distance from the current position of the pacman to each unvisited corner. This is obviously admissible and consistent, since every time the pacman reach to a corner, the total distance can be reduced, and the heuristic value of the goal state is 0.

```
class CornersProblem(search.SearchProblem):

    def __init__(self, startingGameState):
        """
        Stores the walls, pacman's starting position and corners.
        """
        self.walls = startingGameState.getWalls()
        self.startingPosition = startingGameState.getPacmanPosition()
        top, right = self.walls.height-2, self.walls.width-2
        self.corners = ((1,1), (1,top), (right, 1), (right, top))
        for corner in self.corners:
            if not startingGameState.hasFood(*corner):
                print 'Warning: no food in corner ' + str(corner)
        self._expanded = 0 # DO NOT CHANGE; Number of search nodes expanded
        # Please add any code here which you would like to use
        # in initializing the problem
        visited = [0,0,0,0]
        for (i,corner) in enumerate(self.corners):
            if self.startingPosition == corner:
                visited[i] = 1
        self.startState = (self.startingPosition,visited)

    def getStartState(self):
        """
        Returns the start state (in your state space, not the full Pacman state
        space)
        """
        return self.startState

    def isGoalState(self, state):
```

```

"""
Returns whether this search state is a goal state of the problem.
"""

if state[1] == [1,1,1,1]:
    return True
return False

def getSuccessors(self, state):
    """
    Returns successor states, the actions they require, and a cost of 1.

    As noted in search.py:
        For a given state, this should return a list of triples, (successor,
        action, stepCost), where 'successor' is a successor to the current
        state, 'action' is the action required to get there, and 'stepCost'
        is the incremental cost of expanding to that successor
    """

    successors = []
    for action in [Directions.NORTH, Directions.SOUTH, Directions.EAST, Directions.WEST
        ↪ ]:
        # Add a successor state to the successor list if the action is legal
        # Here's a code snippet for figuring out whether a new position hits a wall:
        #   x,y = currentPosition
        #   dx, dy = Actions.directionToVector(action)
        #   nextx, nexty = int(x + dx), int(y + dy)
        #   hitsWall = self.walls[nextx][nexty]

        x, y = state[0]
        dx, dy = Actions.directionToVector(action)
        nextx, nexty = int(x + dx), int(y + dy)
        if not self.walls[nextx][nexty]:
            nextCorner = [item for item in state[1]]
            if (nextx,nexty) in self.corners:
                i = self.corners.index((nextx,nexty))
                nextCorner[i] = 1
            nextState = ((nextx,nexty),nextCorner)
            successors.append((nextState,action,1))

```

```

self._expanded += 1 # DO NOT CHANGE
return successors

def getCostOfActions(self, actions):
    """
    Returns the cost of a particular sequence of actions. If those actions
    include an illegal move, return 999999. This is implemented for you.
    """
    if actions == None: return 999999
    x,y= self.startingPosition
    for action in actions:
        dx, dy = Actions.directionToVector(action)
        x, y = int(x + dx), int(y + dy)
        if self.walls[x][y]: return 999999
    return len(actions)

def cornersHeuristic(state, problem):

    corners = problem.corners # These are the corner coordinates
    walls = problem.walls # These are the walls of the maze, as a Grid (game.py)

    pos = state[0]
    cornerFlag = state[1]
    res = 0
    for i,corner in enumerate(corners):
        if not cornerFlag[i]:
            res += abs(pos[0] - corner[0]) + abs(pos[1] - corner[1])
    return res

```

We can see that the heuristic is admissible and consistent that it can find the optimal solution the same as what UCS found.

```
C:\WINDOWS\system32\cmd.exe
(python27) D:\Assignments\ArtificialIntelligence\P01_Pacman\search>python pacman.py -l mediumCorners -p SearchAgent -a fn=  
=ucs,prob=CornersProblem,heuristic=cornersHeuristic -z .5 --frameTime 0
[SearchAgent] using function ucs
[SearchAgent] using problem type CornersProblem
Path found with total cost of 106 in 0.2 seconds
Search nodes expanded: 1967
Pacman emerges victorious! Score: 434
Average Score: 434.0
Scores: 434.0
Win Rate: 1/1 (1.00)
Record: Win

(python27) D:\Assignments\ArtificialIntelligence\P01_Pacman\search>python pacman.py -l mediumCorners -p SearchAgent -a fn=  
=aStarSearch,prob=CornersProblem,heuristic=cornersHeuristic -z .5 --frameTime 0
[SearchAgent] using function aStarSearch and heuristic cornersHeuristic
[SearchAgent] using problem type CornersProblem
Path found with total cost of 106 in 0.0 seconds
Search nodes expanded: 503
Pacman emerges victorious! Score: 434
Average Score: 434.0
Scores: 434.0
Win Rate: 1/1 (1.00)
Record: Win

(python27) D:\Assignments\ArtificialIntelligence\P01_Pacman\search>
```

3 Question 3: Eating All The Dots (4 points)

```
python pacman.py -l testSearch -p SearchAgent -a fn=astar,prob=FoodSearchProblem,heuristic=foodHeuristic
```

We design a heuristic that calculates the total Manhattan distance from the current position of the pacman to each food (similar to Question 2, which is indeed a very efficient heuristic). This is also obviously admissible and consistent, since every time the pacman get to one food, the total distance can be reduced, and the heuristic value of the goal state is 0.

```
def foodHeuristic(state, problem):

    position, foodGrid = state
    foodLst = foodGrid.asList()
    # print(position) # (10, 3)
    # print(foodLst) # [(1, 1), (1, 4), (1, 5), (2, 1), (3, 1), (4, 1), (4, 4), (5, 1), (7,
    ↪ 4), (10, 4), (13, 4), (13, 5), (14, 5)]

    sumup = 0
    for food in foodLst:
        sumup += abs(position[0] - food[0]) + abs(position[1] - food[1])
    return sumup
```

We can see that the heuristic is admissible and consistent that it can find the optimal solution the same as what UCS found.

```
C:\WINDOWS\system32\cmd.exe
(python27) D:\Assignments\ArtificialIntelligence\P01_Pacman\search>python pacman.py -l trickySearch -p SearchAgent -a fn=
ucs,prob=FoodSearchProblem,heuristic=foodHeuristic -z .5 --frameTime 0
[SearchAgent] using function ucs
[SearchAgent] using problem type FoodSearchProblem
Path found with total cost of 60 in 22.2 seconds
Search nodes expanded: 16689
Pacman emerges victorious! Score: 570
Average Score: 570.0
Scores: 570.0
Win Rate: 1/1 (1.00)
Record: Win

(python27) D:\Assignments\ArtificialIntelligence\P01_Pacman\search>python pacman.py -l trickySearch -p SearchAgent -a fn=
astar,prob=FoodSearchProblem,heuristic=foodHeuristic -z .5 --frameTime 0
[SearchAgent] using function astar and heuristic foodHeuristic
[SearchAgent] using problem type FoodSearchProblem
Path found with total cost of 60 in 2.8 seconds
Search nodes expanded: 5403
Pacman emerges victorious! Score: 570
Average Score: 570.0
Scores: 570.0
Win Rate: 1/1 (1.00)
Record: Win

(python27) D:\Assignments\ArtificialIntelligence\P01_Pacman\search>
```

4 Question 4: Minimax (5 points)

```
python autograder.py -q q2 --no-graphics
```

```
class MinimaxAgent(MultiAgentSearchAgent):

    def DFMinimax(self, depth, gameState, currAgent):
        actions = gameState.getLegalActions(currAgent)
        if depth > self.depth or len(actions) == 0:
            return (self.evaluationFunction(gameState), Directions.STOP)
        if currAgent == 0: # MAX node
            maxVal = []
            for action in actions:
                state = gameState.generateSuccessor(currAgent, action)
                maxVal.append((self.DFMinimax(depth, state, 1) [0], action))
            return max(maxVal)
        else: # MIN node
            minVal = []
            for action in actions:
                state = gameState.generateSuccessor(currAgent, action)
                if currAgent == gameState.getNumAgents() - 1:
                    minVal.append((self.DFMinimax(depth+1, state, 0) [0], action))
                else: # one by one action
                    minVal.append((self.DFMinimax(depth, state, currAgent+1) [0], action))
            return min(minVal)
```

```
def getAction(self, gameState):
    _, action = self.DFMinimax(1,gameState,0)
    return action
```

The figure below shows my agent passes all the tests.

```
C:\WINDOWS\system32\cmd.exe
(python27) D:\Assignments\ArtificialIntelligence\P01_Pacman\multiagent>python autograder.py -q q2 --no-graphics
Starting on 9-30 at 14:42:06

Question q2
=====

*** PASS: test_cases\q2\0-lecture-6-tree.test
*** PASS: test_cases\q2\0-small-tree.test
*** PASS: test_cases\q2\1-1-minmax.test
*** PASS: test_cases\q2\1-2-minmax.test
*** PASS: test_cases\q2\1-3-minmax.test
*** PASS: test_cases\q2\1-4-minmax.test
*** PASS: test_cases\q2\1-5-minmax.test
*** PASS: test_cases\q2\1-6-minmax.test
*** PASS: test_cases\q2\1-7-minmax.test
*** PASS: test_cases\q2\1-8-minmax.test
*** PASS: test_cases\q2\2-1a-vary-depth.test
*** PASS: test_cases\q2\2-1b-vary-depth.test
*** PASS: test_cases\q2\2-2a-vary-depth.test
*** PASS: test_cases\q2\2-2b-vary-depth.test
*** PASS: test_cases\q2\2-3a-vary-depth.test
*** PASS: test_cases\q2\2-3b-vary-depth.test
*** PASS: test_cases\q2\2-4a-vary-depth.test
*** PASS: test_cases\q2\2-4b-vary-depth.test
*** PASS: test_cases\q2\2-one-ghost-3level.test
*** PASS: test_cases\q2\3-one-ghost-4level.test
*** PASS: test_cases\q2\4-two-ghosts-3level.test
*** PASS: test_cases\q2\5-two-ghosts-4level.test
*** PASS: test_cases\q2\6-tied-root.test
*** PASS: test_cases\q2\7-1a-check-depth-one-ghost.test
*** PASS: test_cases\q2\7-1b-check-depth-one-ghost.test
*** PASS: test_cases\q2\7-1c-check-depth-one-ghost.test
*** PASS: test_cases\q2\7-2a-check-depth-two-ghosts.test
*** PASS: test_cases\q2\7-2b-check-depth-two-ghosts.test
*** PASS: test_cases\q2\7-2c-check-depth-two-ghosts.test
*** Running MinimaxAgent on smallClassic 1 time(s).
Pacman died! Score: 84
Average Score: 84.0
Scores:      84.0
Win Rate:    0/1 (0.00)
Record:      Loss
*** Finished running MinimaxAgent on smallClassic after 1 seconds.
*** Won 0 out of 1 games. Average score: 84.000000 ***
*** PASS: test_cases\q2\8-pacman-game.test

### Question q2: 5/5 ###

Finished at 14:42:07

Provisional grades
=====
Question q2: 5/5
-----
Total: 5/5

Your grades are NOT yet registered. To register your grades, make sure
to follow your instructor's guidelines to receive credit on your project.

(python27) D:\Assignments\ArtificialIntelligence\P01_Pacman\multiagent>
```


5 Question 5: $\alpha - \beta$ Pruning (5 points)

python autograder.py -q q3 --no-graphics

```
class AlphaBetaAgent(MultiAgentSearchAgent):

    def DFMinimax(self, depth, gameState, currAgent, alpha, beta):
        actions = gameState.getLegalActions(currAgent)
        if depth > self.depth or len(actions) == 0:
            return (self.evaluationFunction(gameState), Directions.STOP)
        if currAgent == 0: # MAX node
            val = (-0x3f3f3f3f, Directions.STOP)
            for action in actions:
                state = gameState.generateSuccessor(currAgent, action)
                val = max(val, (self.DFMinimax(depth, state, 1, alpha, beta)[0], action))
                if val[0] > beta:
                    return val
                alpha = max(alpha, val[0])
            return val
        else: # MIN node
            val = (0x3f3f3f3f, Directions.STOP)
            for action in actions:
                state = gameState.generateSuccessor(currAgent, action)
                if currAgent == gameState.getNumAgents() - 1:
                    val = min(val, (self.DFMinimax(depth+1, state, 0, alpha, beta)[0], action))
                else: # one by one action
                    val = min(val, (self.DFMinimax(depth, state, currAgent+1, alpha, beta)[0],
                                     ↪ action))
                if val[0] < alpha:
                    return val
                beta = min(beta, val[0])
            return val

    def getAction(self, gameState):
        _, action = self.DFMinimax(1, gameState, 0, -0x3f3f3f3f, 0x3f3f3f3f)
        return action
```

The figure below shows my agent passes all the tests.

```
C:\WINDOWS\system32\cmd.exe
(python27) D:\Assignments\ArtificialIntelligence\P01_Pacman\multiagent>python autograder.py -q q3 --no-graphics
Starting on 9-30 at 14:44:30

Question q3
=====

*** PASS: test_cases\q3\0-lecture-6-tree.test
*** PASS: test_cases\q3\0-small-tree.test
*** PASS: test_cases\q3\1-1-minmax.test
*** PASS: test_cases\q3\1-2-minmax.test
*** PASS: test_cases\q3\1-3-minmax.test
*** PASS: test_cases\q3\1-4-minmax.test
*** PASS: test_cases\q3\1-5-minmax.test
*** PASS: test_cases\q3\1-6-minmax.test
*** PASS: test_cases\q3\1-7-minmax.test
*** PASS: test_cases\q3\1-8-minmax.test
*** PASS: test_cases\q3\2-1a-vary-depth.test
*** PASS: test_cases\q3\2-1b-vary-depth.test
*** PASS: test_cases\q3\2-2a-vary-depth.test
*** PASS: test_cases\q3\2-2b-vary-depth.test
*** PASS: test_cases\q3\2-3a-vary-depth.test
*** PASS: test_cases\q3\2-3b-vary-depth.test
*** PASS: test_cases\q3\2-4a-vary-depth.test
*** PASS: test_cases\q3\2-4b-vary-depth.test
*** PASS: test_cases\q3\2-one-ghost-3level.test
*** PASS: test_cases\q3\3-one-ghost-4level.test
*** PASS: test_cases\q3\4-two-ghosts-3level.test
*** PASS: test_cases\q3\5-two-ghosts-4level.test
*** PASS: test_cases\q3\6-tied-root.test
*** PASS: test_cases\q3\7-1a-check-depth-one-ghost.test
*** PASS: test_cases\q3\7-1b-check-depth-one-ghost.test
*** PASS: test_cases\q3\7-1c-check-depth-one-ghost.test
*** PASS: test_cases\q3\7-2a-check-depth-two-ghosts.test
*** PASS: test_cases\q3\7-2b-check-depth-two-ghosts.test
*** PASS: test_cases\q3\7-2c-check-depth-two-ghosts.test
*** Running AlphaBetaAgent on smallClassic 1 time(s).
Pacman died! Score: 84
Average Score: 84.0
Scores:      84.0
Win Rate:    0/1 (0.00)
Record:      Loss
*** Finished running AlphaBetaAgent on smallClassic after 1 seconds.
*** Won 0 out of 1 games. Average score: 84.000000 ***
*** PASS: test_cases\q3\8-pacman-game.test

### Question q3: 5/5 ###

Finished at 14:44:32

Provisional grades
=====
Question q3: 5/5
-----
Total: 5/5

Your grades are NOT yet registered. To register your grades, make sure
to follow your instructor's guidelines to receive credit on your project.

(python27) D:\Assignments\ArtificialIntelligence\P01_Pacman\multiagent>
```