

PIZZA HUTS

● WHERE EVERY SLICE TELLS A STORY

[Home](#)

[About](#)

[Contact](#)





ABOUT ME

Contact



I am Dibyajyoti Pradhan, an aspiring Data Analyst with a strong interest in data analysis, business insights, and data-driven decision-making.

- Skilled in SQL, Advanced Excel, Python (Pandas), and Power BI
- Experienced in data cleaning, data analysis, reporting, and visualization
- Strong understanding of SQL queries, joins, aggregations, subqueries, CTEs, and window functions
- Interested in transforming raw business data into meaningful insights and actionable recommendations
- In this project, I analyzed Pizza Hut sales data using SQL to understand sales performance, customer preferences, product demand, and revenue trends



PROJECT OVERVIEW

[Home](#)[About](#)[Contact](#)

Analyzed Pizza Hut sales data using SQL to evaluate revenue, order trends, product performance, and customer preferences.

The project focuses on identifying top-selling pizzas, popular sizes, category performance, order volume, and revenue trends to generate actionable business insights.





RETRIEVE THE TOTAL NUMBER OF ORDERS PLACED

[Home](#)[About](#)[Contact](#)

```
SELECT
```

```
    COUNT(order_id) AS total_orders
```

```
FROM
```

```
orders;
```

Result Grid



	total_orders
	21350



CALCULATE THE TOTAL REVENUE GENERATED FROM PIZZA SALES

[Home](#)[About](#)[Contact](#)

```
SELECT
```

```
    ROUND(SUM(order_details.quantity * pizzas.price),  
           2) AS total_sales
```

```
FROM
```

```
    order_details
```

```
    JOIN
```

```
    pizzas ON pizzas.pizza_id = order_details.pizza_id
```

Result Grid



	total_sales
▶	817860.05



IDENTIFY THE HIGHEST-PRICED PIZZA

[Home](#)[About](#)[Contact](#)

```
SELECT
    pizza_types.name, pizzas.price
FROM
    pizza_types
    JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
ORDER BY pizzas.price DESC
LIMIT 1;
```

Result Grid			Filter Rows:
	name	price	
▶	The Greek Pizza	35.95	



IDENTIFY THE MOST COMMON PIZZA SIZE ORDERED

[Home](#)[About](#)[Contact](#)

```
SELECT
    pizzas.size,
    COUNT(order_details.order_details_id) AS order_count
FROM
    pizzas
    JOIN
    order_details ON pizzas.pizza_id = order_details.pizza_id
GROUP BY pizzas.size
ORDER BY order_count DESC;
```

Result Grid			Filter
	size	order_count	
▶	L	18526	
	M	15385	
	S	14137	
	XL	544	
	XXL	28	



LIST THE TOP 5 MOST ORDERED PIZZA TYPES ALONG WITH THEIR QUANTITIES

[Home](#)[About](#)[Contact](#)

```
SELECT
    pizza_types.name, SUM(order_details.quantity) AS quantity
FROM
    pizza_types
    JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
    JOIN
    order_details ON pizzas.pizza_id = order_details.pizza_id
GROUP BY pizza_types.name
ORDER BY quantity DESC
LIMIT 5;
```

Result Grid			Filter Rows:
	name	quantity	
▶	The Classic Deluxe Pizza	2453	
	The Barbecue Chicken Pizza	2432	
	The Hawaiian Pizza	2422	
	The Pepperoni Pizza	2418	
	The Thai Chicken Pizza	2371	



JOIN THE
NECESSARY TABLES
TO FIND THE TOTAL
QUANTITY OF EACH
PIZZA CATEGORY
ORDERED.

[Home](#)[About](#)[Contact](#)

```
SELECT
    pizza_types.category,
    SUM(order_details.quantity) AS quantity
FROM
    pizza_types
    JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
    JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.category
ORDER BY quantity DESC;
```

Result Grid			Filter Rows
	category	quantity	
▶	Classic	14888	
	Supreme	11987	
	Veggie	11649	
	Chicken	11050	



DETERMINE THE DISTRIBUTION OF ORDERS BY HOUR OF THE DAY

[Home](#)[About](#)[Contact](#)

```
SELECT  
    HOUR(order_time) AS hour, COUNT(order_id) AS order_count  
FROM  
    orders  
GROUP BY HOUR(order_time);
```

Result Grid			Filter
	hour	order_count	
	11	1231	
	12	2520	
	13	2455	
	14	1472	
	15	1468	



JOIN RELEVANT TABLES TO FIND THE CATEGORY-WISE DISTRIBUTION OF PIZZAS

[Home](#)[About](#)[Contact](#)

```
SELECT  
    category, COUNT(name)  
FROM  
    pizza_types  
GROUP BY category;
```

Result Grid			Filter Rows
	category	count(name)	
▶	Chicken	6	
	Classic	8	
	Supreme	9	
	Veggie	9	



GROUP THE ORDERS BY DATE AND CALCULATE THE AVERAGE NUMBER OF PIZZAS ORDERED PER DAY

[Home](#)[About](#)[Contact](#)

```
SELECT  
    round(avg(quantity),0) as avg_pizza_order  
FROM  
    (SELECT  
        orders.order_date, SUM(order_details.quantity) AS quantity  
    FROM  
        orders  
    JOIN order_details ON orders.order_id = order_details.order_id  
    GROUP BY orders.order_date) AS order_quantity;
```

Result Grid	
	avg_pizza_order
▶	138



DETERMINE THE TOP 3 MOST ORDERED PIZZA TYPES BASED ON REVENUE.

[Home](#)[About](#)[Contact](#)

```
select pizza_types.name,  
sum(order_details.quantity* pizzas.price) as revenue  
from pizza_types join pizzas  
on pizza_types.pizza_type_id = pizzas.pizza_type_id  
join order_details  
on order_details.pizza_id = pizzas.pizza_id  
group by pizza_types.name order by revenue desc limit 3;
```

Result Grid			Filter Rows:
	name	revenue	
▶	The Thai Chicken Pizza	43434.25	
	The Barbecue Chicken Pizza	42768	
	The California Chicken Pizza	41409.5	



CALCULATE THE PERCENTAGE CONTRIBUTION OF EACH PIZZA TYPE TO TOTAL REVENUE



```
select pizza_types.category,  
round((sum(order_details.quantity* pizzas.price) /(SELECT  
ROUND(SUM(order_details.quantity * pizzas.price),  
2) AS total_sales  
FROM  
order_details  
JOIN  
pizzas ON pizzas.pizza_id = order_details.pizza_id))*100,0) as revenue  
from pizza_types join pizzas  
on pizza_types.pizza_type_id = pizzas.pizza_type_id  
join order_details  
on order_details.pizza_id = pizzas.pizza_id  
group by pizza_types.category order by revenue desc;
```

Result Grid			Filter
	category	revenue	
▶	Classic	27	
	Supreme	25	
	Veggie	24	
	Chicken	24	

[Home](#)[About](#)[Contact](#)

ANALYZE THE CUMULATIVE REVENUE GENERATED OVER TIME

```
select order_date, sum(revenue) over(order by order_date) as cumulative_revenue from  
(select orders.order_date,  
sum(order_details.quantity* pizzas.price) as revenue  
from order_details join pizzas  
on order_details.pizza_id = pizzas.pizza_id  
join orders  
on orders.order_id = order_details.order_id  
group by orders.order_date) as sales;
```

Result Grid   Filter Rows:		
	order_date	cumulative_revenue
▶	2015-01-01	2713.8500000000004
	2015-01-02	5445.75
	2015-01-03	8108.15
	2015-01-04	9863.6
	2015-01-05	11929.55





About

Contact

THANK YOU

FOR ATTENTION

● PIZZA HUTS SALES REPORTS