The state of the s	School:	Campus:	
	Academic Year: Subject Name:	Subject Code:	
Centurion UNIVERSITY Shaping Lives Empowering Communities	Semester: Program:	Branch: Specialization:	
	Date:		
	Applied and Action Learning		

(Learning by Doing and Discovery)

Name of the Experiement: Read the Chain - Web3. is Basics

* Coding Phase: Pseudo Code / Flow Chart / Algorithm

ALGORITHM:

- 1. Start
- 2. Open remix IDE write the smart contract in SimpleStorage.sol
- 3. Compile the smart contract in remix
- 4. Copy the generated abi and save it somewhere
- 5. Deploy the contract in sepolia testnet using metamask
- 6.Copy the deployed contract address
- 7. Create a react frontend project using create react app
- 8.Add the contract address and network information in .env file
- 9.Install web3.js
- 10.Use the ABI and contract address to connect the frontend with smart contract
- 11.End

* Software used

- 1.Metamask wallet
- 2.Remix IDE
- 3.Brave Browser

* Testing Phase: Compilation of Code (error detection)

Smart contract solidity code

```
//SPDX-License-Identifier: MIT
pragma solidity ^0.8.0;
contract SimpleStorage {
    uint public storedData;

    constructor(uint _data) {
        storedData = _data;
    }
    function set(uint x) public {
        storedData = x;
    }
    function get() public view returns (uint) {
        return storedData;
    }
}
```

ABI key

```
xport const simpleStorageABI
       "inputs": [
                "internalType": "uint256",
                "name": "_data",
                "type": "uint256"
       "stateMutability": "nonpayable",
       "type": "constructor"
       "inputs": [],
"name": "get",
        "outputs": [
                "internalType": "uint256",
                "name": "",
                "type": "uint256"
       ],
"stateMutability": "view",
       "type": "function"
       "inputs": [
                "internalType": "uint256",
                "name": "x",
"type": "uint256"
       "name": "set",
       "outputs": [],
       "stateMutability": "nonpayable",
```

* Implementation Phase: Final Output (no error)

After compilation deploy the smart contract in sepolia test network using metamask 🌉 MetaMask **DEPLOY & RUN** > 🗆 **TRANSACTIONS** Account 1 ① ः ENVIRONMENT # Sepolia Injected Provider - MetaMask **Deploy a contract** Sepolia (11155111) network ACCOUNT 🛨 🗹 🕒 This site wants you to deploy a contract 0x5b3...5c960 (0.4295216765... No + Create Smart Account Estimated changes ? changes Estimated Gas 3000000 Custom Request from ② remix.ethereum.org 0 Wei Network fee ? / 0.0003 S SepoliaETH CONTRACT Speed Market ~12 sec SimpleStorage - SimpleStorage.sol \$ evm version: prague 123 Deploy Publish to IPFS Cancel Confirm Type the library name to see available commands. creation of SimpleStorage pending... [block:8976963 txIndex:31] from: 0x5b3...5c960 to: SimpleStorage.(constructor) value: 0 wei data: 0x608...0007b logs: 0 hash: 0xae9...09e10 Debug In this smart contract we have two accessible libraries one is web3.js and another is ethers.js, here we used ethers.js.


* Implementation Phase: Final Output (no error)

Now we have to work on our frontend first create a folder for your frontend then open terminal and install react modules needed for the project. Now create Abi.js file in the src folder where we have to store the abi for our smart contract and now create a .env file and store the contract address and network information.

```
UX
frontend > ‡ .env
                       REACT APP CONTRACT ADDRESS=0xf00A07027fF338c8e8fdb29f094B5Ff8Fc0e6831
                       REACT_APP_NETWORK=sepolia
  Jord To Appjs > @O default
import React, { useEffect, useState } from 'react';
import Neb3 from 'web3';
import { simpleStorageABI } from './abi';
import { To astContainer, toast } from 'react-toastify';
import { To astContainer, toast } from 'react-toastify';
import { react-toastify/dist/ReactToastify.css';
import { FaSpinner } from 'react-icons/fa';
                                                                                                                                                       setWalletAddress(null);
                                                                                                                                                       setStoredValue(null):
  const contractAddress = process.env.REACT APP CONTRACT ADDRESS;
                                                                                                                                                       toast.info("Wallet disconnected.");
  function App() {
  const [walletAddress, setWalletAddress] = useState(null);
  const [web3, setWeb3] = useState(null);
  const [contract, setContract] = useState(null);
  const [contract, setContract] = useState(null);
}
                                                                                                                                                    const fetchStoredValue = async (contractRef = contract) => {
                                                                                                                                                       try {
   if (contractRef) {
     const value = await contractRef.methods.get().call();
     constvalue(value.toString());
     const [storedValue, setStoredValue] = useState(null);
const [inputValue, setInputValue] = useState('');
const [loading, setLoading] = useState(false);
     const connectWallet = async () => {
  if (window.ethereum) {
            const web3Instance = new Meb3(window.ethereum);
await window.ethereum.request({ method: 'eth_requestAccounts' });
const accounts = await web3Instance.eth.getAccounts();
                                                                                                                                                          console.error(err);
             const contractInstance = new web3Instance.eth.Contract(simpleStorageABI, contractAddress);
                                                                                                                                                    const handleSet = async () => {
  if (contract && inputValue && web3 && walletAddress) {
            setWalletAddress(accounts[0]);
setWeb3(web3Instance);
setContract(contractInstance);
                                                                                                                                                             toast.info("Transaction submitted...");
await contract.methods.set(inputValue).send({ from: walletAddress });
             toast.success("Wallet connected!");
fetchStoredValue(contractInstance);
                                                                                                                                                             setInputValue('');
toast.success("Value updated successfully!");
          } catch (err) {
  toast.error("Connection failed.");
  console.error(err);
                                                                                                                                                              fetchStoredValue();
                                                                                                                                                          } catch (err) {
  toast.error("Transaction failed.");
           } finally {
  setLoading(false);
                                                                                                                                                           cbutton onClick={disconnectWallet} style={{ ...buttonStyle, backgroundColor: '=#ff5555', marginBottom: '20px' }}
     return (
| <div style={{
| padding: '30px',
                                                                                                                                                           <strong>Stored Value:</strong> <span style={{ color: '=#50fa7b' }}>{storedValue}</span>
          postang, Joph
fontFamily: 'Segoe UI, sans-serif',
background: 'linear-gradient(to right, □#0f2027, □#203a43, □#2c5364)',
                                                                                                                                                          <div style={{ marginTop: '10px' }}>
<input</pre>
                                                                                                                                                              type="number"
placeholder="Enter new value"
           minHeight: '100vh
                                                                                                                                                               value={inputValue}
                                                                                                                                                               onChange={(e) => setInputValue(e.target.value)}
          <ToastContainer />
             margin: 'auto',
background: '□#1e2a38',
              padding: '30px',
borderRadius: '15px',
                                                                                                                                                               style={{ ...buttonStyle, marginLeft: '10px' }}
              boxShadow: '0 10px 20px □rgba(0,0,0,0.3)'
                                                                                                                                                               {loading ? <FaSpinner className="spin" /> : 'Update'}
                 textAlign: 'center',
             marginBottom: '20px',
color: '■#61dafb'
}}>∰ Simple Storage DApp</h1>
                                                                                                                                                            style={{ ...buttonStyle, backgroundColor: '\| #6272a4', marginTop: '20px' }}
              {!walletAddress ? (
                                                                                                                                                             Retrieve Latest Data
                                                                                                                                                           </button>
                    style={buttonStyle}>
                    Connect MetaMask Wallet
```


* Implementation Phase: Final Output (no error)


Now open terminal and run the project by writting the code npm start






Connecting the wallet with the DApp





Now your wallet is successfully connected with your DApp



* Observations

- 1.The lab demonstrates how to integrate a blockchain smart contract with a frontend application using Web3.js, enabling real-time interaction between users and the blockchain.
- 2.It highlights connecting wallets, reading/writing contract data, and handling blockchain events from the UI.

ASSESSMENT

Rubrics	Full Mark	Marks Obtained	Remarks
Concept	10		
Planning and Execution/	10		
Practical Simulation/ Programming			
Result and Interpretation	10		
Record of Applied and Action Learning	10		
Viva	10		
Total	50		

Signature of the Student:

Name:

Regn. No.:

Page No.....