1. Create Table EMP1.

Querry :- CREATE TABLE EMP1 (
ID NUMBER(2)
Name VARCHAR(10)
Basic NUMBER(6,2)
Designation VARCHAR2(10)
Age NUMBER(2)
);

Output :-

Name	NULL?	TYPE
ID		NUMBER(2)
NAME		VARCHAR(10)
BASIC		NUMBER(6,2)
DESIGNATION		VARCHAR2(10)
AGIE		NUMBER(2)

2. Change Basic from float to integer.

ALTER TABLE EMP1
MODIFY Basic NUMBER(6);

output

Name	Null?	Type
ID		NUMBER(2)
NAME		VARCHAR2(10)
BASIC		NUMBER(6)
DESIGNATION		VARCHAR2(10)
AGIE		NUMBER(2)

3. Change Name Size from 10 to 15

Querry :- ALTER TABLE EMP1
MODIFY Name VARCHAR2(15);

output : Table altered.

check:

DESC EMP1;

OUTPUT:

Name	Null	Type
ID		NUMBER(2)
NAME		VARCHAR2(15)
BASIC		NUMBER(6)
DESIGNATION		VARCHAR2(10)
AGE		NUMBER(2)

4. Creat EMP_trainee with same changed structure.

Query:
```
CREATE TABLE EMP_trainee(
  ID NUMBER(2),
  Name VARCHAR2(15),
  Basic NUMBER(6),
  Designation VARCHAR2(10)
  Age NUMBER(2)
);
```

Table Created.

Now rename ID to Emp_id.

```
ALTER TABLE EMP_trainee
 RENAME COLUMN ID TO EMP_id;
```

OUTPUT:

Name	Null?	Type
EMP_ID		NUMBER(2)
NAME		VARCHAR2(15)
BASIC		NUMBER(6)
DESIGNATION		VARCHAR2(10)
AGE		NUMBER(2)

5. Insert given data into EMP1

Query:
```
INSERT INTO EMP1
  VALUES(1, 'Rohit', 6700, 'Manager', 24);
INSERT INTO EMP1
  VALUES(2, 'Sunit', 6200, 'Engineer', 27);
INSERT INTO EMP1
  VALUES(3, 'Payal', 6300, 'Engineer', 25);
INSERT INTO EMP1
  VALUES(4, 'Kunal', 6700, 'Trainee', 28);
INSERT INTO EMP1
  VALUES(5, 'Sunita', 6230, 'Trainee', 26);
```

```
INSERT INTO EMP1
  VALUES(6, 'Bimal', 7000, 'Trainee', 25);
COMMIT;
```

Output :- 1 row Created.
1 row Created.
1 row Created.
1 row Created.
1 row Created.
1 row Created.

Display the records :

```
SELECT * FROM EMP1;
```

OUTPUT :

ID	NAME	BASIC	DESIGNATION	AGE
1	Rohit	6700	Manager	24
2	Sunil	6200	Engineer	27
3	Payal	6300	Engineer	25
4	Kunal	6700	Trainee	28
5	Sunita	6230	Trainee	26
6	Bimal	7000	Trainee	25

6. Insert all Trainee row into EMP_Trainee

Query:

```
INSERT INTO EMP_trainee
SELECT ID, Name, Basic, Designation, Age
FROM EMP1
WHERE LOWER(Designation)= 'trainee';
```

OUTPUT: 3 rows created.

Display table :

```
SELECT * FROM EMP_trainee;
```

OUTPUT :

EMP_ID	NAME	BASIC	DESIGNATION	AGE
4	Kunal	6700	Trainee	28
5	Sunita	6230	Trainee	26
6	Bimal	7000	Trainee	25

7. Add Skills and DOJ columns

Query:
```
ALTER TABLE EMP1
    ADD ( SKILLS VARCHAR2(10),
          DOJ DATE
        );
```

OUTPUT: Table altered.

```
UPDATE EMP1
SET SKILLS = 'Java',
    DOJ = TO_DATE('10-01-2025', 'DD-MM-YYYY')
WHERE ID = 1;

UPDATE EMP1
SET SKILLS = 'Python',
    DOJ = TO_DATE('15-02-2025', 'DD-MM-YYYY')
WHERE ID=2;

UPDATE EMP1
SET SKILLS = 'SQL'
    DOJ = TO_DATE('20-03-2025', 'DD-MM-YYYY)
WHERE ID = 3;

UPDATE EMP1
SET SKill = 'Java',
    DOJ = TO_DATE('05-04-2025')('DD-MM-YYYY)
WHERE ID = 4;

UPDATE EMP1
SETSKILLS = 'HTML',
    DOJ = TO_DATE('10-05-2025')('DD-MM-YYYY)
    WHERE ID=5

UPDATE EMP1
    SETS SKILLS = 'C'
    DOJ = TO_DATE('15-06-2025', 'DD-MM-YYYY)
    WHERE ID=6;

COMMIT;
```

OUTPUT:
```
1 row updated.
1 row updated.
1 row updated.
1 row updated.
1 row updated.
1 row updated.
```

Display: SELECT * FROM EMP1

OUTPUT:

ID	NAME	DOJ	BASIC	DESIGNATION	AGE	SKILLS
1	Rohit	10-JAN-25	6700	Manager	21	JAVA
2	Sunil	15-FEB-25	6200	Engineer	27	Python
3	Payal	20-MAR-25	6300	Engineer	25	SQL
4	Kunal	05-APR-25	6700	Trainee	26	HTML
5	Sunita	10-MAY-25	6230	Trainee	26	Java
6	Bimal	15-JUN-25	7000	Trainee	25	C

8. Update more than One row in One Query.

```
UPDATE EMP1
SET Basic = Basic + 500
WHERE Designation = 'Engineer';
```

OUTPUT: 2 rows updated.

Check: SELECT ID, Name, Basic, Designation
FROM EMP1
WHERE DESignation = "Engineer';

OUTPUT:

ID	NAME	BASIC	DESIGNATION
2	SUNIL	6700	Engineer
3	Payal	6800	Engineer.

9. Rename Age to Age_in_Years

```
ALTER TABLE EMP1
RENAME COLUMN Age TO Age_in_years;
```

OUTPUT: Table altered.

Check: DESC EMP1

OUTPUT:

NAME	NULL?	TYPE
ID		NUMBER(2)
NAME		VARCHAR2(15)
BASIC		NUMBER(6)
DESIGNATION		VARCHAR2(10)

AGIE_IN_YEARS	NUMBER(2)
SKILLS	VARCHAR2(10)
DOJ	DATE

10. Drop Age from EMP_trainee

Query: ALTER TABLE EMP_trainee
DROP COLUMN Age;

OUTPUT: Table altered

Check: DESC EMP_trainee;

OUTPUT:

NAME	NULL?	TYPE
EMP_ID		NUMBER(2)
NAME		VARCHAR2(15)
BASIC		NUMBER(6)
DESIGNATION		VARCHAR2(10)

11. Rename EMP2 to EMP_Mgr_Engr.

Query: RENAME EMP1 TO EMP_Mgr_Engr;

OUTPUT: Table renamed.

Check: SELECT * FROM EMP_Mgr;

ID	NAME	AGIE_IN_YEARS	SKILLS	BASIC	DESIGNAI
1	Rohit	10-JAN-25	24 Java	6700	Manager
2	Sunil	15-FEB-25	27 Python	6700	Manager.
3	Payal	20-MAR-25	25 SQL	6800	Engineer.
4	Kunal	05-APR-25	28 Java	6700	Trainee.
5	Sunita	10-MAY-25	26 HTML	6230	Trainee.
6	Bimal	25-JUN-25	25 C	7000	Trainee

12. Truncate EMP_Mgr_Engr.

Query: TRUNCATE TABLE EMP_Mgr_Engr;

Output: Table truncated

Check the Table:

SELECT * FROM EMP_Mgr_Engr;

OUTPUT: NO ROWS selected

Check Structure:

DESC EMP_Mgr_Engr;

NAME	NULL?	Type
ID		NUMBER(2)
NAME		VARCHAR2(15)
BASIC		NUMBER(6)
DESIGNATION		VARCHAR2(10)
AGE_IN_YEARS		NUMBER(2)
SKILLS		VARCHAR2(10)
DOJ		DATE

28/08/26