The pxTFG package

UOC final-work metadata and front matter

Scvria
P3CTeX / UOC PEC Repository

2026/10/22 – Version 0.3

Abstract

pxTFG adds UOC final-project metadata, licensing and summaries without changing the P3CTeX visual style. The generic pxMEM package remains responsible for the structure of a memory.

Contents

1 Enable TFG

The TFG module loads via pxCORE when the TFG class option is set:

```
\documentclass[TFG,PR,CAT]{P3CTeX}   % standalone PR
\documentclass[TFG,MEM,PR,CAT]{P3CTeX}  % final memory
```

Neither TFG nor MEM implies the other. Select them at class-loading time; \PECTeXconfig{TFG} and \PECTeXconfig{MEM} do not load modules retroactively. The existing PR, PAC, PEC and CA profiles retain their semantics.

2 Metadata

pxTFG reuses P3CTeX data rather than creating duplicates. Use the normal class data keys student (author), grade (degree), subj-fullname (project title), ca-fullname/ca-shortname (deliverable), and date (document date). Use the class language option CAT, ES or EN; there is no TFG language field.

2.1 Configuration: \pxTFGsetup

\pxTFGsetup{<key=value,...>} stores TFG-only fields:

tutor Final-work supervisor.

pra Professor responsible for the subject.

area Work area/specialisation.

credits Credit count (ECTS).

keywords Work keywords supplied by the author.

licence Licence identifier or copyright notice.

licence-text Optional licence declaration.

licence-icon Optional path to a licence symbol image.

```
\PECTeXconfig{data={
  student={Estudiant},grade={Enginyeria Informatica},
  subj-fullname={Projecte},ca-fullname={Proposta},
  ca-shortname={PR1},date={\today}
}}
\pxTFGsetup{
  tutor={Tutora},pra={Professor responsable},
  area={Computacio},credits={12},
  keywords={Projecte, Sistemes},licence={CC BY}
}
```

3 Public commands

3.1 \pxTFGworkcard

`\pxTFGworkcard` prints the UOC final-work information card, using the shared class data and the TFG-only fields. Its labels follow the document language: Fitxa del Treball Final, Ficha del Trabajo Final or Final Project Information. It creates an unnumbered section in TFG PR documents or an unnumbered chapter in TFG+MEM documents, with a table-of-contents entry. The sheet includes PRA, keywords and the document language; the licence is a separate page. With P3CTeX and its TOC enabled, the TFG front matter is inserted automatically before the TOC. Manual card printing is unnecessary.

3.2 \pxTFGabstract

`\pxTFGabstract{<language>}{<text>}` registers one abstract for a particular language. Re-registering the same language replaces its text. It does not print the abstract and does not change Babel's document language.

```
\pxTFGabstract{CAT}{Resum del treball.}
\pxTFGabstract{ES}{Resumen del trabajo.}
\pxTFGabstract{EN}{Project abstract.}
```

3.3 \pxTFGabstracts

\pxTFGabstracts prints the abstracts already registered in CAT, ES, EN order, skipping absent entries. Headings are Resum, Resumen and Abstract; each appears in the table of contents.

3.4 \pxTFGcoverdetails

\pxTFGcoverdetails prints the configured supervisor, PRA and area. It can be placed in the existing P3CTeX cover's auxiliary-text slot without a separate cover implementation:

```
\PECTeXcover{text-auxtext={\pxTFGcoverdetails}}
```

3.5 \pxTFGlicencepage

\pxTFGlicencepage prints the configured licence page, including optional text and symbol. With no configured licence it does nothing.

3.6 \pxTFGfrontmatter

\pxTFGfrontmatter prints the licence page if configured, the work card with the Catalan summary, and supplied Spanish and English abstracts on subsequent pages. It does not print a cover, TOC, figure/table lists or any chapters. P3CTeX invokes it automatically before its TOC when TFG is loaded, or after the cover when the TOC is disabled. Manual invocation is optional and repeated output is suppressed. The generic report indexes belong to pxMEM, which can also be used without TFG.

4 Standalone TFG PR example

```
\documentclass[TFG,PR,CAT]{P3CTeX}
\PECTeXconfig{data={
  student={Estudiant},grade={Enginyeria Informatica},
  subj-fullname={Projecte},ca-fullname={PR1},
  ca-shortname={PR1}
}}
\pxTFGsetup{tutor={Tutora},area={Computacio},
  credits={12},licence={CC BY}}
\begin{document}
\section{Objectius}
Text de la PR1.
\end{document}
```

A normal PR remains independently compilable. Potentially reusable sections can be surrounded by selection comments as described in the `pxMEM` manual; no TFG-to-MEM dependency is introduced.

5 Final TFG memory example

```
\documentclass[TFG,MEM,CAT]{P3CTeX}
\PECTeXconfig{cover=true,toc=true,data={
  student={Estudiant},grade={Enginyeria Informatica},
  subj-fullname={Projecte},ca-fullname={Memoria},
  ca-shortname={MEM}
}}
\pxTFGsetup{tutor={Tutora},area={Computacio},
  credits={12},licence={CC BY}}
\pxTFGabstract{CAT}{Resum.}
\pxTFGabstract{EN}{Abstract.}
\begin{document}
\pxMEMsource{PR1}{../PR1/PR1.tex}
\chapter{Introduccio}
\pxMEMinclude{PR1}{objectius}
\pxMEMannex{Evidencies}{Material addicional.}
\end{document}
```

6 Public API summary

`\pxTFGsetup{keys}` Set TFG-only metadata.

`\pxTFGabstract{lang}{text}` Store an abstract.

`\pxTFGworkcard` Print the UOC work card.

`\pxTFGabstracts` Print registered abstracts.

`\pxTFGcoverdetails` Show TFG metadata on a P3CTeX cover.

`\pxTFGlicencepage` Print the optional licence page.

`\pxTFGfrontmatter` Print TFG preliminary content.