PAC1

Pràctiques de Procrastinació-Avançada en LaTeX

Universitat Oberta de Catalunya

Vladimir Scoriae

I, **Vladimir Scoriae**, declare that I hold the total and full authorship of all the tasks that are carried out in this document. I am the only one who has elaborated each exercise. I have not shared the statements with anyone and the only help I have received has been through the UOC classroom and teachers there.

March 2, 2026

Contents

1 First UOC section **2**
1.1 UOC subsection 2
1.1.1 UOC subsubsection 2

2 pxPRP: property maps and lists **2**
2.1 Objects, keys, and access 2
2.2 Overwrite and append 2
2.3 Lists: `\pxPutValue`, `\pxListSet`, `\pxListAll` 2
2.4 Clear key/object and predicates 2
2.5 Boolean flags and scalar access 2
2.6 List clear and compact API 2

3 pxUML: class diagrams **3**
3.1 Classes and diagram 3
3.2 Enums and associations 4

4 pxSRC: safe images **4**

5 pxTAB: predefined tables **9**

6 pxCORE: setup and debug **10**

7 pxGDX: layout helpers **10**

1 First UOC section

P^{3}CTEX Sample text with UOC section style.

1.1 UOC subsection

1.1.1 UOC subsubsection

More text with UOC subsection style.
Thin horizontal rule:

Thick horizontal rule (centered):

---

2 pxPRP: property maps and lists

2.1 Objects, keys, and access

`\pxGET␣DEMO.k1[2]` → v2.
`\pxPRINTF␣DEMO.k2[2]` → **DEMO.k2[2]:**vB.

2.2 Overwrite and append

Before overwrite: OVER.state[1] = old. After: OVER.state[1] = newA, OVER.state[2] = newB.

2.3 Lists: `\pxPutValue`, `\pxListSet`, `\pxListAll`

LST.items = (a, b, c).
All values (expected 1–3): 1 – 2 – 3.

2.4 Clear key/object and predicates

Before clear: TMP.k[1] = X. After: TMP.k[1] = Z. Now: TMP.k[1] = P.
Object MISSING is not present, as expected.
CHK exists. Key `nums` exists in CHK. Length of CHK.nums: 3.

2.5 Boolean flags and scalar access

ON, ON.
Scalar SCALAR.flag: true.
Scalar SCALAR.text: Hello, world..
Missing key: [].

2.6 List clear and compact API

Length before clear: 3. Length after clear: 0. Values: x,y.
After `\pxSETlst`: z,a. After `\pxSET`: A. After `\pxPUT`: AB. With separator: A, B.

3 pxUML: class diagrams

3.1 Classes and diagram



Inspection: Person attributes: [- name : String,- age : Integer].
Service operations: [+ run() : void].
Parents of DerivedClass: [BaseClass].
Non-existent class: [].

3.2 Enums and associations



4 pxSRC: safe images

Figure 1: Single image caption

Figure 2: Caption (optional width; color uses default)

Figure 3: Pair caption

Figure 4: Step one

Figure 5: Step two

Figure 6: Step three

Figure 7: Step four

5 pxTAB: predefined tables

Name	Age	City
Alice	20	Barcelona
Bob	22	Madrid

Item	Quantity
Apples	3
Oranges	5
Bananas	2

Code	Description
PX1	First code
PX2	Second code

m11	m12	m13
m21	m22	m23

Language	Users
LaTeX	Many
P3CTeX	Felizment cada cop més

Table 1: Sample pxTAB float table

Module	Feature
pxSRC	Safe image inclusion
pxTAB	Predefined table styles

Table 1 shows a small pxTAB float that can be cross-referenced in the usual way.

Criterion	Weight	Notes
Design	40%	Structure and clarity
Implementation	40%	Correctness and style
Testing	20%	Coverage and edge cases

Student	PEC 1	PEC 2	Final
Alice	8.0	9.0	8.5
Bruno	7.5	8.0	7.8
Carla	9.0	9.5	9.3
Daniel	6.5	7.0	6.8

6 pxCORE: setup and debug

Debug state: [DEBUG-OFF].

7 pxGDX: layout helpers

Example title text