The pxTFG package

UOC final-work metadata and front matter

Scvria
P3CTeX / UOC PEC Repository

2026/10/10 – Version 0.1

Abstract

pxTFG adds UOC final-project semantics to P3CTeX without changing its pxGDX visual style. It is independent from the generic pxMEM report and content-reuse package.

Contents

1 Enable TFG **1**

2 Metadata **2**
2.1 Configuration: \pxTFGsetup 2

3 Public commands **2**
3.1 \pxTFGworkcard 2
3.2 \pxTFGabstract 3
3.3 \pxTFGabstracts 3
3.4 \pxTFGfrontmatter 3

4 Standalone TFG PR example **3**

5 Final TFG memory example **3**

6 Public API summary **4**

1 Enable TFG

The TFG module loads via pxCORE when the TFG class option is set:

```
\documentclass[TFG,PR,CAT]{P3CTeX}   % standalone PR
\documentclass[TFG,MEM,CAT]{P3CTeX}  % final memory
```

Neither `TFG` nor `MEM` implies the other. Select them at class-loading time; `\PECTeXconfig{TFG}` and `\PECTeXconfig{MEM}` do not load modules retroactively. The existing PR, PAC, PEC and CA profiles retain their semantics.

2 Metadata

`pxTFG` reuses P3CTeX data rather than creating duplicates. Use the normal class data keys `student` (author), `grade` (degree), `subj-fullname` (project title), `ca-fullname`/`ca-shortname` (deliverable), and `date` (document date). Use the class language option `CAT`, `ES` or `EN`; there is no TFG language field.

2.1 Configuration: `\pxTFGsetup`

`\pxTFGsetup{<key=value,...>}` stores four TFG-only fields:

`tutor` Final-work supervisor.

`area` Work area/specialisation.

`credits` Credit count (ECTS).

`licence` Licence text for the work card.

```
\PECTeXconfig{data={
  student={Estudiant},grade={Enginyeria Informatica},
  subj-fullname={Projecte},ca-fullname={Proposta},
  ca-shortname={PR1},date={\today}
}}
\pxTFGsetup{
  tutor={Tutora},area={Computacio},
  credits={12},licence={CC BY}
}
```

3 Public commands

3.1 `\pxTFGworkcard`

`\pxTFGworkcard` prints the UOC final-work information card, using both the shared class data and the four TFG fields. Its labels follow the document language: Fitxa del Treball Final, Ficha del Trabajo Final or Final Project Information. It creates an unnumbered section in TFG PR documents or an unnumbered chapter in TFG+MEM documents, with a table-of-contents entry.

3.2 \pxTFGabstract

\pxTFGabstract{<language>}{<text>} registers one abstract for a particular language. Re-registering the same language replaces its text. It does not print the abstract and does not change Babel's document language.

```
\pxTFGabstract{CAT}{Resum del treball.}
\pxTFGabstract{ES}{Resumen del trabajo.}
\pxTFGabstract{EN}{Project abstract.}
```

3.3 \pxTFGabstracts

\pxTFGabstracts prints the abstracts already registered in CAT, ES, EN order, skipping absent entries. Headings are Resum, Resumen and Abstract; each appears in the table of contents.

3.4 \pxTFGfrontmatter

\pxTFGfrontmatter prints the work card followed by the registered abstracts. It does not print a cover or TOC; those belong to P3CTeX. Place it in the body near the beginning of the document.

4 Standalone TFG PR example

```
\documentclass[TFG,PR,CAT]{P3CTeX}
\PECTeXconfig{data={
  student={Estudiant},grade={Enginyeria Informatica},
  subj-fullname={Projecte},ca-fullname={PR1},
  ca-shortname={PR1}
}}
\pxTFGsetup{tutor={Tutora},area={Computacio},
  credits={12},licence={CC BY}}
\begin{document}
\pxTFGworkcard
\section{Objectius}
Text de la PR1.
\end{document}
```

A normal PR remains independently compilable. Potentially reusable sections can be surrounded by selection comments as described in the pxMEM manual; no TFG-to-MEM dependency is introduced.

5 Final TFG memory example

```
\documentclass[TFG,MEM,CAT]{P3CTeX}
```

```
\PECTeXconfig{cover=true,toc=false,data={
  student={Estudiant},grade={Enginyeria Informatica},
  subj-fullname={Projecte},ca-fullname={Memoria},
  ca-shortname={MEM}
}}
\pxTFGsetup{tutor={Tutora},area={Computacio},
  credits={12},licence={CC BY}}
\pxTFGabstract{CAT}{Resum.}
\pxTFGabstract{ES}{Resumen.}
\pxTFGabstract{EN}{Abstract.}
\begin{document}
\pxTFGfrontmatter
\tableofcontents
\pxMEMsource{PR1}{../PR1/PR1.tex}
\chapter{Introduccio}
\pxMEMinclude{PR1}{objectius}
\pxMEMannex{Evidencies}{Material addicional.}
\end{document}
```

6 Public API summary

\pxTFGsetup{keys} Set TFG-only metadata.

\pxTFGabstract{lang}{text} Store an abstract.

\pxTFGworkcard Print the UOC work card.

\pxTFGabstracts Print registered abstracts.

\pxTFGfrontmatter Print card plus abstracts.