

# Continuous Space (or neural network) language model

Alexandre Allauzen

# Outline

- 1 Statistical language modeling : the  $n$ -gram model
- 2 Neural network language model
- 3 SOUL language model

# Plan

- 1 Statistical language modeling : the  $n$ -gram model
- 2 Neural network language model
- 3 SOUL language model

# The goal of statistical language model (LM)

Aims to estimate a probability for all possible word sequences  $W$  build on a finite vocabulary  $V$ .

## The $n$ -gram assumption

A word can be predicted by its truncated **history** :  $n - 1$  previous words.

$n = 4$ , the *four*-gram

$$P(w_i | w_1, \dots, w_{i-2}, w_{i-1}) = P(w_i | w_{i-3}, w_{i-2}, w_{i-1}) \quad (1)$$

## Applications

Automatic speech recognition, Machine translation, ...

# The goal of statistical language model (LM)

Aims to estimate a probability for all possible word sequences  $W$  build on a finite vocabulary  $V$ .

## The $n$ -gram assumption

A word can be predicted by its truncated **history** :  $n - 1$  previous words.

$n = 4$ , the *four*-gram

$$P(w_i | w_1, \dots, w_{i-2}, w_{i-1}) = P(w_i | w_{i-3}, w_{i-2}, w_{i-1}) \quad (1)$$

## Applications

Automatic speech recognition, Machine translation, ...

# The goal of statistical language model (LM)

Aims to estimate a probability for all possible word sequences  $W$  build on a finite vocabulary  $V$ .

## The $n$ -gram assumption

A word can be predicted by its truncated **history** :  $n - 1$  previous words.

$n = 4$ , the *four*-gram

$$P(w_i | w_1, \dots, w_{i-2}, w_{i-1}) = P(w_i | \mathbf{w_{i-3}, w_{i-2}, w_{i-1}}) \quad (1)$$

## Applications

Automatic speech recognition, Machine translation, ...

# The goal of statistical language model (LM)

Aims to estimate a probability for all possible word sequences  $W$  build on a finite vocabulary  $V$ .

## The $n$ -gram assumption

A word can be predicted by its truncated **history** :  $n - 1$  previous words.

$n = 4$ , the *four*-gram

$$P(w_i | w_1, \dots, w_{i-2}, w_{i-1}) = P(w_i | \mathbf{w_{i-3}, w_{i-2}, w_{i-1}}) \quad (1)$$

## Applications

Automatic speech recognition, Machine translation, ...

# The $n$ -gram language model in practice

A  $n$ -gram language model is a set of discrete distribution, one per history.

## Training and inference

- $n$  ranges from 2 to 4
- One parameter for each observed  $n$ -gram
- + smoothing parameters for unseen  $n$ -grams
- Inference is straightforward

## Data sparsity issue

English 4-gram LM for WMT:

- training corpus: 6 billions of words
- number of parameters: more than 2,4 billions
- Most of the  $n$ -grams appear only once in the training data



# The lack of generalization

## A flat vocabulary

- Each word is only a possible outcome of a discrete random variable,
- an index in the vocabulary.

What is the relationship between two words ?

## An illustration

A training sentence:

LAST SUNDAY EVENING I FOUND A PLACE TO EAT IN **PARIS**.

What can be inferred for KARLSRUHE in the following sentence ?

LAST SUNDAY EVENING I FOUND A PLACE TO EAT IN **KARLSRUHE**.

# The lack of generalization

## A flat vocabulary

- Each word is only a possible outcome of a discrete random variable,
- an index in the vocabulary.

What is the relationship between two words ?

## An illustration

A training sentence:

LAST SUNDAY EVENING I FOUND A PLACE TO EAT IN **PARIS**.

What can be inferred for KARLSRUHE in the following sentence ?

LAST SUNDAY EVENING I FOUND A PLACE TO EAT IN **KARLSRUHE**.

# The lack of generalization

## A flat vocabulary

- Each word is only a possible outcome of a discrete random variable,
- an index in the vocabulary.

What is the relationship between two words ?

## An illustration

A training sentence:

LAST SUNDAY EVENING I FOUND A PLACE TO EAT IN **PARIS**.

What can be inferred for KARLSRUHE in the following sentence ?

LAST SUNDAY EVENING I FOUND A PLACE TO EAT IN **KARLSRUHE**.

# The lack of generalization

## A flat vocabulary

- Each word is only a possible outcome of a discrete random variable,
- an index in the vocabulary.

What is the relationship between two words ?

## An illustration

A training sentence:

LAST SUNDAY EVENING I FOUND A PLACE TO EAT IN **PARIS**.

What can be inferred for KARLSRUHE in the following sentence ?

LAST SUNDAY EVENING I FOUND A PLACE TO EAT IN **KARLSRUHE** .

# Plan

- 1 Statistical language modeling : the  $n$ -gram model
- 2 Neural network language model
- 3 SOUL language model

# Estimate $n$ -gram probabilities in a continuous space

Introduced in [Bengio et al., 2001, Bengio et al., 2003] and applied to speech recognition and machine translation in [Schwenk and Gauvain, 2002].

## In a nutshell

- 1 associate each word with a continuous feature vector
- 2 express the probability function of a word sequence in terms of the feature vectors of these words
- 3 learn simultaneously the feature vectors and the parameters of that probability function.

## Why should it work ?

- "similar" words are expected to have a similar feature vectors
- the probability function is a smooth function of these feature values
  - a small change in the features will induce a small change in the probability
  - Remember: PARIS and KARLSRUHE

# Estimate $n$ -gram probabilities in a continuous space

Introduced in [Bengio et al., 2001, Bengio et al., 2003] and applied to speech recognition and machine translation in [Schwenk and Gauvain, 2002].

## In a nutshell


- 1 associate each word with a continuous feature vector
- 2 express the probability function of a word sequence in terms of the feature vectors of these words
- 3 learn simultaneously the feature vectors and the parameters of that probability function.

## Why should it work ?

- "similar" words are expected to have a similar feature vectors
- the probability function is a smooth function of these feature values
  - a small change in the features will induce a small change in the probability
  - Remember: PARIS and KARLSRUHE

# Project a word sequence in a continuous space

- The vocabulary is a neuron layer.
- Project the word in the continuous space: add a second layer fully connected.
- For a 4-gram, the history is a sequence of 3 words.
- Merge these three vectors to derive a single vector for the history




- A neuron layer represents a vector of values,
- one neuron per value



# Project a word sequence in a continuous space


- The vocabulary is a neuron layer.
- Project the word in the continuous space: add a second layer fully connected.
- For a 4-gram, the history is a sequence of 3 words.
- Merge these three vectors to derive a single vector for the history



- The connection between two layers is a matrix operation
- The matrix  $R$  contains all the connection weights
- $v$  is a continuous vector


# Project a word sequence in a continuous space

- The vocabulary is a neuron layer.
- Project the word in the continuous space: add a second layer fully connected.
- For a 4-gram, the history is a sequence of 3 words.
- Merge these three vectors to derive a single vector for the history



# Project a word sequence in a continuous space


- The vocabulary is a neuron layer.
- Project the word in the continuous space: add a second layer fully connected.
- For a 4-gram, the history is a sequence of 3 words.
- Merge these three vectors to derive a single vector for the history



# Estimate the $n$ -gram probability

## The program


- Given the history expressed as a feature vector.
- Create a feature vector for the word to be predicted in the **prediction space**.
- Estimate probabilities for all words given the history.
- All the parameters must be learnt ( $\mathbf{R}$ ,  $\mathbf{W}_{ih}$ ,  $\mathbf{W}_{ho}$ ).



# Estimate the $n$ -gram probability

## The program


- Given the history expressed as a feature vector.
- Create a feature vector for the word to be predicted in the **prediction space**.
- Estimate probabilities for all words given the history.
- All the parameters must be learnt ( $R$ ,  $W_{ih}$ ,  $W_{ho}$ ).



# Estimate the $n$ -gram probability

## The program


- Given the history expressed as a feature vector.
- Create a feature vector for the word to be predicted in the **prediction space**.
- Estimate probabilities for all words given the history.
- All the parameters must be learnt ( $R$ ,  $W_{ih}$ ,  $W_{ho}$ ).



# Estimate the $n$ -gram probability

## The program

- Given the history expressed as a feature vector.
- Create a feature vector for the word to be predicted in the **prediction space**.
- Estimate probabilities for all words given the history.
- All the parameters must be learnt ( $\mathbf{R}$ ,  $\mathbf{W}_{ih}$ ,  $\mathbf{W}_{ho}$ ).




# Early assessment

## Key points

- The projection **in continuous spaces**
- reduces the sparsity issues
- Learn simultaneously the projection and the prediction

## In practice

- Significant and systematic improvements
- In machine translation and speech recognition tasks






# Early assessment

## Key points

- The projection **in continuous spaces**
- reduces the sparsity issues
- Learn simultaneously the projection and the prediction

## In practice

- Significant and systematic improvements
- In machine translation and speech recognition tasks




# Early assessment

## Key points

- The projection **in continuous spaces**
- reduces the sparsity issues
- Learn simultaneously the projection and the prediction

## In practice

- Significant and systematic improvements
- In machine translation and speech recognition tasks
- ☺ **Everybody should use it !**



# Early assessment


## Key points

- The projection **in continuous spaces**
- reduces the sparsity issues
- Learn simultaneously the projection and the prediction

## In practice

- Significant and systematic improvements
  - In machine translation and speech recognition tasks
- ☺ **Learning and inference time**

With a small training set



# Early assessment


## Key points

- The projection **in continuous spaces**
- reduces the sparsity issues
- Learn simultaneously the projection and the prediction

## In practice

- Significant and systematic improvements
- In machine translation and speech recognition tasks
- ☹ **Learning and inference time**

With a large training set




# Why it is so long ? - Inference

## Forward propagation of the history

- The projection: select a row in  $\mathbf{R}$
- Compute a vector for the predicted word.
- Estimate the probability for all the words  $\in V$

## Complexity issues

- The input vocabulary can be as large as we want.
- Increasing the order of  $n$  does not increase the complexity.
- **The problem is the output vocabulary size.**




# Why it is so long ? - Inference

## Forward propagation of the history

- The projection: select a row in  $\mathbf{R}$
- Compute a vector for the predicted word.
- Estimate the probability for all the words  $\in V$

## Complexity issues

- The input vocabulary can be as large as we want.
- Increasing the order of  $n$  does not increase the complexity.
- **The problem is the output vocabulary size.**




# Why it is so long ? - Inference

## Forward propagation of the history

- The projection: select a row in  $\mathbf{R}$
- Compute a vector for the predicted word.
- Estimate the probability for all the words  $\in V$

## Complexity issues

- The input vocabulary can be as large as we want.
- Increasing the order of  $n$  does not increase the complexity.
- **The problem is the output vocabulary size.**




# Why it is so long ? - Inference

## Forward propagation of the history

- The projection: select a row in  $\mathbf{R}$
- Compute a vector for the predicted word.
- Estimate the probability for all the words  $\in V$

## Complexity issues

- The input vocabulary can be as large as we want.
- Increasing the order of  $n$  does not increase the complexity.
- **The problem is the output vocabulary size.**






# Why it is so long ? - Inference

## Forward propagation of the history

- The projection: select a row in  $\mathbf{R}$
- Compute a vector for the predicted word.
- Estimate the probability for all the words  $\in V$

## Complexity issues

- The input vocabulary can be as large as we want.
- Increasing the order of  $n$  does not increase the complexity.
- **The problem is the output vocabulary size.**



# Why it is so long ? - Training


## Stochastic Gradient Ascent using back-propagation

One epoch of training = for each training example:

- Present the example (1  $n$ -gram)
- Forward propagation
- Back-propagation of the error to update each matrix.

## In practice

- A billion of training  $n$ -grams  $\Rightarrow$  a billion of inferences
- Many epochs  $\Rightarrow$  many billions of inferences.



# Why it is so long ? - Training


## Stochastic Gradient Ascent using back-propagation

One epoch of training = for each training example:

- Present the example (1  $n$ -gram)
- Forward propagation
- Back-propagation of the error to update each matrix.

## In practice

- A billion of training  $n$ -grams  $\Rightarrow$  a billion of inferences
- Many epochs  $\Rightarrow$  many billions of inferences.



# Why it is so long ? - Training


## Stochastic Gradient Ascent using back-propagation

One epoch of training = for each training example:

- Present the example (1  $n$ -gram)
- Forward propagation
- Back-propagation of the error to update each matrix.

## In practice

- A billion of training  $n$ -grams  $\Rightarrow$  a billion of inferences
- Many epochs  $\Rightarrow$  many billions of inferences.



# Why it is so long ? - Training


## Stochastic Gradient Ascent using back-propagation

One epoch of training = for each training example:

- Present the example (1  $n$ -gram)
- Forward propagation
- Back-propagation of the error to update each matrix.

## In practice

- A billion of training  $n$ -grams  $\Rightarrow$  a billion of inferences
- Many epochs  $\Rightarrow$  many billions of inferences.



# Why it is so long ? - Training


## Stochastic Gradient Ascent using back-propagation

One epoch of training = for each training example:

- Present the example (1  $n$ -gram)
- Forward propagation
- Back-propagation of the error to update each matrix.

## In practice

- A billion of training  $n$ -grams  $\Rightarrow$  a billion of inferences
- Many epochs  $\Rightarrow$  many billions of inferences.



# Usual tricks to speed-up training (and inference)

## Re-sampling and batch training

- For each epoch: down-sampling of the training data
- Forward and Back-propagation for a group of  $n$ -grams

## Reduce the output vocabulary

- Use the Neural network to predict only the  $K$  most frequent words.
- For a tractable model:  $K = 6\,000$  to  $20\,000$ .
- Requires the normalization of the distribution for the whole vocabulary.

⇒ use the standard  $n$ -gram LM.

# Usual tricks to speed-up training (and inference)

## Re-sampling and batch training

- For each epoch: down-sampling of the training data
- Forward and Back-propagation for a group of  $n$ -grams

## Reduce the output vocabulary

- Use the Neural network to predict only the  $K$  most frequent words.
  - For a tractable model:  $K = 6\,000$  to  $20\,000$ .
  - Requires the normalization of the distribution for the whole vocabulary.
- ⇒ use the standard  $n$ -gram LM.



# Plan

- 1 Statistical language modeling : the  $n$ -gram model
- 2 Neural network language model
- 3 SOUL language model

# A kind of class-based language model

## Main ideas

As proposed by [Mnih and Hinton, 2008]:

- Represent the vocabulary as a clustering tree [Brown et al., 1992].
- Predict the path in this clustering tree.

## Word clustering

- Associate each word  $w$  with a single class  $c_1(w)$
- Split these word classes in sub-classes ( $c_2(w)$ ) and so on.

# A kind of class-based language model


## Main ideas

As proposed by [Mnih and Hinton, 2008]:

- Represent the vocabulary as a clustering tree [Brown et al., 1992].
- Predict the path in this clustering tree.

## Word clustering

- Associate each word  $w$  with a single class  $c_1(w)$
- Split these word classes in sub-classes ( $c_2(w)$ ) and so on.



# A kind of class-based language model


## Main ideas

As proposed by [Mnih and Hinton, 2008]:

- Represent the vocabulary as a clustering tree [Brown et al., 1992].
- Predict the path in this clustering tree.

## Word clustering

- Associate each word  $w$  with a single class  $c_1(w)$
- Split these word classes in sub-classes ( $c_2(w)$ ) and so on.



# A kind of class-based language model


## Main ideas

As proposed by [Mnih and Hinton, 2008]:


- Represent the vocabulary as a clustering tree [Brown et al., 1992].
- Predict the path in this clustering tree.

## Word clustering

- Associate each word  $w$  with a single class  $c_1(w)$
- Split these word classes in sub-classes ( $c_2(w)$ ) and so on.





# Word probability




$$P(w_i|h) = P(c_1(w_i)|h) \prod_{d=2}^D P(c_d(w_i)|h, c_{1:d-1})$$

- $c_{1:D}(w_i) = c_1, \dots, c_D$  : path for the word  $w_i$  in the clustering tree,
- $D$  : depth of the tree,
- $c_d(w_i)$ : (sub-)class,
- $c_D(w_i)$ : leaf.

# The SOUL language model



# The SOUL language model





# The SOUL language model

## Overview

- A class-based language model
- Estimated in a continuous space with neural networks
- The class introduction  $\Rightarrow$  many small output layers instead of a single but big layer.

## In practice

- The first level: The 8k most frequent words + 4k word classes
- The depth is between 3 and 4.

# The SOUL language model

## Overview

- A class-based language model
- Estimated in a continuous space with neural networks
- The class introduction  $\Rightarrow$  many small output layers instead of a single but big layer.

## In practice

- The first level: The 8k most frequent words + 4k word classes
- The depth is between 3 and 4.

# Training algorithm

## Step 1:

Train a standard NNLM model with the short-list as an output (3 epochs and a short-list of 8k words).

## Step 2:

Reduce the dimension of the context space using with PCA (final dimension is 10 in our experiments).

## Step 3:

Perform a recursive  $K$ -means word clustering based on the distributed representation induced by the continuous space (except for words in the short-list).

## Step 4:

Train the whole model

# Training algorithm

## Step 1:

Train a standard NNLM model with the short-list as an output (3 epochs and a short-list of 8k words).

## Step 2:

Reduce the dimension of the context space using with PCA (final dimension is 10 in our experiments).

## Step 3:

Perform a recursive  $K$ -means word clustering based on the distributed representation induced by the continuous space (except for words in the short-list).

## Step 4:

Train the whole model

# Training algorithm

## Step 1:

Train a standard NNLM model with the short-list as an output (3 epochs and a short-list of 8k words).

## Step 2:

Reduce the dimension of the context space using with PCA (final dimension is 10 in our experiments).

## Step 3:

Perform a recursive  $K$ -means word clustering based on the distributed representation induced by the continuous space (except for words in the short-list).

## Step 4:

Train the whole model

# Training algorithm

## Step 1:

Train a standard NNLM model with the short-list as an output (3 epochs and a short-list of 8k words).

## Step 2:

Reduce the dimension of the context space using with PCA (final dimension is 10 in our experiments).

## Step 3:

Perform a recursive  $K$ -means word clustering based on the distributed representation induced by the continuous space (except for words in the short-list).

## Step 4:


Train the whole model

# Summary



- SOUL LM combines two techniques: neural network and class-based language models.
- SOUL LM is the first complete large-scale continuous space language model.
- Within a large-scale task, significant improvement is achieved.
- When increasing context length, SOUL LM improves the performance.



# Future/Other work - Recurrent model




[Kalchbrenner and Blunsom, 2013b]



# Future/Other work - Sentence model





# Future/Other work - Towards translation models








[Kalchbrenner and Blunsom. 2013a]

# Future/Other work - Linguistic structure



[Socher et al., 2011]

-  Bengio, Y., Ducharme, R., and Vincent, P. (2001).  
A neural probabilistic language model.  
*Neural Information Processing Systems*, 13:933–938.
-  Bengio, Y., Ducharme, R., Vincent, P., and Janvin, C. (2003).  
A neural probabilistic language model.  
*JMLR*, 3:1137–1155.
-  Brown, P., de Souza, P., Mercer, R., Della Pietra, V., and Lai, J. (1992).  
Class-based n-gram models of natural language.  
*Computational Linguistics*, 18(4):467–479.
-  Kalchbrenner, N. and Blunsom, P. (2013a).  
Recurrent continuous translation models.  
*In Proceedings of the Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 1700–1709, Seattle, Washington, USA. Association for Computational Linguistics.
-  Kalchbrenner, N. and Blunsom, P. (2013b).  
Recurrent convolutional neural networks for discourse compositionality.

In *Proceedings of the Workshop on Continuous Vector Space Models and their Compositionality*, pages 119–126, Sofia, Bulgaria. Association for Computational Linguistics.



Mnih, A. and Hinton, G. (2008).

A scalable hierarchical distributed language model.

In *Neural Information Processing Systems*, volume 21, pages 1081–1088.



Schwenk, H. and Gauvain, J.-L. (2002).

Connectionist language modeling for large vocabulary continuous speech recognition.

In *Proc. of ICASSP'02*, pages 765–768.



Socher, R., Lin, C. C.-Y., Ng, A. Y., and Manning, C. D. (2011).

Parsing Natural Scenes and Natural Language with Recursive Neural Networks.

In *Proceedings of the 26th International Conference on Machine Learning (ICML)*.