Market Basket Analysis for Corse Topics CSV File

Didem Aykurt

2022-12-24

Market Basket Analysis

Market basket analysis is an essential technique for market research that helps identify which products to purchase together for each transaction or, if the customer buys the product, identify which product strongly relates to purchasing or is recommended to buy. Market basket analysis, like recommended products, advertisements, shopping online, identifying the relational group of people who have identical product buy, marketing promotion, coupon offers, and so on. All this marketing strategy to increase the cross-selling and up-selling of products and decrease the time customers spend on product research also eliminates risk in a future business plan. There are three types of recommender systems:

The Knowledge-base Recommendations system helps to predict the group of products bought together. The collaborative Filtering technique uses the data for customer preferences and remanent products to a similar type of buyer.

The Content-based technique uses historical purchase data to predict and recommend a similar product.

Market basket analysis has a different model to analyze the relationship between products and one of the models is association rules the following step: IF [antecedent] THEN [consequent] these technics set of rules if "buy this" then "high relation product to buy that" Association rules have three types of measures:

Association rules have three types of measures:

Support helps to measure the frequency group of products bought.

$$Support = P(antecent \ AND \ consequent)$$

Confidence measures the probability that the customer will buy an antecedent product rather than a consequent product as a conditional probability.

$$Confidence = \frac{\stackrel{\frown}{P(antecentANDconsequent)}}{\stackrel{\frown}{P(antecedent)}}$$

The Lift measures the ratio of confidence to expected confidence so helps to increase confidence.

$$Benchmark confidence = \frac{no.\,transaction\,with\,consequent\,itemset}{no.\,transections\,in\,database}$$

A result lift ratio is a considerable value that means a high probability of buying the consequent product.

Market Basket Analysis for CorseTopics CSV

The CorseTopics dataset included 365 observations with 8 variables intro, Datamining, Survey, Cat.Data, Regression, Forecast, DOE, and SW.Each that all the topics for one course.

```
# Install and Load Packages for market basket analysis
#install.packages("pacman")
library("pacman")
pacman::p_load(arules, arulesViz)
```

LOAD and prepare CourseTopics CSV data

```
marketBas.df<-read.csv("C:/Users/didem/OneDrive/Documents/CSUG Master
DA/MIS510-1 Data Mining_4 term/Module 6 Market basket
Analysis/Coursetopics.csv", header=TRUE)</pre>
```

Check to null object(result False means there isn't null)

```
is.null(marketBas.df)
## [1] FALSE
```

Print the list in a useful column format

```
t(t(names(marketBas.df)))
##
        [,1]
## [1,] "Intro"
## [2,] "DataMining"
## [3,] "Survey"
## [4,] "Cat.Data"
## [5,] "Regression"
## [6,] "Forecast"
## [7,] "DOE"
## [8,] "SW"
#show the first nine rows
head(marketBas.df, 9)
##
     Intro DataMining Survey Cat.Data Regression Forecast DOE SW
## 1
                             0
                                       0
         1
                     1
                                                  0
                                                            0
                                                                 0
                                                                    0
                     0
## 2
         0
                             1
                                       0
                                                  0
                                                            0
                                                                 0
                                                                    0
## 3
         0
                     1
                             0
                                       1
                                                  1
                                                            0
                                                                    1
                                                                 0
                     0
                             0
                                                  0
## 4
         1
                                       0
                                                            0
                                                                 0
                                                                    0
## 5
         1
                     1
                             0
                                       0
                                                  0
                                                            0
                                                                 0
                                                                    0
         0
                     1
                             0
                                       0
                                                  0
                                                                 0
                                                                    0
## 6
                                                            0
## 7
                                                                 0
```

```
## 8
                           0
                                    0
## 9
         1
                    0
                                                               0
                                                            0
#find summary statistics for each column
summary(marketBas.df)
##
        Intro
                       DataMining
                                          Survey
                                                          Cat.Data
## Min.
           :0.0000
                     Min.
                            :0.0000
                                      Min.
                                             :0.0000
                                                       Min.
                                                              :0.0000
  1st Qu.:0.0000
                     1st Qu.:0.0000
                                      1st Qu.:0.0000
                                                       1st Qu.:0.0000
## Median :0.0000
                                      Median :0.0000
                     Median :0.0000
                                                       Median :0.0000
## Mean
           :0.3945
                     Mean
                            :0.1781
                                      Mean
                                             :0.1863
                                                       Mean
                                                              :0.2082
## 3rd Qu.:1.0000
                     3rd Qu.:0.0000
                                      3rd Qu.:0.0000
                                                       3rd Qu.:0.0000
##
   Max.
           :1.0000
                     Max.
                            :1.0000
                                      Max.
                                             :1.0000
                                                       Max.
                                                              :1.0000
##
      Regression
                        Forecast
                                           DOE
                                                             SW
## Min.
           :0.0000
                     Min.
                            :0.0000
                                      Min.
                                             :0.0000
                                                       Min.
                                                              :0.0000
   1st Ou.:0.0000
                     1st Ou.:0.0000
                                      1st Qu.:0.0000
                                                       1st Ou.:0.0000
## Median :0.0000
                     Median :0.0000
                                      Median :0.0000
                                                       Median :0.0000
## Mean
           :0.2082
                     Mean
                            :0.1397
                                      Mean
                                             :0.1726
                                                       Mean
                                                              :0.2219
  3rd Qu.:0.0000
##
                     3rd Qu.:0.0000
                                      3rd Qu.:0.0000
                                                       3rd Qu.:0.0000
## Max. :1.0000
                     Max. :1.0000
                                      Max. :1.0000
                                                       Max. :1.0000
```

Remove first column and convert to matrix

```
marketBas.mat<- as.matrix(marketBas.df[,-1])</pre>
```

Convert the binary incidence matrix into a transactions database


```
marketBas.trans<- as(marketBas.mat,"transactions")
inspect(head(marketBas.trans))

## items
## [1] {DataMining}
## [2] {Survey}
## [3] {DataMining, Cat.Data, Regression, SW}
## [4] {}
## [5] {DataMining}
## [6] {DataMining}</pre>
```

Plot the Sort topics

```
itemFrequencyPlot(marketBas.trans, topN=7, type="absolute", main="Top 10
topics")
```


Top 10 topics



The above graph tells highest to lowest frequency topics that helps to focus and structure as the higher to lower SW, Cat.Data, Regression, Survey, DataMining, DOE, and Forecast.

Topic Frequncy of 1%

itemFrequencyPlot(marketBas.trans, support=0.01)



The above chart shows all the topics having take frequency of 14% and above. And the top three topics are SW, Cat.Data, and Regression.

Association rules

when running the apriori() function in R, including the minimum support, minimum confidence, and target as arguments. And this case's minimum support is 0.01, with minimum confidence of 0.1. I will build the basket and find which topics significantly occur to understand which topics are preferable.

```
rules<- apriori(marketBas.trans, parameter = list( supp=0.01, conf=0.1,
target="rules"))
## Apriori
##
## Parameter specification:
## confidence minval smax arem aval originalSupport maxtime support minlen
##
           0.1
                  0.1
                         1 none FALSE
                                                 TRUE
                                                             5
                                                                  0.01
## maxlen target ext
##
        10 rules TRUE
##
## Algorithmic control:
## filter tree heap memopt load sort verbose
       0.1 TRUE TRUE FALSE TRUE
                                         TRUE
##
## Absolute minimum support count: 3
## set item appearances ...[0 item(s)] done [0.00s].
## set transactions ...[7 item(s), 365 transaction(s)] done [0.00s].
## sorting and recoding items ... [7 item(s)] done [0.00s].
## creating transaction tree ... done [0.00s].
## checking subsets of size 1 2 3 4 done [0.00s].
## writing ... [121 rule(s)] done [0.00s].
## creating S4 object ... done [0.00s].
summary(marketBas.trans)
## transactions as itemMatrix in sparse format with
## 365 rows (elements/itemsets/transactions) and
## 7 columns (items) and a density of 0.1878669
##
## most frequent items:
##
           SW
                Cat.Data Regression
                                                              (Other)
                                        Survey DataMining
           81
                                                                  114
##
                      76
                                            68
                                                        65
##
## element (itemset/transaction) length distribution:
## sizes
                         5
     0
         1
             2
                 3
                     4
                             6
##
## 84 173 44 43
                    16
                             1
##
```

```
##
                    Median
      Min. 1st Ou.
                               Mean 3rd Ou.
                                               Max.
##
             1.000
                     1.000
     0.000
                              1.315
                                      2.000
                                              6.000
##
## includes extended item information - examples:
##
         labels
## 1 DataMining
## 2
         Survey
## 3
       Cat.Data
```

The result of rules gave 121 rules to create baskets, and the summary showed; 0 topic list has 84 rules, 1 topic list has 173, 2 topics list has 44 rules, 3 topics list has 43 rules, 4 topics list has 16, 5 topics list has 4 rules, and 6 topics list has 1.

Inspect the first six rules, sorted by their lift

```
inspect(head(sort(rules, by="lift"), n=6))
##
                                                            confidence
                                   rhs
                                                support
coverage
## [1] {DataMining, DOE}
                                => {Cat.Data}
                                                0.01643836 0.6666667
0.02465753
## [2] {Survey, Regression}
                                => {Cat.Data}
                                                0.01643836 0.6666667
0.02465753
## [3] {DataMining, Regression} => {Forecast}
                                                0.01917808 0.4375000
0.04383562
## [4] {DataMining, Regression} => {Cat.Data}
                                                0.02739726 0.6250000
0.04383562
## [5] {Regression, DOE}
                                => {SW}
                                                0.01917808 0.6363636
0.03013699
## [6] {Regression, Forecast} => {DataMining} 0.01917808 0.5000000
0.03835616
##
       lift
                count
## [1] 3.201754
                 6
## [2] 3.201754
## [3] 3.131127
## [4] 3.001645 10
## [5] 2.867565
                 7
## [6] 2.807692
```


The results of the sort-by-lift statistics show how many times more likely this is to be in there as opposed to chance. The result of rule 1 shows a high probability of the topic group being DataMining and DOE who have more like to have Cat.Data topic as their result of lift ratio is 3.2 chance of having Cat.Data at the same time if the student has two other topics. Rule sixth shows that if students have Regression and Forecast together, they have a 2.8 chance to have a data DataMining topic. The top 6 lift score specify Cat.Data topic taken with Survey is 4 times, and DataMining is 3 times. The foremost lift is always superior for product assosiaction that needs more focus.

Rules by confidence

```
rulesConf<- sort(rules, by="confidence", decreasing = TRUE)</pre>
inspect(head(rulesConf))
##
      1hs
                                  rhs
                                            support
                                                       confidence coverage
## [1] {DataMining, DOE}
                              => {Cat.Data} 0.01643836 0.6666667
0.02465753
## [2] {Survey, Regression} => {Cat.Data} 0.01643836 0.6666667
0.02465753
## [3] {Regression, DOE}
                              => {SW} 0.01917808 0.6363636
0.03013699
## [4] {DataMining, Regression} => {Cat.Data} 0.02739726 0.6250000
0.04383562
## [5] {Survey, DOE}
                              => {Cat.Data} 0.01917808 0.5833333
0.03287671
## [6] {Survey, Forecast} => {Cat.Data} 0.02191781 0.5714286
0.03835616
##
      lift
               count
## [1] 3.201754 6
## [2] 3.201754 6
## [3] 2.867565 7
## [4] 3.001645 10
## [5] 2.801535 7
## [6] 2.744361 8
```

Rules Graph

```
#install.packages("arulesViz")
library(arulesViz)
plot(rules, method="graph", control=list(type="items"))
## Warning: Unknown control parameters: type
## Available control parameters (with default values):
## layout
            = stress
## circular = FALSE
## ggraphdots = NULL
## edges
           = <environment>
## nodes = <environment>
## nodetext = <environment>
## colors = c("#EE0000FF", "#EEEEEEFF")
           = ggplot2
## engine
## max
        = 100
## verbose = FALSE
## 'lift' (change control parameter max if needed).
```



The visualization shows three dots' support values are 0.05 and lift over 2.5. Those stay middle on DataMining, Regression, and Cat.Data.

Which topics led to Cat.Data

```
rules<-apriori(marketBas.trans, parameter = list(minlen=2, supp=0.01,</pre>
conf=0.1, target="rules"), appearance = list(default="lhs", rhs="Cat.Data"),
control=list(verbose=F))
inspect(rules, ruleSep= "--->", itemSep="+")
##
        lhs
                                               support
                                                          confidence
                                     rhs
coverage
## [1] {Forecast}
                               ---> {Cat.Data} 0.04383562 0.3137255
0.13972603
                               ---> {Cat.Data} 0.04657534 0.2698413
## [2] {DOE}
0.17260274
## [3] {DataMining}
                               ---> {Cat.Data} 0.04931507 0.2769231
0.17808219
## [4] {Survey}
                               ---> {Cat.Data} 0.06301370 0.3382353
0.18630137
                               ---> {Cat.Data} 0.05479452 0.2631579
## [5] {Regression}
0.20821918
                               ---> {Cat.Data} 0.06301370 0.2839506
## [6] {SW}
0.22191781
## [7] {Forecast+DOE}
                               ---> {Cat.Data} 0.01369863 0.5000000
0.02739726
## [8] {DataMining+Forecast} ---> {Cat.Data} 0.01095890 0.2666667
```

```
0.04109589
## [9] {Survey+Forecast} ---> {Cat.Data} 0.02191781 0.5714286
0.03835616
## [10] {Regression+Forecast} ---> {Cat.Data} 0.01095890 0.2857143
0.03835616
## [11] {Forecast+SW} ---> {Cat.Data} 0.01369863 0.3846154
0.03561644
## [12] {DataMining+DOE}
                             ---> {Cat.Data} 0.01643836 0.6666667
0.02465753
## [13] {Survey+DOE}
                             ---> {Cat.Data} 0.01917808 0.5833333
0.03287671
## [14] {Regression+DOE}
                             ---> {Cat.Data} 0.01095890 0.3636364
0.03013699
## [15] {DOE+SW}
                             ---> {Cat.Data} 0.02465753 0.4285714
0.05753425
## [16] {DataMining+Survey} ---> {Cat.Data} 0.01643836 0.5454545
0.03013699
## [17] {DataMining+Regression} ---> {Cat.Data} 0.02739726 0.6250000
0.04383562
## [18] {DataMining+SW} ---> {Cat.Data} 0.01643836 0.4285714
0.03835616
## [19] {Survey+Regression} ---> {Cat.Data} 0.01643836 0.6666667
0.02465753
## [20] {Survey+SW}
                             ---> {Cat.Data} 0.02191781 0.4444444
0.04931507
## [21] {Regression+SW}
                            ---> {Cat.Data} 0.01643836 0.3000000
0.05479452
##
       lift
                count
## [1] 1.506708 16
## [2] 1.295948 17
## [3] 1.329960 18
## [4] 1.624420 23
## [5] 1.263850 20
## [6] 1.363710 23
## [7] 2.401316 5
## [8] 1.280702 4
## [9] 2.744361 8
## [10] 1.372180 4
## [11] 1.847166 5
## [12] 3.201754 6
## [13] 2.801535 7
## [14] 1.746411 4
## [15] 2.058271
## [16] 2.619617 6
## [17] 3.001645 10
## [18] 2.058271 6
## [19] 3.201754 6
## [20] 2.134503 8
## [21] 1.440789 6
```

In addition, 23 times, Survey and SW had students will likely have Cat.Data. Rules 19, 12, and 17 have the highest lift and a high probability of having Cat.Data.

I will create a basket with minimum support of 0.01 and minimum confidence of 0.5 with R's apriori() function.

```
rules1<- apriori(marketBas.trans, parameter = list(supp=0.01, conf=0.5,</pre>
target="rules"))
## Apriori
##
## Parameter specification:
## confidence minval smax arem aval originalSupport maxtime support minlen
                         1 none FALSE
##
           0.5
                  0.1
                                                 TRUE
                                                            5
                                                                 0.01
## maxlen target ext
##
        10 rules TRUE
##
## Algorithmic control:
## filter tree heap memopt load sort verbose
       0.1 TRUE TRUE FALSE TRUE
##
                                    2
                                         TRUE
##
## Absolute minimum support count: 3
## set item appearances ...[0 item(s)] done [0.00s].
## set transactions ...[7 item(s), 365 transaction(s)] done [0.00s].
## sorting and recoding items ... [7 item(s)] done [0.00s].
## creating transaction tree ... done [0.00s].
## checking subsets of size 1 2 3 4 done [0.00s].
## writing ... [14 rule(s)] done [0.00s].
## creating S4 object ... done [0.00s].
```

Inspect the first six rules, sorted by their lift


```
inspect(head(sort(rules1, by="lift"), n=6))
##
      lhs
                                   rhs
                                                support
                                                           confidence
coverage
## [1] {DataMining, DOE}
                               => {Cat.Data}
                                                0.01643836 0.6666667
0.02465753
## [2] {Survey, Regression}
                               => {Cat.Data}
                                                0.01643836 0.6666667
0.02465753
## [3] {DataMining, Regression} => {Cat.Data}
                                                0.02739726 0.6250000
0.04383562
## [4] {Regression, DOE}
                               => {SW}
                                                0.01917808 0.6363636
0.03013699
## [5] {Regression, Forecast} => {DataMining} 0.01917808 0.5000000
0.03835616
## [6] {Cat.Data, Regression} => {DataMining} 0.02739726 0.5000000
0.05479452
##
      lift
                count
## [1] 3.201754 6
```

```
## [2] 3.201754 6
## [3] 3.001645 10
## [4] 2.867565 7
## [5] 2.807692 7
## [6] 2.807692 10
```

Lift ratio for confidence 0.5 show high value of group is DataMining and DOE with Cat.Data topic same result of confidence 0.1's lift ratio. Although sixth line is group different if student assign Cat.Data and Regression topics 2.8 chance to have DataMining topic.

Visualizing rules


```
library(arulesViz)
plot(rules1, jitter=0)
```



Graph shows lift support and confidence values for all 14 rules. If the dot is darker color means lift value is high so one dot over the 0.65 point of confidence, support between 0.016 to 0.020 and lift over the 3.

Visual the group

```
library(arulesViz)
plot(rules1, method = "grouped")
```



The high probability topics are DataMining and Survey, and two plus topics with Cat.Data. The highest support group of topics is DataMining, Regression with Cat.Data topic.

Reference

- Shmueli, G., Bruce, P. C., Yahav, I., Patel, N. R., & Lichtendahl, K. C. (2018). Data mining for Business Analytics: Concepts, techniques, and applications in R (1st ed.). John Wiley & Sons.
- Megha Goriya(2021), Published in Analytics Vidhya. Market Basket Analysis using

 Association Rules. https://medium.com/analytics-vidhya/market-basket-analysis-using-association-rules-2b0f3e2a897d
- Ricardo Rodriguez ,Market Basket Analysis on Tech Business

 Guide. https://techbusinessguide.com/what-is-market-basket-analysis/
- Rajarajachozhan(2020). Market basket analysis in e-commerce business explained (A Case study). https://gecdesigns.com/blog/how-can-market-basket-analysis-help-e-commerce-business