General Purpose Transistors

NPN and PNP Silicon

MMBT3904WT1G, NPN, SMMBT3904WT1G, NPN, MMBT3906WT1G, PNP, SMMBT3906WT1G, PNP

These transistors are designed for general purpose amplifier applications. They are housed in the SOT−323/SC−70 package which is designed for low power surface mount applications.

Features

- S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC−Q101 Qualified and PPAP Capable
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector − Emitter Voltage MMBT3904WT1, SMMBT3904WT1 MMBT3906WT1, SMMBT3906WT1	V_{CEO}	 40 −40	Vdc
Collector − Base Voltage MMBT3904WT1, SMMBT3904WT1 MMBT3906WT1, SMMBT3906WT1	V_{CBO}	 60 −40	Vdc
Emitter − Base Voltage MMBT3904WT1, SMMBT3904WT1 MMBT3906WT1, SMMBT3906WT1	V_{EBO}	 6.0 −5.0	Vdc
Collector Current − Continuous MMBT3904WT1, SMMBT3904WT1 MMBT3906WT1, SMMBT3906WT1	I_C	 200 −200	mAdc

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation (Note 1) @T_A = 25°C	P_D	150	mW
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	833	°C/W
Junction and Storage Temperature	T_J, T_{stg}	−55 to +150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Device mounted on FR4 glass epoxy printed circuit board using the minimum recommended footprint.





SC−70 (SOT−323)
CASE 419
STYLE 3

MARKING DIAGRAM



xx = AM for MMBT3904WT1, SMMBT3904WT
= 2A for MMBT3906WT1, SMMBT3906WT1
M = Date Code*
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*Date Code orientation may vary depending up-on manufacturing location.

ORDERING INFORMATION

Device	Package	Shipping†
MMBT3904WT1G, SMMBT3904WT1G	SC−70/ SOT−323 (Pb−Free)	3000 / Tape & Reel
MMBT3906WT1G, SMMBT3906WT1G	SC−70/ SOT−323 (Pb−Free)	3000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Max	Unit
OFF CHARACTERISTICS					
Collector – Emitter Breakdown Voltage (Note 2)		$V_{(BR)CEO}$			Vdc
(I_C = 1.0 mAdc, I_B = 0)	MMBT3904WT1, SMMBT3904WT1		40	–	
(I_C = –1.0 mAdc, I_B = 0)	MMBT3906WT1, SMMBT3906WT1		–40	–	
Collector – Base Breakdown Voltage		$V_{(BR)CBO}$			Vdc
(I_C = 10 μAdc, I_E = 0)	MMBT3904WT1, SMMBT3904WT1		60	–	
(I_C = –10 μAdc, I_E = 0)	MMBT3906WT1, SMMBT3906WT1		–40	–	
Emitter – Base Breakdown Voltage		$V_{(BR)EBO}$			Vdc
(I_E = 10 μAdc, I_C = 0)	MMBT3904WT1, SMMBT3904WT1		6.0	–	
(I_E = –10 μAdc, I_C = 0)	MMBT3906WT1, SMMBT3906WT1		–5.0	–	
Base Cutoff Current		I_{BL}			nAdc
(V_{CE} = 30 Vdc, V_{EB} = 3.0 Vdc)	MMBT3904WT1, SMMBT3904WT1		–	50	
(V_{CE} = –30 Vdc, V_{EB} = –3.0 Vdc)	MMBT3906WT1, SMMBT3906WT1		–	–50	
Collector Cutoff Current		I_{CEX}			nAdc
(V_{CE} = 30 Vdc, V_{EB} = 3.0 Vdc)	MMBT3904WT1, SMMBT3904WT1		–	50	
(V_{CE} = –30 Vdc, V_{EB} = –3.0 Vdc)	MMBT3906WT1, SMMBT3906WT1		–	–50	
ON CHARACTERISTICS (Note 2)					
DC Current Gain		h_{FE}			–
(I_C = 0.1 mAdc, V_{CE} = 1.0 Vdc)	MMBT3904WT1, SMMBT3904WT1		40	–	
(I_C = 1.0 mAdc, V_{CE} = 1.0 Vdc)			70	–	
(I_C = 10 mAdc, V_{CE} = 1.0 Vdc)			100	300	
(I_C = 50 mAdc, V_{CE} = 1.0 Vdc)			60	–	
(I_C = 100 mAdc, V_{CE} = 1.0 Vdc)			30	–	
(I_C = –0.1 mAdc, V_{CE} = –1.0 Vdc)	MMBT3906WT1, SMMBT3906WT1		60	–	
(I_C = –1.0 mAdc, V_{CE} = –1.0 Vdc)			80	–	
(I_C = –10 mAdc, V_{CE} = –1.0 Vdc)			100	300	
(I_C = –50 mAdc, V_{CE} = –1.0 Vdc)			60	–	
(I_C = –100 mAdc, V_{CE} = –1.0 Vdc)			30	–	
Collector – Emitter Saturation Voltage		$V_{CE(sat)}$			Vdc
(I_C = 10 mAdc, I_B = 1.0 mAdc)	MMBT3904WT1, SMMBT3904WT1		–	0.2	
(I_C = 50 mAdc, I_B = 5.0 mAdc)			–	0.3	
(I_C = –10 mAdc, I_B = –1.0 mAdc)	MMBT3906WT1, SMMBT3906WT1		–	–0.25	
(I_C = –50 mAdc, I_B = –5.0 mAdc)			–	–0.4	
Base – Emitter Saturation Voltage		$V_{BE(sat)}$			Vdc
(I_C = 10 mAdc, I_B = 1.0 mAdc)	MMBT3904WT1, SMMBT3904WT1		0.65	0.85	
(I_C = 50 mAdc, I_B = 5.0 mAdc)			–	0.95	
(I_C = –10 mAdc, I_B = –1.0 mAdc)	MMBT3906WT1, SMMBT3906WT1		–0.65	–0.85	
(I_C = –50 mAdc, I_B = –5.0 mAdc)			–	–0.95	

2. Pulse Test: Pulse Width ≤ 300 μs; Duty Cycle ≤ 2.0%.

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted) (Continued)

Characteristic		Symbol	Min	Max	Unit
SMALL−SIGNAL CHARACTERISTICS					
Current−Gain − Bandwidth Product		f_T			MHz
(I_C = 10 mAdc, V_{CE} = 20 Vdc, f = 100 MHz)	MMBT3904WT1, SMMBT3904WT1		300	−	
(I_C = −10 mAdc, V_{CE} = −20 Vdc, f = 100 MHz)	MMBT3906WT1, SMMBT3906WT1		250	−	
Output Capacitance		C_{obo}			pF
(V_{CB} = 5.0 Vdc, I_E = 0, f = 1.0 MHz)	MMBT3904WT1, SMMBT3904WT1		−	4.0	
(V_{CB} = −5.0 Vdc, I_E = 0, f = 1.0 MHz)	MMBT3906WT1, SMMBT3906WT1		−	4.5	
Input Capacitance		C_{ibo}			pF
(V_{EB} = 0.5 Vdc, I_C = 0, f = 1.0 MHz)	MMBT3904WT1, SMMBT3904WT1		−	8.0	
(V_{EB} = −0.5 Vdc, I_C = 0, f = 1.0 MHz)	MMBT3906WT1, SMMBT3906WT1		−	10.0	
Input Impedance		h_{ie}			k Ω
(V_{CE} = 10 Vdc, I_C = 1.0 mAdc, f = 1.0 kHz)	MMBT3904WT1, SMMBT3904WT1		1.0	10	
(V_{CE} = −10 Vdc, I_C = −1.0 mAdc, f = 1.0 kHz)	MMBT3906WT1, SMMBT3906WT1		2.0	12	
Voltage Feedback Ratio		h_{re}			X 10^{-4}
(V_{CE} = 10 Vdc, I_C = 1.0 mAdc, f = 1.0 kHz)	MMBT3904WT1, SMMBT3904WT1		0.5	8.0	
(V_{CE} = −10 Vdc, I_C = −1.0 mAdc, f = 1.0 kHz)	MMBT3906WT1, SMMBT3906WT1		0.1	10	
Small−Signal Current Gain		h_{fe}			−
(V_{CE} = 10 Vdc, I_C = 1.0 mAdc, f = 1.0 kHz)	MMBT3904WT1, SMMBT3904WT1		100	400	
(V_{CE} = −10 Vdc, I_C = −1.0 mAdc, f = 1.0 kHz)	MMBT3906WT1, SMMBT3906WT1		100	400	
Output Admittance		h_{oe}			μmhos
(V_{CE} = 10 Vdc, I_C = 1.0 mAdc, f = 1.0 kHz)	MMBT3904WT1, SMMBT3904WT1		1.0	40	
(V_{CE} = −10 Vdc, I_C = −1.0 mAdc, f = 1.0 kHz)	MMBT3906WT1, SMMBT3906WT1		3.0	60	
Noise Figure		NF			dB
(V_{CE} = 5.0 Vdc, I_C = 100 μAdc, R_S = 1.0 k Ω, f = 1.0 kHz)	MMBT3904WT1, SMMBT3904WT1		−	5.0	
(V_{CE} = −5.0 Vdc, I_C = −100 μAdc, R_S = 1.0 k Ω, f = 1.0 kHz)	MMBT3906WT1, SMMBT3906WT1		−	4.0	

SWITCHING CHARACTERISTICS

Characteristic	Condition		Symbol	Min	Max	Unit
Delay Time	(V_{CC} = 3.0 Vdc, V_{BE} = −0.5 Vdc)	MMBT3904WT1, SMMBT3904WT1	t_d	−	35	ns
	(V_{CC} = −3.0 Vdc, V_{BE} = 0.5 Vdc)	MMBT3906WT1, SMMBT3906WT1		−	35	
Rise Time	(I_C = 10 mAdc, I_{B1} = 1.0 mAdc)	MMBT3904WT1, SMMBT3904WT1	t_r	−	35	
	(I_C = −10 mAdc, I_{B1} = −1.0 mAdc)	MMBT3906WT1, SMMBT3906WT1		−	35	
Storage Time	(V_{CC} = 3.0 Vdc, I_C = 10 mAdc)	MMBT3904WT1, SMMBT3904WT1	t_s	−	200	ns
	(V_{CC} = −3.0 Vdc, I_C = −10 mAdc)	MMBT3906WT1, SMMBT3906WT1		−	225	
Fall Time	(I_{B1} = I_{B2} = 1.0 mAdc)	MMBT3904WT1, SMMBT3904WT1	t_f	−	50	
	(I_{B1} = I_{B2} = −1.0 mAdc)	MMBT3906WT1, SMMBT3906WT1		−	75	





* Total shunt capacitance of test jig and connectors

Figure 1. Delay and Rise Time Equivalent Test Circuit

Figure 2. Storage and Fall Time Equivalent Test Circuit

TYPICAL TRANSIENT CHARACTERISTICS



Figure 3. Turn – On Time



Figure 4. Rise Time



Figure 5. Storage Time



Figure 6. Fall Time

TYPICAL AUDIO SMALL–SIGNAL CHARACTERISTICS NOISE FIGURE VARIATIONS

(V_{CE} = 5.0 VDC, T_A = 25°C, BANDWIDTH = 1.0 HZ)



Figure 7. Noise Figure



Figure 8. Noise Figure

H PARAMETERS

(V_{CE} = 10 VDC, F = 1.0 KHZ, T_A = 25°C)



Figure 9. Current Gain



Figure 10. Output Admittance



Figure 11. Input Impedance



Figure 12. Voltage Feedback Ratio

TYPICAL STATIC CHARACTERISTICS



Figure 13. DC Current Gain



Figure 14. Collector Saturation Region



Figure 15. Collector Emitter Saturation Voltage vs. Collector Current



Figure 16. Base Emitter Saturation Voltage vs. Collector Current



Figure 17. Base Emitter Voltage vs. Collector Current



Figure 18. Temperature Coefficients



Figure 19. Capacitance



Figure 20. Current Gain Bandwidth Product vs. Collector Current



Figure 21. Safe Operating Area

MMBT3906WT1, SMMBT3906WT1





* Total shunt capacitance of test jig and connectors

Figure 22. Delay and Rise Time Equivalent Test Circuit

Figure 23. Storage and Fall Time Equivalent Test Circuit

TYPICAL TRANSIENT CHARACTERISTICS



Figure 24. Turn−On Time

Figure 25. Fall Time

TYPICAL AUDIO SMALL−SIGNAL CHARACTERISTICS
NOISE FIGURE VARIATIONS

(V_{CE} = −5.0 VDC, T_A = 25°C, BANDWIDTH = 1.0 HZ)





Figure 26.

Figure 27.

H PARAMETERS

(V_{CE} = −10 VDC, F = 1.0 KHZ, T_A = 25°C)



Figure 28. Current Gain



Figure 29. Output Admittance



Figure 30. Input Impedance



Figure 31. Voltage Feedback Ratio

STATIC CHARACTERISTICS



Figure 32. DC Current Gain



Figure 33. Collector Saturation Region



Figure 34. Collector Emitter Saturation Voltage vs. Collector Current



Figure 35. Base Emitter Saturation Voltage vs. Collector Current



Figure 36. Base Emitter Voltage vs. Collector Current



Figure 37. Temperature Coefficients



Figure 38. Capacitance



Figure 39. Current Gain Bandwidth Product vs. Collector Current



Figure 40. Safe Operating Area



SCALE 4:1

SC−70 (SOT−323)
CASE 419
ISSUE R

DATE 11 OCT 2022



NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH

	MILLIMETERS			INCHES		
DIM	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A	0.80	0.90	1.00	0.032	0.035	0.040
A1	0.00	0.05	0.10	0.000	0.002	0.004
A2	0.70 REF			0.028 BSC		
b	0.30	0.35	0.40	0.012	0.014	0.016
c	0.10	0.18	0.25	0.004	0.007	0.010
D	1.80	2.00	2.20	0.071	0.080	0.087
E	1.15	1.24	1.35	0.045	0.049	0.053
e	1.20	1.30	1.40	0.047	0.051	0.055
e1	0.65 BSC			0.026 BSC		
L	0.20	0.38	0.56	0.008	0.015	0.022
H_E	2.00	2.10	2.40	0.079	0.083	0.095

GENERIC MARKING DIAGRAM



XX = Specific Device Code
M = Date Code
▪ = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.



* For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

SOLDERING FOOTPRINT

STYLE 1:
CANCELLED

STYLE 2:
PIN 1. ANODE
2. N.C.
3. CATHODE

STYLE 3:
PIN 1. BASE
2. EMITTER
3. COLLECTOR

STYLE 4:
PIN 1. CATHODE
2. CATHODE
3. ANODE

STYLE 5:
PIN 1. ANODE
2. ANODE
3. CATHODE

STYLE 6:
PIN 1. EMITTER
2. BASE
3. COLLECTOR

STYLE 7:
PIN 1. BASE
2. EMITTER
3. COLLECTOR

STYLE 8:
PIN 1. GATE
2. SOURCE
3. DRAIN

STYLE 9:
PIN 1. ANODE
2. CATHODE
3. CATHODE−ANODE

STYLE 10:
PIN 1. CATHODE
2. ANODE
3. ANODE−CATHODE

STYLE 11:
PIN 1. CATHODE
2. CATHODE
3. CATHODE

DOCUMENT NUMBER:	**98ASB42819B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**SC−70 (SOT−323)**	**PAGE 1 OF 1**

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales