
((1)))Ro'Tag





Ro'Tag D5 UHF

This miniature UHF tag is used for harsh environmental conditions and designed for mounting on metal surface.

Key features

- Round tag, diameter 5mm
- FR4 packaging
- Metal compatible

Applications

Small item tagging, tool management solutions, aircraft and automotive part tagging...

Functional specifications

•	
Туре	UHF
Frequency	867MHz or 915MHz+/-13MHz (Contact reading)
Air interface protocol	EPC Global Class1Gen2; ISO 18000-6C
IC Type	Ucode 8
Memory	EPC: 128 bits, TID: 96bits, user memory: 0bits
Data retention	20 years
Functionalities	Read/write
Write cycles	100,000 cycles

Physical specifications

Front side

Dimensions	Diameter 5mm, thickness COB(include resin)1.0mm+/-0.02mm; FR4 material:0.45mm+/-0.02mm	
Material	FR4+black resin protection	
Metal compatible	Yes	
Fixing method	Glue	
Packing	Packed by sheet, 100pcs/	



Packaging

Back side



Environmental and industry compliance

Temperature	-15°C to +75°C

Item code

RTD5UHF1779EU	Ro'Tag D5 UHF, Ucode8, noir, EU	
---------------	---------------------------------	--

V2.2

Non-contractual datasheet