# Active Noise Control of Speech in Headphones

using Linear Prediction

16. december 2016

Kasper Kiis Jensen, Maxime Démurger Oliver Palmhøj Jokumsen, Christian Claumarch Mikkel Krogh Simonsen 16gr761@es.aau.dk

Acoustics and Audio Technology - Fall 2016
Department of Electronic Systems
Aalborg University
Denmark





Group 761

#### stroductio

What is Active No Control (ANC)

Present cons headphones

#### Method:

Adaptive Filtered-x leas mean squares FIR algorithm

Wiener filteri

#### Results

Simulatio

### Computati

Computation

Listen

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University Denmark

### Introduction

What is Active Noise Control (ANC) Present consumer headphones

### Methods

Adaptive Filtered-x least mean squares FIR algorithm Wiener filtering

### Results

Simulation

### Discussion

Computation

## Conclusion

Listen

Introduction

What is Active Noise Control (ANC)

Present consum

#### Methods

Adaptive Filtered-x leas mean squares FIR algorithm

Wiener filterin

Result

Simulation


Computation

Conclusio Listen

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University Denmark

- ► The basic theory of ANC
  - ▶ 250 Hz
  - ▶ 2500 Hz

- Original signal
- - Counterphase signal
- Error



Group 761

#### Introductio

What is Active Noise Control (ANC)

Present consum

#### Methods

Adaptive Filtered-x leasemean squares FIR

Wiener filteri

#### Regulte

Simulatio

#### Discussio


Computation

Conclusi

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University Denmark

## ► Feedforward system

- ► 1: Reference microphone
- ► 2: Headphone loudspeaker
- ► 3: Error mirophone
- ► 4: Digital signal Processor (DSP)



#### Introduction

What is Active Noise Control (ANC)

Present consun

#### Methods

Adaptive Filtered-x leas mean squares FIR algorithm

Amplitude

Wiener filteri

#### Result

Simulation

#### Computation


Computatio


Listen

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University ► Counter phase signal delayed 10 samples

- ▶ 250 Hz
- ▶ 2500 Hz

- Original signal
- - Counterphase signal
- Error







Group 761

#### ntroduction

What is Active Noise Control (ANC)

Present consu

#### Methods

Adaptive Filtered-x leas mean squares FIR algorithm

Wiener filterin

#### Results

Simulation

#### Discussion

Computation

### Conclusion

Acoustics and Audio

Technology
Dept. of Electronic Systems
Aalborg University
Denmark

► Conversion delay



Group 761

#### Introduction

What is Active No Control (ANC)

Present consumer

Adaptive Filtered-x leas mean squares FIR

Wiener filterin

#### Regulto

Simulation

#### Discussion

Conclusio

Listen

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University Denmark ▶ How well does the consumer headphones attenuate?

► Denon AH-GC20

2.200 kr (2016)

► Bose QC25


2.799 kr (2016)

► Bose QC15

2.696 kr (2011)

► B&O H8

3.495 kr (2016)





Group 761

#### Introduction

What is Active Nois Control (ANC)

Present consumer

#### Methods

Adaptive Filtered-x leas mean squares FIR algorithm

Wiener filterin

#### Results

Simulation

#### Discussion

Computation

Conclusio

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University Denmark ▶ Conversion delay

# Mikkel for president!

