Active Noise Control of Speech in Headphones
using Linear Prediction

December 22nd 2016

Christian Claumarch, Kasper Kiis Jensen
Maxime Démurger, Mikkel Krogh Simonsen
Oliver Palmhøj Jokumsen
16gr761@es.aau.dk

Acoustics and Audio Technology - Fall 2016
Department of Electronic Systems
Aalborg University
Denmark

AALBORG UNIVERSITY
DENMARK

Agenda

- The basic theory of ANC
  - 250 Hz
  - 2500 Hz



- Headphone cups attenuate high frequencies passively
- Lower frequencies must be attenuated actively
- Feedforward system
  - 1: Reference microphone
  - 2: Headphone loudspeaker
  - 3: Error microphone
  - 4: Digital signal Processor (DSP)



- Problem with feedforward
- Sampling and reconstruction delay
  - Anti Aliasing filter
  - Reconstructions filter
- The measured delay of a Σ/Δ-converter - TLV320AIC3204
- Spacing between microphones
  - Min: 75.5 mm
  - Max: 302 mm

f_s [kHz]	48	96	192
Delay [μs]	900	450	225
Delay [samples]	43	43	43

- Counterphase signal delayed 10 samples
  - 250 Hz
  - 2500 Hz



Introduction
Speech vs. Periodic Noise

- Periodic noise is *easy* to cancel
- Signal characteristics
  - Periodic signals
    - Wide Sense Stationary (WSS)
  - Speech Signals
    - Quasiperiodic
    - 50 Hz – 4000 Hz
    - Can be assumed WSS for 20 *m*s – 30 *m*s
- Speech noise is *difficult* to cancel

- How well does the consumer headphones ANC attenuate?
  - Denon AH-GC20 2.200 kr (2016)
  - Bose QC25 2.799 kr (2016)
  - Bose QC15 2.696 kr (2011)
  - BeoPlay H8 3.495 kr (2016)



- ANC ideally attenuate infinitely
- Delays are introduced by sampling and reconstruction
- Periodic signals can be attenuated infinitely
- Speech signals are not attenuated very well

Combining a Feedforward ANC Algorithm With a Linear Prediction (LP) Scheme to Compensate for Delay.

- Control filter
  - Transfer function from (1) to (2)
  - Adaptive
- Cancelation path
  - Transfer function from (2) to (3)
  - Linear time-invariant
- Adaptive FXLMS-algorithm
  - Optimization problem



- Auto Correlation Function estimation
  - Framelength N
  - Overlap O
- Wiener-Hopf equation: $\hat{R}\bar{\hat{a}} = -\bar{\hat{r}}$
  - Inverting matrix
  - Levinson-Durbin
- Wiener filtering in cascade
  - Prediction length P



- Multirate processing for reducing conversion delay
  - High sample rate
  - Low processing rate
- Smaller prediction length
  - 10 instead of 43

f_s [kHz]	48	96	192
Delay [μs]	900	450	225
Delay [samples]	43	43	43

- Input for control filter and CP
  - $x[n]$
  - $\hat{x}[n+P]$



- Delays are introduced due to sampling and reconstruction
- Delays are reduced using multirate processing
- Compensation by Linear Prediction using Wiener filtering
- Noise cancelling using a feedforward FXLMS-algorithm

- Simulink
- Archimedes Project
- Prediction Gain
- Filter-banks vs. Fourier transform
- Listen to results

- Prediction order P = 43
- Optimal parameters
  - Framelength N = 1600
  - Overlap O = 1500
- Prediction Gain PG = 5.4 dB



- Prediction order P = 10
- Optimal parameters
  - Framelength N = 1200
  - Overlap O = 1100
- Prediction Gain PG = 10 dB



Simulation Results
Attenuation Performance

- ANC attenuation with varying system delay
  - Feedforward LP FXLMS
  - Feedforward FXLMS



- Frequency response
  - Feedforward LP FXLMS
  - Feedforward FXLMS



- Proof of concept
- Computational cost of system (instructions per sample)
  - Linear Prediction: > 50,000
  - Feedforward FXLMS: > 4,000
  - Multirate: < 100

Questions?

AALBORG UNIVERSITY
DENMARK