Active Noise Control of Speech in Headphones

using Linear Prediction

22. december 2016

Christian Claumarch, Kasper Kiis Jensen Maxime Démurger, Mikkel Krogh Simonsen Oliver Palmhøj Jokumsen 16gr761@es.aau.dk

> Acoustics and Audio Technology - Fall 2016 Department of Electronic Systems Aalborg University Denmark





Group 761

Introduction

What is Active No Control (ANC)

Problem of A

Methods

Feedforward FXL

Multirate Processing

Combined syste

Simulations Result

Linear Predict

Attenuation Performan

Discussion

Computational Cos

Introduction

What is Active Noise Control (ANC)

Problem of ANC

Methods

Feedforward FXLMS

Linear Prediction

Multirate Processing

Combined system

Simulations Results

Linear Prediction Parameters

Attenuation Performance

Discussion

Computational Cost

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University Denmark



ntroduction

What is Active Noise Control (ANC)

Problem of AN

Methods

Feedforward FXLMS

Linear Prediction

Combined system

Simulations Results

Linear Predict

Attenuation Performan

Discussion

Computational Cos


Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University

20

► The basic theory of ANC

- ▶ 250 Hz
- ▶ 2500 Hz

- Original signal
- - Counterphase signal
- Error





ntroduction

What is Active Noise Control (ANC)

Problem of All

ivietnous

Feedforward FXLN

Multirate Processing

Simulations Results

Linear Prediction Parameters


Attenuation Performar

Discussio

Computational Cos

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University

- Headphone cups attenuate high frequencies passively
- ► Lower frequencies must be attenuated actively
- ▶ Feedforward system
 - ► 1: Reference microphone
 - ► 2: Headphone loudspeaker
 - ► 3: Error mirophone
 - ► 4: Digital signal Processor (DSP)





oduction

What is Active Noi Control (ANC)

Problem of ANC

.

Feedforward FXI

Linear Prediction

Combined syste

Simulations Resu

Linear Prediction
Parameters
Attanuation Borforman

Di-----

Computational Cos

Feedforward problem

- Sampling and reconstruction delay.
 - ► Anti Aliasing filter
 - Reconstructions filter
- ► The measured delay of a Sigma Delta converter TLV320AIC3204
- ► Spacing between microphones

► Min: 75.5 *m*m

► Max: 302 *m*m

f_s [kHz]	48	96	192
Delay [μs]	900	450	225
Delay [samples]	43	43	43

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University

Group 761

ntroduction

What is Active No

Problem of ANC

Methods

Feedforward FXLMS

Linear Prediction

Combined syste

Simulations Results

Amplitude

20

Linear Predict

Attenuation Performan

Discussion


Computational Cos


Acoustics and Audio
Technology
Dept. of Electronic Systems
Aalborg University
Denmark

► Counterphase signal delayed 10 samples

- ▶ 250 Hz
- ► 2500 Hz

- Original signal
- - Counterphase signal
- Error







Group 761

Introduction

What is Active No

Problem of ANC

Foodforward EXLI

Feedlorward FXLM

Multirate Processin

Combined evet

Cimulations Door

Simulations Result

Linear Prediction

Attenuation Performan

Discussion

Computational Cos

Acoustics and Audio
Technology
Dept. of Electronic Systems
Aalborg University
Denmark

- ► Periodic noise is easy to cancel
- ► Signal Characteristics
 - ► Periodic Signals
 - ► Strict Sense Stationary (SSS)
 - ► Speech Signals
 - Quasiperiodic
 - ► 50 Hz 4000 Hz
 - ► 50 Hz 4000 Hz
 - ▶ Can be assumed Wide Sense Stationary (WSS) for 20 ms 30 ms
- Speech noise is difficult to cancel



Introduction

What is Active Nois Control (ANC)

Problem of ANC

Methode

Enedforward EVI MS

Linear Prediction

Combined syste

Simulations Results

Linear Predic Parameters

Attenuation Performar

Discussion

Computational Co.

Acoustics and Audio
Technology
Dept. of Electronic Systems
Aalborg University
Depmark

20

▶ How well does the consumer headphones attenuate?

► Denon AH-GC20

2.200 kr (2016)

Bose QC25


2.799 kr (2016)

► Bose QC15

2.696 kr (2011)

▶ BeoPlay H8

3.495 kr (2016)





Group 761

Problem of ANC

Acoustics and Audio Technology Dept. of Electronic Systems Aalhorg University Denmark

- ► ANC ideally attenuate infinitely
- Delays are introduced by sampling and reconstruction
- ► Periodic signals can be attenuated infinitely
- ► Speech signals are not attenuated very well



Group 761

Introduction

What is Active Noise Control (ANC)

Problem of ANC

Foodlanged EVI MC

Feedforward FXLMS

Multirate Processi

Combined system

Simulations Results

Linear Prediction

Attenuation Performance

Discussion

Computational Cos

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University Combining a feedforward ANC algorithm with a Linear prediction (LP) scheme to compensate for delay.



Introductio

What is Active Noi Control (ANC)

Problem of A

Method

Feedforward FXLMS

Linear Prediction

Multirate Processing

Multirate Processing

Simulations Resu

Linear Prediction

Attenuation Performan

Discussio


Computational Cos

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University

20

► Control filter

- ► Transfer function from (1) to (2)
- Adaptive
- Cancelation path
 - ► Transfer function from (2) to (3)
 - ▶ Linear time-invariant
- ► Adaptive FXLMS-algorithm
 - ► Optimization problem





ntroductio

What is Active Noi Control (ANC)

Problem of Al

Methods

Feedforward FXL

Linear Prediction

Combined eveter

Simulations Results

Linear Prediction


Attenuation Performan

Discussion

Computational Co

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University ► Auto Correlation Function estimation

- ► Framelength N
- ▶ Overlap O
- Wiener-hopf equation: $\hat{R}\bar{\hat{a}} = -\bar{\hat{r}}$
 - ► Inverting matrix
 - ► Levinson-Durbin
- ► Wiener filtering in cascade
 - ► Prediction length P





Multirate Processing

Simulations Results

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University

► Multirate Processing for reducing conversion delay

- ► High sample rate
- ► Low processing rate
- ► Smaller prediction length
 - ▶ 10 instead of 43

f_s [kHz]	48	96	192
Delay [μs]	900	450	225
Delay [samples]	43	43	43

Denmark



Combined system


Simulations Results

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University Denmark

20

► Input for control filter and CP

x[n]
 x̂[n+P]





Combined system

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University Denmark

Delays are introduced due to sampling and reconstruction

- Delays are reduced using multirate processing
- ► Compensation by Linear Prediction using Wiener filtering
- ► Noise cancelling using a feedforward FXLMS-algorithm



Group 761

ntroduction

What is Active Nois Control (ANC)

Problem of A

Methods

Feedforward FXLI

Linear Prediction

Combined evet

Simulations Results

ear Prediction

Attenuation Performance

Discussion

Computational Co

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University

- ► Simulink
- ► Archimedes Project
- Prediction Gain
- ► Filter banks vs Fourier transform
- Listening tests



Introductio

What is Active Nois Control (ANC)

Problem of All

Methods

Feedforward FX

Linear Prediction

Multirate Processing

Combined syst

Simulations Results

Linear Prediction Parameters

Attenuation Performa


Discussion

Computational Co

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University



- ▶ Optimal parameters
 - ► Framelength N = 1600
 - ► Overlap O = 1500
- ► Prediction Gain PG = 5.4 dB





Introduction

What is Active Noi Control (ANC)

Problem of All

Methods

Feedforward FXI

Linear Prediction

Combined syst

Simulations Results

Linear Prediction Parameters

Attenuation Performan


Discussion

Computational Co

Acoustics and Audio
Technology
Dept. of Electronic Systems
Aalborg University
Denmark



- ▶ Optimal parameters
 - ► Framelength N = 1200
 - ► Overlap O = 1100
- ► Prediction Gain PG = 10 dB





Introductio

What is Active No Control (ANC)

Problem of AN

Methods

Feedforward EXLN

Linear Prediction

Multirate Processing

Simulations Results

Linear Predic


Attenuation Performance

Discussion

Computational Co.

 ANC attenuation with varying system delay

- ► Feedforward FXLMS
- ► Feedforward LP FXLMS



Acoustics and Audio
Technology
Dept. of Electronic Systems
Aalborg University
Denmark




Simulations Results

Attenuation Performance

► Frequency response

- ► Feedforward FXLMS
- ► Feedforward LP FXLMS





Group 761

Simulations Results

Computational Cost

20

► Computational cost of System (instructions pr. sample) ► Linear Prediction: 55000

► Feedforward FXLMS: 4000

► Multirate: < 100

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University Denmark

Questions?

