# Active Noise Control of Speech in Headphones

using Linear Prediction

17. december 2016

Kasper Kiis Jensen, Maxime Démurger Oliver Palmhøj Jokumsen, Christian Claumarch Mikkel Krogh Simonsen 16gr761@es.aau.dk

> Acoustics and Audio Technology - Fall 2016 Department of Electronic Systems Aalborg University Denmark





Group 761

Introduction

What is Active No Control (ANC)

Problem of Al

Present con:

headphones

Methods

Feedforward FXLM

Linear Predict

Combined sys

Simulations Results

Computation

Conclus

Listen

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University Denmark

12

Introduction

What is Active Noise Control (ANC)

Problem of ANC

Present consumer headphones

Methods

Feedforward FXLMS

Linear Prediction

Combined system

Simulations Results

Discussion

Computation

Conclusion

Listen



. .

What is Active Noise

Control (ANC)

Problem of ANC

Present consu

## Methods

Feedforward FXLMS

Linear Predicti

,

Omidiations result

Computatio

Liston


Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University

12

► The basic theory of ANC

- ▶ 250 Hz
- ▶ 2500 Hz

- Original signal
- - Counterphase signal
- Error





Group 761

## ntroduction

What is Active Noise Control (ANC)

Problem of AN

Present cons

## Methods

Feedforward FXLMS

Linear Predicti

Simulations Results

### Simulations Result

Discussion

Computation

0011010


Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University ► Feedforward system

► 1: Reference microphone

► 2: Headphone loudspeaker

3: Error mirophone

► 4: Digital signal Processor (DSP)





nduction

What is Active No

### Problem of ANC

Present consu

## Mathods

Feedforward FXLM

Combined ou

Simulations Results

Discussion

Computation

Lieton

► Feedforward problem

- Sampling and reconstruction delay.
  - ► Anti Aliasing filter
  - ► Reconstructions filter
- ► The measured delay of a Sigma Delta converter TLV320AIC3204
- Spacing between microphones

► Min: 75.5 *m*m

► Max: 302 mm

$f_s[kHz]$	48	96	192
Delay [μs]	900	450	225
Delay [samples]	43	43	43

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University



Group 761

## ntroductio

What is Active No

## Problem of ANC

Present consul

## Methods

Feedforward FXLMS

Linear Fredicti

Simulations Bosults

Amplitude

12

## Olificiations riesur


Computati


Conclusio

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University ► Counter phase signal delayed 10 samples

- ▶ 250 Hz
- ▶ 2500 Hz

- Original signal
- - Counterphase signal
- Error







Group 761

### Problem of ANC

Simulations Results

▶ Signal Characteristics

- ▶ Periodic Signals
  - Periodic

  - ► Strict Sense Stationary (SSS)
- ► Speech Signals
  - Quasiperiodic
  - ► Can be assumed Wide Sense Stationary for 20 ms 30 ms
- Periodic noise is easy to cancel
- Speech noise is difficult to cancel

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University Denmark



Group 761

## Introduction

What is Active Noi

Problem of Al

Present consumer

## Mathods

Feedforward FXLMS

Linear Prediction

Combined eve

## Simulations Results

Computation

Conclusion

Listen

Acoustics and Audio
Technology
Dept. of Electronic Systems
Aalborg University
Depmark

▶ How well does the consumer headphones attenuate?

► Denon AH-GC20

2.200 kr (2016)

Bose QC25


2.799 kr (2016)

► Bose QC15

2.696 kr (2011)

► BeoPlay H8

3.495 kr (2016)



Frequency [Hz]



Group 761

What is Active Noise

Control (ANC)

Problem of ANC

Present consumer headphones

Foodforward EVI M

Linear Prediction

Lillear Fredictio

Simulations Results

Simulations Results

Discussion

....

Linton

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University

12

Combining a feedforward Filtered-x Least Mean Square (FXLMS) algorithm with a Linear prediction (LP) scheme to compensate for delay.



### Introductio

What is Active Noi

Problem of A

Present consu headphones

### Mathad

### Feedforward EXLMS

Linear Prediction

. . . . .

Simulations Results

## Simulations Resul


## Computation

Computation

Linton

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University ► Control filter

- ► Transfer function from (1) to (2)
- Adaptive
- Cancelation path
  - ► Transfer function from (2) to (3)
  - ▶ Linear Time Invariant
- ► Adaptive FXLMS Algorithm
  - Optimization problem





## Methods

### Linear Prediction


## Simulations Results

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University Denmark

12

▶ Auto Correlation Function estimation.

- ► Frame length N
- Overlap O
- Wiener hopf equation:  $\hat{R}\bar{a} = -\bar{\hat{r}}_{\nu}$ 
  - Inverting matrix
  - ► Levinson Durbin
- ▶ Wiener filtering in cascade
  - Prediction order P





Group 761

## Introductio

What is Active Nois

Problem of Al

Present consum

## Methods

Feedforward FXLMS

Linear Prediction

Combined system

.

Simulations Results

Computation

----

Lister

Acoustics and Audio
Technology
Dept. of Electronic Systems
Aalborg University
Denmark



Group 761

## Methods

Simulations Results

Acoustics and Audio Technology Dept. of Electronic Systems Aalborg University Denmark

# Questions?

