

The image shows the Arduino IDE interface with the following components:

- Top Bar:** Displays the Arduino IDE logo and the text "Arduino IDE 2.3.1.0".
- Menu Bar:** Includes "File", "Edit", "Sketch", "Tools", and "Help".
- Toolbar:** Contains icons for opening files, saving, and running the sketch.
- Project Name:** "plantillaAdafruitIO" is shown in the top left.
- Sketch Name:** "plantillaAdafruitIO.ino" is shown in the top left of the editor.
- Code Editor:** Contains the following C++ code:

```
14/ }
148
149 Serial.print("Connecting to MQTT... ");
150
151 uint8_t retries = 3;
152 while ((ret = mqtt.connect()) != 0) { // connect will return 0 if
153     Serial.println(mqtt.connectErrorString(ret));
154     Serial.println("Retrying MQTT connection in 5 seconds...");
155     mqtt.disconnect();
156     delay(5000); // wait 5 seconds
157     retries--;
158     if (retries == 0) {
159         // basically die and wait for WDT to reset me
160         while (1);
161     }
162 }
163
164 Serial.println("MQTT Connected!");
165 }
166
```
- Output Window:** Shows the "Serial Monitor" output. The message "Message (Enter to send message to 'ESP32 Dev Module' on 'COM5')" is displayed at the top. Below it, the following messages are shown:

```
Sending val 11 to test feed...OK!
Sending val 12 to test feed...OK!
Sending val 13 to test feed...OK!
Sending val 14 to test feed...OK!
Sending val 15 to test feed...OK!
```

Created at	Value
2026/10/02 04:07:01PM	15
2026/10/02 04:06:59PM	14
2026/10/02 04:06:57PM	13
2026/10/02 04:06:55PM	12
2026/10/02 04:06:53PM	11
2026/10/02 04:06:51PM	10
2026/10/02 04:06:49PM	9
2026/10/02 04:06:47PM	8

