
Simple RSS Reader

1.1 Goal

Build an iOS app to let users read rss feeds.

We expect to receive:

- The code of the application
- A log with the important decisions and the process to develop the app (we may use the git commit comments for this)

In the next section we list the stories that need to be implemented in the application with the related API endpoints for each story.

Any question please, don't hesitate to ask the person who sent you the exercise.

1.2 Stories

1.2.1 As a User I want to register and login

POST http://167.99.162.146/users/register

Content-Type: application/json

```
{"user": "cacciaresi", "password": "cacciaresi"}
```

```
> {% client.global.set("auth_token", response.body.access_token); %}
```

```
{  
  "access_token": "eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9"  
}
```

POST http://167.99.162.146/users/login

Content-Type: application/json

```
{"user": "cacciaresi", "password": "cacciaresi"}
```

```
> {% client.global.set("auth_token", response.body.access_token); %}
```

```
{
```

```
"access_token": "eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9",  
"user_id": 16  
}
```

1.2.2 As a User I want to subscribe to a RSS feed

```
POST http://167.99.162.146/feeds/add
```

```
Authorization: Bearer {{auth_token}}
```

```
Content-Type: application/json
```

```
{"url": "http://contenidos.lanacion.com.ar/herramientas/rss/origen=2"}
```

```
HTTP/1.1 201 Created
```

```
Date: Fri, 21 Sep 2018 03:51:48 GMT
```

```
Server: WSGIServer/0.2 CPython/3.6.3
```

```
Content-Type: application/json
```

```
Vary: Accept
```

```
Allow: OPTIONS, POST
```

```
X-Frame-Options: SAMEORIGIN
```

```
Content-Length: 120
```

```
{  
  "id": 5,  
  "title": "Política - lanacion.com",  
  "url": "http://contenidos.lanacion.com.ar/herramientas/rss-origen=2"  
}
```

1.2.3 As a User I want to read the articles of my RSS feeds

```
GET http://167.99.162.146/feeds  
Authorization: Bearer {{auth_token}}  
Content-Type: application/json
```

```
GET http://167.99.162.146/feeds
```

```
HTTP/1.1 200 OK  
Date: Fri, 21 Sep 2018 03:52:12 GMT  
Server: WSGIServer/0.2 CPython/3.6.3  
Content-Type: application/json  
Vary: Accept  
Allow: OPTIONS, GET  
X-Frame-Options: SAMEORIGIN
```

Content-Length: 122

```
[  
  {  
    "id": 5,  
    "title": "Política - lanacion.com",  
    "url": "http://contenidos.lanacion.com.ar/herramientas/rss-origen=2"  
  }  
]
```

Response code: 200 (OK); Time: 49ms; Content length: 117 bytes

GET http://167.99.162.146/feeds/5/articles

Authorization: Bearer {{auth_token}}

Content-Type: application/json

GET http://167.99.162.146/feeds/5/articles

HTTP/1.1 200 OK

Date: Fri, 21 Sep 2018 03:56:27 GMT

Server: WSGIServer/0.2 CPython/3.6.3

Content-Type: application/json

Vary: Accept

Allow: GET, OPTIONS

X-Frame-Options: SAMEORIGIN

Content-Length: 3349

```
{
  "status": "200",
  "articles": [
    {
      "id": 148,
      "title": "El día que Néstor Kirchner expresó su rechazo a los fueros parlamentarios",
      "url": "http://www.lanacion.com.ar/2174110-el-dia-nestor-kirchner-expreso-su-rechazo",
      "summary": "",
      "content": null,
      "date": "2018-09-21T00:33:00Z",
      "read_by": [],
      "loaded": "2018-09-21T01:51:33.688710Z"
    },
    {
      "id": 149,
```

```
"title": "Presupuesto 2019: quiénes ganan y quiénes pierden con los cambios en el proyecto",
"url": "http://www.lanacion.com.ar/2174042-ganadores-perdedores-cambios-presupuesto",
"summary": "",
"content": null,
"date": "2018-09-21T00:11:00Z",
"read_by": [],
"loaded": "2018-09-21T01:51:33.701581Z"
}
]
}
```

Response code: 200 (OK); Time: 63ms; Content length: 3264 bytes

1.2.4 As a User I want to update/refresh a RSS feed

PUT http://167.99.162.146/feeds/5/refresh

Authorization: Bearer {{auth_token}}

Content-Type: application/json

PUT http://167.99.162.146/feeds/5/refresh

HTTP/1.1 200 OK

Date: Fri, 21 Sep 2018 03:57:06 GMT
Server: WSGIServer/0.2 CPython/3.6.3
Content-Type: application/json
Vary: Accept
Allow: PUT, OPTIONS
X-Frame-Options: SAMEORIGIN
Content-Length: 20

```
{  
  "new_articles": 10  
}
```

Response code: 200 (OK); Time: 207ms; Content length: 20 bytes

1.2.5 As a User I want to delete a RSS feed

DELETE http://167.99.162.146/feeds/5
Authorization: Bearer {{auth_token}}
Content-Type: application/json

DELETE http://167.99.162.146/feeds/5

HTTP/1.1 200 OK
Date: Fri, 21 Sep 2018 04:02:31 GMT
Server: WSGIServer/0.2 CPython/3.6.3
Content-Type: application/json
Vary: Accept
Allow: OPTIONS, DELETE
X-Frame-Options: SAMEORIGIN
Content-Length: 2

{}

Response code: 200 (OK); Time: 31ms; Content length: 2 bytes

1.2.6 As a User I want to mark an article of a RSS feed as read/unread

PUT http://167.99.162.146/feeds/5/articles/148/toggle_read
Authorization: Bearer {{auth_token}}
Content-Type: application/json

PUT http://167.99.162.146/feeds/5/articles/148/toggle_read

HTTP/1.1 200 OK
Date: Fri, 21 Sep 2018 03:57:32 GMT
Server: WSGIServer/0.2 CPython/3.6.3
Content-Type: application/json
Vary: Accept
Allow: PUT, OPTIONS
X-Frame-Options: SAMEORIGIN
Content-Length: 49

```
{  
  "article_id": 148,  
  "read_by_current_user": true  
}
```

Response code: 200 (OK); Time: 87ms; Content length: 49 bytes