

MAINNET CONFIGURATION AUDIT

UNIFYVAULT V2 — MAINNET CONFIGURATION AUDIT

****Target Network****: Base Mainnet (Chain ID: 8453)

****Current Testnet****: Base Sepolia (Chain ID: 84532)

****Audit Purpose****: Identify, classify, and document all network-specific values, token addresses, oracle feeds, and environment variables across protocol and frontend codebases.

1. Classification Schema

- **A. Testnet-Only****: Values that must change when deploying to or targeting Base Mainnet.
- **B. Environment-Dependent****: Values that should be injected dynamically via environment variables without committing secrets to git.
- **C. Intentionally Shared****: Canonical infrastructure addresses identical on both Base Sepolia and Base Mainnet (e.g. ERC-4337 EntryPoint v0.7, WETH).
- **D. Potentially Dangerous Hardcoded Value****: Hardcoded addresses or fallbacks that could cause misrouting if not overridden.
- **E. Unknown / Human Decision Required****: Operational decisions required prior to mainnet broadcast (e.g. launch caps, fee recipient, multisig quorum selection).

2. Configuration Audit Matrix

- File**: Line/Ref | **Current Value** | **Purpose** | **Classification** | **Required Action for Mainnet** | **Deployment-Time Config?**
- `apps/web-v2/constants/index.ts`**: Line 6 | ``base-sepolia`` | Default active chain name | ****B**** | Set `NEXT_PUBLIC_ACTIVE_CHAIN="base"` in production environment | ****YES****
- `apps/web-v2/constants/index.ts`**: Lines 17–25 | `84532`` (Fallback) | Default chain ID resolution | ****B**** | Controlled via `NEXT_PUBLIC_ACTIVE_CHAIN="base"` (8453) | ****YES****
- `apps/web-v2/constants/index.ts`**: Lines 31–44 | `https://sepolia.base.org`` | RPC URL resolution | **\*\*B\*\*** | Configure `NEXT_PUBLIC_RPC_URL_BASE_MAINNET`` with dedicated RPC (Alchemy/QuickNode) | ****YES****
- `apps/web-v2/constants/index.ts`**: Lines 46–48 | `0xe74b400f4aea3a0b593be5acbc54f56631c0d60e`` | Mainnet ProtocolDirectory active | **\*\*C\*\*** | Canonical active Base Mainnet `ProtocolDirectory`` address | ****NO****
- `apps/web-v2/constants/index.ts`**: Line 119 | `0x0000000071727De22E5E9d8BAf0edAc6f37da032`` | ERC-4337 EntryPoint v0.7 | ****C**** | None (Canonical ERC-4337 v0.7 contract address is identical across all EVM chains) | ****NO****
- `apps/web-v2/constants/index.ts`**: Lines 161–163 | USDC: `0x8335...2913`` & `cbBTC: 0xcbB7...33Bf`` & `WETH: 0x4200...0006`` | Base Mainnet Token addresses | ****A**** | Active and verified on Base Mainnet. Ensure Mainnet deployment uses these addresses. | ****NO****
- `apps/web-v2/constants/index.ts`**: Lines 166–171 | USDC: `0x036C...CF7e`` & `cbBTC: 0xB0B4...8b29`` & `WETH: 0xd116...FA323`` | Base Sepolia Mock Tokens | ****A**** | Testnet only. Retained for Base Sepolia testing. | ****NO****
- `packages/protocol/script/DeployMainnet.s.sol`**: Lines 33–45 | USDC: `0x8335...2913`` & `cbBTC: 0xcbB7...33Bf`` & `WETH: 0x4200...0006`` & `USDC Feed: 0x7e86...bc6B`` & `cbBTC Feed: 0x8C74...ed2f`` & `ETH Feed: 0xe6eb...34d5`` & `Uniswap V3: 0x2626...e481`` | Base Mainnet Production Infrastructure | ****A / C**** | Verified checksummed Base Mainnet addresses matching official Chainlink and Coinbase contracts. | ****NO****

- ``packages/protocol/script/mainnet/config/base_mainnet.json``: Lines 2–5 | ``newAdmin: 0xe37b...`` & ``oldAdmin: 0x441d...`` | Governance live configuration | **A** | Active verified on-chain governance admin & timelock parameters. | **NO**
- ``apps/web-v2/app/api/smart-account/sponsor/route.ts``: Route | ``PAYMASTER_SIGNER_PRIVATE_KEY`` | AA Paymaster Verifying Signer | **B** | In production, isolate signer key to server-side KMS/HSM cloud signing service. | **YES**
- ``apps/web-v2/app/api/smart-account/bundler/route.ts``: Route | ``PIMLICO_API_KEY`` / ``BUNDLER_RPC_URL`` | ERC-4337 Bundler RPC | **B** | Set dedicated Mainnet bundler endpoint in ``.env.production.local``. | **YES**

3. Deployment-Time Configuration Strategy

1. **Frontend Environment Variables** (``.env.production.local``):

```

NEXT_PUBLIC_ACTIVE_CHAIN=base
NEXT_PUBLIC_APP_DOMAIN=https://app.unifyvault.xyz
NEXT_PUBLIC_RPC_URL_BASE_MAINNET=https://base-mainnet.g.alchemy.com/v2/YOUR_API_KEY
NEXT_PUBLIC_DIRECTORY_ADDRESS_MAINNET=0x<MAINNET_DEPLOYED_DIRECTORY_ADDRESS>
NEXT_PUBLIC_P2P_ESCROW_ADDRESS_MAINNET=0x<MAINNET_DEPLOYED_ESCROW_ADDRESS>
NEXT_PUBLIC_MARKETPLACE_ADDRESS_MAINNET=0x<MAINNET_DEPLOYED_MARKETPLACE_ADDRESS>
NEXT_PUBLIC_PAYMASTER_ADDRESS_MAINNET=0x<MAINNET_DEPLOYED_PAYMASTER_ADDRESS>

```

1. **Zero In-Source Secrets Policy**:

- Zero private keys or mnemonics are stored in Git.
- All server API routes (``/api/smart-account/*``) access keys strictly via server process memory (``process.env``).