

Data Communication BLM3051



Furkan ÇAKMAK

1

Lecture Information Form - Weekly Subjects

BLM3051
Data
Communication
Week 3

Week	Date	Subjects
1	04.10.2022	Introduction to Data Communication Standards Used on Data Communication, Architectural models
2	11.10.2022	OSI Reference Model , Layers and Their Functions
3	18.10.2022	Signaling and Signal Encoding
4	25.10.2022	Parallel and Serial Transmission, Communication Media and Their Technical Specs., Multiplexing (TDM, FDM)
5	01.11.2022	Error Detection and Error Correction Techniques
6	08.11.2022	Data Link Control Techniques, Flow Control
7	15.11.2022	Asynchronous and Synchronous Data Link Protocols (BSC, HDLC)
8	22.11.2022	1. Vize Haftası
9	29.11.2022	LAN Technologies Continued, IEEE 802.4, 802.5, 802.11
10	06.12.2022	Connectionless and Connection Oriented Services, Switching
11	13.12.2022	Wide Area Networking Technologies (X.25, ISDN, FR, ATM, xDSL.)
12	20.12.2022	Communications Equipment's, TCP/IP Model, Security Issues
13	27.12.2022	Research Presentation 1
14	03.01.2022	Research Presentation 2

Furkan ÇAKMAK

2

Digital Data Transmission Techniques

BLM3051
Data
Communication

Week 4

- Medium specs;
 - Connector type to provide mechanical connection in the transmission medium
 - Number of wires
 - Signal type
 - Purpose
 - Frequency, amplitude and phase
- Parallel Transmission
- Serial Transmission


Furkan Çakmak

3

Parallel Transmission

BLM3051
Data
Communication

Week 4



N Wired Connection



Furkan Çakmak

4

Parallel Transmission - Con't

BLM3051
Data
Communication

Week 4



- Standard Parallel Interface
 - 155 kByte/sec
- ECP/EPP (Enhanced Parallel Port/Enhanced Capability Port)
 - 3 MByte/sec
- Maximum Cable Length: 7.5m

Furkan Çakmak


5

Parallel Transmission - Con't

BLM3051
Data
Communication

Week 4

- Laplink
- Interlink




Furkan Çakmak

6

Serial Transmission

BLM3051
Data
Communication
Week 4



Furkan Çakmak

7

Serial Transmission - Con't

BLM3051
Data
Communication
Week 4

- RS-232-C
 - 9 wires
 - RX
 - TX
 - GND
 - 6 x Flow Control Wire
 - 155 kbits/sec
 - 15 meters
 - NRZ-L
 - $(-15 \sim -5)V_{DC} \rightarrow 1$
 - $(+5 \sim +15)V_{DC} \rightarrow 0$
 - RS-422: 300 meters
- Asynchronous transmission in WAN
 - 2 wires
- Synchronous transmission in WAN
 - 4 wires

Furkan Çakmak

8

Asynchronous Serial Transmission

BLM3051
Data
Communication
Week 4

- Simple, Cheap
- The data arrival rhythm between the sides is not the same.
- It is not possible to tell when the incoming transmission started and when it ends
- Receiver and transmitter must agree on how long each bit will remain on the line.
- Start bit: 0, positive voltage
 - 8-N-1
 - $1 + 8 + 1 \rightarrow$ LSB
 - N: not parity bit
 - 7-E-1
 - $1 + 7 + 1$ (Even)
- Stop bit: 2-bits long


Furkan Çakmak

9

Asynchronous Serial Transmission - Con't

BLM3051
Data
Communication
Week 4

- Since the communication between the sender and receiver is not made simultaneously, there are **gaps** of variable duration between the bytes sent.




Furkan Çakmak

10

Asynchronous Serial Transmission - Con't

BLM3051
Data
Communication
Week 4

- Time skew
 - If the processing speed difference between the two sides is 5%
 - 8th -> 45%
- Dial-up
 - Carrier Signal



Furkan Çakmak

11

Synchronous Serial Transmission

BLM3051
Data
Communication
Week 4

- Much more big data transfer compare to Async within one transmission (>1000 byte)
- If there is no data transmission
 - A special bit sequence is sent in the line.
- In order for the information to be transferred properly, operations must be carried out depending on a common timing mark.
- Like an assembly line.
- Clock line: A different line
 - Clock pulse
 - Short distance transmissions

Furkan Çakmak

12

Synchronous Serial Transmission - Con't

BLM3051
Data
Communication
Week 4

- Logical Level Synchronization
 - Preamble Bit Array
 - Postamble Bit Array
 - Max 100 bits for control data.
 - HDLC (High Level Data Link Control)
 - 48 bits for control purposes.
 - Example
 - If we want to transfer 1000 characters in HDLC mode, how much bits send?
 - 1 character → 8 bit
 - 1000 characters → 1 block
 - Control data → 48-bit
 - 1 block → 8000 bit
 - $8000 + 48 \rightarrow 8048$ bits
 - Load of control data per bloc → $48 / 8048 \approx 0,6\%$

Furkan Çakmak

13

Asynchronous ST vs Synchronous ST

BLM3051
Data
Communication
Week 4

Synchronous	Asynchronous
+ Much more efficient usage + Better error control + High transmission speed	+ Simple + Cheap + Additional effort required for timing + Limited speed - Limited error control mechanism (parity) - 20% loss due to start / end bits

Furkan Çakmak

14

DTE-DCE Interfaces

BLM3051
Data
Communication
Week 4

- DCE (Data Circuit-Terminating Equipment)
 - Modem
- DTE (Data Terminal Equipment)
 - Computer
 - Printer
 - Fax
 - etc.



Furkan Çakmak

15

DTE-DCE Interfaces - Con't

BLM3051
Data
Communication
Week 4

- Standards between DTE and DCE
 - EIA
 - EIA-232
 - EIA-442
 - EIA-449
 - ITU-T
 - V.24
 - V.32
 - V.32bis
 - V.34
 - X.2
 - X.24


Furkan Çakmak

16

Transmission Medium

BLM3051
Data
Communication
Week 4

- Wire
- Light
- Radio Wave
- Guided and Unguided media




Furkan Çakmak

17

Guided Media

BLM3051
Data
Communication
Week 4

- Coaxial Cable
 - AUI (Attachement)
 - Ethernet
 - Thick: 10mm
 - Thin: 5mm
- Twisted pair
 - DGM (Data Grade)
 - CATs
 - 2-12 twist/step
 - Different Colors
 - There are 3 different types
 - UTP (Unshielded Twisted Pair)
 - 100m = 90m + 10m
 - ScTP/FTP (Screened Twisted Pair/Foiled Twisted Pair)
 - STP (Shielded Twisted Pair)



Furkan Çakmak

18

Guided Media - Con't

BLM3051
Data
Communication

Week 4

• UTP cables category criterias:

- Signal Frequency
- Wire length
- Correct connections
- Attenuation
- NEXT (Near-End Crosstalk)
- PSNEXT (Power Sum NEXT)
- FEXT (Far-End Crosstalk)
- ELFEXT (Equal Level FEXT)
- PSELFEXT (Power Sum ELFEXT)

• CAT 5e

- gigabit Ethernet
- 4 pieces of 2
- Propagation delay
 - Skew
 - Fastest - Slowest

AWG	Weight (kg/km)
22	2,895
23	2,295
24	1,820
26	1,145

Remote

RJ45 = Cat. 5e/6/6_A GG45 = Cat. 7/7_A

Furkan Çakmak

19

Classification of UTP Cables

BLM3051
Data
Communication

Week 4

Type	Usage Purpose	Freq. (MHz)	Connector Type ⁷⁴	Usage Area
Cat-1	Voice	1	6P2C / RJ-11	Voice / Phone
Cat-2	Voice - Data	4	8P8C / RJ-45	Voice / 4Mbps TokenRing / Terminal
Cat-3	Voice - Data	16	8P8C / RJ-45	Voice / 10Base-T / 25Mbps ATM
Cat-4	Data	20	8P8C / RJ-45	10Base-T / TokenRing
Cat-5	Data	100	8P8C / RJ-45	10Base-T / 100Base-T / ATM / CDDI
Cat-5e	Data	> 100	8P8C / RJ-45	100Base-T / 1000Base-T
Cat-6	Data	250	8P8C / RJ-45	1000Base-T / 10GBase-T@55m
Cat-6a ⁷⁵	Data	> 500	8P8C / RJ-45	10GBase-T
Cat-7	Data	600	8P8C / GG-45 ⁷⁶	10GBase-T
Cat-7a	Data	1000	8P8C / GG-45	40Gbps@50m / 100Gbps@15m
Cat-8	Data	> 1.200	Double Connectivity	> 40 Gbps@30-50m

Furkan Çakmak


20

Guided Media - Fiber Optic Cabels

BLM3051
Data
Communication

Week 4

- ~~Coaxial Cables~~
- ~~Twisted Pair Cables~~
- Fiber Optic Cables
 - 300.000 km/sec
 - ≥ 100 Gbps (reached 500 Gbps)
 - Core
 - Cladding
 - Primary buffer
 - Secondary buffer
 - Armor
 - Plastic Shield
- SMF (Single Mode Fiber)
- MMF (Multi Mode Fiber)



Furkan Çakmak

21

Guided Media - Fiber Optic Cabels - Con't

BLM3051
Data
Communication

Week 4

- Single Mode Fiber (SMF)
 - Core: $9\ \mu\text{m}$
 - Light wavelength: $1.3 - 1.5\ \mu\text{m}$
 - $1.3\ \mu\text{m} \approx 9\ \mu\text{m} \rightarrow$ Transmission is carried out as a single, unbreakable beam



Furkan Çakmak


22

Guided Media - Fiber Optic Cabels - Con't


BLM3051
Data
Communication

Week 4

Step Index



Grade Index



Furkan Çakmak

23

Guided Media - Fiber Optic Cabels - Con't

BLM3051
Data
Communication

Week 4



Furkan Çakmak

24

Guided Media - Fiber Optic Cabels - Con't

BLM3051
Data
Communication
Week 4

- Light sources used in fiber optic media:
 - LED (Light Emitting Diode)
 - Nonfocusable
 - ILD (Injection Laser Diode)
 - Focusable
 - Receiver side: fotodiod (Photosensitive cell)
 - It is a circuit element that can generate electrical signals depending on the strength of the light falling on it.

Furkan Çakmak

25

Advantages of Fiber Optic Cables over Copper Cables

BLM3051
Data
Communication
Week 4

- Broad Bandwidth
- Immunity to Electromagnetic Interference
- Attenuation
- Insulation
- Space Saving
- Security
 - Eavesdrop

Furkan Çakmak

26

Things to Consider When using Fiber Optic Cables

BLM3051
Data
Communication

Week 4

- The core parts of the fibers used at both ends must overlap exactly.
 - Attention should be paid to dirt, oil, dust and scratches.
 - Dirt, dust, etc. should be cleaned with air gun or alcohol.
 - Scratches should be polished and rounded.
- Fiber cables are fragile like glass and must be kept gently bent.
- When not in use, fiber cables should be stored with special headers to protect them from dust and scratches.
- The laser beam at the end of the fiber optic cable is dangerous to the eyes.

Furkan Çakmak

27

Unguided Media

BLM3051
Data
Communication



Week 4

- Technologies that aim to use the atmosphere:

- RF (Radio Frequency)
- Microwave
- IR (Infra Red)

- Ionosphere

- Ground propagation < 2 MHz
- Sky propagation 2-30 MHz
- Line of sight propagation > 30 MHz



Furkan Çakmak

28

Unguided Media - Radio Frequency

BLM3051
Data
Communication
Week 4

- 3 kHz - 1 GHz
- Television ve Radio
- Omnidirectional
- Antennas do not need to be aligned
- RF can go through the Wall.
- Obtain approval from authorities to use RF.
- Non-approval RF types:
 - Bluetooth, IEEE 802.11, etc.

Furkan Çakmak

29

Unguided Media - Microwaves

BLM3051
Data
Communication
Week 4

- 1-300 GHz
- Satellite - Ground Station
- Parabolic and horn antennas
 - Unidirectional
 - LOS - Line Of Sight
- Microwaves can not go through the Wall
- It can be harmful to the living creature between the transceiver, depending on the signal strength used.


Furkan Çakmak

30

Unguided Media - Infra Red

BLM3051
Data
Communication
Week 4

- 300GHz-400THz
- Point-to-point
 - Device's remotes
- Infra Red can not go through the Wall
- Tapping-eavesdropping
- Jamming Immune
- 75 kbps in max. 8m distance
 - Top: 4 Mbps



Furkan Çakmak

31

Comparison of Transmission Medium

BLM3051
Data
Communication
Week 4

Ortam Özellik	UTP	STP	Coax	FO	RF	IR	Mikro Dalga	Uydu	Hücrel
Fiyat (\$/m)	Düşük	Orta	Orta	Yüksek	Orta	Düşük (Yüksek)	Yüksek	Yüksek	Yüksek
Hız	1 Mbps- 1 Gbps	1 Mbps- 150 Mbps	1 Mbps- 1 Gbps	10 Mbps- 10 Gbps	1 Mbps- 10 Mbps	4 Mbps (Gbps)	1 Mbps- 10 Gbps	1 Mbps- 10 Gbps	9.6 kbps- 19.2 kbps
Sinyal Zayıflaması	Yüksek	Yüksek	Orta	Düşük	Düşük- Orta	Düşük- Orta	Değişken	Değişken	Düşük
EMI	Yüksek	Orta	Orta	Düşük	Yüksek	Yüksek	Yüksek	Yüksek	Orta
Güvenlik	Düşük	Düşük	Düşük	Yüksek	Düşük	Orta- Yüksek	Orta	Orta	Düşük
Düğüm Ekleme	Kolay	Kolay	Kolay	Zor	Kolay	Kolay	Kolay	Kolay	Kolay
Mesafe	Kısa	Kısa	Orta	Uzun	Orta- Uzun	Kısa- Uzun	Uzun	Uzun	Uzun

Furkan Çakmak

32

Thank you for your listening.

BLM3051
Data
Communication
Week 4



Furkan Çakmak