

## Lesson 36: Overfitting Prevention

Data Science with Python – BSc Course

45 Minutes

**The Problem:** Neural networks have millions of parameters and can memorize training data. How do we ensure they generalize to new data?


**After this lesson, you will be able to:**

- Apply dropout regularization
- Use early stopping to prevent overfitting
- Diagnose overfitting from learning curves
- Build robust neural network models

**Finance Application:** Preventing models from fitting to noise in market data

## The Gap Between Train and Test


- Training loss keeps decreasing, validation loss increases
- Model memorizes training data instead of learning patterns



**Sign: train accuracy 99%, test accuracy 60% = severe overfitting**

## Randomly Ignoring Neurons


- During training: randomly set fraction of neurons to zero
- Forces network to not rely on any single neuron



**Dropout = training many thinned networks, averaging at test time**

## Implementation


- `model.add(Dropout(0.5))` – drop 50% of neurons
- Place after Dense layers, typically 0.2-0.5 rate



Common pattern: Dense → Dropout → Dense → Dropout

## Stop Before Overfitting


- Monitor validation loss; stop when it starts increasing
- `EarlyStopping(patience=10, restore_best_weights=True)`



Patience = how many epochs without improvement before stopping

## Reading the Learning Curve


- Underfitting: both train and val loss high
- Overfitting: train low, val high (growing gap)
- Good fit: both low, small gap



Always plot train and val loss together during development

## Penalizing Large Weights

- Add  $\lambda \sum w^2$  to loss function
- Keras: `Dense(64, kernel_regularizer=l2(0.01))`




L2 regularization keeps weights small, reducing model complexity



## Creating More Training Data


- For images: rotate, flip, crop, adjust brightness
- For time series: add noise, time warping



More diverse training data = better generalization

## Special Considerations for Financial Data

- Financial data is noisy – regularization is essential
- Use dropout + early stopping + small networks



**Rule: simpler models often work better on financial data**

## Hands-On Exercise (25 min)

### Task: Compare Regularization Techniques

- 1 Create overfit-prone dataset (few samples, many features)
- 2 Train baseline MLP – observe severe overfitting
- 3 Add Dropout(0.5) – compare train/val curves
- 4 Add EarlyStopping – when does training stop?
- 5 Compare final test accuracy across all variants

**Deliverable:** Side-by-side learning curves + accuracy comparison table.

**Extension:** Try combining dropout + L2 + early stopping

**Problem Solved:** We can now prevent neural networks from memorizing data and ensure generalization.

**Key Takeaways:**

- Dropout: randomly zero neurons during training
- Early stopping: halt when validation loss stops improving
- L2 regularization: penalize large weights
- Always monitor train vs validation loss curves

**Next Lesson:** Text Preprocessing (L37) – preparing text for NLP

**Memory:** Dropout = random zeros. Early stopping = stop at best val. Watch the gap.