

# L22: NFT Metadata and IPFS

## Module C: NFTs & Digital Assets

Blockchain & Cryptocurrency Course

December 2025

By the end of this lesson, you will be able to:

- Understand the JSON metadata format standard for NFTs
- Explain how IPFS content addressing works
- Describe the role of pinning services in NFT permanence
- Compare IPFS and Arweave for decentralized storage
- Evaluate metadata permanence and availability challenges

# NFT Metadata: The JSON Standard

**Metadata Structure:** OpenSea standard (widely adopted)

## Core Fields:

- `name` – Display name of the NFT
- `description` – Human-readable description
- `image` – URI to primary visual asset (IPFS, HTTP)
- `external_url` – Link to project website or details
- `attributes` – Array of trait objects

## Example Metadata JSON:

```
{
  "name": "Bored Ape #1234",
  "description": "A unique Bored Ape Yacht Club NFT",
  "image": "ipfs://QmXyZ.../1234.png",
  "attributes": [
    {"trait_type": "Background", "value": "Blue"},
    {"trait_type": "Hat", "value": "Beanie"}
  ]
}
```

**Attributes Array:** Defines traits and properties

**Attribute Object Structure:**

- `trait_type` – Category name (e.g., “Hat”, “Eyes”)
- `value` – Specific value (e.g., “Beanie”, “Laser Eyes”)
- `display_type` (optional) – How to render (number, date, boost)

**Rarity Calculation:**

- Each trait has a frequency distribution in the collection
- Rarer traits (low frequency) increase NFT value
- Tools like Rarity Sniper calculate rarity scores

**Example Rarity Analysis:**

- Background: Blue (20% frequency) vs. Gold (2% frequency)
- Laser Eyes: 1% frequency (highly rare)

**IPFS:** Decentralized peer-to-peer file storage protocol

## Key Concepts:

- **Content Addressing:** Files identified by cryptographic hash
- **CID (Content Identifier):** Unique hash of file content
- **Immutability:** Same content always produces same CID
- **Distributed:** Files stored across multiple nodes
- **Retrieval:** Any node with the file can serve it

## Example IPFS URI:

- `ipfs://QmXyZ123abc...` (CID)
- Gateway URL: `https://ipfs.io/ipfs/QmXyZ123abc...`

## Traditional Web (Location Addressing):

- URL points to server location: `https://server.com/file.jpg`
- Content can change without URL changing
- Server failure = file unavailable

## IPFS (Content Addressing):

- CID derived from file content: `QmXyZ...`
- Changing content changes CID
- File available from any node that has it
- Verifiable integrity (hash mismatch = tampering detected)

## Advantage for NFTs:

- Guarantees metadata/image match the CID in tokenURI
- No server dependency (decentralized retrieval)

## CID Components:

- **Version:** CIDv0 (QmXyZ...) or CIDv1 (bafybeig...)
- **Multicodec:** Specifies content type (dag-pb, raw, etc.)
- **Multihash:** Hash algorithm (SHA-256) + hash value

## Example:

- CIDv0: QmYwAPJzv5CZsnA625s3Xf2nemtYgPpHdWEz79ojWnPbdG
- CIDv1: bafybeigdyrzt5sfp7udm7hu76uh7y26nf3efuylqabf3oclgtqy55fbzdi

## Determinism:

- Same file always produces same CID
- Different files always produce different CIDs

**IPFS Garbage Collection:** Nodes delete unpinned files to save space

**Pinning:** Explicitly keeping a file on IPFS nodes

**Without Pinning:**

- File may be removed from all nodes (lost)
- NFT metadata/images become unavailable
- Broken image links in wallets and marketplaces

**Pinning Services:**

- **Pinata:** Popular commercial pinning service
- **NFT.Storage:** Free pinning for NFT data (funded by Filecoin)
- **Infura IPFS:** Enterprise-grade IPFS infrastructure
- **Self-hosting:** Run your own IPFS node and pin files

**Critical Issue:** If all pinning stops, files may disappear from IPFS



**Gateway:** HTTP bridge to access IPFS content

## Public Gateways:

- [https://ipfs.io/ipfs/\[CID\]](https://ipfs.io/ipfs/[CID])
- [https://gateway.pinata.cloud/ipfs/\[CID\]](https://gateway.pinata.cloud/ipfs/[CID])
- [https://cloudflare-ipfs.com/ipfs/\[CID\]](https://cloudflare-ipfs.com/ipfs/[CID])

## Why Gateways Matter:

- Browsers do not natively support `ipfs://` protocol
- Wallets and marketplaces use gateways to display NFTs
- Gateway downtime = NFTs appear broken (even if IPFS file exists)

## Centralization Risk:

- Most users rely on centralized gateways (ipfs.io, Cloudflare)
- Gateway can censor or throttle content
- Solution: Native IPFS support in browsers (IPFS Companion extension)

# Arweave: Permanent Decentralized Storage

**Arweave:** Blockchain designed for permanent data storage

## Key Differences from IPFS:

- **Permanence:** One-time payment for perpetual storage
- **Blockchain-based:** Data stored on Arweave blockchain
- **Economic model:** Storage endowment fund pays miners forever
- **No pinning needed:** Data guaranteed to persist

## Arweave URI:

- `ar://[Transaction ID]`
- Gateway: `https://arweave.net/[Transaction ID]`

## Use Cases:

- High-value NFTs requiring guaranteed permanence
- Historical records and archives
- Alternative to IPFS for critical metadata

Feature	IPFS	Arweave
Storage Model	Peer-to-peer distributed	Blockchain-based
Permanence	Requires pinning	Guaranteed (one-time fee)
Cost	Free + pinning service fees	Pay once (e.g., \$5-10/GB)
Retrieval	Fast (popular files cached)	Slower (blockchain retrieval)
Adoption	High (majority of NFTs)	Growing (premium projects)
Censorship Risk	Gateway-dependent	Minimal (blockchain-based)
Data Mutability	Immutable (new CID if changed)	Immutable (on-chain)

## Recommendation:

- IPFS: Most NFT projects (cost-effective, fast)
- Arweave: Premium/historical NFTs (guaranteed permanence)

## Real-World Issues:

- ❶ **Unpinned IPFS files:** Project abandons pinning, files lost
- ❷ **Centralized metadata servers:** Company shuts down, NFTs break
- ❸ **Mutable tokenURI:** Smart contract allows owner to change metadata
- ❹ **Gateway failures:** IPFS gateways go offline, NFTs appear broken
- ❺ **Link rot:** HTTP URLs stop working (404 errors)

## Case Study: Nifty Gateway (2021):

- Platform used centralized servers for metadata
- Outage caused all NFTs to display broken images
- Community backlash led to IPFS migration

## Mutable Metadata:

- Smart contract owner can update tokenURI
- Allows bug fixes and metadata improvements
- Risk: Owner could change artwork or traits (rug pull)

## Immutable Metadata:

- tokenURI frozen after minting (contract locked)
- Guarantees metadata cannot be altered
- Standard for high-value collections (e.g., CryptoPunks)

## Verification:

- Check smart contract code for setTokenURI() functions
- Verify contract ownership is renounced (no admin control)
- Use Etherscan to audit contract mutability

## For NFT Projects:

- 1 **Use IPFS or Arweave:** Avoid centralized servers
- 2 **Pin all files:** Use reputable pinning services (Pinata, NFT.Storage)
- 3 **Freeze metadata:** Make `tokenURI` immutable after reveal
- 4 **Redundancy:** Pin to multiple services (IPFS + Arweave)
- 5 **Document storage:** Inform buyers where metadata is hosted
- 6 **Community pinning:** Encourage holders to pin collection files

## For NFT Buyers:

- Verify metadata is on IPFS/Arweave (not HTTP)
- Check if `tokenURI` is immutable
- Confirm pinning service reputation

## Current NFT Storage Breakdown (Estimated):

- **IPFS:** 60-70% of NFT projects
- **Centralized servers:** 20-25% (HTTP URLs)
- **Arweave:** 5-10% (growing)
- **Fully on-chain:** ~5% (rare, expensive)

## Trends:

- Migration from centralized to IPFS accelerating
- Premium projects adopting Arweave for permanence guarantees
- Layer 2 solutions (Polygon) enabling cheaper on-chain storage

**NFT.Storage:** Protocol Labs initiative (Filecoin Foundation)

## Service Features:

- Free IPFS pinning for NFT data
- Automatic backup to Filecoin network
- Simple API for developers
- No usage limits or expiration

## How It Works:

- 1 Developer uploads NFT metadata/images via API
- 2 Files pinned to IPFS nodes
- 3 Backed up to Filecoin decentralized storage
- 4 Retrieval via standard IPFS gateways

**Sustainability:** Funded by Filecoin ecosystem to support Web3 adoption



## Warning Signs of Poor Metadata Practices:

- ❶ **HTTP URLs:** `https://project.com/metadata/123.json`
  - Centralized, subject to server failure
- ❷ **Mutable tokenURI:** Contract has `setTokenURI()` function
  - Owner can change metadata at will
- ❸ **No pinning documentation:** Project silent on storage strategy
  - Files may not be pinned (risk of loss)
- ❹ **Unknown IPFS gateway:** Custom gateway not reputable
  - Gateway failure = broken NFTs
- ❺ **Unrevealed metadata:** Placeholder images before reveal
  - Risk of metadata not matching expectations

**CryptoPunks (2017):** Early NFT project, metadata evolution

## **Original Implementation:**

- Images and traits stored on-chain (contract storage)
- No external metadata files needed
- True permanence and decentralization

## **Wrapped Punks (2021):**

- ERC-721 wrapper for original punks (compatibility)
- Metadata on IPFS for marketplace display
- Maintains on-chain source of truth

**Lesson:** On-chain storage provides maximum permanence but at high cost

**Lazy Loading:** Metadata generated on-demand, not pre-stored

## Approach:

- Smart contract computes metadata dynamically
- `tokenURI()` function generates JSON on-chain
- No external storage needed (fully on-chain)

## Example: Loot (2021):

- Randomized adventure gear NFTs
- Metadata generated as Base64-encoded SVG in contract
- Zero external dependencies

## Trade-offs:

- Maximum decentralization and permanence
- Limited to text/simple graphics (gas constraints)
- Not suitable for complex images or videos

- 1 NFT metadata follows a JSON standard (name, description, image, attributes)
- 2 IPFS uses content addressing (CIDs) for decentralized, immutable storage
- 3 Pinning is critical for IPFS file permanence (unpinned files can be lost)
- 4 Arweave provides guaranteed permanent storage for a one-time fee
- 5 Metadata permanence challenges include unpinned files, mutable URIs, and centralized servers
- 6 Best practice: Use IPFS/Arweave, pin to multiple services, freeze metadata after minting

- ❶ What are the trade-offs between IPFS and Arweave for NFT metadata storage?
- ❷ Should NFT metadata be immutable, or is mutability acceptable for bug fixes?
- ❸ How can the NFT community ensure long-term metadata availability without centralized pinning services?
- ❹ Is fully on-chain metadata the ideal, or are off-chain solutions sufficient?
- ❺ What happens to NFT value if metadata becomes unavailable but ownership records remain?

### L23: NFT Marketplaces

We will explore:

- OpenSea, Blur, and Rarible business models
- Listing mechanics and order book systems
- Marketplace fees and royalty enforcement
- Wash trading and market manipulation detection
- Aggregators and cross-marketplace trading

**Preparation:** Create a wallet and browse NFT collections on OpenSea