


# Why Would a Fraud Analyst Trust 500 Weak Detectors Over One Expert?

## The Dilemma

- A **decision tree** makes predictions by asking yes/no questions about features (e.g., "Is amount  $\geq$  \$500?"  $\rightarrow$  "Is location foreign?")
- A single decision tree overfits to training noise
- High variance: different samples produce wildly different trees
- Two trees can disagree completely on the same transaction
- What if you let 500 imperfect trees vote?

## Insight

RF combines many weak learners — variance drops without increasing bias.



**Ensemble learning = combining imperfect models to produce reliable decisions**

# Polling the Room vs. Asking One Expert – Which Do You Trust More?

## Think Before You Compute

Imagine asking one friend for a restaurant recommendation versus polling 20 friends. The single friend might have a strong bias (loves sushi, hates Italian). But 20 friends? Their biases cancel, and the consensus is more stable.

- How many friends would you ask?
- Did their individual biases cancel out?
- Was the consensus more stable than any single opinion?

**Pause and reflect:** when you last chose a restaurant by asking friends, you were bagging human opinions.

## Reflection Prompt

Think of a time you made a better decision by gathering multiple opinions.

---

**Bootstrap aggregating (bagging) formalizes this intuition: sample, train, average**

# What Makes a Random Forest Different from Bagging, Boosting, and a Single Tree?

## Taxonomy of Ensemble Methods

Property	RF	Bagging	Boosting	Single Tree
Sampling	Bootstrap	Bootstrap	Sequential	All
Feature subset	$\sqrt{p}$	All	All	All
Tree correlation	Low	High	Sequential	N/A
Bias	Low	Low	Low	Low
Variance	Low	Medium	Low	High
Parallel	Yes	Yes	No	N/A

## Insight

RF adds feature randomization **on top of** bagging to decorrelate trees.

**Random Forest**  
Vote of decorrelated trees

**Bagging**  
Vote of correlated trees

**Boosting**  
Sequential error correction

**Single Tree**  
One fragile model

Breiman (2001) showed feature randomization is what makes RF variance reduction superior to plain bagging


# How Does a Single Transaction Navigate 500 Trees to a Fraud Verdict?

## One Transaction, 500 Votes

- Bootstrap sample 63.2% of training data per tree
- At each split, consider only  $\sqrt{p}$  random features
- Each tree votes: fraud or legit
- Majority vote = final prediction
- OOB samples validate without a held-out test set

## Insight

Each tree sees different data AND different features – this double randomness is the source of RF's power.



$$63.2\% = 1 - (1 - 1/n)^n \rightarrow 1 - 1/e \text{ for large } n$$


# How Does Feature Randomization Kill the Correlation Between Trees?

## The Decorrelation Trick

- Bagging alone: if one feature dominates, all trees split on it — correlated — slow variance reduction
- RF fix: restrict each split to  $\sqrt{p}$  random features — different trees use different features —  $\rho$  drops
- $\text{Var}(\bar{f}) = \rho\sigma^2 + \frac{1-\rho}{B}\sigma^2$

## Insight

Reducing  $\rho$  is more powerful than increasing  $B$ .



$\text{Var}(\text{RF}) = \rho\sigma^2 + (1 - \rho)\sigma^2/B$  — the first term is the irreducible correlation floor


# What Happens When the Forest Memorizes Noise Instead of Signal?

## Three Ways RF Can Still Fail

- **Overfitting to noise:** too many deep trees on small data
- **Feature leakage:** a feature that encodes the label
- **Class imbalance:** RF votes majority — rare class outvoted

## Insight

Class imbalance is the #1 failure mode in fraud detection – always check class distribution.



**Solutions:** `max_depth`, `min_samples_leaf`, `class_weight='balanced'`, SMOTE for resampling

# Why Do So Many Fraud Teams Reach for Random Forests First?


## RF as the Industry Default

- Ensemble voting aggregates weak signals
- Feature importance reveals which attributes matter
- OOB error = free cross-validation
- Scales to millions with parallel training

## Insight

RF popularity = simplest reasonable solution that works out of the box.

## Ensemble Voting (Classification)



[https://github.com/Digital-AI-Finance/methods-algorithms/trees/master/slides/04\\_Random\\_Forests/05\\_ensemble\\_voting](https://github.com/Digital-AI-Finance/methods-algorithms/trees/master/slides/04_Random_Forests/05_ensemble_voting)

Kaggle surveys rank RF/gradient boosting as top methods for tabular data


# Who Wins and Who Loses When Trees Replace Rules?

## Stakeholder Analysis

- **Winners:** Fraud analysts (better detection), Risk managers (feature importance for audit), Data engineers (parallel, easy deploy)
- **Losers:** Compliance officers (less interpretable than logistic regression), Customers flagged by opaque ensemble

## Insight

RF shifts fraud detection from human-crafted rules to data-driven patterns.




ECOA and GDPR require adverse action explanations – SHAP values bridge the gap



# When Should You Reach for Random Forests – and When Should You Not?

## The Decision Framework

1. **Is your data tabular?** If images/text → deep learning.
2. **Do you need probability calibration?** RF probabilities often poorly calibrated → Platt scaling.
3. **Must the model be fully interpretable?** If yes → logistic regression or single tree.



## Insight

No Free Lunch: RF excels on tabular, non-linear, feature-rich data.

When in doubt: start with RF as baseline, then try XGBoost/LightGBM for marginal improvement

# Can You Diagnose This Fraud Detection Model?


## The Scenario

A payment processor runs RF with 1000 trees. Features: amount, time, merchant category, distance from home, device fingerprint. Flags 2% as fraud; actual fraud rate is 0.1%.

- Calculate the expected false positive rate
- Which feature likely ranks highest in importance?
- Model misses 40% of fraud – what would you change?
- Is the OOB error reliable here?

## Deliverable

Fill in the table on the right.



- ☐ OOB error
- ☐ Top 3 features
- ☐ Overfitting?
- ☐ Class balance

Hint: with 0.1% fraud rate and 2% flag rate, most flags are false positives