

## 16. Learning Rate Comparison

Neural Networks - From Brain to Business

Understand how learning rate affects training speed and stability.




The **learning rate** controls how big a step we take during gradient descent. It's one of the most important hyperparameters in neural network training.

**Too small** (e.g., 0.0001): Training is stable but extremely slow. The network may never reach a good solution in reasonable time.

**Too large** (e.g., 1.0): Training is unstable. The loss may oscillate wildly or even diverge to infinity. The network overshoots the minimum.

**Just right** (typically 0.001-0.01): Steady progress toward minimum. Fast enough to converge in reasonable time, stable enough not to diverge.

Finding the optimal learning rate often requires experimentation. Techniques like **learning rate schedules** (reducing rate over time) and **adaptive methods** (Adam, RMSprop) help automate this process.



**Weight update:**

$$w := w - \eta \cdot \nabla L$$

**Effect of learning rate:** - Small eta:  $\Delta w$  is small, slow movement - Large eta:  $\Delta w$  is large, fast but potentially unstable movement

**Common learning rate schedules:**

Step decay:

$$\eta_t = \eta_0 \times \gamma^{\lfloor t/k \rfloor}$$

Exponential decay:

$$\eta_t = \eta_0 \times e^{-\lambda t}$$

Imagine walking downhill with a blindfold:

- **Too small step:** You inch forward, taking forever to reach the bottom - **Too large step:** You leap so far you might land on the opposite hill - **Just right:** Steady steps that make good progress without losing balance

The terrain (loss landscape) determines what "just right" means. Steeper hills allow smaller steps; flat areas can use larger steps.

## Practice Problem 1

### Problem 1

You train with learning rate 0.1 and observe: Loss at epoch 1 = 0.8, epoch 2 = 0.5, epoch 3 = 0.4, epoch 4 = 0.38, epoch 5 = 0.37. What pattern do you see?

### Solution

#### Pattern: Diminishing returns (normal convergence)

Analysis: - Epoch 1-2: Improvement of 0.3 (37.5% reduction) - Epoch 2-3: Improvement of 0.1 (20% reduction) - Epoch 3-4: Improvement of 0.02 (5% reduction) - Epoch 4-5: Improvement of 0.01 (2.6% reduction)

This is **healthy training behavior**: - Rapid early progress (large gradients far from minimum) - Slowing improvement (smaller gradients near minimum) - Convergence to stable value

The learning rate (0.1) appears appropriate for this problem.



### Problem 2

You train with learning rate 1.0 and observe: Loss at epoch 1 = 0.8, epoch 2 = 1.5, epoch 3 = 3.2, epoch 4 = 8.7, epoch 5 = NaN. What happened?

### Solution

#### Diagnosis: Learning rate too high - divergence

What happened: - Epoch 1-2: Loss increased (0.8  $\rightarrow$  1.5) - overshoot minimum - Epoch 2-3: Continued increasing - oscillating past optimal - Epoch 3-4: Accelerating growth - unstable regime - Epoch 5: NaN (Not a Number) - loss exploded to infinity

**Why:** - Large eta means large weight updates - Updates so large they jump past the minimum to higher loss regions - Positive feedback: higher loss  $\rightarrow$  larger gradient  $\rightarrow$  even larger update - Eventually overflows numerical precision (NaN)

**Fix:** Reduce learning rate significantly (try 0.01 or 0.001)

- Learning rate is critical: too small = slow, too large = unstable
- Look for diminishing returns pattern = healthy training
- Look for increasing loss = learning rate too high
- Learning rate schedules reduce rate over time
- Adaptive optimizers (Adam) adjust rate automatically