GM MOBIL | FAW TRUCKS

NEW MIXER TRUCK 4x2

DB140MT



1 TAHUN GARANSI
TANPA BATASAN KILOMETER

Your Trusted Business Partner

FA-BGM-260225

SPECIFICATION FAW TRUCKS DB140MT 4 × 2 MIXER TRUCK

DRIVETRAIN		
Driving Type	4 × 2	
CABIN		
Type	Tiger VH Flat Roof, All Metal Closed, Manual Cabin Lifting.	
Seats	3	
Accessories	Standard Air Conditioner (AC), Radio Tape + USB MP3, Driver seat with adjuster, Power Window.	
MASS		
Curb Weight (kg)	5650	
Axle Weight Distribution (kg)	Front Axle	2290
	Rear Axle	3360
Gross Vehicle Weight - GVW Rated (kg)	10000	
PERFORMANCE		
Min. Turning Radius (m)	8.8	
Max. Speed (km/h)	79	
Max. Gradeability (%)	70	
Fuel Tank Capacity (L)	80	
ENGINE		
Model	**YUCHAI YC4D140-48** 4-cylinder in-line, Common Rail, Turbo charger & Intercooler	
Displacement (cc)	4214	
Max. Output Power (HP @Rpm)	140 @2800	
Max. Torque (Nm @Rpm)	450 @1400 - 1700	
Standard Emission	Euro 4	
TRANSMISSION		
Model	WLY5T46-09-83	
Forward Gear Ratio	1 = 6.32; 2 = 3.927; 3 = 2.283; 4 = 1.396; 5 = 1	
Reverse Gear Ratio	R = 5.858	
CLUTCH		
Type	Dry type, single plate, diaphragm spring clutch, hydraulic controlled and air auxiliary power supply.	
Driven Plate Diameter (mm)	Ø330	
AXLE CONSTRUCTIONS		
Front Axle	Type	I-Section Beam heavy duty
	Axle Load Capacity (kg)	3600
Rear Axle	Type	1080 Cast Axle
	Reduction Ratio	5.286
	Axle Load Capacity (kg)	6400
FRAME		
Type	Side rails, Punching and Riveted Constructions.	
Main Rail Section (mm)	216 × 75 × 6	
Frame Width (mm)	795	
SUSPENSION		
Front Suspension	8 Leaf Springs	
Rear Suspension	10 Leaf Springs + 3 Auxiliary Leaf Springs	

INTERIOR



Air Conditioner system with automatic control, audio system and USB Port.



Steer sytem with power steering, Tilt Steering Wheel and Spacious Cabin.



Equipped with Multi Information Display for easy monitoring, maintenance and identify initial problem with the vehicle.

POWER STEERING		
Model	Integrated Recirculation, Hydraulic Power Steering	
BRAKE SYSTEM		
Driving Brake	Full Air Brake, Double Circuit Air Brake	
Parking Brake	Spring Energy Storage Type	
Auxiliary Brake	Exhaust Brake	
DIMENSIONS		
Wheelbase - WB (mm)	3560	
Overall Dimensions	Length (mm)	6765
	Width (mm)	2090
	Height (mm)	2990
Wheeltrack - Front (mm)	1620	
Wheeltrack - Rear (mm)	1590	
Front Overhang (mm)	1200	
Rear Overhang (mm)	2005	
Min. Ground Clearance (mm)	210	
Approach Angle (°)	27	
Departure Angle (°)	33	
WHEEL		
Rim	6.5 - 16	
Tyre	8.25R16 14PR	
ELECTRICAL SYSTEM		
Type	Single Line, Negative Grounded	
Voltage (V)	24	
Battery (V/Ah)	2 × 12/90	
MIXER SPECIFICATIONS		
Max. Mixing Capacity (m^3)	3.3	
Drum diameter (mm)	1950	
Charging speed (m^3/min)	2 at 12 Rpm	
Discharging speed (m^3/min)	2	
Hydraulic Motor type	PMP - PMH - M72	
Hydraulic Pump type	PMP - PMH - P72	
Deaccelerator type	PMP - PMB 7.1	
Inclination (°)	16	
Rotary Speed (Rpm)	0 to 18	
Min. charging spout size (mm)	200	
Water Supply type	Air Pressure Water Tank/DC Water Pump	
Water tank capacity (L)	200	
Remaining rate	<0.2%	

**The specification can change without prior notice. Performance data depend on operational conditions.*

GM MOBIL | FAW TRUCKS

Jalan Lingkar Luar Barat No.9, Rawa Buaya, Cengkareng, Jakarta Barat 11740 - Indonesia Telp : (021) 5830 0788 Corporate
Email : gmmcare@gmmobil.com

GMM CARE 24 HOURS 1500 329 WA Care:0822 9999 9329

AFTER SALES SERVICE 24 HOURS

PARTS CENTER PT GAYA MAKMUR MOBIL

www.gmmobil.com

PT Gaya Makmur Mobil @gayamakmurmobil @gayamakmurmobil PT Gaya Makmur Mobil PT Gaya Makmur Mobil