GM MOBIL | FAW TRUCKS

NEW CHASSIS CARGO 4x4

# DD140CG-CD




1 TAHUN GARANSI
TANPA BATASAN KILOMETER

Your Trusted Business Partner

# SPECIFICATION FAW TRUCKS DD140CG-CD 4 × 4 CHASSIS CARGO

| DRIVETRAIN | | |
|---|---|---|
| Driving Type | 4 x 4 | |
| **CABIN** | | |
| Type | Tiger VH Flat Roof, All Metal Closed, Manual Cabin Lifting. | |
| Seats | 3 | |
| Accessories | Standard Air Conditioner (AC), Radio Tape + USB MP3, Driver Seat with Adjuster, Power window. | |
| **MASS** | | |
| Model | **DD140CG** | **DD140CD** |
| Curb Weight (kg) | 3600 | 3640 |
| Axle Weight Distribution (kg) | | |
| Front Axle | 2150 | 2170 |
| Rear Axle | 1450 | 1470 |
| Gross Vehicle Weight - GVW Rated (kg) | 9400 | 8000 |
| **PERFORMANCE** | | |
| Model | **DD140CG** | **DD140CD** |
| Min. Turning Radius (m) | 7.35 | 6.35 |
| Max. Speed (km/h) | 96 | |
| Max. Gradeability (%) | 92 | |
| Fuel Tank Capacity (L) | 150 | |
| **ENGINE** | | |
| Model | **YUCHAI YC4D140-48** 4-cylinder in-line, Common Rail, Turbo charger & Intercooler | |
| Displacement (cc) | 4214 | |
| Max. Output Power (HP @Rpm) | 140 @2800 | |
| Max. Torque (Nm @Rpm) | 450 @1400 - 1700 | |
| Standard Emission | Euro 4 | |
| **TRANSMISSION** | | |
| Model | WLY6TS55C | |
| Forward Gear Ratio | 1 = 6.32; 2 = 3.927; 3 = 2.283; 4 = 1.396; 5 = 1; 6 = 0.789 | |
| Reverse Gear Ratio | R = 5.858 | |
| **CLUTCH** | | |
| Type | Dry type, single plate, diaphragm spring clutch, hydraulic controlled and air auxiliary power supply. | |
| Driven Plate Diameter (mm) | Ø340 | |
| **TRANSFER CASE** | | |
| Model | 2FD290 | |
| Ratio | Hi = 1; Lo = 2.09 | |
| **AXLE CONSTRUCTIONS** | | |
| Front Axle | Type | QT295L |
| | Axle Load Capacity (kg) | 3000 |
| Rear Axle | Type | 340, Single Reduction |
| | Reduction Ratio | 5.571 |
| | Axle Load Capacity (kg) | 7000 |
| Gross Vehicle Weight - GVW (Kg) | 10000 | |

**The specification can change without prior notice. Performance data depend on operational conditions.*

## INTERIOR



Air Conditioner system with automatic control, audio system and USB Port.



Steering sytem with power steering, Tilt Steering Wheel and Spacious Cabin.



Equipped with Multi Information Display for easy monitoring, maintenance and identify initial problem with the vehicle.

| FRAME | | |
|---|---|---|
| Type | Side rails, Punching and Riveted construction. | |
| Main Rail Section (mm) | 237 × 75 × 7 | |
| Frame Width (mm) | 795 | |
| **SUSPENSION** | | |
| Model | **DD140CG** | **DD140CD** |
| Front Suspension | 4 Leaf Springs + Shock Absorber | 8 Leaf Springs + Shock Absorber |
| Rear Suspension | 10 Leaf Springs + 5 Auxiliary Leaf Springs, with Stabilizer | 10 Leaf Springs + 8 Auxiliary Leaf Springs, with Stabilizer |
| **POWER STEERING** | | |
| Model | Integrated Recirculation, Hydraulic Power Steering | |
| **BRAKE SYSTEM** | | |
| Driving Brake | Full Air Brake, Double Circuit Air Brake | |
| Parking Brake | Spring Energy Storage Type | |
| Auxiliary Brake | Exhaust Brake | |
| **DIMENSIONS** | | |
| Model | **DD140CG** | **DD140CD** |
| Wheelbase - WB (mm) | 3900 | 3300 |
| Length (mm) | 7513 | 5913 |
| Width (mm) | 2090 | |
| Height (mm) | 2615 | |
| Wheel Track - Front (mm) | 1650 | |
| Wheel Track - Rear (mm) | 1590 | |
| Front Overhang (mm) | 1213 | |
| Rear Overhang (mm ) | 2400 | 1400 |
| Min. Ground Clearance (mm) | 235 | |
| Approach Angle (°) | 32 | |
| Departure Angle (°) | 14 | 23 |
| **WHEEL** | | |
| Rim | 6.5 - 16 | |
| Tyre | 8.25R16 16PR | |
| **ELECTRICAL SYSTEM** | | |
| Type | Single line, Negative Grounded | |
| Voltage (V) | 24 | |
| Battery (V/Ah) | 2 × 12/90 | |

GM MOBIL | FAW TRUCKS

www.gmmobil.com

Jalan Lingkar Luar Barat No.9, Rawa Buaya, Cengkareng, Jakarta Barat 11740 - Indonesia Telp : (021) 5830 0788 Corporate Email : gmmcare@gmmobil.com

GMM CARE 24 HOURS
1500 329
WA Care : 0822 9999 9329

AFTER SALES SERVICE 24 HOURS
PARTS CENTER
PT GAYA MAKMUR MOBIL

PT Gaya Makmur Mobil @gayamakmurmobil @gayamakmurmobil PT Gaya Makmur Mobil PT Gaya Makmur Mobil