GM MOBIL | FAW TRUCKS

EURO 5 CHASSIS BBM 6x2

# FB240CB




1 TAHUN GARANSI
TANPA BATASAN KILOMETER

Your Trusted Business Partner

FA-BGM-260225

# SPECIFICATION FAW TRUCKS FB240CB 6 × 2 CHASSIS BBM

| | | |
|---|---|---|
| **DRIVETRAIN** | | |
| Driving Type | 6 × 2 | |
| **CABIN** | | |
| Type | J5M V2.0 Cab Over Engine, ECE R29 Certified, 1 Sleeper Bed, Full Floating with Front Air Suspension & Rear Coil Spring Suspension, All Metal Closed, Electric & Manual Cabin Lifting. | |
| Seats | 2 | |
| Accessories | Standard Air Conditioner (AC), Radio Tape + USB MP3, Driver seat with cooler and adjuster, Power window. | |
| **MASS** | | |
| Curb Weight (kg) | 8010 | |
| Axle Weight Distribution (kg) | Front Axle | 3720 |
| | Middle Axle | 2390 |
| | Rear Axle | 1900 |
| Gross Vehicle Weight - GVW Rated (kg) | 25000 | |
| **PERFORMANCE** | | |
| Min. Turning Radius (m) | 8.4 | |
| Max. Speed (km/h) | 89 | |
| Max. Gradeability (%) | 46 | |
| Fuel Tank Capacity (L) | 280 | |
| **ENGINE** | | |
| Model | **FAWDE CA6DLD.24E5** 6-cylinder in-line, Common Rail, Turbo charger & Intercooler | |
| Displacement (cc) | 6600 | |
| Max. Output Power (HP @Rpm) | 240 @2300 | |
| Max. Torque (Nm @Rpm) | 940 @1300 - 1700 | |
| Standard Emission | Euro 5 Standard (*Beyond Euro 4 Compliance*) | |
| **TRANSMISSION** | | |
| Model | CA9TB160M | |
| Forward Gear Ratio | C = 14.393; 1 = 10.04; 2 = 7.1; 3 = 5.05; 4 = 3.71; 5 = 2.7; 6 = 1.92; 7 = 1.36; 8 = 1 | |
| Reverse Gear Ratio | R = 14.414 | |
| **CLUTCH** | | |
| Type | Dry type, single plate, diaphragm spring clutch, hydraulic controlled and air auxiliary power supply. | |
| Driven Plate Diameter (mm) | Ø430 | |
| **AXLE CONSTRUCTIONS** | | |
| Front Axle | Type | I-Section Beam heavy duty |
| | Axle Load Capacity (kg) | 7000 |
| Middle Axle | Type | 457, Single Reduction |
| | Reduction Ratio | 5.286 |
| | Axle Load Capacity (kg) | 13000 |
| Rear Axle | Type | Lazy Axle |
| | Axle Load Capacity (kg) | 13000 |
| Gross Vehicle Weight - GVW (kg) | 33000 | |
| **FRAME** | | |
| Type | Side rails, Punching and Riveted construction. | |
| Main Rail Section (mm) | 280 × 80 × 8 | |
| Auxiliary Rail Section (mm) | 264 × 70 × 5 | |
| Frame Width (mm) | 865 | |

**The specification can change without prior notice. Performance data depend on operational conditions.*

## INTERIOR



Air Conditioner system with automatic control, audio system and USB Port.



ECE-R29 Is a Technology that Uses specified cabin impact limits to ensure passenger protection based on ("ATDs") Anthropomorphic Test Devices.



Driver's seat with air suspension system, cooler and adjuster for driver's comfort



Equipped with Multi Information Display for easy monitoring, maintenance and identify initial problem with the vehicle.

## FEATURES AND BENEFITS



Fuel Filter with Water Separator supported with system string and 2 Stage Water Removal Technology to provide better and consistent water removal capability.



Multi State Switch Load system to control fuel consumption according to the weight load for the result of maximum fuel efficiency.



The combination of Selective Catalytic Reduction technology and AdBlue creating an environment friendly vehicle. Adblue is a liquid containing 32,5% of urea to neutralize the harmful Nitrogen Oxides (NOx) into water and nitrogen.

| | | |
|---|---|---|
| **SUSPENSION** | | |
| Front Suspension | 10 Leaf Springs with Shock Absorber | |
| Rear Suspension | Bogie Suspension with 10 Leaf Springs | |
| **POWER STEERING** | | |
| Model | Integrated Recirculation, Hydraulic Power Steering | |
| **BRAKE SYSTEM** | | |
| Driving Brake | Full Air Brake, Double Circuit Air Brake, Anti-Lock Braking System (ABS) and Auto Slack Adjuster | |
| Parking Brake | Spring Energy Storage Type | |
| Auxiliary Brake | Exhaust Brake | |
| **DIMENSIONS** | | |
| Wheelbase - WB (mm) | 4200 + 1350 | |
| Overall Dimensions | Length (mm) | 9475 |
| | Width (mm) | 2500 |
| | Height (mm) | 3500 |
| Wheel Track - Front (mm) | 2070 | |
| Wheel Track - Rear (mm) | 1850 | |
| Front Overhang (mm) | 1385 | |
| Rear Overhang (mm) | 2540 | |
| Min. Ground Clearance (mm) | 290 | |
| Approach Angle (°) | 21 | |
| Departure Angle (°) | 17 | |
| **WHEEL** | | |
| Rim | 8.25 - 22.5 | |
| Tyre | 11.00R22.5 18PR | |
| **ELECTRICAL SYSTEM** | | |
| Type | Single line, Negative Grounded | |
| Voltage (V) | 24 | |
| Battery (V/Ah) | 2 × 12/150 | |

GM MOBIL | FAW TRUCKS

Jalan Lingkar Luar Barat No.9, Rawa Buaya, Cengkareng, Jakarta Barat 11740 - Indonesia Telp : (021) 5830 0788 Corporate
Email : gmmcare@gmmobil.com

GMM CARE 24 HOURS 1500 329 WA Care:0822 9999 9329

AFTER SALES SERVICE 24 HOURS

PARTS CENTER PT GAYA MAKMUR MOBIL

www.gmmobil.com

PT Gaya Makmur Mobil | @gayamakmurmobil | @gayamakmurmobil | PT Gaya Makmur Mobil | PT Gaya Makmur Mobil