GM MOBIL | FAW TRUCKS

EURO 5 DUMP TRUCK 6x4

# FD375DT




1 TAHUN GARANSI
TANPA BATASAN KILOMETER

*Your Trusted Business Partner*

FA-BGM-260225

# SPECIFICATION FAW TRUCKS FD375DT 6 × 4 DUMP TRUCK

| | | |
|---|---|---|
| **DRIVETRAIN** | | |
| Driving Type | 6 × 4 | |
| **CABIN** | | |
| Type | JH6 Flat Roof, ECE R29 Certified, 1 Sleeper Bed, Full Floating with Front Air Suspension & Rear Coil Spring Suspension, All Metal Closed, Electric & Manual Cabin Lifting. | |
| Seats | 2 | |
| Accessories | Standard Air Conditioner (AC), Radio Tape + USB MP3, Driver seat with adjuster, Power Window. | |
| **MASS** | | |
| Curb Weight (kg) | 16100 | |
| Axle Weight Distribution (kg) | Front Axle | 6100 |
| | Rear Axle | 5350 |
| | | 4650 |
| Gross Vehicle Weight - GVW Rated (kg) | 31500 | |
| **PERFORMANCE** | | |
| Min. Turning Radius (m) | 8.5 | |
| Max. Speed (km/h) | 65 | |
| Max. Gradeability (%) | 86 | |
| Fuel Tank Capacity (L) | 400 | |
| **ENGINE** | | |
| Model | **WEICHAI WP10H375E50** 6-cylinder in-line, Common Rail, Turbo charger & Intercooler | |
| Displacement (cc) | 9500 | |
| Max. Output Power (HP @Rpm) | 375 @1900 | |
| Max. Torque (Nm @Rpm) | 1800 @1000 - 1400 | |
| Standard Emission | Euro 5 Standard (Beyond Euro 4 Compliance) | |
| **TRANSMISSION** | | |
| Model | 12JSD200T-B | |
| Forward Gear Ratio | 1 = 15.53; 2 = 12.22; 3 = 9.39; 4 = 7.33; 5 = 5.73; 6 = 4.46; 7 = 3.48; 8 = 2.74; 9 = 2.1; 10 = 1.64; 11 = 1.28; 12 = 1 | |
| Reverse Gear Ratio | R1 = 14.86; R2 = 3.33 | |
| **CLUTCH** | | |
| Type | Dry type, single plate, diaphragm spring clutch, hydraulic controlled and air auxiliary power supply. | |
| Driven Plate Diameter (mm) | Ø430 | |
| **CAXLE CONSTRUCTIONS** | | |
| Front Axle | Type | I-Section Beam Heavy Duty |
| | Axle Load Capacity (kg) | 9000 |
| Rear Axle | Type | LC300, Double Hub Reduction |
| | Reduction Ratio | 5.921 |
| | Axle Load Capacity (kg) | 2 × 16000 |
| Gross Vehicle Weight - GVW (kg) | 41000 | |
| **DIFFERENTIAL LOCK** | | |
| Inter Axle Differential Lock | Yes | |
| Inter Wheel Differential Lock | Yes | |

**The specification can change without prior notice. Performance data depend on operational conditions.*

## INTERIOR



Air Conditioner system with automatic control, audio system and USB Port.



ECE-R29 Is a Technology that Uses specified cabin impact limits to ensure passenger protection based on ("ATDs") Anthropomorphic Test Devices.



Driver's seat with Air Suspension system and adjuster for driver's comfort



Equipped with Multi Information Display for easy monitoring, maintenance and identify initial problem with the vehicle.

## FEATURES AND BENEFITS



Fuel Filter with Water Separator supported with system string and 2 Stage Water Removal Technology to provide better and consistent water removal capability.



Multi State Switch Load system to control fuel consumption according to the weight load for the result of maximum fuel efficiency.



The combination of Selective Catalytic Reduction technology and AdBlue creating an environment friendly vehicle. Adblue is a liquid containing 32,5% of urea to neutralize the harmful Nitrogen Oxides (NOx) into water and nitrogen.

| | | |
|---|---|---|
| **FRAME** | | |
| Type | Side rails, Punching and Riveted construction. | |
| Main Rail Section (mm) | 300 × 80 × 8 | |
| Auxiliary Rail Section (mm) | 284 × 70 × 5 | |
| Frame Width (mm) | 865 | |
| **SUSPENSION** | | |
| Front Suspension | 11 Leaf Springs with Shock Absorber & Stabilizer | |
| Rear Suspension | Bogie Suspension with 13 Leaf Springs | |
| **POWER STEERING** | | |
| Model | Integrated Recirculation, Hydraulic Power Steering | |
| **BRAKE SYSTEM** | | |
| Driving Brake | Full Air Brake, Double Circuit Air Brake | |
| Parking Brake | Spring Energy Storage Type | |
| Auxiliary Brake | Engine Brake | |
| **DIMENSIONS** | | |
| Wheelbase - WB (mm) | 4300 + 1350 | |
| Overall Dimensions | Length (mm) | 8930 |
| | Width (mm) | 2500 |
| | Height (mm) | 3525 |
| Wheel track - Front (mm) | 2070 | |
| Wheel track - Rear (mm) | 1870 | |
| Front Overhang (mm) | 1480 | |
| Rear Overhang (mm) | 1800 | |
| Min. Ground Clearance (mm) | 350 | |
| Approach Angle (°) | 18 | |
| Departure Angle (°) | 40 | |
| **WHEEL** | | |
| Rim | 8.5 - 20 | |
| Tyre | 12.00R20 18PR | |
| **ELECTRICAL SYSTEM** | | |
| Type | Single line, Negative Grounded | |
| Voltage (V) | 24 | |
| Battery (V/Ah) | 2 × 12/180 | |
| **DUMP SPECIFICATIONS** | | |
| Hydraulic Type | Underbody - Standard (Non-Telescopic) | |
| Inner Dimension (mm) | 5800 × 2300 × (1000 + 800 optional) | |


GM MOBIL | FAW TRUCKS

www.gmmobil.com

Jalan Lingkar Luar Barat No.9, Rawa Buaya, Cengkareng, Jakarta Barat 11740 - Indonesia Telp : (021) 5830 0788 Corporate
Email : gmmcare@gmmobil.com



GMM CARE 24 HOURS 1500 329 WA Care: 0822 9999 9329

AFTER SALES SERVICE 24 HOURS

PARTS CENTER PT GAYA MAKMUR MOBIL

PT Gaya Makmur Mobil | @gayamakmurmobil | @gayamakmurmobil | PT Gaya Makmur Mobil | PT Gaya Makmur Mobil