GM MOBIL | FAW TRUCKS

EURO 5 TRACTOR HEAD CNG 6x4

FD380TH



1 TAHUN GARANSI
TANPA BATASAN KILOMETER

Your Trusted Business Partner

FA-BGM-260225

SPECIFICATION FAW TRUCKS FD380TH CNG 6 × 4 TRACTOR HEAD

DRIVETRAIN		
Driving Type	6 × 4	
CABIN		
Type	JH6 High Roof, ECE R29 Certified, 2 Sleeper Bed, Full Floating with Air Suspension, All Metal Closed, Electric & Manual Cabin Lifting.	
Seats	2	
Accessories	Standard Air Conditioner (AC), Radio Tape + USB MP3, Driver seat with cooler and adjuster, Power Window.	
MASS		
Curb Weight (kg)	11950	
Axle Weight Distribution (kg)	Front Axle	6400
	Rear Axle	2850
		2700
Gross Combination Weight - GCW Rated (kg)	49000	
PERFORMANCE		
Min. Turning Radius (m)	8	
Max. Speed (km/h)	98	
Max. Gradeability (%)	35	
Fuel Tank Capacity (L)	(212 × 8) + (120 × 4)	
ENGINE		
Model	**WEICHAI WP12NG.380E51** 6-cylinder in-line, Common Rail, Turbo charger & Intercooler	
Displacement (cc)	11596	
Max.Output Power (HP @Rpm)	380 @1900	
Max.Torque (Nm @Rpm)	1700 @1200 - 1500	
Standard Emission	Euro 5 Standard (*Beyond Euro 4 Compliance*)	
TRANSMISSION		
Model	C12JSDQXL180TA	
Forward Gear Ratio	1 = 12.26; 2 = 9.563; 3 = 7.356; 4 = 5.801; 5 = 4.521; 6 = 3.531; 7 = 2.712; 8 = 2.115; 9 = 1.627; 10 = 1.283; 11 = 1; 12 = 0.781	
Reverse Gear Ratio	R1 = 11.28; R2 = 2.49	
CLUTCH		
Type	Dry type, single plate, diaphragm spring clutch, hydraulic controlled and air auxiliary power supply.	
Driven Plate Diameter (mm)	Ø430	
AXLE CONSTRUCTIONS		
Front Axle	Type	I-Section Beam heavy duty
	Axle Load Capacity (Kg)	7000
Rear Axle	Type	457, Single Reduction
	Reduction Ratio	4.875
	Axle Load Capacity (Kg)	2 × 13000
Gross Combination Weight - GCW (kg)	70000	
DIFFERENTIAL LOCK		
Inter Axle Differential Lock	Yes	
Inter Wheel Differential Lock	Yes	
FRAME		
Type	Side rails, Punching and Riveted construction.	
Main Rail Section (mm)	300 × 80 × 8	
Auxiliary Rail Section (mm)	284 × 70 × 5	
Frame Width (mm)	800	

**The specification can change without prior notice. Performance data depend on operational conditions.*

INTERIOR



Air Conditioner system with automatic control, audio system and USB Port.



ECE-R29 Is a Technology that Uses specified cabin impact limits to ensure passenger protection based on ("ATDs") Anthropomorphic Test Devices.



Driver's seat with Air Suspension system and adjuster for driver's comfort.



Equipped with Multi Information Display for easy monitoring, maintenance and identify initial problem with the vehicle.

FEATURES AND BENEFITS



Fuel Filter with Water Separator supported with system string and 2 Stage Water Removal Technology to provide better and consistent water removal capability.



Auto Slack Adjuster brake for maximum braking result and brake pad adjustment free.



The combination of Selective Catalytic Reduction technology and AdBlue creating an environment friendly vehicle. Adblue is a liquid containing 32,5% of urea to neutralize the harmful Nitrogen Oxides (NOx) into water and nitrogen.



Multi State Switch Load system to control fuel consumption according to the weight load for the result of maximum fuel efficiency.

SUSPENSION		
Front Suspension	10 Leaf Springs with Shock Absorber	
Rear Suspension	Bogie Suspension with 10 Leaf Springs	
POWER STEERING		
Model	Integrated Recirculation, Hydraulic Power Steering	
BRAKE SYSTEM		
Driving Brake	Full Air Brake, Double Circuit Air Brake, Anti-Lock Braking System (ABS) and Auto Slack Adjuster	
Parking Brake	Spring Energy Storage Type	
Auxiliary Brake	Exhaust Brake	
DIMENSIONS		
Wheelbase - WB (mm)	3800 + 1350	
Overall Dimensions	Length (mm)	7415
	Width (mm)	2500
	Height (mm)	3950
Wheel track - Front (mm)	2020	
Wheel track - Rear (mm)	1830	
Front Overhang (mm)	1495	
Rear Overhang (mm)	770	
Min. Ground Clearance (mm)	260	
Approach Angle (°)	17	
Departure Angle (°)	40	
WHEEL		
Rim	9.0 - 22.5	
Tyre	315/80R22.5 20PR	
ELECTRICAL SYSTEM		
Type	Single line, Negative Grounded	
Voltage (V)	24	
Battery (V/Ah)	2 × 12/180	
FIFTH WHEEL		
Kingpin Diameter Ø	90 mm / 3.5"	
Distance to Center Rear Axle (mm)	375	
Distance to Ground (mm)		

GM MOBIL | FAW TRUCKS

Jalan Lingkar Luar Barat No.9, Rawa Buaya, Cengkareng, Jakarta Barat 11740 - Indonesia Telp : (021) 5830 0788 Corporate
Email : gmmcare@gmmobil.com

www.gmmobil.com

PT Gaya Makmur Mobil | @gayamakmurmobil | @gayamakmurmobil | PT Gaya Makmur Mobil | PT Gaya Makmur Mobil

GMM CARE 24 HOURS 1500 329 WA Care: 0822 9999 9329
AFTER SALES SERVICE 24 HOURS
PARTS CENTER PT GAYA MAKMUR MOBIL