GM MOBIL | FAW TRUCKS

EURO 5 TRACTOR HEAD 6x4

FD460TH



1 TAHUN GARANSI
TANPA BATASAN KILOMETER

Your Trusted Business Partner

FA-BGM-260225

SPECIFICATION FAW TRUCKS FD460TH 6 × 4 TRACTOR HEAD

DRIVETRAIN		
Driving Type	6 × 4	
CABIN		
Type	JH6 High Roof, 2 Sleeper Bed, ECE R29 Certified, 4 Point Full Floating with Air Suspension, All Metal Closed, Electric & Manual Cabin Lifting.	
Seats	2	
Accessories	Standard Air Conditioner (AC), Radio Tape + USB MP3, Driver seat with cooler and adjuster, Power Window.	
MASS		
Curb Weight (kg)	9950	
Axle Weight Distribution (kg)	Front Axle	4720
	Rear Axle	2690
		2540
Gross Combination Weight - GCW Rated (kg)	62000	
PERFORMANCE		
Min. Turning Radius (m)	7.2	
Max. Speed (km/h)	65	
Max. Gradeability (%)	48	
Fuel Tank Capacity (L)	600	
ENGINE		
Model	**FAWDE CA6DM2-46E51** 6-cylinder in-line, Common Rail, Turbo charger & Intercooler	
Displacement (cc)	11050	
Max.Output Power (HP @Rpm)	460 @1900	
Max.Torque (Nm @Rpm)	2200 @1000 - 1300	
Standard Emission	Euro 5 Standard (*Beyond Euro 4 Compliance*)	
TRANSMISSION		
Model	C12JSDQXL240T	
Forward Gear Ratio	1 = 14.09; 2 = 10.99; 3 = 8.45; 4 = 6.67; 5 = 5.196; 6 = 4.15; 7 = 3.4; 8 = 2.65; 9 = 2.04; 10 = 1.61; 11 = 1.25; 12 = 1	
Reverse Gear Ratio	R1 = 12.964; R2 = 3.123	
CLUTCH		
Type	Dry type, single plate, diaphragm spring clutch, hydraulic controlled and air auxiliary power supply.	
Driven Plate Diameter (mm)	Ø430	
AXLE CONSTRUCTIONS		
Front Axle	Type	I-Section Beam heavy duty
	Axle Load Capacity (kg)	7000
Rear Axle	Type	LC300, Double Hub Reduction
	Reduction Ratio	5.921
	Axle Load Capacity (kg)	2 × 16000
Gross Combination Weight - GCW (kg)	100000	
DIFFERENTIAL LOCK		
Inter Axle Differential Lock	Yes	
Inter Wheel Differential Lock	Yes	
FRAME		
Type	Side rails, Punching and Riveted construction.	
Main Rail Section (mm)	300 × 80 × 8	
Auxiliary Rail Section (mm)	284 × 70 × 5	
Frame Width (mm)	800	

**The specification can change without prior notice. Performance data depend on operational conditions.*

INTERIOR



Air Conditioner system with automatic control, audio system and USB Port.



ECE-R29 Is a Technology that Uses specified cabin impact limits to ensure passenger protection based on ("ATDs") Anthropomorphic Test Devices.



Driver's seat with Air Suspension system and adjuster for driver's comfort



Equipped with Multi Information Display for easy monitoring, maintenance and identify initial problem with the vehicle.

FEATURES AND BENEFITS



Fuel Filter with Water Separator supported with system string and 2 Stage Water Removal Technology to provide better and consistent water removal capability.



Auto Slack Adjuster brake for maximum braking result and brake pad adjustment free.



The combination of Selective Catalytic Reduction technology and AdBlue creating an environment friendly vehicle. Adblue is a liquid containing 32,5% of urea to neutralize the harmful Nitrogen Oxides (NOx) into water and nitrogen.



Multi State Switch Load system to control fuel consumption according to the weight load for the result of maximum fuel efficiency.

SUSPENSION		
Front Suspension	10 Leaf Springs with Shock Absorber	
Rear Suspension	Bogie Suspension with 11 Leaf Springs	
POWER STEERING		
Model	Integrated Recirculation, Hydraulic Power Steering	
BRAKE SYSTEM		
Driving Brake	Full Air Brake, Double Circuit Air Brake, Anti-Lock Braking System (ABS), Auto Slack Adjuster	
Parking Brake	Spring Energy Storage Type	
Auxiliary Brake	Engine brake	
DIMENSIONS		
Wheelbase - WB (mm)	3300 + 1350	
Overall Dimensions	Length (mm)	7000
	Width (mm)	2500
	Height (mm)	3585
Wheel track - Front (mm)	2070	
Wheel track - Rear (mm)	1870	
Front Overhang (mm)	1525	
Rear Overhang (mm)	825	
Min. Ground Clearance (mm)	350	
Approach Angle (°)	19	
Departure Angle (°)	42	
WHEEL		
Rim	8.5 - 20	
Tyre	12.00R20 20PR	
ELECTRICAL SYSTEM		
Type	Single line, Negative Grounded	
Voltage (V)	24	
Battery (V/Ah)	2 × 12/180	
FIFTH WHEEL		
Kingpin Diameter Ø	90 mm / 3.5"	
Distance to Center Rear Axle (mm)	400	
Distance to Ground (mm)		

GM MOBIL | FAW TRUCKS

www.gmmobil.com

Jalan Lingkar Luar Barat No.9, Rawa Buaya, Cengkareng, Jakarta Barat 11740 - Indonesia Telp : (021) 5830 0788 Corporate
Email : gmmcare@gmmobil.com

GMM CARE 24 HOURS 1500 329 WA Care:0822 9999 9329
AFTER SALES SERVICE 24 HOURS
PARTS CENTER PT GAYA MAKMUR MOBIL

PT Gaya Makmur Mobil | @gayamakmurmobil | @gayamakmurmobil | PT Gaya Makmur Mobil | PT Gaya Makmur Mobil