GM MOBIL | FAW TRUCKS

EURO 6 TRACTOR HEAD 6x4

FD660TH



1 TAHUN GARANSI
TANPA BATASAN KILOMETER

Your Trusted Business Partner

FA-BGM-260831

SPECIFICATION FAW TRUCKS FD660TH 6 × 4 TRACTOR HEAD

DRIVETRAIN		
Driving Type	6 × 4	
CABIN		
Type	J7 High Roof Semi Flat Floor Cab with 2 Sleeper Bed, 4 Point Full Floating with Air Suspension, Electric & Manual Cabin Lifting.	
Seats	2	
Accessories	Standard Air Conditioner (AC), USB MP3, Adjustable driver seat with Air Suspension, 10-inch Infotainment Display, HD 360° Surround View Camera System, Power Window.	
MASS		
Curb Weight (kg)	11200	
Gross Combination Weight - GCW (kg)	270000	
PERFORMANCE		
Min. Turning Radius (m)	7.85	
Max. Speed (km/h)	81	
Max. Gradeability (%)	16	
Fuel Tank Capacity (L)	600	
ENGINE		
Model	**FAWDE CA6DX1-66E66** 6-cylinder in-line, Common Rail, Turbo charger & Intercooler	
Displacement (cc)	15570	
Max.Output Power (HP @Rpm)	660 @1600	
Max.Torque (Nm @Rpm)	3300 @1300	
Standard Emission	Euro 6 Standard (Beyond Euro 4 Compliance)	
TRANSMISSION		
Model	ZF-12TX3461TO	
Type	AMT Overdrive, Retarder with Spline type PTO output	
Forward Gear Ratio	1 = 12.92; 2 = 9.98; 3 = 7.69; 4 = 5.94; 5 = 4.57; 6 = 3.53; 7 = 2.83; 8 = 2.19; 9 = 1.68; 10 = 1.3; 11 = 1; 12 = 0.77	
Reverse Gear Ratio	R1 = 12.03; R2 = 9.29	
CLUTCH		
Type	Dry type, single plate, diaphragm spring clutch, hydraulic controlled and air auxiliary power supply.	
Driven Plate Diameter (mm)	Ø430	
AXLE CONSTRUCTIONS		
Front Axle	Type	F9N-2055
	Axle Load Capacity (kg)	9000
Rear Axle	Reduction Ratio	6.733
	Axle Load Capacity (kg)	2 × 16000
DIFFERENTIAL LOCK		
Inter Axle Differential Lock	Yes	
Inter Wheel Differential Lock	Yes	

**The specification can change without prior notice. Performance data depend on operational conditions.*

FRAME		
Type	Side rails, Punching and Riveted construction.	
Main Rail Section (mm)	300 × 80 × 8	
Auxiliary Rail Section (mm)	284 × 70 × 5	
Frame Width (mm)	800	
SUSPENSION		
Front Suspension	10 Leaf Springs (20 × 90) with Shock Absorber and Stabilizer	
Rear Suspension	11 Leaf Springs (25 × 90) with Stabilizer	
POWER STEERING		
Model	Integrated Recirculation, Hydraulic Power Steering	
BRAKE SYSTEM		
Driving Brake	Full Air Brake, Double Circuit Air Brake, ABS + ESC , Auto Slack Adjuster.	
Parking Brake	Spring Energy Storage Type	
Auxiliary Brake	Hydraulic Retarder	
DIMENSIONS		
Wheelbase - WB (mm)	3550 + 1450	
Overall Dimensions	Length (mm)	7430
	Width (mm)	2500
	Height (mm)	3835
Wheel track - Front (mm)	2070	
Wheel track - Rear (mm)	1870	
Front Overhang (mm)	1500	
Rear Overhang (mm)	930	
Min. Ground Clearance (mm)	400	
Approach Angle (°)	19	
Departure Angle (°)	42	
WHEEL		
Rim	8.5 - 24	
Tyre	12.00R24 20PR	
ELECTRICAL SYSTEM		
Type	Single line, Negative Grounded	
Voltage (V)	24	
Battery (V/Ah)	2 × 12/220	
FIFTH WHEEL		
Kingpin Diameter Ø	90 mm / 3.5"	
Distance to Center Rear Axle (mm)	375	
Distance to Ground (mm)	1600	
OTHERS		
One Touch Engine Start, Automatic LED headlamps with front fog lamps, Extended service primary fuel filter (without electric heating, with water separator) + biodiesel compatible fuel filter), FCW (Forward Collision Warning), LDW (Lane Departure Warning), DMS (Driver-fatigue Monitoring System)		