GM MOBIL | FAW TRUCKS

EURO 5 DUMP TRUCK 8x4

HD430DT



1 TAHUN GARANSI
TANPA BATASAN KILOMETER

Your Trusted Business Partner

FA-BGM-260225

SPECIFICATION FAW TRUCKS HD430DT 8 × 4 DUMP TRUCK

DRIVETRAIN		
Driving Type	8 × 4	
CABIN		
Type	JH6 Flat Roof, 1 Sleeper Bed, ECE R29 Certified, Full Floating with Front Air Suspension & Rear Coil Spring Suspension, All Metal Closed, Electric & Manual Cabin Lifting.	
Seats	2	
Accessories	Standard Air Conditioner (AC), Radio Tape + USB MP3, Driver seat with adjuster, Power Window.	
MASS		
Curb Weight (kg)	17350	
Axle Weight Distribution (kg)	Front Axle	4790
		4030
	Rear Axle	4290
		4240
Gross Vehicle Weight - GVW Rated (kg)	38000	
PERFORMANCE		
Min. Turning Radius (m)	10.5	
Max. Speed (km/h)	75	
Max. Gradeability (%)	62	
Fuel Tank Capacity (L)	400	
ENGINE		
Model	**WEICHAI WP12.430E50** 6-cylinder in-line, Common Rail, Turbo charger & Intercooler	
Displacement (cc)	11596	
Max. Output Power (HP @Rpm)	430 @2000	
Max. Torque (Nm @Rpm)	2000 @1300 - 1600	
Standard Emission	Euro 5 Standard (Beyond Euro 4 Compliance)	
TRANSMISSION		
Model	12JSDX240T	
Forward Gear Ratio	1 = 13.154; 2 = 10.349; 3 = 8.223; 4 = 6.52; 5 = 5.126; 6 = 4.09; 7 = 3.211; 8 = 2.526; 9 = 2; 10 = 1.591; 11 = 1.251; 12 = 1	
Reverse Gear Ratio	R1 = 12.582; R2 = 3.071	
CLUTCH		
Type	Dry type, single plate, diaphragm spring clutch, hydraulic controlled and air auxiliary power supply.	
Driven Plate Diameter (mm)	Ø430	
CAXLE CONSTRUCTIONS		
Front Axle	Type	I-Section Beam Heavy Duty
	Axle Load Capacity (kg)	2 × 9000
Rear Axle	Type	LC300, Double Hub Reduction
	Reduction Ratio	5.921
	Axle Load Capacity (kg)	2 × 16000
Gross Vehicle Weight - GVW (kg)	50000	
DIFFERENTIAL LOCK		
Inter Axle Differential Lock	Yes	
Inter Wheel Differential Lock	Yes	
FRAME		
Type	Side rails, Punching and Riveted construction.	
Main Rail Section (mm)	300 × 80 × 8	
Auxiliary Rail Section (mm)	284 × 70 × 8	
	268 × 62 × 5	
Frame Width (mm)	865	

INTERIOR



Air Conditioner system with automatic control, audio system and USB Port.



ECE-R29 Is a Technology that Uses specified cabin impact limits to ensure passenger protection based on ("ATDs") Anthropomorphic Test Devices.



Driver's seat with Air Suspension system and adjuster for driver's comfort



Equipped with Multi Information Display for easy monitoring, maintenance and identify initial problem with the vehicle.

FEATURES AND BENEFITS



Fuel Filter with Water Separator supported with system string and 2 Stage Water Removal Technology to provide better and consistent water removal capability.



Multi State Switch Load system to control fuel consumption according to the weight load for the result of maximum fuel efficiency.



The combination of Selective Catalytic Reduction technology and AdBlue creating an environment friendly vehicle. Adblue is a liquid containing 32,5% of urea to neutralize the harmful Nitrogen Oxides (NOx) into water and nitrogen.

SUSPENSION		
Front Suspension	11 Leaf Springs with Shock Absorber & Stabilizer	
Middle Suspension	13 Leaf Springs with Shock Absorber	
Rear Suspension	Bogie Suspension with 13 Leaf Springs	
POWER STEERING		
Model	Integrated Recirculation, Hydraulic Power Steering	
BRAKE SYSTEM		
Driving Brake	Full Air Brake, Double Circuit Air Brake	
Parking Brake	Spring Energy Storage Type	
Auxiliary Brake	Engine Brake	
DIMENSIONS		
Wheelbase - WB (mm)	1900 + 3750 + 1450	
Overall Dimensions	Length (mm)	10580
	Width (mm)	2500
	Height (mm)	3590
Wheel track - Front (mm)	2070	
Wheel track - Rear (mm)	1870	
Front Overhang (mm)	1495	
Rear Overhang (mm)	1985	
Min. Ground Clearance (mm)	370	
Approach Angle (°)	29	
Departure Angle (°)	40	
WHEEL		
Rim	8.5 - 24	
Tyre	12.00R24 20PR	
ELECTRICAL SYSTEM		
Type	Single line, Negative Grounded	
Voltage (V)	24	
Battery (V/Ah)	2 × 12/180	
DUMP SPECIFICATIONS		
Hydraulic Type	Front - Telescopic	
Inner Dimension (mm)	7600 × 2300 × (1000 + 1000 optional)	

**The specification can change without prior notice. Performance data depend on operational conditions.*

GM MOBIL | FAW TRUCKS

Jalan Lingkar Luar Barat No.9, Rawa Buaya, Cengkareng, Jakarta Barat 11740 - Indonesia Telp : (021) 5830 0788 Corporate
Email : gmmcare@gmmobil.com

www.gmmobil.com

PT Gaya Makmur Mobil @gayamakmurmobil @gayamakmurmobil PT Gaya Makmur Mobil PT Gaya Makmur Mobil

GMM CARE 24 HOURS 1500 329 WA Care: 0822 9999 9329

AFTER SALES SERVICE 24 HOURS

PARTS CENTER PT GAYA MAKMUR MOBIL