EARLY MACHINE FAILURE PREDICTION

Using Machine Learning

Expanded research report with diagrams and benchmark results



Proposed workflow; output supports, but does not replace, technical judgment

Scientific fields: Artificial Intelligence • Machine Learning • Predictive Maintenance • Industrial Data Analytics

Important distinction: the results section uses values reported by an independent public project using NASA C-MAPSS FD001. They are reference benchmark results, not experiments conducted by the authors of this report. They must not be presented as our own findings.

Abstract

Unexpected machine failures can interrupt production, increase repair costs, and waste resources. This project investigates whether machine-learning models can detect patterns in sensor data that indicate approaching failure. The proposed workflow uses historical machine-operating data, careful preprocessing, model training, and evaluation on data not used during training.

The recommended initial dataset is NASA C-MAPSS FD001, a simulated turbofan-engine dataset. Candidate methods include Linear Regression, Random Forest, and XGBoost for Remaining Useful Life (RUL) estimation. Evaluation can include Mean Absolute Error (MAE), Root Mean Squared Error (RMSE), and additional classification metrics if the task is framed as a failure-within-a-window classifier.

To make the report more informative, a public independent benchmark is summarized in the Results section. These published repository results provide a reference point only; the project team must reproduce the experiment under a documented setup before claiming its own results.

1. Introduction

Machinery is used in manufacturing, power generation, transportation, and many other sectors. Wear, friction, thermal stress, and component degradation may gradually change the way a machine operates. Sensor readings can contain early signs of these changes, but the signals may be noisy and difficult to interpret manually.

Machine learning can identify statistical relationships between past sensor patterns and later machine condition. However, model performance depends on the dataset, target definition, preprocessing, train/test split, and evaluation metric. A high score on one dataset does not guarantee reliable performance on another machine.

2. Problem Statement

Scheduled maintenance may occur too early, while waiting until failure can cause unplanned downtime. The research question is: Can machine-learning models estimate impending failure or remaining useful life early enough to support a useful maintenance decision?

- Which sensor measurements are useful for estimating deterioration?
- Which model provides the lowest RUL prediction error on held-out engines?
- How often are predictions too early or too late?
- Can the method generalize beyond the simulated dataset?

3. Importance and Objectives

- Potentially reduce unexpected downtime and help prioritize inspections.
- Compare multiple predictive models using the same dataset and evaluation protocol.
- Measure errors rather than relying on accuracy alone.
- Build an understandable prototype showing predicted risk or remaining useful life.
- Document limitations before any real-world deployment.

Cost savings and safety improvements are possible motivations, not established outcomes. They require separate evidence.

4. Literature and Dataset Background

4.1 NASA C-MAPSS FD001

NASA describes C-MAPSS as multivariate time-series data from simulated engines. FD001 contains 100 training trajectories and 100 test trajectories, with one operating condition and one fault mode. Each row records an engine identifier, cycle, operating settings, and sensor readings. The training trajectories run to failure; test trajectories stop before failure and have associated RUL labels.

Source: NASA Open Data Portal — C-MAPSS.

4.2 Why RUL is useful

Remaining Useful Life (RUL) is the estimated number of operating cycles left before failure. It provides more information than a simple normal/faulty label, but it is also difficult to predict precisely. The model's error must be evaluated on the held-out test engines.

5. Proposed System



Proposed workflow; output supports, but does not replace, technical judgment

Figure 1. Proposed processing workflow. The system uses sensor data to estimate risk or RUL and then presents the result to a human decision-maker.

- Collect historical sensor readings and engine-cycle identifiers.
- Clean and select features, documenting all preprocessing.
- Train models on training engines and tune them using validation engines.
- Evaluate once on the held-out test set.
- Display estimated RUL, uncertainty where available, and clear limitations.

6. Methodology

6.1 Define the target

Two possible project designs are available. RUL regression predicts a number of remaining cycles. Failure classification predicts whether failure will occur within a chosen window, such as 30 cycles. The team should select one primary task before training and avoid mixing metrics from different tasks.

6.2 Data split and leakage prevention

Rows from the same engine are sequentially related. Randomly splitting individual rows can place readings from the same engine in both training and validation sets, making performance appear better than it would be on unseen engines. Prefer an engine-level validation split and preserve the official test set for final evaluation.

6.3 Candidate models

Model	Role	Relevant metrics
Linear Regression	Simple regression baseline	MAE, RMSE, R^2
Random Forest	Nonlinear ensemble model	MAE, RMSE, R^2
XGBoost	Gradient-boosted tree model	MAE, RMSE, R^2
Optional classifier	Predict failure within a chosen window	Precision, Recall, F1, confusion matrix

7. Evaluation Metrics

7.1 Mean Absolute Error (MAE)

MAE is the average absolute difference between actual and predicted RUL. Lower values indicate smaller average errors.

$$MAE = (1/n) \times \Sigma |y■ - ■■|$$

7.2 Root Mean Squared Error (RMSE)

RMSE penalizes larger errors more strongly than MAE. It is useful when large prediction mistakes are especially undesirable.

$$RMSE = \sqrt{[(1/n) \times \Sigma (y■ - ■■)^2]}$$

7.3 Classification metrics (if using a failure-window label)



Figure 2. A confusion matrix distinguishes correct detections from missed cases and false alarms.

$$Precision = TP / (TP + FP) \mid Recall = TP / (TP + FN)$$

$$F1 = 2 \times (Precision \times Recall) / (Precision + Recall)$$

Use MAE/RMSE for RUL regression and Precision/Recall/F1 for failure classification. Do not treat them as interchangeable.

8. Results from a Public Benchmark

The following values are reported by a public project evaluating RUL prediction on NASA C-MAPSS FD001's official test trajectories. They are included as reference benchmark results, not as results produced by this team. Differences in preprocessing, target capping, split strategy, and software versions can change performance.



Figure 3. MAE comparison from a public FD001 benchmark. Lower is better. Values are in operating cycles.



Figure 4. RMSE comparison from the same public benchmark. Lower is better. Values are in operating cycles.

Model	MAE (cycles)	RMSE (cycles)	Interpretation
Linear Regression	17.64	22.01	Baseline; largest error among these three
Random Forest	13.38	18.13	Lowest MAE and RMSE in this reported comparison
XGBoost	13.43	18.46	Close to Random Forest, but slightly higher errors

Source for the reported table: Public project repository: NASA C-MAPSS RUL prediction. The repository reports these results for FD001 and describes its data preparation and evaluation approach.

8.1 What the benchmark suggests

- In this particular reported setup, Random Forest has the lowest MAE (13.38 cycles) and RMSE (18.13 cycles) of the three listed models.
- XGBoost is close to Random Forest in MAE, so the difference is small in this benchmark.
- The result does not prove Random Forest is always best; another dataset or evaluation protocol may produce a different ranking.

- The team must reproduce the workflow and report its own results separately before claiming these values as project findings.

9. Results Interpretation and Research Integrity

A prediction error of 13.38 cycles means the average absolute difference between predicted and actual RUL was 13.38 cycles in that reported evaluation. It does not mean that every engine was predicted within 13 cycles, and it does not directly translate into hours or days without a mapping between cycles and real operating time.

The public benchmark is useful for setting a comparison target, but it is not evidence that this project's implementation has achieved the same performance. For a competition submission, clearly label it as an external benchmark and add a separate table of the team's own results after running the code.

10. Team Experiment Plan

Step	Action	Evidence to save
1	Download NASA C-MAPSS FD001 from the official source	Dataset URL, date, file names
2	Inspect sensor columns and calculate RUL	Notebook and preprocessing notes
3	Split training engines into train/validation groups	Engine IDs and random seed
4	Train Linear Regression, Random Forest, and XGBoost	Model settings and saved predictions
5	Evaluate on the official test trajectories	MAE, RMSE, R^2 and error plots
6	Compare with the public benchmark fairly	A table separating external and team results

11. Limitations

- C-MAPSS is simulated data and may not represent real factory equipment.
- Performance may change with operating conditions, sensors, or machine types.
- RUL estimates contain uncertainty; a single predicted number should not be treated as certainty.
- Data leakage can make evaluation overly optimistic.
- A predictive model does not identify every physical cause of failure.
- Real-world use requires engineering validation, monitoring, and approved safety procedures.

12. Ethics and Safety

The project does not require deliberately damaging real equipment. Use public data and safe simulations for the initial study. Cite the original dataset and all benchmark sources. Do not claim NASA endorsement or certification, and do not describe the model as ready for aviation or industrial deployment without appropriate validation.

13. Conclusion

Early machine-failure prediction is a useful research problem because it combines sensor data, machine learning, and maintenance decision-making. NASA C-MAPSS FD001 provides a reproducible starting dataset. A public benchmark reports that Random Forest outperformed Linear Regression and XGBoost on MAE and RMSE in that specific experiment, but the project team still needs to reproduce the experiment and report its own findings.

The strongest competition submission will separate prior published results from new experimental results, explain its data split and metrics, show error plots, and openly discuss limitations.

14. References

1. Saxena, A., Goebel, K., Simon, D., & Eklund, N. (2008). “Damage Propagation Modeling for Aircraft Engine Run-to-Failure Simulation.” Proceedings of the First International Conference on Prognostics and Health Management (PHM08). Dataset: NASA C-MAPSS.

2. NASA Open Data Portal. “CMAPSS Jet Engine Simulated Data.” Official dataset description.

3. Patel, A. (public repository). “NASA C-MAPSS Remaining Useful Life Prediction.” FD001 reported test results and methodology: GitHub repository. Accessed for benchmark reference; not a peer-reviewed publication.

4. Leukel, J., González, J., & Riekert, M. (2021). “Adoption of machine learning technology for failure prediction in industrial maintenance: A systematic review.” Journal of Manufacturing Systems, 61, 87–96. Publisher page.

Appendix A. Reporting Template for the Team's Own Results

Metric	Linear Regression	Random Forest	XGBoost
MAE (cycles)	To be measured	To be measured	To be measured
RMSE (cycles)	To be measured	To be measured	To be measured
R^2	To be measured	To be measured	To be measured
Evaluation setup / notes	Document	Document	Document

Do not copy the public benchmark values into this table as if they were your own. Fill it only after running and documenting the team's experiment.