

The hagenberg-thesis Package

W. Burger and W. Hochleitner

University of Applied Sciences Upper Austria
Department of Digital Media, Hagenberg (Austria)

2023/10/26

Abstract

The `hagenberg-thesis` package is a collection of modern LaTeX templates for university theses (bachelor, master, or diploma programs) and related documents. This manual describes the main features of this package. Pre-configured document templates for English and German manuscripts and a complete tutorial are available on the package's home repository.

1 Introduction

The complete source of this package and auxiliary materials are available on CTAN¹ and its development repository.² The package is made available under the terms of the Creative Commons Attribution 4.0 International Public License.³

2 Document classes

The `hgb` package provides the following document classes, which are based on the standard LaTeX classes `book`, `report`, and `article`, respectively:

- `hgbthesis` (`book`): for bachelor's, master's, and diploma theses;
- `hgbreport` (`report`): for project and term reports;
- `hgbarticle` (`article`): for drafting journal articles.

2.1 Class options

2.1.1 General options

All document classes accept the following general options:

- `english` or `german` (select the primary language),
- `smartquotes` (use smart quotes replacement),
- `apa` (use `apa` bibliography style instead of `numeric-comp`),
- `noUpdateCheck` (suppress check of package release date).

¹<https://ctan.org/pkg/hagenberg-thesis>

²<https://github.com/Digital-Media/HagenbergThesis>

³<https://creativecommons.org/licenses/by/4.0/legalcode>

2.1.2 Class-specific options

In addition, the following class-specific options are accepted:

- **hgbthesis**: `type={bachelor, master, diploma, phd, internship, custom}`,
`titlelanguage={english, german}, proposal`;
- **hgbreport**: `notitlepage`;
- **hgbarticle**: `twocolumn`.

For example, to start a master’s thesis in German, simply place

```
\documentclass[type=master,german,smartquotes]{hgbthesis}
```

at the beginning of the document.

The **proposal** option is intended for a *thesis proposal* (“Exposé” or “Proposal”) and is only effective in *conjunction* with the main thesis types, e.g.,

```
\documentclass[type=bachelor,proposal,english,titlelanguage=german]{hgbthesis}
```

The result is a short exposé that contains only one chapter. Thus, chapter numbers are not displayed. Remove the **proposal** option to migrate a proposal document straight to the final thesis (and restore the usual numbering scheme).

2.2 Thesis parameters (class hgbthesis)

hgbthesis supports several types of thesis documents. The following parameters must be specified for *all* types at the beginning of the main document:

- `\title{...}`,
- `\author{...}`,
- `\programtype{...}`,
- `\programname{...}`,
- `\institution{...}`,
- `\placeofstudy{...}`,
- `\dateofsubmission{yyyy}{mm}{dd}`,
- `\advisor{...}` (optional),

Note that **hgbthesis** only supports a *single author* inside the `\author{...}` macro argument (commands `\and` and `\thanks{...}` are deactivated)!

Other (optional) settings for **hgbthesis** include:

- `\license{cc|strict}`
Use the Creative Commons License (`cc` = default) or strict terms (“all rights reserved”);
- `\logfile{xxx.pdf}`
Specifies a custom logo image for the title page, to be placed in `images/xxx.pdf` (default is `logo.pdf`).

3 Style files and user commands

The package comes with a set of style (`*.sty`) files that can be used independently of the document classes listed above: `hgb.sty`, `hgbabbrev.sty`, `hgbbib.sty`, `hgbheadings.sty`,

hgblistings.sty, hgbmath.sty.

3.1 General user commands and environments (hgb.sty)

- **\hgbDate**
Outputs the package version date, e.g., “2023/10/26”.
- **\getcurrentlabel**
Yields the most recently assigned label number.
- **\calibrationbox{width}{height}**
Inserts a test box for checking the final print size (in millimeters).
- **\begin{block}...\end{block}**
Dummy environment, provides a limited scope for variable/command redefinitions.
- **\begin{english}...\end{english}**
Temporarily switches to English language settings.
- **\begin{german}...\end{german}**
Temporarily switches to German language settings.

3.2 Text commands (hgbabbrev.sty)

Special characters:

- **\bs**: Inserts a backslash character (short for `\textbackslash`).
- **\obnh**: Inserts an optional break with no hyphen (e.g., `PlugIn{\obnh}Filter`).

German abbreviations:

- **\bzgl**: bzgl.
- **\bzw**: bzw.
- **\ca**: ca.
- **\dah**: d. h.
- **\Dah**: D. h.
- **\ds**: d. sind
- **\etc**: etc.
- **\evtl**: evtl.
- **\ia**: i. Allg.
- **\sa**: s. auch
- **\so**: s. oben
- **\su**: s. unten
- **\ua**: u. a.
- **\Ua**: U. a.
- **\uae**: u. Ä.
- **\usw**: usw.
- **\uva**: u. v. a.

- `\uvm`: u. v. m.
- `\va`: vor allem
- `\vgl`: vgl.
- `\zB`: z. B.
- `\ZB`: Zum Beispiel

English abbreviations:

- `\ie`: i.e.
- `\eg`: e.g.
- `\etc`: etc.
- `\Eg`: E.g.
- `\wrt`: w.r.t.

Note that none of the above abbreviation macros “eats” subsequent white space, i.e., they can be used without additional controls, as in “`\wrt what I said`”, for example.

3.3 Bibliography commands (`hgbbib.sty`)

- `\AddBibFile`
A wrapper to `biblatex`’s `\addbibresource` macro (for backward compatibility only).
- `\MakeBibliography[options]`
Inserts the reference section or chapter. By default, references are automatically split into category subsections.⁴ Use the option `nosplit` to produce a traditional (i.e., contiguous) list of references.
- `\mcite[text1]{key1}[text2]{key2}\dots[textN]{keyN}`
Analogous to `biblatex`’s `\cites` command⁵ but inserts semicolons between reference entries for better readability.

3.4 Code environments (`hgblistings.sty`)

The following types of code environments are defined:

- `CCode`: for C (ANSI),
- `CppCode`: for C++ (ISO),
- `CsCode`: for C#,
- `CssCode`: for CSS,
- `GenericCode`: for generic code,
- `HtmlCode`: for HTML,
- `JavaCode`: for Java,
- `JsCode`: for JavaScript,
- `LaTeXCode`: for LaTeX,
- `ObjCCode`: for ObjectiveC,

⁴Predefined reference categories are `literature`, `avmedia`, `online` and `software`.

⁵<http://mirrors.ctan.org/macros/latex/contrib/biblatex/doc/biblatex.pdf> (see Sec. 3.8.3)

- **PhpCode**: for PHP,
- **PythonCode**: for Python,
- **Swift**: for Swift,
- **XmlCode**: for XML.

`hgblistings` is based on the `listingsutf8`⁶ package, thus any valid `listings`⁷ option may be used; for example, the option `numbers=none` to suppress line numbers:

```
\begin{JavaCode}[numbers=none]
... // Java code comes here
\end{JavaCode}
```

3.5 Mathematical commands (`hgmath.sty`)

`hgmath` requires (and automatically loads) the `amsmath`⁸ package, thus, all commands and symbols of `amsmath` are available by default. The following *additional* commands can only be used in math mode:

- **\Cpx**: \mathbb{C} (complex numbers),
- **\N**: \mathbb{N} (natural numbers),
- **\R**: \mathbb{R} (real numbers),
- **\Q**: \mathbb{Q} (rational numbers),
- **\Z**: \mathbb{Z} (integer numbers).

3.6 Algorithms (`hgbalgo.sty`)

`hgbalgo` is a stand-alone package that is based on – and extends – the `algorithmicx` and `algpseudocodex` packages.⁹ It fixes some (mostly indentation-related) problems, adds color, and provides some additional commands. It also loads the `algorithm`¹⁰ package, which defines a compatible float container for algorithms: `\begin{algorithm} ... \end{algorithm}`.

Additional algorithm commands:

- **\StateNN[<nesting>]{<text>}**: Creates a *non-numbered* statement like `algorithmicx`'s `\State` command but provides controlled indentation inside nested constructs. The optional integer argument `<nesting>` can be used to specify the *nesting depth* to compensate for a bug in `algorithmicx` (the nesting level inside a block is not set properly before the first `\State` command). Omitting the optional argument should give correct indentation in most situations.
- **\Input{<text>}**: For describing the input parameters in a procedure's preamble.
- **\Output{<text>}**: For describing the output values in a procedure's preamble.
- **\Returns{<text>}**: For describing the return values in a procedure's preamble.

⁶<https://ctan.org/pkg/listingsutf8>

⁷<https://ctan.org/pkg/listings>

⁸<https://ctan.org/pkg/amsmath>

⁹<https://ctan.org/pkg/algorithmicx>, <https://ctan.org/pkg/algpseudocodex>

¹⁰<https://ctan.org/pkg/algorithms>

Vertical spacing commands: The following commands are provided for fine-tuning the vertical spacing between individual statements of an algorithm (the standard spacing commands like `\smallskip` etc. have no effect between statements):¹¹

- `\algsmallskip`: inserts 3pt extra space,
- `\algmedskip`: inserts 6pt extra space,
- `\algbigskip`: inserts 12pt extra space.

They are supposed to be used inside (i.e., at the end of) statements, for example:

```
\State $x \gets x + 1$ \algsmallskip
```

Defined algorithm colors:

- `AlgKeywordColor` (for algorithm keywords),
- `AlgProcedureColor` (for procedure and function names).

These colors can be redefined at any time (see the `xcolor`¹² package), e.g., by

```
\definecolor{AlgKeywordColor}{named}{black}
\definecolor{AlgProcedureColor}{rgb}{0.0, 0.5, 0.0} % dark green
```

4 PDF/A generation (`hgbpdfa.sty`)

Package `hgbpdfa` contains definitions for generating PDF/A-compliant output files. It is based on the `pdfmanagement-testphase` package (requires version 0.95s or higher) and must be loaded before the `\documentclass` statement in the main document, for example, by

```
\RequirePackage{hgbpdfa}
```

If omitted, a plain PDF (non PDF/A-compliant) file is generated.

5 Customizing thesis title pages

The content and structure of the title pages generated for the various thesis types (`bachelor`, `master` etc.) may be customized to meet the specific requirements of different institutions or departments. Thus customization is usually done at the institutional level and not be the individual student.

5.1 Standard title page setups (*themes*)

The various front page arrangements are called *themes* in the following. Technically, each theme is associated with a particular `.sty` (LaTeX package) file, i.e.,

```
hgbtheme-bachelor.sty,
hgbtheme-master.sty,
hgbtheme-diploma.sty,
```

¹¹Note that the standard spacing commands work *between* `procedure` and `function` blocks in the usual way.

¹²<https://ctan.org/pkg/xcolor>

```
hgbtheme-phd.sty,
hgbtheme-internship.sty.
```

All these “inherit” from a parent theme file

```
hgbtheme-thesis.sty,
```

which contains the bulk of the definitions, while derived themes typically contain only a small number of specific settings.

5.2 Custom title page themes

To customize the title pages to their needs, authors (or administrators) should *not* modify any of the standard theme files, since these may not be local but loaded from a package distribution. There are two recommended ways instead:

5.2.1 Option 1: Adapt hgbtheme-custom.sty

File `hgbtheme-custom.sty` (which is part of this distribution) is a blank theme file that may be freely edited. Like all standard themes it inherits from `hgbtheme-thesis.sty`, whose commands are all visible and may be redefined (see Sec. 5.3 for available commands). To activate the associated theme simply use `custom` as the document type, i.e.,

```
\documentclass[type=custom,...]{hgbthesis}
```

This should be sufficient if only a *single* custom theme is needed.

5.2.2 Option 2: Create multiple custom themes

Thesis administrator may find it useful to define multiple custom themes for their institution or department. For this purpose, simply copy file `hgbtheme-custom.sty` to, e.g., a new file `hgbtheme-physics.sty`,¹³ and modify it accordingly. The associated theme can then be activated by

```
\documentclass[type=physics,...]{hgbthesis}
```

An error will be raised if the associated `.sty` file cannot be found.

5.3 Commands and variables available to custom theme styles

The following macros and variables are assured to be available for defining custom themes (see `hgbtheme-thesis.sty` for their typical usage):

Page generation commands:

- `\hgb@MakeFrontPages`
- `\hgb@MakeTitlePage`
- `\hgb@MakeAdvisorPage`
- `\hgb@MakeCopyrightPage`
- `\hgb@MakeDeclarationPage`

Variables:

¹³To be placed in the same directory as the main document. Note the naming conventions!

- \hgb@TitlePageFont
- \hgb@TitleLanguage
- \hgb@ThesisNameDE, \hgb@ThesisNameEN
- \hgb@ProposalNameDE, \hgb@ProposalNameEN
- \hgb@IsProposal
- \hgb@Institution
- \hgb@PlaceOfStudy
- \hgb@LogoHeight
- \hgb@LogoFile
- \hgb@Advisor
- \hgb@StrictLicenseDE, \hgb@StrictLicenseEN, \hgb@StrictLicense
- \hgb@ccLicenseDE, \hgb@ccLicenseEN, \hgb@ccLicense
- \hgb@TheLicense
- \theauthor
- \hgb@DeclarationTitleDE, \hgb@DeclarationTitleEN
- \hgb@DeclarationTextDE, \hgb@DeclarationTextEN
- hgb@DateOfSubmission (DTM date)

6 Package dependencies

The hagenberg-thesis package builds on the following LaTeX packages:

abstract, algorithm, algorithmicx, algpseudocodex, amsbsy, amsfonts, amsmath, amssymb, babel, biblatex, breakurl, caption, cmap, csquotes, datetime2, enumitem, epstopdf, exscale, fancyhdr, float, fontenc, geometry, graphicx, hypcap, hyperref, ifpdf, inputenc, lengthconvert, listingsutf8, lmodern, marvosym, moreverb, overpic, pdfpages, pict2e, subdepth, titlesec, titling, tocbasic, url, upquote, verbatim, xcolor, xifthen, xstring, xspace.