

The hagenberg-thesis Package

W. Burger and W. Hochleitner

University of Applied Sciences Upper Austria
Department of Digital Media, Hagenberg

2026/09/14

Abstract

The `hagenberg-thesis` package is a collection of LaTeX templates for academic theses (bachelor, master, diploma or PhD programs) and related documents. This manual describes the main features of this package and how they may be customized. Pre-configured document templates for English and German manuscripts and a complete tutorial are available on the package's home repository.

Contents

1	Introduction	3
2	Document classes	3
2.1	Class options	3
2.1.1	General options	3
2.1.2	Class-specific options	3
2.2	Thesis settings (class hgbthesis)	4
2.3	Degree program type and academic degree	5
3	Style files and user commands	6
3.1	General user commands and environments (hgb.sty)	7
3.2	Language switching commands and smart quotes (hgb.sty)	7
3.3	Text commands (hgbabbrev.sty)	7
3.4	Bibliography commands (hgbbib.sty)	8
3.5	Code environments (hgblistings.sty)	8
3.5.1	Code style	9
3.6	Mathematical commands (hgbmath.sty)	10
3.7	Algorithms (hgbalgo.sty)	10
3.8	Documentation of AI tool usage (hgbaiusage.sty)	11
3.9	PDF/A generation (hgbpdfa.sty)	13
4	Custom front pages using <i>themes</i>	13
4.1	Preconfigured themes	13
4.2	Brand: logo and institution name	14
4.3	Customizing themes	14
4.3.1	Option 1: Adapt hgbtheme-custom.sty	14
4.3.2	Option 2: Create multiple custom themes	15
4.4	Commands and variables available to custom theme styles	15
5	Package dependencies	16

1 Introduction

W. Burger and W. Hochleitner

University of Applied Sciences Upper Austria
Department of Digital Media, Hagenberg

The complete source of this package and auxiliary materials are available on CTAN¹ and its development repository.² The package is made available under the terms of the Creative Commons Attribution 4.0 International Public License.³ The only exception are the texts of the detailed documentation of AI tool usage in `hgbaiusage-cognisance.sty` (see Sec. 3.8), which are licensed under the Creative Commons Attribution-ShareAlike 4.0 International Public License.⁴

2 Document classes

The `hgb` package provides the following document classes, which are based on the standard LaTeX classes `book`, `report`, and `article`, respectively:

- **hgbthesis** (`book`): for bachelor's, master's, diploma, and PhD theses as well as internship reports,
- **hgbreport** (`report`): for project and term reports,
- **hgbarticle** (`article`): for drafting journal articles.

2.1 Class options

2.1.1 General options

All three document classes accept the following general options:

- `language={english|german}`: main document language (default: `english`).⁵
- `twoside={false|true}`: page layout (default: `false` = single-sided). The bare option `oneside` is deprecated (use `twoside=false`).
- `smartquotes=true`: smart quotes replacement ("`...`" → "`...`"); default is `smartquotes=false`,
- `apa=true`: use APA bibliography style instead of `numeric-comp`; default is `apa=false`,
- `codestyle={color|mono|classic}`: appearance of code listings, see Sec. 3.5.1 (default: `color`),
- `updatecheck=true` (default): perform check of package release date; use `updatecheck=false` to suppress.

2.1.2 Class-specific options

In addition, the following class-specific options are accepted:

hgbthesis:

- `type={bachelor|master|diploma|phd|internship}`: thesis type (default: `master`),

¹<https://ctan.org/pkg/hagenberg-thesis>

²<https://github.com/Digital-Media/HagenbergThesis>

³<https://creativecommons.org/licenses/by/4.0/legalcode>

⁴<https://creativecommons.org/licenses/by-sa/4.0/legalcode>

⁵The bare options `english` and `german` still work but are deprecated. Note that `german` implicitly loads Babel's `ngerman` setup; when switching languages (see Sec. 3.2) only `german` should be used.

- `titlelanguage={english|german}`: language on title pages, defaults to main document language if omitted,
- `theme={themeID}`: cover page theme style (default: `default`, see Sec. 4),
- `degree={key}`: academic degree on the title page, e.g., `engineering` (see Sec. 2.3),
- `proposal=true`: flag to indicate proposal documents (`proposal=false` is the default).

hgbreport:

- `titlepage={true|false}`: title page on/off (default: `true`). The bare option `notitlepage` is deprecated (use `titlepage=false`).

hgbarticle:

- `twocolumn=true`: two-column page layout (default: `twocolumn=false`),
- `review=true`: review mode with line numbers (default: `review=false`).

For example, to start a master’s thesis in German, simply place

```
\documentclass[type=master,degree=engineering,language=german,smartquotes=true]{
  hgbthesis}
```

at the beginning of the document.

The `proposal` option is intended for a *thesis proposal* (“Exposé” or “Proposal”) and is only effective in *conjunction* with the main thesis types, e.g.,

```
\documentclass[type=bachelor,language=english,titlelanguage=german,proposal=true]{
  hgbthesis}
```

The result is a short exposé that contains only one chapter. Thus, chapter numbers are not displayed. Remove the `proposal` option to migrate a proposal document straight to the final thesis (and restore the usual numbering scheme).

The example also shows that the main document language (`language=english`) and the language on the title page (`titlelanguage=german`) can be set independently.

2.2 Thesis settings (class hgbthesis)

`hgbthesis` supports several types of thesis documents. The following parameters must be specified at the beginning of the main document:

- `\title{...}`,
- `\subtitle{...}` (optional),
- `\author{...}`,
- `\programtype{...}` (optional, derived from `type` by default, see Sec. 2.3),
- `\programname{...}`,
- `\institution{...}` (optional if provided by the theme, see Sec. 4.2),
- `\placeofstudy{...}`,
- `\academicdegree{...}` (optional, free text replacing the degree selected by the class option `degree`, see Sec. 2.3),
- `\dateofsubmission{yyyy}{mm}{dd}`,
- `\advisor[...]` (optional, multiple `\advisor` statements allowed),

Note that `hgbthesis` only supports a *single author* inside the `\author{...}` macro argument (commands `\and` and `\thanks{...}` are deactivated)!

The command `\advisor[role]{name}` accepts an optional argument to associate a *role* with the advisor’s *name*, e.g., `\advisor[Supervisor]{Prof.~Marie Curie, PhD}`. Multiple advisors can be specified, for example

```

\advisor[1.~Betreuerin]{Professor Frida K.~Putnik, PhD}
\advisor[2.~Betreuer]{Franz Grillparzer, TU Wien}
\advisor[Gutachter]{Dr.~B.~,Rutal, MIT}

```

Other (optional) settings for `hgbthesis` include:

- `\license{cc|strict}`: Use the *Creative Commons License* (`cc` = default) or strict license terms (“all rights reserved”).
- `\logfile{xxx.pdf}`: This command is **deprecated** – the thesis logo should be specified in the associated *theme* file instead (see Sec. 4).

2.3 Degree program type and academic degree

The type of the degree program and the academic degree on the title page are derived from the class options `type` and `degree`, so that all theses of a degree program use the same wording. The *type of degree program* is derived from `type` and printed in the title page language (see Table 1). `\programtype{...}` replaces it by any text, e.g., for an internship report in a master’s program.

Table 1: Type of degree program derived from the class option `type`.

type=	German	English
<code>bachelor</code>	Bachelorstudiengang	Bachelor’s degree program
<code>master</code>	Masterstudiengang	Master’s degree program
<code>diploma</code>	Diplomstudiengang	Diploma degree program
<code>phd</code>	Doktoratsstudium	Doctoral program
<code>internship</code>	Bachelorstudiengang	Bachelor’s degree program

The *academic degree* is selected by the class option `degree=key`, where *key* denotes the subject group and the level (bachelor or master) is taken from `type`. For example,

```

\documentclass[type=master,degree=engineering,...]{hgbthesis}

```

results in “Master of Science in Engineering (MSc)” on the title page. Table 2 lists all supported keys. They cover all academic degrees of Austrian FH degree programs as defined by AQ Austria (board decision of July 7, 2021).⁶ An unknown key, or a key that is not available for the given type (e.g., `degree=security-management` with `type=bachelor`), results in an error. The academic degree is shown by themes based on `default` (see Sec. 4), but not for internship reports and not for proposals (`proposal=true`). Thus the option can remain unchanged when a proposal is turned into the final thesis.

Academic degrees not covered by the option (e.g., of universities, of other countries, or doctoral degrees) are specified as free text by `\academicdegree{...}`, for example,

```

\academicdegree{Master of Science (MSc)}

```

If both are given, `\academicdegree` takes precedence and a warning is issued. Custom themes may define additional keys by

```

\hgbDefineDegree{<key>}{<bachelor degree>}{<master degree>}

```

where an empty argument means that the degree does not exist at that level.

⁶<https://www.aq.ac.at/de/akkreditierung/fachhochschulen/downloads.php>

Table 2: Supported values of the class option **degree** (academic degrees of Austrian FH degree programs).

degree=	type=	Academic degree
arts-design	bachelor	Bachelor of Arts in Arts and Design (BA)
	master	Master of Arts in Arts and Design (MA)
engineering	bachelor	Bachelor of Science in Engineering (BSc)
	master	Master of Science in Engineering (MSc)
social-sciences	bachelor	Bachelor of Arts in Social Sciences (BA)
	master	Master of Arts in Social Sciences (MA)
business	bachelor	Bachelor of Arts in Business (BA)
	master	Master of Arts in Business (MA)
military-leadership	bachelor	Bachelor of Arts in Military Leadership (BA)
	master	Master of Arts in Military Leadership (MA)
police-leadership	bachelor	Bachelor of Arts in Police Leadership (BA)
security-management	master	Master of Arts in Security Management (MA)
cultural-studies	bachelor	Bachelor of Arts in Cultural Studies (BA)
	master	Master of Arts in Cultural Studies (MA)
natural-sciences	bachelor	Bachelor of Science in Natural Sciences (BSc)
	master	Master of Science in Natural Sciences (MSc)
health-studies	bachelor	Bachelor of Science in Health Studies (BSc)
	master	Master of Science in Health Studies (MSc)
law	bachelor	Bachelor of Laws (LLB)
	master	Master of Laws (LLM)

3 Style files and user commands

The package comes with a set of style (***.sty**) files that can be used independently of the document classes listed above:

- **hgb.sty**: language and date setup, custom commands;
- **hgbabbrev.sty**: various abbreviation macros;
- **hgbaiusage.sty**: documentation of AI tool usage (for **hgbthesis**; texts of the detailed form in **hgbaiusage-cognisance.sty**, CC BY-SA 4.0);
- **hgbalgo.sty**: additions to **algpseudocodex** package;
- **hgbbib.sty**: bibliography setup;
- **hgbdict.sty**: language dictionary functions;
- **hgbheadings.sty**: definition of page headers;
- **hgblistings.sty**: setup for code listings;
- **hgbmath.sty**: setup and commands for math typesetting;
- **hgbpdfa.sty**: setup for PDF/A generation.

3.1 General user commands and environments (`hgb.sty`)

- `\hgbDate`: Outputs the package version date, e.g., “2026/09/14”.
- `\getcurrentlabel`: Yields the most recently assigned label number.
- `\calibrationbox{width}{height}`: Inserts a test box for checking the final print size (in millimeters).
- `\begin{block}...\end{block}`: Dummy environment, provides a limited scope for variable/command redefinitions.

3.2 Language switching commands and smart quotes (`hgb.sty`)

- `\SetLanguage{<language>}`: Switches to the specified language. This and the other language switching commands listed below also refresh the `smartquotes` settings (if activated).
- `\begin{SwitchLanguage}{<language>}...\end{SwitchLanguage}`: Temporarily switches to the specified language and reverts to the current language afterwards.
- `\begin{english}...\end{english}`: Temporarily switches to English language settings, short for `\begin{SwitchLanguage}{english}...`
- `\begin{german}...\end{german}`: Temporarily switches to German language settings, short for `\begin{SwitchLanguage}{german}...`
- `\SmartquotesActive`: For debugging only. Returns `true/false` if smart quotes are activated in the current context (or an appropriate message if the `csquotes` package was not loaded at all).

3.3 Text commands (`hgbabbrev.sty`)

Special characters:

- `\bs`: Inserts a backslash character (short for `\textbackslash`).
- `\obnh`: Inserts an optional break with no hyphen (e.g., `PlugIn{\obnh}Filter`).

German abbreviations:

- `\bzgl`: bzgl.
- `\bzw`: bzw.
- `\ca`: ca.
- `\dah`: d. h.
- `\Dah`: D. h.
- `\ds`: d. sind
- `\etc`: etc.
- `\evtl`: evtl.
- `\ia`: i. Allg.
- `\oa`: o.a.
- `\sa`: s. auch
- `\so`: s. oben
- `\su`: s. unten
- `\ua`: u. a.
- `\Ua`: U. a.
- `\uae`: u. Ä.

- `\usw`: usw.
- `\uva`: u. v. a.
- `\uvm`: u. v. m.
- `\va`: vor allem
- `\vgl`: vgl.
- `\zB`: z. B.
- `\ZB`: Zum Beispiel

English abbreviations:

- `\ie`: i.e.
- `\eg`: e.g.
- `\etc`: etc.
- `\Eg`: E.g.
- `\wrt`: w.r.t.

Note that none of the above abbreviation macros “eats” subsequent white space, i.e., they can be used without additional controls, as in “`\wrt what I said`”, for example.

3.4 Bibliography commands (`hgbbib.sty`)

- `\AddBibFile`
A wrapper to `biblatex`’s `\addbibresource` macro (for backward compatibility only).
- `\MakeBibliography[options]`
Inserts the reference section or chapter. By default, references are automatically split into category subsections.⁷ Use the option `nosplit` to produce a traditional (i.e., contiguous) list of references.
- `\mcite[text1]{key1}[text2]{key2}...[textN]{keyN}`
Analogous to `biblatex`’s `\cites` command⁸ but inserts semicolons between reference entries for better readability.

3.5 Code environments (`hgblistings.sty`)

The code environments listed in Table 3 are defined. Their keywords correspond to current language versions (e.g., C23, C++23, C# 13, Java 21, Python 3, PHP 8.4, Swift 6); built-in types and functions form a second keyword class. The table also lists the language names for including code files with `\lstinputlisting`, for example,

```
| \lstinputlisting[language=Java]{code/Main.java}
```

Languages that are also defined by `listings` are extended by the dialect `[hgb]`, which is set as default dialect where possible (e.g., `language=Java` selects `[hgb] Java`). For HTML, LaTeX, Scala, SQL and XML, the dialect must be specified explicitly (e.g., `language={[hgb]SQL}`); otherwise, the original definition of `listings` is used.

⁷Predefined reference categories are `literature`, `avmedia`, `online` and `software`.

⁸<http://mirrors.ctan.org/macros/latex/contrib/biblatex/doc/biblatex.pdf> (see Sec. 3.8.3)

Table 3: Code environments and language names for `\lstinputlisting`.

Language	Environment	language=
Bash	BashCode	bash
C	CCode	C
C++	CppCode	C++
C#	CsCode	CSharp
CSS	CssCode	CSS
Dart	DartCode	Dart
GLSL	GlsCode	GLSL
Go	GoCode	Go
HTML	HtmlCode	{[hgb]HTML}
Java	JavaCode	Java
JavaScript	JsCode	JavaScript
JSON	JsonCode	JSON
Kotlin	KotlinCode	Kotlin
LaTeX	LaTeXCode	{[hgb]TeX}
MATLAB	MatlabCode	Matlab
Objective-C	ObjCCode	ObjectiveC
PHP	PhpCode	PHP
Python	PythonCode	Python
R	RCode	R
Rust	RustCode	Rust
Scala	ScalaCode	{[hgb]Scala}
SQL	SqlCode	{[hgb]SQL}
Swift	SwiftCode	Swift
TypeScript	TsCode	TypeScript
XML	XmlCode	{[hgb]XML}
YAML	YamlCode	YAML
generic code	GenericCode	{}

`hgblistings` is based on the `listingsutf8`⁹ package, thus any valid `listings`¹⁰ option may be used; for example, the option `numbers=none` to suppress line numbers:

```
\begin{JavaCode}[numbers=none]
... // Java code comes here
\end{JavaCode}
```

3.5.1 Code style

The appearance of all code environments is selected by the class option `codestyle`:

- `codestyle=color` (default): white background with a thin gray line between the line numbers and the code; syntax highlighting with colors similar to common development environments (Visual Studio Code) with sufficient contrast (WCAG 2 AA) for keywords (dark blue), built-in types and functions (teal), strings (dark red) and comments (green, italic),
- `codestyle=mono`: the same layout without colors (comments in italics), e.g., for printing in black and white,

⁹<https://ctan.org/pkg/listingsutf8>

¹⁰<https://ctan.org/pkg/listings>

- `codestyle=classic`: gray background without colors, as in previous versions of this package.

The styles are also defined as `listings` styles `hgbcolor`, `hgbmono` and `hgbclassic`, so they can be selected for individual listings as well:

```
\begin{JavaCode}[style=hgbmono]
... // Java code without colors
\end{JavaCode}
```

The following colors are used and may be redefined in the preamble:

- `ListingsKeywordColor`: keywords,
- `ListingsTypeColor`: built-in types and functions,
- `ListingsStringColor`: strings,
- `ListingsCommentColor`: comments,
- `ListingsLineNumberColor`: line numbers,
- `ListingsRuleColor`: line between the line numbers and the code,
- `ListingsBackgroundColor`: background (`classic` only).

For example,

```
\definecolor{ListingsKeywordColor}{HTML}{0000FF}
```

3.6 Mathematical commands (`hgbmath.sty`)

`hgbmath` requires (and automatically loads) the `amsmath`¹¹ package, thus, all commands and symbols of `amsmath` are available by default. The following *additional* commands can only be used in math mode:

- `\Cpx`: $\mathbb{C}$ (complex numbers),
- `\N`: $\mathbb{N}$ (natural numbers),
- `\R`: $\mathbb{R}$ (real numbers),
- `\Q`: $\mathbb{Q}$ (rational numbers),
- `\Z`: $\mathbb{Z}$ (integer numbers).

3.7 Algorithms (`hgbalgo.sty`)

`hgbalgo` is a stand-alone package that is based on – and extends – the `algorithmicx` and `algpseudocodex` packages.¹² It fixes some (mostly indentation-related) problems, adds color, and provides some additional commands. It also loads the `algorithm`¹³ package, which defines a compatible float container for algorithms: `\begin{algorithm} ... \end{algorithm}`.

Additional algorithm commands:

- `\StateNN[<nesting>]{<text>}`: Creates a *non-numbered* statement like `algorithmicx`'s `\Statex` command but provides controlled indentation inside nested constructs. The optional integer argument `<nesting>` can be used to specify the *nesting depth* to compensate for a bug in `algorithmicx` (the nesting level inside a block is not set properly before the first `\State` command). Omitting the optional argument should give correct indentation in most situations.
- `\Input{<text>}`: For describing the input parameters in a procedure's preamble.

¹¹<https://ctan.org/pkg/amsmath>

¹²<https://ctan.org/pkg/algorithmicx>, <https://ctan.org/pkg/algpseudocodex>

¹³<https://ctan.org/pkg/algorithms>

- `\Output{<text>}`: For describing the output values in a procedure’s preamble.
- `\Returns{<text>}`: For describing the return values in a procedure’s preamble.

Vertical spacing commands: The following commands are provided for fine-tuning the vertical spacing between individual statements of an algorithm (the standard spacing commands like `\smallskip` etc. have no effect between statements):¹⁴

- `\algsmallskip`: inserts 3pt extra space,
- `\algmedskip`: inserts 6pt extra space,
- `\algbigskip`: inserts 12pt extra space.

They are supposed to be used inside (i.e., at the end of) statements, for example:

```
| \State $x \gets x + 1$ \algsmallskip
```

Defined algorithm colors:

- `AlgKeywordColor`: for algorithm keywords,
- `AlgProcedureColor`: for procedure and function names.

These colors can be redefined at any time (see the `xcolor`¹⁵ package), e.g., by

```
| \definecolor{AlgKeywordColor}{named}{black}
| \definecolor{AlgProcedureColor}{rgb}{0.0, 0.5, 0.0} % dark green
```

3.8 Documentation of AI tool usage (`hgbaiusage.sty`)

Package `hgbaiusage` is loaded by `hgbthesis` and creates the documentation of the usage of generative AI tools, which follows the affidavit, i.e., it is placed directly after `\maketitle`. It starts a new unnumbered chapter, and all texts are printed in the title page language (option `titlelanguage`). The texts are those of the FH OÖ templates (2026), as is the text of the affidavit created by `\maketitle`.

Short form

The environment `aiusage` composes the documentation of predefined text modules, for example,

```
| \begin{aiusage}
|   \aiusedfor{literature-search}
|   \aiusedfor{proofreading}
| \end{aiusage}
```

The following commands are available inside the environment:

- `\aiusednone`: no generative AI tools were used (cannot be combined with the other commands),
- `\aiusedfor{<key>}`: AI tools were used for a predefined purpose (see Table 4),
- `\aiusedforother{<text>}`: AI tools were used for another purpose; `<text>` continues the sentence like the predefined text modules (see the examples below).

An empty environment results in a warning. Examples of other purposes in English and German:

```
| \aiusedforother{create the figures in Chapter 3.}
| \aiusedforother{um die Abbildungen in Kapitel 3 zu erzeugen.}
```

¹⁴Note that the standard spacing commands work *between* procedure and function blocks in the usual way.

¹⁵<https://ctan.org/pkg/xcolor>

Table 4: Predefined purposes for `\aiusedfor` (short form).

<i>key</i>	Text (English)
<code>ideas</code>	gather initial ideas for potential research questions and relevant theories.
<code>literature-search</code>	search for literature.
<code>literature-understanding</code>	better understand academic literature (e.g., summaries).
<code>proofreading</code>	proofread parts of the thesis and improve the linguistic style.

Detailed form

The environment `aiusagedetails` creates a form with two statements on the responsible use of AI tools (with check boxes) and a table of eleven activities, listing the AI tools used for each activity and a description of their use. Its texts were adapted by FH OÖ (2026) from Gimpel et al. (2023)¹⁶ and, unlike the rest of the package, are licensed under CC BY-SA 4.0. Therefore, they are kept in the separate file `hgbaiusage-cognisance.sty`, and the source reference is printed below the form. The detailed form replaces the short form, since only one of them is intended; if both are used, a warning is issued. For example,

```
\begin{aiusagedetails}
  \aiconfirm{accuracy}
  \aiconfirm{responsibility}
  \aiactivity{coding}{GitHub Copilot}{Generation of test functions (Chapter 4)}
  \aiactivity{editing}{DeepL Write}{Proofreading of Chapters 1--5}
  \aifurtheruse{Generation of test data for the evaluation (Section 5.2).}
  \aifurtheruse{Creation of charts from the measurement data (Section 5.3).}
\end{aiusagedetails}
```

The environment only collects the following entries; the form is created at its end.

- `\aiconfirm{accuracy}`, `\aiconfirm{responsibility}`: checks the box of the statement that the outputs of AI tools were verified and corrected where required, and that the responsibility lies with the author(s), respectively. A statement that is not confirmed results in a warning.
- `\aiactivity{<key>}{<tools>}{<description>}`: AI tools used for an activity (see Table 5) and a description of their use (type of usage, affected sections, etc.). Multiple entries for the same activity are appended; activities without entries remain empty (or are omitted with the option `compact`, see below).
- `\aifurtheruse{<text>}`: further use of AI tools that fits none of the activities (optional). Use one `\aifurtheruse` per use: a single entry is printed as a paragraph, several entries as a bulleted list; without any entry, *None* or *Keine* is printed below the heading.

By default, the table lists all activities, as the FH OÖ template does. With the optional argument `compact`, only the activities with entries are listed; if no activity has an entry, a sentence stating this replaces the table:

```
\begin{aiusagedetails}[compact]
  ...
\end{aiusagedetails}
```

¹⁶Gimpel, H., Dilger, P., Lämmermann, L., Urbach, N. (2023). COGNISANCE: Declaration of Generative AI Tool Usage in Higher Education Tests. Research Center for Information Management. <https://doi.org/10.17605/OSF.IO/VGXF7>

The sample documents contain an example line for every activity, most of them commented out. Unlike the template, the form contains no instructions to the authors (e.g., to name the AI tools used); these are given as comments in the sample documents instead.

Table 5: Activities for `\aiactivity` (detailed form).

<i>key</i>	Activity (English)
<code>ideas</code>	Idea generation & conceptualization
<code>literature</code>	Literature search and analysis
<code>methodology</code>	Methodology
<code>coding</code>	Coding
<code>data</code>	Data collection and analysis
<code>interpretation</code>	Interpretation and validation
<code>structure</code>	Structuring and planning the text
<code>generation</code>	Generating the text
<code>translation</code>	Translating text
<code>editing</code>	Reviewing & editing the text
<code>references</code>	Citation management

3.9 PDF/A generation (`hgbpdfa.sty`)

Package `hgbpdfa` contains definitions for generating PDF/A-compliant (PDF/A-2b) output files. It is based on the emerging LaTeX-3 `pdfmanagement` package.¹⁷ `hgbpdfa.sty` is loaded by `hgbarticle.cls`. For `hgbthesis` and `hgbreport`, it is loaded at the very beginning of the main document, i.e., before `\documentclass` (as in all sample documents), and may be omitted if no PDF/A output is required. The font encoding (T1) and the Latin Modern fonts (`lmodern`) are loaded by all classes independently of `hgbpdfa` when compiling with `pdflatex`. PDF meta-data insertion is done with the associated `hyperref-generic` module (using `\hypersetup`) in `hgb.sty`.

4 Custom front pages using *themes*

The content and structure of the front pages generated for the various thesis types (`bachelor`, `master` etc.) may be easily customized to meet the specific requirements of different institutions or departments. Note that this kind of customization is typically done at the institutional level and not by the individual author (student).

4.1 Preconfigured themes

The various front page arrangements are called *themes* in the following. Each theme is identified by a unique *themeID* and associated with a particular style file (LaTeX package) named `hgbtheme-themeID.sty`. For example, the theme with *themeID* = `default` is defined by the associated file

`hgbtheme-default.sty`.

¹⁷<https://ctan.org/pkg/pdfmanagement-testphase>

Additional resources required by a theme (such as graphics files) must be named with the complete *theme name* (`hgbtheme-themeID`) as a prefix, for example,¹⁸

`hgbtheme-fhooe26-logo.pdf`

which contains the logo graphics used by theme `fhooe26`. The following themes are part of this package:

- **default**: title page following the title page prototype for theses of the University of Applied Sciences Upper Austria (FH OÖ), with the logo at the top left and left-aligned text. This theme always uses the *current* official brand (logo and name) of the institution (see Sec. 4.2).
- **fhooe26**: same layout as **default** with the FH OÖ brand pinned, i.e., it keeps the FH OÖ logo and name after future brand changes.
- **classic**: the former **default** theme (centered layout with the FH OÖ shield logo).
- **fhooe24**: title page with the FH OÖ cover background of 2024.
- **custom**: template for a custom theme (see Sec. 4.3).

To *use* a specific theme, option `theme=themeID` is added to the `\documentclass` command, for example,

```
\documentclass[theme=default,...]{hgbthesis}
```

4.2 Brand: logo and institution name

Theme **default** keeps the *brand*, i.e., the logo and the name of the institution, separate from the layout of the title page. The brand is set by the command

```
\hgb@SetBrand[<logo height>]{<logo file>}{<name in German>}{<name in English>}
```

where the optional logo height defaults to 28 mm. The institution's name is printed in the title page language, unless it is specified explicitly by `\institution{...}` in the document. Brand themes like `fhooe26` load **default** as their parent theme and call `\hgb@SetBrand` afterwards, for example,

```
\hgb@UseTheme{default} % parent theme (layout)
\hgb@SetBrand{my-logo.pdf}{Name der Hochschule}{Name of the institution}
```

The same approach can be used in a custom theme to adapt the title page to another institution.

4.3 Customizing themes

To customize the title page setup to their needs, authors (or administrators) should *not* modify any of the standard theme files, since these may not be local but loaded from a package distribution. There are two recommended ways instead:

4.3.1 Option 1: Adapt `hgbtheme-custom.sty`

Copy the theme file `hgbtheme-custom.sty` (which is part of this distribution) to the *main document directory* (if not there already) and open it in your LaTeX editor. It defines `hgbtheme-default.sty` as the parent theme by the initial command

```
\hgb@UseTheme{default}
```

All commands defined in the parent theme are visible and may be redefined, typically by `\renewcommand` (see Sec. 4.4 for available commands). To activate the associated theme simply use **custom** as the *themeID* in the associated document option, i.e.,

¹⁸This is to avoid file name conflicts since themes are part of the CTAN distribution and thus all theme-related files will eventually end up in a single, flat directory.

```
| \documentclass[theme=custom,...]{hgbthesis}
```

This is the simplest approach if only a *single* custom theme is needed.

4.3.2 Option 2: Create multiple custom themes

Thesis administrators may find it useful to define *multiple* custom themes for their institution or department(s). For this purpose, simply copy file `hgbtheme-default.sty` or `hgbtheme-custom.sty` to a new file, e.g., `hgbtheme-physics.sty`,¹⁹ and modify it accordingly. The associated theme can then be invoked by

```
| \documentclass[theme=physics,...]{hgbthesis}
```

An error will be raised if the associated `.sty` file cannot be found.

4.4 Commands and variables available to custom theme styles

Any theme style must at least define the command

```
\hgb@MakeFrontPages{..}
```

which is pre-defined (as throwing an error) in `hgbthesis.cls` and invoked by `\maketitle`. If `default` is used as the parent theme, `\hgb@MakeFrontPages` is already set up properly and redefinition is optional, i.e.,

```
| \hgb@UseTheme{default} % parent theme
| \renewcommand{\hgb@MakeFrontPages}{..} % optional
```

Moreover, the following macros and variables are assured to be available for defining custom themes (see `hgbtheme-default.sty` for their typical usage). These are defined in `hgbthesis.cls` and should *not* be redefined:

```
\hgb@Author
\hgb@Title
\hgb@SubTitle
\hgb@Institution
\hgb@ProgramType
\hgb@ProgramName
\hgb@AcademicDegree (empty if not specified)
\hgb@PlaceOfStudy

\hgb@ThesisName
\hgb@ProposalName

\hgb@AdvisorCount
\hgb@getAdvisorRole{<number>}
\hgb@getAdvisorName{<number>}

\hgb@MainLanguage
\hgb@TitleLanguage
\hgb@TitlePageFont

\hgb@SubmissionYear
\hgb@SubmissionMonth
\hgb@SubmissionDay
```

¹⁹To be placed in the main document directory. Note the naming conventions!

```
\hgb@GetMonthName{<language>}{<monthnumber>}
```

```
\hgb@License
```

```
\hgb@IsProposal (boolean, without \)
```

Class `hgbthesis.cls` also defines a special *hook*

```
\hgb@InitThemeHook
```

for adding custom initialization code for the current theme in the form

```
| \AddToHook{hgb@InitThemeHook}{<initialization code>},
```

typically placed at the beginning of the theme file. The collected code for this hook is executed immediately *before* `\maketitle`.

In addition, theme `hgbtheme-classic.sty` defines the following commands for generating individual title pages, which are inherited by theme `default` (and thus by `fhooe26` and `custom`):

```
\hgb@MakeTitlePage (redefined by default)
```

```
\hgb@MakeCompanyPage (internship reports only)
```

```
\hgb@MakeCopyrightPage
```

```
\hgb@MakeDeclarationPage
```

Each of these may be redefined by inheriting themes. Theme `default` additionally provides `\hgb@SetBrand` (see Sec. 4.2).

5 Package dependencies

The `hagenberg-thesis` package builds on the following LaTeX packages:

`abstract`, `algorithm`, `algorithmicx`, `algpseudocodex`, `amsbsy`, `amsfonts`, `amsmath`, `amssymb`, `babel`, `biblatex`, `breakurl`, `caption`, `cmap`, `csquotes`, `datetime2`, `enumitem`, `epstopdf`, `exscale`, `extramarks`, `fancyhdr`, `float`, `fontenc`, `forloop`, `geometry`, `graphicx`, `hypcap`, `hyperref`, `ifpdf`, `inputenc`, `lengthconvert`, `lineno`, `listingsutf8`, `lmodern`, `marvosym`, `moreverb`, `overpic`, `pdfmanagement-testphase`, `pdfpages`, `pict2e`, `subdepth`, `titlesec`, `titling`, `tocbasic`, `url`, `upquote`, `verbatim`, `xcolor`, `xifthen`, `xstring`, `xspace`.