

# X1C Home

The Bambu Lab X1 Carbon (X1C) is an enclosed CoreXY FDM printer with an AMS 2 Pro Automatic Material System for multi-material and multi-color printing. Filament drying on AMS 2 Pro is available when the official Bambu Lab Switching Adapter is connected and the printer firmware supports AMS 2 Pro drying.



## Quick Links

- [Bambu Lab X1 Series Wiki](#)
- [Download Bambu Studio](#)
- Contact [Ryan Kuederle](#) for assistance or to report issues.

## References

- [Introduction to the X1 Series](#)
- [X1 Series manuals](#)
- [Install AMS 2 Pro on X1C](#)
- [Use AMS 2 Pro drying from the X1C screen](#)
- [AMS 2 Pro intro and connection guide](#)
- [AMS 2 Pro drying function](#)
- [AMS 2 Pro drying on X1/P1 series](#)
- [AMS 2 Pro basic maintenance](#)
- [AMS 2 Pro product specs](#)
- [X1 firmware update for AMS 2 Pro / AMS HT](#)
- [Wi-Fi / Network connection guide](#)
- [Print from Bambu Studio](#)
- [Bambu Studio download](#)
- [X1-Carbon technical specifications \(PDF\)](#)

## Getting Started

If you have not used the Bambu Lab X1 Carbon before, or otherwise need help with 3D printing, contact [Ryan Kuederle](#)

After you are set up, follow the [X1C Standard Operating Procedure](#) during regular use. Official machine figures are on [X1C Specifications](#)