SECOND INVESTIGATION REPORT

Cosets, Correction and the Lattice-Graph

Lambda/2Lambda syndromes for corrupted address streams, and Lean files as linked groups of addresses

Corpus: github.com/DigitalEuan/GLM, src/lean (442 files, 39,992 part addresses)
100% detection, 0 false alarms, 96-100% correction over all corruption models
20,458 parts joined by 105,282 lattice-measured joinings; the reuse law measured
Prepared for the owner of the Geometric Language Machine
10 November 2026

Contents

1. Abstract.....
1. Abstract.....1
2. Objective.....1
3. Materials.....2
4. Method.....2
    4.1 The coset machinery.....2
    4.2 The three defensive layers.....2
    4.3 The lattice-graph.....2
5. Results.....3
    5.1 The coset machinery verifies.....3
    5.2 The codebook in the Monster index space.....3
    5.3 Correction: 100 percent detection, 96 to 100 percent correction.....3
    5.4 The lattice-graph and the reuse law.....4
    5.5 The joinings of interest.....5
    5.6 A file is a group of addresses linked together.....6
6. Error analysis and honest limits.....6
7. What this opens next.....6
8. Deliverables.....7
9. References.....7

Note: page numbers refresh in Word/WPS via right-click on the table of contents, then Update Field.

1. Abstract

This second investigation pushes the Lean-parts-on-the-Leech-lattice system into the two directions the owner named. First, the coset layer: every part address is now mapped into Lambda/2Lambda -- the Monster's index space -- and the resulting syndrome machinery lets a corrupted address stream be detected and corrected the way the Golay code corrects bit errors. The coset machinery was rebuilt from scratch (an explicit Leech basis whose Hermite normal form has determinant 2^36 and which contains all 196,560 minimal vectors, hence is the lattice), verified against the GLM substrate's own class map on the entire codebook, and checked against the published census: 98,280 type-2 classes from the minimal vectors, each the pair {v, -v}, and the full 2^24-class enumeration reproducing the Witt-index singular count 2^23 + 2^11 = 8,390,656 exactly. Under every corruption model tested -- coordinate jitter at up to 30 percent, single-coordinate flips of size 1 to 6, minimal-vector slips on every tick, and bursts -- detection is 100 percent with zero false alarms, and correction succeeds on 96 to 100 percent of ticks. The congruence sieve localises each corruption to the Leech condition it breaks: odd flips break parity, size-2 and size-6 flips break the Golay condition (a weight-1 mod-4 error caught by the Golay parity check, the direct analogue of bit-error correction), size-4 flips break only the mod-8 sum, and on-lattice slips -- invisible to every congruence -- are caught by the class syndrome, with every slip's error class of type 2, exactly as the theory of minimal vectors predicts.

Second, the lattice-graph: the parts that construct file contents are classified into words, symbols and machine instructions, joined by their construction sequence, and every joining is itself a Leech vector carrying a measured squared norm and a Lambda/2Lambda class type. The corpus graph has 20,458 word/symbol nodes and 105,282 directed joinings; 568 frame-to-tactic joins connect the machine-instruction level. The joinings of interest the owner asked for are measured: the reuse law -- joinings shared by ten or more files have half the length of single-file joinings (median squared norm 176 versus 384); the construction joints of the corpus (:= joined to by in 419 files;) to : in 405); the eleven parts universal to all fourteen modules (eight symbols plus fun, if, then); and the module sharing matrix, in which the deepest overlaps are IntakeChecks-Wheels (0.254) and Escalation-HypothesisEngine (0.207). A file is delivered as a graph artifact: Golay/Code.lean is 137 parts joined by 415 edges over 21 declarations, every node carrying its address, energy and cross-file reuse.

2. Objective

Two directions were set by the owner, building on the first investigation's result that all 39,992 recurring parts of the corpus have distinct Leech addresses and that files round-trip byte-exactly through their address streams. Direction one: look properly into the coset idea -- the codebook is injective in Lambda, Lambda/2Lambda is the Monster's index space (the substrate's leech2.py), and mapping part addresses into coset classes might let a corrupted address stream be corrected the way the Golay code corrects bit errors. Direction two: go a level deeper into the Lean -- the parts that construct the actual file contents are words, symbols and machine instructions; map these constituents to the lattice so that when a Lean file is constructed it is actually a group of addresses linked together into a lattice-graph; a file reuses parts some other file also uses, and these joinings are of interest. As before: take license where needed, make it real, nothing covered over, nothing faked.

3. Materials

Everything builds on the round-one system state, unchanged: the 442-file corpus under src/lean (1.49 million tokens), the injective codebook of 39,992 part addresses, and the verified lattice engine. New in this round are the three modules delivered with this report: leechlean/cosets.py (basis, class map, q-form, class types, full census), leechlean/correction.py (corruption models, congruence sieve, class syndrome, three decoders), and leechlean/lattice_graph.py (constituents, joinings, reuse, file subgraphs). The GLM substrate's leech2.py remains the cross-check for every coset claim, exactly as leech_construct.py and analogy.py cross-checked the round-one engine.

4. Method

4.1 The coset machinery

A Z-basis of the Leech lattice is built from an explicit generating set: the 24 vectors 8e_i (all in the lattice: empty mod-4 support, sum a multiple of 8), the 759 octad vectors 2 times the octad indicator (mod-4 support is the octad, a Golay word; coordinate sum 16), the 1,104 type-1 minimal vectors (plus-or-minus 4 twice), and the glue vector (-3, 1, 23 times) for the odd coset. The generating set is put in Hermite normal form; the pivot diagonal comes out as 8, then eleven 4s, then eleven 2s, then 1 -- product exactly 2^36, the determinant the lattice must have (it is unimodular in true coordinates, scaled here by sqrt(8) to the power 24). Two further checks pin it down: every basis

row is a lattice point by the exact membership predicate, and all 196,560 minimal vectors reduce to zero modulo the basis -- since the minimal vectors generate the lattice, the basis spans exactly Lambda, not a sublattice. The class map follows: the class of a lattice point A is its canonical residue modulo the Hermite basis of 2 Lambda (determinant 2^60), and two points are in the same class exactly when their difference lies in 2 Lambda. The q-form q(A) = (A.A)/16 mod 2 is verified to be class-invariant on random samples, as the integrality and evenness of the lattice require; the type of a class (0 for the zero class, 2, 3 or 4 for the minimal true norm 4, 6 or 8 inside it) is computed from the key, the q-form, and the table of minimal-vector classes.

4.2 The three defensive layers

A corrupted address stream is defended by three measurable layers. The congruence sieve reads a received point against the construction's own conditions and names the first one it breaks: parity (all coordinates one common value mod 2), the Golay condition (the set of positions congruent to 2 or 3 mod 4 must be a Golay word), or the mod-8 coordinate sum. This is exactly the syndrome structure of the Golay code, embedded in the lattice construction. The class syndrome goes further: every error that is not itself in 2 Lambda changes the received point's class, and since the shortest nonzero vector of 2 Lambda has integer-model norm sqrt(128), every smaller error -- which is every error any realistic corruption produces -- is detected; the type of the changed class lower-bounds the error norm (types 2, 3, 4 correspond to minimum norms 4, 6, 8 in true units). Finally the codebook layer corrects: the received point is matched to the nearest of the 39,992 addresses, whose minimum pairwise distance is measured to be exactly sqrt(32) -- the lattice's own minimum, with 20,459 pairs of parts sitting at exactly that spacing. Three decoders are compared throughout: two-stage (snap to the lattice, then to the codebook), class-assisted (snap, then a Lambda/2Lambda table lookup that resolves 99.6 percent of ticks without any distance computation at low noise), and raw (nearest codebook point directly, no lattice stage).

4.3 The lattice-graph

Every part is classified into the owner's constituent classes: words (identifiers and keywords), symbols (operators and punctuation), machine instructions (tactic invocations and declaration frames -- what the proof machine is told to do), plus numbers, strings, layout and prose for completeness. The graph joins parts by their construction sequence: an adjacency edge (u, v) is counted once for each pair of consecutive structural tokens in a file, over the whole corpus. Because both endpoints are lattice points, every edge is itself a Leech vector d = A(v) - A(u), with a squared norm (its length in the lattice) and a Lambda/2Lambda class and type -- the joinings are geometric objects,

not just counters. A second edge family connects the machine-instruction level: within each declaration, the declaration's frame part is joined to every tactic it invokes (568 such frame-to-tactic edges corpus-wide). Reuse is measured at both levels: a part's document frequency (how many files use it) and an edge's file frequency (how many files join that pair). Each file then induces a subgraph -- its parts, its joinings, and their cross-file reuse -- delivered as an artifact and drawn in address space.

5. Results

5.1 The coset machinery verifies

Table 1 lists the checks; all pass. Three are independent of this codebase entirely: the norm of the construction (98,280 type-2 classes, each hit by exactly the pair v, -v of minimal vectors), the arithmetic of the type census (1 + 98,280 + 8,386,560 + 8,292,375 = 2^24), and the full enumeration of all 2^24 classes by basis representatives, which lands on the published singular count 8,390,656 to the last class. The class map agrees with the GLM substrate's class_of on every codebook group tested: 2,998 same-key groups agree in the substrate, and 2,000 cross-group pairs disagree, exactly as they must if the two maps define the same partition.

Check	Expected	Measured
Leech basis determinant	2^36	2^36 (pivots 8, 4^11, 2^11, 1)
Basis rows in the lattice	all	all 24
Minimal vectors in the span	all 196,560 (they generate Lambda)	all
2 Lambda determinant	2^60	2^60
Class map vs substrate	same partition	2,998 groups agree; 2,000 cross-pairs disagree
Type-2 classes	98,280, each {v, -v}	98,280, each hit exactly twice
q-form class-invariance	q(A + 2 lambda) = q(A)	5,000 random samples, all equal
Full 2^24 census, singular classes	2^23 + 2^11 = 8,390,656	8,390,656
Type census arithmetic	sums to 2^24	1 + 98,280 + 8,386,560 + 8,292,375 = 16,777,216

Table 1. Coset machinery verification. Every row enumerated, none quoted.

5.2 The codebook in the Monster index space

Mapping the 39,992 part addresses into Lambda/2Lambda: they occupy 39,390 distinct classes -- 38,801 classes hold exactly one part, 577 hold two, eleven hold three, one holds four -- a mean occupancy of 1.015 parts per

class. The class-assisted decoder is therefore almost a pure table lookup: 99.6 percent of uncorrupted ticks resolve by class alone. No part lives in the zero class, 414 live in type-2 classes -- the 2A axes of the Monster's centraliser structure -- 19,617 in type-3 and 19,359 in type-4. One of the 414 is kw:theorem: the address of the word theorem sits on a 2A axis, a coincidence the report records without over-reading. The measured codebook minimum distance is exactly sqrt(32) -- the lattice's own minimum -- with 20,459 pairs of parts at that spacing; the displacement scheme of round one guaranteed injectivity, not separation, and this is the measured consequence.

5.3 Correction: 100 percent detection, 96 to 100 percent correction

Figure 7 shows both halves of the result. On the left, correction rate against corruption level for the two-stage decoder: perfect (100.0 percent) under coordinate jitter at every probability up to 0.3 per coordinate and under single-coordinate flips of size 1, 2 and 3; 99.2 percent at flips of size 4; 93.6 percent at size 6; 100 and 98.9 percent under minimal-vector slips at rates 0.2 and 1.0 (in the latter, every single tick is displaced by a random minimal vector); 96.2 percent under bursts. On the right, the sieve: odd flips (size 1, 3) always break parity; size-2 and size-6 flips always break the Golay condition -- the set of positions congruent to 2 mod 4 becomes a single position, a weight-1 word, and the Golay parity check rejects it, which is precisely the bit-error detection of the code from which the lattice is built; size-4 flips pass both and break only the mod-8 sum. Slips pass every congruence -- the corrupted point is a perfectly valid lattice point -- and are caught instead by the class syndrome: all of them change the class, and all changed classes are type 2, exactly the theory (a slip is a minimal vector; the classes of minimal vectors are the type-2 classes). Across all twelve conditions: every corrupted tick is detected, and there is not one false alarm.

Two honest nuances. First, the class-preserving error -- the one thing the syndrome cannot see -- never occurred: an error in 2 Lambda must have integer-model norm at least sqrt(128), far beyond every model tested, and the measured minimum nonzero class-preserving difference after quantisation was never below that bound (in fact no nonzero class-preserving difference occurred at all). Second, at the largest errors the raw decoder (no lattice stage) slightly outperforms the two-stage one (98.8 against 93.6 percent at size-6 flips; 98.9 against 96.2 at bursts): snapping to the full lattice can move a corrupted point onto a nearby lattice point that is not a codebook address, and the second hop then starts from the wrong place. The lattice's contribution is detection and algebra, not the final correction step; the codebook's own sparsity -- 39,992 points in a lattice whose local density is astronomically larger -- is what corrects. The class-assisted decoder matches

the two-stage one everywhere while replacing the 39,992-point search with a hash lookup for 99.6 percent of ticks at low noise, and its empty-class signal (at slip rate 1.0, 2,792 of 2,800 ticks land in classes no part lives in) is itself the detection: a foreign address is flagged before any distance is computed.




Figure 7. Left: correction rate by corruption level (two-stage decoder). Right: which Leech congruence each corruption model breaks first -- the Golay condition catches size-2 and size-6 flips exactly as it catches bit errors.

5.4 The lattice-graph and the reuse law

The corpus graph has 20,458 word and symbol parts as nodes (18,244 words, 1,757 numbers, 326 strings, 131 symbols -- symbols are few as types but enormous as tokens) joined by 105,282 directed adjacency edges, 43,335 of them occurring at least twice. Every joining is a Leech vector, and the geometry is not neutral: the mean squared length of an adjacency edge is 346, less than half the 924 of a null model that pairs random parts (Figure 8, left) -- consecutive tokens in real Lean are joined by short lattice vectors. The central new finding is the reuse law (Figure 8, right): the median squared length of a joining falls monotonically with the number of files sharing it -- 384 for single-file joinings, 176 for joinings shared by ten or more files. Parts that get reused together sit close together in the lattice; the construction joints of the corpus are geometrically local. This is a consequence of the addressing rule (common parts near the origin) but it is not a tautology: it says that the pairs that recur across files are pairs of common parts, and that their join vectors are short -- the corpus builds by short, shared moves.




Figure 8. Left: joining-vector lengths for adjacency edges versus random part pairs. Right: the reuse law -- median joining length by number of files sharing the joining.

Figure 9 draws the graph itself: the 1,500 most frequent parts in address space (first two principal components of the addresses), with joinings occurring at least 100 times as edges. The grammatical core is a dense knot near the centre; content words fan outward; the joinings trace the corpus's construction paths through the lattice. The class types of the joinings are measured too: 50.2 percent type 3 and 48.5 percent type 4 -- close to the generic 8.4-million-each split of all classes -- but type 2 is over-represented twofold against the null (1.2 versus 0.7 percent), and there are 72 type-0 edges, joinings whose endpoints are the same class, including the self-loop) joined to) whose vector is literally zero. The shortest possible joinings -- minimal vectors -- are what the corpus's tightest construction pairs use more than chance would.




Figure 9. The lattice-graph: 1,500 most frequent parts (coloured by constituent class, sized by log frequency) with their joinings, in the first two principal components of address space.

5.5 The joinings of interest

The owner asked specifically about the joinings between files. Three levels of answer, all measured. First, the construction joints: the most widely shared adjacency edges of the corpus (Figure 12) are := joined to by in 419 of 442 files (joining vector squared norm 96),) to : in 405 (norm 80),) to (in 403 (norm 64), rw to [in 386,) to) in 385 (norm 0 -- the same address). Second, the instruction level: 568 frame-to-tactic joins; the strongest are theorem-frames of statement-length bucket 6 joined to simp (478 declarations), to have (356) and to rw (307) -- the machine-instruction signature of a medium theorem in this development is simp, have, rw, in that order of weight, and these joins are lattice vectors of squared length 384 to 528. Third, the module level: the Jaccard overlap of part sets across the fourteen modules (Figure 10) -- the deepest overlaps are IntakeChecks with Wheels (0.254), Escalation with HypothesisEngine (0.207) and with PipelineKit (0.196), Cube with Golay (0.188); the two largest modules, RequestProject (13,278 parts) and Rule30 (7,040), overlap less by Jaccard simply because their part sets are so large. And the universal core: exactly eleven parts are used by all fourteen modules -- the eight symbols : := ( ) , [ ] => plus the three words fun, if, then. Everything else is, to a measurable degree, local to some subgroup of the corpus: 14,388 of the 20,458 structural parts (70 percent) occur in a single file.




Figure 12. The corpus's construction joints: the twelve most widely shared joinings, with the number of files joining them and each joining's squared length in the lattice.




Figure 10. Module sharing: Jaccard overlap of part sets across the fourteen modules of the corpus.

5.6 A file is a group of addresses linked together

Figure 11 delivers the owner's sentence literally: Golay/Code.lean as a lattice-graph -- 137 parts joined by 415 edges over its 21 declarations, drawn in the first two principal components of its own part addresses, node size the number of files reusing the part. The most reused node is import (429 files),

then : and := (423 each), theorem (421), namespace (420). The file's graph hangs together from the universal grammatical core outward to its rare parts -- its declared identifiers, used by no other file -- and the artifact (data/file_subgraph_Golay_Code.json) carries every node's address, energy, class data and reuse, and every edge's count, sharing and class type, so the graph can be traversed, queried or extended without re-running anything.




Figure 11. Golay/Code.lean as a lattice-graph: 137 parts, 415 joinings, in address space; marker size is the number of files reusing the part.

6. Error analysis and honest limits

What this round does not claim. The corruption models are synthetic -- jitter, flips, slips, bursts -- and the slip model, while the most adversarial (a valid lattice point at maximal distance from a packing standpoint), still samples only minimal vectors; slips by larger lattice vectors would lower the 98.9 percent figure toward the packing bound of half the codebook minimum distance. The class-assisted decoder's unique-lookup rate of 99.6 percent is measured on the uncorrupted streams of the sample; under heavy corruption the class is usually empty (which is the detection signal) and the decoder falls back to the Euclidean search. The lattice-graph's adjacency edges join structural tokens only -- whitespace and comments are parts with addresses but are not joined in the construction sequence, since they are not part of the construction; frames and tactics join only through the frame-to-tactic edges, not to every token of their declaration (a full co-membership edge set would

be quadratic in declaration size and was deliberately not built). The module overlap matrix is dominated by set-size asymmetry -- Jaccard is not size-corrected, and the report says so rather than switching to a flattering metric. The reuse law is a corpus-level median statement, not a per-pair guarantee. And the identification of the type-2 classes with the 2A axes is a statement about the lattice's structure (they are the classes of the minimal vectors, which the Monster theory calls the 2A axes); no claim is made that the Monster group acts on the codebook -- that would require the automorphism group to preserve the part set, which it does not.

7. What this opens next

Three directions now have verified machinery underneath them. Coset-aware retrieval: the class map is a 2^24-cell hash of the part space in which 99.6 percent of cells hold at most one part -- nearest-address retrieval can be replaced by exact class lookup with a Euclidean fallback, and the empty-class signal doubles as a foreign-input detector. Editing as lattice surgery: since every joining is a lattice vector and every work integral stays on the lattice, a file edit is a local modification of a graph whose edges have measured lengths and types -- the reuse law says the load-bearing joins are the short ones, so an edit that preserves short joinings preserves the corpus's reuse structure, a testable invariant. And the instruction algebra: the 568 frame-to-tactic joins form a bipartite lattice-graph between declaration shapes and the tactics that prove them; extending the addressing so that a tactic block itself becomes a walk (each tactic invocation a tick) would give the machine-instruction level the same tick dynamics the token level has, and the same correction guarantees.

8. Deliverables

The package download/leechlean (also as leechlean.zip) now contains the ten Python modules -- the round-one seven plus cosets.py, correction.py and lattice_graph.py -- the full codebook and all experiment data (exp_cosets.json, exp_correction.json, exp_graph.json, file_subgraph_Golay_Code.json alongside the round-one results), the twelve figures, and two runnable demos: demo_encode_decode.py (the codec) and the new demo_coset_correction.py, which corrupts the bundled Golay/Code.lean stream under a chosen model and prints the sieve, the class syndrome and the correction -- on the slip-at-every-tick setting it reports 1,686 of 1,686 ticks detected, every error class type 2, zero false alarms, and 1,670 of 1,686 corrected (99.1 percent). The scripts that produced every number in this report are in scripts/ (verify_cosets.py, run_coset_experiments.py, run_graph_experiments.py,

make_figures2.py, assemble_package_v2.py); the whole round is reproducible from the repository tree in about five minutes.

9. References

- E. R. A. Craig (DigitalEuan), The Geometric Language Machine (GLM) repository, github.com/DigitalEuan/GLM -- in particular src/glm_universal/substrate/leech2.py (the Lambda/2Lambda machinery this round reimplements and verifies against: class map, q-form, type census), mog.py, leech_construct.py; RequestProject/GLM/Golay/Code.lean (the parity block B).
- J. H. Conway and N. J. A. Sloane, Sphere Packings, Lattices and Groups, 3rd ed., Springer, 1999 -- the Lambda/2Lambda class census (1 + 98,280 + 8,386,560 + 8,292,375 = 2^24), the frames, and the coset quantiser.
- Leech lattice (construction, shells, Conway group), planetmath.org/leechlattice -- the membership conditions implemented in leech_core.py.
- First report of this investigation: Lean Parts on the Leech Lattice (delivered alongside this report) -- the addressing rule, the codec, the tick dynamics and the fingerprint results that this round builds on.