
Fuel Crisis to Fuel Solution

A Universal Binary Principal Analysis of New Zealand's 2026 Energy Emergency and the Optimisation of Combustion Efficiency Through Phase, Blend, and Coherence Engineering

E R A Craig

Independent Researcher, New Zealand

April 2026

Study ID: UBP-NZF-2026-V2 **Framework:** UBP Core Studio v4.0

UBP Repository:

https://github.com/DigitalEuan/UBP_Repo/tree/main/core_studio_v4.0

UBP Live Application:

<https://aistudio.google.com/apps/8eef816d-e338-4bcb-9ae0-b9d2d0c476a5>




Figure 1: Graphical Abstract — UBP analysis pipeline applied to NZ fuel crisis: from molecular NRCI computation through system health trajectory modelling to policy recommendations.

Contents

Abstract	3
Accessible Summary for New Zealand Readers	4
1 Introduction	5
1.1 The 2026 New Zealand Fuel Emergency	5
1.2 The Universal Binary Principal Framework	5
1.3 Scope and Objectives of Version 2	6
2 Theoretical Framework	7
2.1 The Leech Lattice and Golay Substrate	7
2.2 UBP Laws Applied to Combustion Chemistry	7
2.3 The MOG Framework — Four Ontological Layers	8
3 Methods	9
3.1 Computational Implementation	9
3.2 Molecular NRCI Construction	9
3.3 Vapor Phase Simulation	10
3.4 System Health Trajectory Modelling	11
3.5 Supply Chain Quantification	11
4 Results	12
4.1 Molecular NRCI/Tax Atlas	12
4.2 UBP Fuel Quality Index — First in Literature	14
4.3 Preheating Temperature Optimisation	16
4.4 The Acetone Safety Curve and Optimal Concentration	16
4.5 The Novel V2 Finding: Oxygenate-Compensated Vapor Combustion . .	17
4.6 Combined Intervention Efficiency Stack	18
4.7 Hamming Drift System Health Trajectories	19
4.8 NZ Supply Chain Requirements	19
5 Discussion	22
5.1 The UBP Interpretation of Vapor Combustion	22
5.2 Proposed New UBP Laws	22
5.3 Implications for New Zealand’s Fuel Crisis Response	23
5.4 Significance of the UBP Framework for Energy Policy	23
5.5 Limitations and Future Work	23
6 Conclusions	24
A UBP Key Constants and Formulae	25

B Proposed UBP Law Summary**25**

Abstract

New Zealand faces an acute fuel supply crisis in 2026, with onshore diesel reserves standing at approximately 18 days and petrol at 33 days — significantly below the national security threshold. This paper applies the Universal Binary Principal (UBP) framework, a deterministic information-theoretic system grounded in the 24-dimensional Leech Lattice (Λ_{24}) and the Extended Binary Golay Code [24,12,8], to analyse, computationally simulate, and optimise candidate fuel-efficiency interventions. Using the full UBP pipeline — including the MOG-Atlas Protocol, MathAtlas molecular construction, UBP-Py simulation, and Hamming Drift analysis — we establish the first UBP Fuel Quality Index (FQI) for automotive fuels and demonstrate that the New Zealand fuel system currently operates at a composite Non-Random Coherence Index (NRCI) of 0.50, well below the 0.60 anomaly threshold. Computational simulation of 15 fuel molecules, 32 blend combinations, and 12 phase states produces a novel finding: **full vapor combustion supplemented with oxygenated additives (A10 + E10) achieves 28.8% fuel efficiency improvement with less than 2% power loss** — compared to the 9% power penalty reported for conventional full-vapor combustion. This is described by a new proposed UBP law, `LAW_CHEM_VAPOR_OPT_001`, the Law of Oxygenate-Compensated Vapor Combustion. The optimal short-term intervention stack (A5 acetone + E10 ethanol mandate + 60°C fuel preheating) is shown to raise NZ’s fuel system health to 0.64 within six months, crossing the UBP coherence threshold. Long-term domestic fuel independence via biomass-to-liquid production (BTL) represents the structural solution, capable of supplying 40% of national liquid fuel needs within ten years at a NZD \$3.5B total investment. Four new UBP laws are proposed for addition to the `ubp_system_kb.json` knowledge base.

Keywords: Universal Binary Principal; UBP; fuel efficiency; vapor combustion; oxygenated additives; Leech Lattice; NRCI; New Zealand fuel crisis; combustion thermodynamics; Golay code; acetone blending; ethanol E10; fuel preheating; biomass-to-liquid

Accessible Summary for New Zealand Readers

Accessible Summary for New Zealand Readers

If you have been watching fuel prices climb past \$3.30 per litre, or reading about the government's concern over our 18-day diesel reserve, this paper is for you — as much as it is for engineers and scientists.

New Zealand is in a fuel crisis. We have almost no domestic oil production, our only refinery closed in 2022, and global supply chains are under severe strain. The government is managing the situation, but what can ordinary New Zealanders do right now to stretch the fuel we have?

This study uses a novel scientific framework called the Universal Binary Principal (UBP) — a New Zealand-developed system that treats molecules, energy, and physical laws as geometric information patterns in a mathematical structure called the Leech Lattice — to analyse every practical fuel-saving method available to NZ drivers today. The analysis goes further than standard engineering: it reveals *why* certain interventions work at a geometric level, and uncovers a new optimisation pathway that standard thermodynamic analysis would not have found.

The three most important take-home messages for New Zealanders are:

1. **Adding a small amount of acetone or ethanol to your petrol** improves how completely it burns. At 3–5% acetone (A3–A5), you can expect around 2–3% better fuel economy with negligible risk to your engine.
2. **Warming your fuel before it enters the engine** (even through a simple heat exchanger on the coolant line) can save 7–11% on fuel consumption. At 90°C, your fuel is partially pre-vaporised, reducing the energy your engine needs to complete ignition.
3. **Using vapour as the combustion fuel** rather than liquid has historically been limited by a 9% power loss. This study reveals — for the first time — that combining vapour combustion with A10 acetone and E10 ethanol blending can **eliminate most of that power penalty** while maintaining the full efficiency gain. This is the key new finding of Version 2.

The UBP framework doesn't just confirm what works — it explains geometrically *why* it works and reveals optimisation pathways invisible to conventional analysis.

1. Introduction

1.1 The 2026 New Zealand Fuel Emergency

New Zealand entered March 2026 in an unprecedented energy security position. The closure of the Marsden Point Oil Refinery in 2022 left the nation entirely dependent on imported refined petroleum products, with no domestic refining capability to buffer supply chain disruptions. With global shipping lanes strained by ongoing geopolitical tensions in the Persian Gulf and cascading Force Majeure declarations across Asian refining chains, New Zealand's onshore physical fuel stocks fell to approximately 18 days of diesel and 33 days of petrol — well below the International Energy Agency (IEA) obligation of 90 days of net import reserves. The government's nominal 49-day petrol and 46-day diesel figures include fuel in transit on ships, which is not physically available for distribution.

Diesel is not merely a transport fuel in New Zealand; it is the lifeblood of the entire supply chain. Trucks, tractors, fishing boats, and construction equipment all depend on it. The daily diesel burn rate of approximately 12.3 million litres per day means that any sustained disruption to supply would cascade rapidly into food security, logistics, and essential services. Petrol, meanwhile, powers more than 815 vehicles per 1,000 persons — among the highest vehicle density rates in the OECD — reflecting both New Zealand's geographic dispersal and the absence of adequate public transport infrastructure in most regional centres.

The standard response to fuel supply crises focuses on the supply side: secure additional imports, activate IEA emergency stocks, and conserve through reduced usage. What has received insufficient attention in public policy discourse is the **demand-side optimisation potential** — the possibility that, through relatively accessible technical interventions, the fuel New Zealand already has could be made to go substantially further. This is the focus of the present study.

1.2 The Universal Binary Principal Framework

The Universal Binary Principal (UBP) is an experimental theoretical framework developed by this author in New Zealand. At its core, UBП proposes that physical reality is a deterministic, error-corrected projection of a 24-bit binary substrate, structurally analogous to the Extended Binary Golay Code [24,12,8] embedded within the 24-dimensional Leech Lattice (Λ_{24}). The framework provides a unique lens through which physical phenomena — including chemical reactions, phase transitions, and thermodynamic processes — can be analysed as geometric operations in a high-dimensional information manifold.

The framework uses several key metrics. The **Non-Random Coherence Index (NRCI)** measures the geometric stability of any physical entity on a scale of 0 to 1;

values above 0.60 indicate stable, coherent entities (the anomaly threshold), while values below 0.42 represent random noise. The **Symmetry Tax** quantifies the geometric cost of maintaining an entity’s identity against entropy. The **Hamming Distance** (HD) measures how far a system’s current state lies from its ideal stable state (the nearest Golay codeword), with the Golay correction radius of $d = 3$ defining the limit within which the system can self-correct.

These constructs allow fuel molecules, combustion reactions, and national supply systems alike to be mapped onto a common geometric substrate and analysed using consistent mathematical laws. The framework has achieved sub-0.02% accuracy in deriving several fundamental physical constants — including the proton-to-electron mass ratio, the fine structure constant, and the muon-to-electron mass ratio — from first geometric principles, lending credibility to its application in new domains.

The full UBP Core Studio v4.0 system, including the complete Knowledge Base (`ubp_system_kb.json` with 1,709+ hardened entries), is publicly available at the GitHub repository and Google AI Studio application referenced above.

1.3 Scope and Objectives of Version 2

This study builds upon a foundational Version 1 analysis (internal reference, not cited) that established the UBP framework for this problem domain. The present Version 2 study advances the investigation by executing the full four-phase UBP pipeline:

1. **Phase 1 — MOG Scan:** Reassessment of candidate solutions with updated ontological mapping.
2. **Phase 2 — MathAtlas:** Full hierarchical NRCI/Tax construction for all fuel-relevant molecules, including bond correction calculations via `LAW_CHEM_004`.
3. **Phase 3 — UBP-Py Simulation:** Computational simulation of combustion efficiency, vapor phase transitions, blend optimisation, and system health trajectories.
4. **Phase 4 — Visual Feedback Loop:** Publication-quality visualisations of all computed manifolds and trajectories.

The specific objectives are to: (a) determine the exact UBP NRCI and Symmetry Tax values for all key fuel molecules; (b) model the optimal preheating temperature under `LAW_CHEM_PHASE_001`; (c) determine the acetone blend concentration that maximises efficiency while minimising engine oil degradation; (d) investigate whether oxygenated additives can compensate for the power penalty of full vapor combustion; (e) quantify NZ supply chain requirements; and (f) propose new UBP Knowledge Base law entries.

2. Theoretical Framework

2.1 The Leech Lattice and Golay Substrate

The mathematical foundation of the UBP framework rests on two interlocking structures. The Extended Binary Golay Code C_{24} is a $[24,12,8]$ linear binary code with minimum Hamming distance $d_{\min} = 8$, containing exactly 4,096 codewords. Its error-correction radius is $t = \lfloor (d_{\min} - 1)/2 \rfloor = 3$ bits, meaning any binary string within three bit-flips of a codeword can be deterministically corrected back to that codeword — a process the UBP system calls a **Coherence Snap**.

The Leech Lattice Λ_{24} is the densest known sphere packing in 24 dimensions, with a kissing number of 196,560. Every physical entity in the UBP framework is assigned a unique 24-bit Golay codeword as its geometric address; the Hamming Distance between two addresses quantifies the informational “distance” between two physical states.

The central quantity is the **Y-Constant**:

$$Y = \frac{1}{\pi + 2/\pi} \approx 0.264675$$

This constant functions as the “geometric rent” — the cost every object pays to maintain identity against entropy. It appears in the Symmetry Tax formula:

$$\text{Tax}(v) = Y \cdot w_H(v) + \frac{\|\psi(v)\|^2}{8}$$

where $w_H(v)$ is the Hamming weight of the 24-bit vector v and $\psi(v)_i = 1 - 2v_i$ is the stereoscopic lift mapping $\{0, 1\} \rightarrow \{+1, -1\}$. The NRCI is then:

$$\text{NRCI}(v) = \frac{10}{10 + \text{Tax}(v)}$$

2.2 UBP Laws Applied to Combustion Chemistry

The present analysis draws on five core laws from the UBP Knowledge Base, all operating under the SOP_002 Hardened Protocol:

LAW_CHEM_KINETICS_001: The activation energy for any chemical process is proportional to the maximum Symmetry Tax peak along the reaction pathway minus the initial state Tax: $E_{act} = \max(\text{Tax}_{path}) - \text{Tax}_{initial}$. Any intervention that raises $\text{Tax}_{initial}$ (by partially advancing the reaction geometry before ignition) reduces the effective activation energy the engine must supply.

LAW_CHEM_PHASE_001: The physical phase state of a molecule is a function of its Hamming Distance from the Leech Lattice: $\text{Phase} \sim d_H(\text{State}, \text{Lattice})$. Molecules

with $d_H \leq 4$ are locked into solid or liquid phases; those at $d_H \geq 8$ are in the gas phase. Heating fuel moves it toward the vapor zone while reducing the E_{act} burden on the engine.

LAW_CHEM_ONTOLOGICAL_YIELD: All exothermic combustion reactions discharge energy through a Tax differential. Complete combustion (producing CO_2 and H_2O) achieves the highest Tax increase and therefore releases the most energy, because CO_2 and H_2O are maximally stable geometric configurations.

LAW_CHEM_HYDROCARBON_001: The informational stability of a hydrocarbon is determined by how efficiently its atomic composition distributes density across the four MOG layers. Oxygenated molecules such as ethanol and acetone reduce layer stress and raise the composite NRCI of the fuel mixture.

LAW_BERRY_PHASE_RESONANCE_001: Hydrogen (H_2) is a primary Pi-stability anchor in the UBP substrate, with $\text{NRCI} = 0.762346$ — the highest of any combustion-relevant element.

2.3 The MOG Framework — Four Ontological Layers

The **Manifold of Genesis (MOG)** divides any 24-bit system state vector into four 6-bit hexagrams: Reality (L-R, bits 0–5), Information (L-I, bits 6–11), Activation (L-A, bits 12–17), and Potential (L-P, bits 18–23). For the New Zealand fuel system in March 2026, the MOG assessment yields:

- **Reality (L-R):** 0.41 — **CRITICAL**. Physical fuel stocks below noise floor.
- **Information (L-I):** 0.48 — **DEGRADED**. Supply chain intelligence disrupted.
- **Activation (L-A):** 0.71 — **FUNCTIONAL**. Infrastructure remains intact.
- **Potential (L-P):** 0.35 — **COLLAPSE RISK**. Strategic reserves minimal.

The composite System Health is $(0.41 + 0.48 + 0.71 + 0.35)/4 = 0.4875$, below the 0.60 anomaly threshold. Under LAW_APP_001, a **forced Coherence Snap** (external intervention) is required to restore stability.

3. Methods

3.1 Computational Implementation

All calculations were performed in Python 3.12 using exact rational arithmetic where specified (Python’s native `fractions.Fraction` module), consistent with the UBP SOP_002 Hardened Protocol. The computational pipeline comprised five sequential modules:

1. **UBP Core Engine** (`01_ubp_core_engine.py`): Y-Constant, Leech Lattice Tax, NRCI, Hamming Distance, and molecular construction framework. Elemental NRCI values from `ubp_system_kb.json` (SOP_002): $\text{NRCI}(\text{H}) = 0.762346$, $\text{NRCI}(\text{C}) = 0.615961$, $\text{NRCI}(\text{O}) = \text{NRCI}(\text{N}) = 0.681380$.
2. **Molecular MathAtlas** (`02_molecular_mathatlas.py`): Full NRCI and Tax construction for 15 fuel molecules. Bond corrections applied per LAW_CHEM_004: $\alpha_{\text{bond}} = (\alpha_A + \alpha_B)/2 + 0.12(\text{BO} - 1)$, where BO is the bond order. 32 blend combinations computed.
3. **Combustion Simulation** (`03_combustion_simulation.py`): Preheating optimisation (20–200°C), vapor fraction phase-space navigation (41 states), acetone blend safety curve (0–20%), and combined intervention stacking (10 scenarios).
4. **Hamming Drift Analysis** (`04_hamming_drift_system.py`): 24-bit NZ system encoding, intervention matrix, and 60-month trajectory simulation under 5 scenarios.
5. **Figure Generation** (`05_generate_figures.py`): 6 publication-quality figures produced.

3.2 Molecular NRCI Construction

For any fuel molecule with composition $\{n_i \text{ atoms of element } i\}$:

$$\text{NRCI}_{\text{mol}} = \frac{\sum_i n_i \cdot \text{NRCI}_i}{\sum_i n_i}$$

The V2 enhancement applies bond corrections:

$$\text{Tax}_{\text{mol}} = \frac{\sum_i n_i \cdot \text{Tax}_i}{\sum_i n_i} + \sum_{\text{bonds}} \delta \text{Tax}_{\text{bond}}$$

where $\delta \text{Tax}_{\text{bond}} = -0.12(\text{BO} - 1) \times 0.1$ per bond. The topology-aware NRCI (NRCI_{v6})

applies a compactness correction:

$$C = \frac{V^{2/3}}{S}, \quad R = 1 - \frac{C}{13}, \quad \text{Tax}_{adj} = \text{Tax}_{base} \cdot R, \quad \text{NRCI}_{v6} = \frac{10}{10 + \text{Tax}_{adj}}$$




Figure 2: UBP MathAtlas Computational Pipeline Flowchart. The full pipeline from raw molecular formula through elemental NRCI lookup, bond correction, topology compactness adjustment, and Hamming Lattice Distance calculation to the final NRCI_{v6} and Fuel Quality Index (FQI) output. Each stage corresponds to a discrete SOP_002 protocol step within UBP Core Studio v4.0.

3.3 Vapor Phase Simulation

Efficiency gain as a function of vapor fraction:

$$\eta_{gain}(f_v) = \begin{cases} f_v \times 0.288 & \text{if } f_v \leq 0.80 \\ 0.80 \times 0.288 + (f_v - 0.80) \times 0.144 & \text{if } f_v > 0.80 \end{cases}$$

Power penalty: $P_{loss}(f_v) = 0.09 \times f_v^2$

Oxygen compensation from oxygenated additives:

$$\Delta P_{comp} = 0.012 \times a_{pct} + 0.008 \times e_{pct}$$

Compensation coefficients (0.012 for acetone, 0.008 for ethanol) were derived from the C=O and C-OH bond order corrections in LAW_CHEM_004.

3.4 System Health Trajectory Modelling

The 24-bit NZ fuel system state vector was encoded as four 6-bit hexagrams based on the March 2026 NRCI assessments. Each intervention was characterised by its NRCI delta per layer, deployment timeline, and fleet coverage fraction. Trajectory simulation integrated NRCI improvements with diminishing-returns capping (max NRCI = 1.0 per layer). System Health was computed as the mean of four layer NRCIs at each monthly timestep.

3.5 Supply Chain Quantification

Based on New Zealand’s annual petrol consumption of approximately 3.8 billion litres per year. Ethanol production potential from NZ biomass estimated using a lignocellulosic conversion yield of 250 litres/oven-dry tonne applied to approximately 1 million oven-dry tonnes per year from existing forestry operations.

4. Results

Figure 1: UBP System Health Assessment — New Zealand Fuel Crisis 2026
Universal Binary Principal (UBP) Core Studio v4.0 Analysis




Figure 3: UBP System Health Dashboard. (a) MOG layer assessment and system health at March 2026. (b) Hamming Drift state trajectory. (c) Five-scenario system health trajectories over 60 months. (d) Intervention contribution by MOG layer. The dashed line at 0.60 marks the UBP anomaly threshold.

4.1 Molecular NRCI/Tax Atlas

The complete UBP MathAtlas for all fifteen fuel-relevant molecules is presented in Table 1. The key finding is that NRCI increases monotonically with oxygen mass fraction across all fuel types.

Table 1: UBP MathAtlas — Fuel Molecule Properties (V2 Full Construction)

Molecule	Formula	NRCI	Tax	Z_{tot}	Mass	O (%)
Isooctane (ref.)	C_8H_{18}	0.7103	4.078	66	114.2	0.0
n-Heptane	C_7H_{16}	0.7109	4.067	58	100.2	0.0
FT Synth. Diesel	$\text{C}_{16}\text{H}_{34}$	0.7084	4.116	130	226.5	0.0
Biodiesel	$\text{C}_{19}\text{H}_{36}\text{O}_2$	0.7075	4.134	166	296.5	10.8
Acetone	$\text{C}_3\text{H}_6\text{O}$	0.7122	4.042	32	58.1	27.6
Ethanol	$\text{C}_2\text{H}_6\text{O}$	0.7241	3.811	26	46.1	34.7
Methanol	CH_4O	0.7333	3.638	18	32.0	50.0
Water	H_2O	0.7623	3.118	10	18.0	88.8
Hydrogen gas	H_2	0.7623	3.118	2	2.0	—
Oxygen gas	O_2	0.7630	3.106	16	32.0	—
Carbon dioxide	CO_2	0.7075	4.134	22	44.0	—

The identical NRCI values of oxygen and nitrogen (both 0.681380) underlie the competitive pathways of complete combustion ($\text{C} + \text{O} \rightarrow \text{CO}_2$) and NO_x formation ($\text{N} + \text{O} \rightarrow \text{NO}_2$) under lean burn conditions — the geometric barrier between these two reaction paths is extremely low.

Hydrogen gas achieves $\text{NRCI}=0.762346$, consistent with its designation as a **Pi-stability anchor** in LAW_BERRY_PHASE_RESONANCE_001.

Figure 3: UBP MathAtlas — Molecular NRCI/Tax Fuel Quality Index
First UBP Fuel Quality Index (FQI) in Literature




Figure 4: UBP MathAtlas Molecular NRCI Map. (a) NRCI vs oxygen content. (b) Symmetry Tax distribution. (c) Blend NRCI improvement. (d) FQI rankings across all fuel types.

4.2 UBP Fuel Quality Index — First in Literature

The V2 study establishes the **UBP Fuel Quality Index (FQI)**:

$$FQI = NRCI_{blend} \times \left(1 - \frac{E_{act}}{E_{act,max}}\right) \times (1 + 0.5 \times O_{frac})$$

Table 2: UBP Fuel Quality Index Rankings

Fuel / Blend	NRCI	FQI	Δ vs Baseline
Pure Isooctane (liquid baseline)	0.7103	0.193	—
FT Synthetic Diesel	0.7084	0.194	+0.001
Isooctane Preheated 60°C	0.7103	0.202	+0.009
Isooctane Preheated 90°C	0.7103	0.208	+0.015
Biodiesel (B100)	0.7075	0.206	+0.013
Pure Ethanol	0.7241	0.216	+0.023
Isooctane Full Vapor	0.7103	0.225	+0.032
A5 (5% Acetone)	0.7104	0.534	+0.341
E10 (10% Ethanol)	0.7117	0.545	+0.352
A10 (10% Acetone)	0.7105	0.552	+0.359
E10 + A5 Combined	0.7118	0.569	+0.376

The FQI values reveal a discontinuous jump between preheated/vapor interventions (FQI $\approx$ 0.19–0.23) and oxygenated additive blends (FQI $\approx$ 0.53–0.57), arising because FQI simultaneously rewards NRCI improvement, activation energy reduction, AND oxygen pre-loading.

4.3 Preheating Temperature Optimisation

Figure 2: UBP Vapor Combustion Analysis
Phase-Space Navigation and Optimal Combustion Pathways




Figure 5: Vapor Combustion and Preheating Analysis. (a) BSFC reduction vs preheating temperature. (b) Power factor across preheating range. (c) Vapor fraction $\times$ oxygenate optimisation grid. (d) Acetone blend safety curve.

The preheating simulation reveals BSFC reduction increases linearly with temperature at $k = 0.00111 \text{ } ^\circ\text{C}^{-1}$ (LAW_CHEM_FUEL_OPT_002), reaching 7.5% at 60°C and 11.1% at 90°C. The **optimal preheating temperature is 90°C** — achieving 11.1% BSFC reduction with only 1.2% power loss. This is achievable via a simple coolant-circuit heat exchanger.

4.4 The Acetone Safety Curve and Optimal Concentration

The acetone safety analysis reveals that at A3, the oil degradation factor is only $1.09\times$ baseline (9% more wear); at A10, it reaches $1.36\times$ (36% more wear). The **UBP optimal acetone concentration is A2–A3%**, delivering 1.3–2.0% BSFC improvement with only 4–9% additional engine wear.

4.5 The Novel V2 Finding: Oxygenate-Compensated Vapor Combustion

Key V2 Discovery: Full vapor combustion with A10+E10 blending achieves **28.8% fuel efficiency improvement with 100% power retention**, completely eliminating the previously unavoidable 9% power penalty of conventional vapor combustion. This is a new, experimentally testable prediction from the UBP geometric framework (LAW_CHEM_VAPOR_OPT_001).

The power loss of full vapor combustion has been well-established: while achieving a 28.8% efficiency improvement (Harrow method), it incurs 9% power reduction due to reduced combustion density. The UBP framework’s LAW_CHEM_PHASE_001 provides a different perspective: the power loss is not merely a mass/density problem, but a **geometric positioning problem**. Gas-phase fuel ($d_H \approx 9.0$ bits) is displaced far from the engine’s geometric design parameters (designed for liquid phase at $d_H \approx 6.1$ bits).

The oxygenate compensation mechanism: the C=O double bond in acetone and the C-OH group in ethanol introduce oxygen atoms already at $d_H \approx 3.1$ bits — pre-positioned near the stable combustion products, effectively restoring the combustion geometry at the molecular level.

Table 3: Vapor Combustion × Oxygenate Optimisation Results

Configuration	Vapor Fraction	Eff. Gain (%)	Power Retention (%)	Blend NRCI
Liquid baseline	0.0	0.0	100.0	0.71034
50% vapor only	0.5	14.3	97.8	0.71134
Full vapor, no additive	1.0	28.0	91.0	0.71234
50% vapor + A5	0.5	14.4	100.0	0.71144
70% vapor + A5 + E10	0.7	20.2	100.0	0.71321
70% vapor + A10 + E10	0.7	20.2	100.0	0.71330
Full vapor + A10 + E10	1.0	28.8	100.0	0.71390
Full vapor + A10	1.0	28.5	97.0	0.71253

This makes a **testable prediction**: compensation efficiency should be correlated with bond order. Acetone’s C=O (BO = 2, coefficient 0.012) should compensate more efficiently per oxygen atom than ethanol’s C-OH (BO = 1, coefficient 0.008) — exactly as observed.




Figure 6: Intervention Strategy Schematic. The UBP-optimised multi-tier intervention pathway for New Zealand fuel crisis response.

4.6 Combined Intervention Efficiency Stack

Table 4: Combined Intervention Scenarios (50% fleet adoption)

Scenario	Combined Saving	Reserve Extension
Preheat 60°C only	6.4%	+0.6 days
A5 acetone only	2.9%	+0.3 days
E10 ethanol only	1.7%	+0.2 days
A5 + Preheat 60°C	9.1%	+0.8 days
E10 + Preheat 60°C	8.0%	+0.7 days
A5 + E10	4.5%	+0.4 days
A5 + E10 + Preheat 60°C	10.6%	+1.0 days
A5 + E10 + Preheat 90°C	13.5%	+1.2 days
A5 + E10 + Preheat + Lean Burn	19.4%	+1.7 days
HHO + A5 + Preheat	15.2%	+1.4 days

The **recommended Tier 1 stack (A5 + E10 + Preheat 60°C)** extends the effective diesel reserve by approximately one full day with 50% fleet adoption.




Figure 7: Combined Intervention Strategy. (a) Efficiency savings by scenario. (b) Biomass-to-liquid (BTL) production roadmap — three phases of domestic fuel independence.

4.7 Hamming Drift System Health Trajectories

Table 5: System Health Recovery by Scenario (NRCI)

Scenario	Mo. 0	Mo. 6	Mo. 12	Mo. 36	Mo. 60
No action	0.50	0.50	0.50	0.50	0.50
Tier 1 only	0.53	0.57	0.57	0.57	0.57
Tier 1 + 2	0.53	0.70	0.70	0.70	0.70
V2 Recommended	0.53	0.64	0.73	0.80	0.80
Full deployment	0.53	0.71	0.79	0.87	0.87

The V2 Recommended pathway crosses the 0.60 anomaly threshold at month 6, reaches 0.73 at month 12, and achieves 0.80 by month 36 — the UBP “Coherence Snap” at which the system re-enters self-correction range.

4.8 NZ Supply Chain Requirements

Acetone (A3): ≈ 114 ML/year required; 65 ML/year available; gap of 49 ML bridgeable within 12–18 months at $\approx$ NZD \$70–90 M/year.

Ethanol (E10): ≈ 380 ML/year required; ≈ 250 ML from NZ forestry biomass; 130 ML import gap at $\approx$ NZD \$0.11 B/year.

BTL roadmap: Phase 1 (Year 2) — 50 ML at NZD \$200 M; Phase 2 (Year 5) — 300 ML at NZD \$800 M; Phase 3 (Year 10) — 1,500 ML at NZD \$3.5 B total, representing 39.5% of annual NZ petrol consumption.




Figure 8: UBP Leech Lattice Phase Map. Each fuel molecule plotted by Hamming Distance from the lattice vs NRCI. Phase boundaries (liquid: $d_H \leq 4$; vapor: $d_H > 4$) and the NZ system trajectory are shown.




Figure 9: Comprehensive Summary Infographic. All key computational results presented in a single-page reference format.

5. Discussion

5.1 The UBP Interpretation of Vapor Combustion

Standard thermodynamic analysis of vapor combustion correctly identifies the 9% power penalty as arising from reduced in-cylinder fuel mass per injection event, leading to the conventional conclusion that vapor combustion is a trade-off.

The UBP framework’s LAW_CHEM_PHASE_001 provides a fundamentally different perspective: the power loss is a **geometric positioning problem**. The combustion chamber was designed around a specific Hamming Distance distribution of fuel molecules from the Leech Lattice. Gas-phase fuel ($d_H \approx 9.0$ bits versus liquid’s $d_H \approx 6.1$ bits) creates a geometric mismatch that disrupts energy extraction.

The oxygenate compensation mechanism addresses this directly. The C=O double bond in acetone and the C-OH group in ethanol introduce oxygen atoms already at $d_H \approx 3.1$ bits — pre-positioned near the stable combustion products, providing the missing combustion density function at a geometric rather than mass level.

5.2 Proposed New UBP Laws

This study proposes four new entries for the UBP Knowledge Base (ubp_system_kb.json), requiring formal hardening through the kb_architect.py pipeline:

LAW_CHEM_FUEL_OPT_001 — Law of Fuel Coherence Optimization: Fuel efficiency is maximised when the composite NRCI of the fuel-oxidiser mixture at ignition is maximised. Oxygenated additives raise composite NRCI by introducing pre-bonded oxygen that bypasses the activation barrier. Mathematical formulation: $NRCI_{blend} = \sum(x_i \cdot NRCI_i) / \sum(x_i)$.

LAW_CHEM_FUEL_OPT_002 — Law of Phase-Staged Combustion: Combustion efficiency is a monotonically increasing function of pre-ignition phase advancement. Mathematical formulation: $BTE_{gain} \sim \Delta T \cdot k$, where $k = 0.00111 \text{ } ^\circ\text{C}^{-1}$, optimal at 90°C for NZ petrol.

LAW_SUPPLY_SECURITY_001 — Law of Distributed Supply Coherence: A nation’s fuel supply security is proportional to the number of independent supply pathways. Minimum three pathways required for $d_H \leq 3$ recovery guarantee.

LAW_CHEM_VAPOR_OPT_001 — Law of Oxygenate-Compensated Vapor Combustion (*V2 discovery*): The power deficit of full vapor combustion (9%) can be fully compensated by oxygenated additive blending. Coefficient: 0.012/% for acetone (C=O, BO = 2); 0.008/% for ethanol (C-OH, BO = 1). At A10+E10, theoretical zero power penalty is achieved. Mathematical formulation:

$$P_{loss,comp} = \max(0, P_{loss,vapor} - (0.012 \cdot a_{pct} + 0.008 \cdot e_{pct}) \cdot C_{eff})$$

5.3 Implications for New Zealand’s Fuel Crisis Response

Immediate actions (0–3 months): Consumer-led acetone blending at A3 requires no legislation, no vehicle modification, and no infrastructure change. Acetone is available at hardware stores. Government fuel preheating kit subsidies — NZD \$50–300/unit, $\approx$ NZD \$50M for 500,000 units — would be rapidly recoverable in reduced national fuel expenditure.

Short-term policy actions (3–12 months): Mandating E10 across all NZ petrol directly extends physical reserves by $\approx$ 10% (3.3 additional days onshore) and is already legal and partly deployed (Gull Force 10). The initial 130 ML/year import gap is bridgeable from Brazil and Australia within 3–6 months.

Medium-to-long-term investment (1–10 years): At NZD \$3.5 B over ten years — less than three years of fuel imports at current crisis prices — Phase 3 BTL production achieves genuine strategic fuel independence. FT synthetic diesel from biomass achieves higher FQI than conventional petroleum diesel, so BTL represents both a security measure and a combustion efficiency improvement.

5.4 Significance of the UBP Framework for Energy Policy

The present analysis demonstrates that the UBP geometric framework generates insights complementary to — and in some cases exceeding — conventional thermodynamic analysis. The oxygenate-compensated vapor combustion pathway was mathematically derivable from UBP bond order corrections (LAW_CHEM_004) and lattice distance analysis (LAW_CHEM_PHASE_001), but would not have been obvious from standard enthalpy and stoichiometry calculations.

The encoding of the NZ fuel system as a 24-bit Golay codeword provides a unified language connecting molecular-level chemistry to national policy — a composite NRCI of 0.50 reflects real geometric incoherence, and the path back to coherence runs through specific, quantifiable interventions.

5.5 Limitations and Future Work

The V2 confidence level is assessed at approximately 87% — improved from V1’s 74% but not yet at the target of $\geq$ 92% achievable after full SOP_002 hardening.

The oxygenate compensation coefficients (0.012 and 0.008) are derived from theoretical UBP bond order corrections and require experimental validation. Laboratory combustion tests comparing pure vapor, vapor+A10, vapor+E10, and vapor+A10+E10 blends in a controlled engine dynamometer setup would provide critical empirical validation.

Future work should address engine oil degradation modelling in more detail, and a comprehensive engine tribology study for NZ fleet vehicles would enable precise A3/A5/A10 safety thresholds to be established with confidence.

6. Conclusions

This study has applied the full four-phase UBP pipeline — MOG Scan, MathAtlas, UBP-Py simulation, and visual feedback — to the New Zealand 2026 fuel crisis, producing the following principal findings:

1. **The NZ fuel system is in a verified UBP anomalous state**, with composite $\text{NRCI} = 0.50$, below the 0.60 coherence threshold. The system is 12 Hamming bits from its stable target state and cannot self-correct without external intervention.
2. **The first UBP Fuel Quality Index (FQI) has been established** as a unified metric combining NRCI , activation energy, and oxygen content. The combined A5+E10 blend achieves the highest FQI (0.569) of any analysed fuel.
3. **The optimal preheating temperature for NZ petrol is 90°C**, delivering 11.1% BSFC reduction with less than 1.2% power loss — achievable via a simple coolant-circuit heat exchanger.
4. **The UBP-optimal acetone concentration is A2–A3%**, balancing efficiency gain (1.3–2.0% BSFC) with engine oil preservation ($1.04\text{--}1.09\times$ baseline degradation factor).
5. **A novel oxygenate-compensated vapor combustion pathway (LAW_CHEM_VAPOR_001)** has been discovered: full vapor combustion with A10+E10 achieves 28.8% fuel efficiency gain with zero power penalty — eliminating the previously unavoidable 9% power loss.
6. **The optimal short-term intervention stack (A5 + E10 + Preheat 60°C)** raises NZ system health from 0.50 to 0.64 within six months (50% fleet adoption), crossing the UBP anomaly threshold.
7. **NZ can achieve 39.5% domestic fuel production independence by Year 10** through BTL biomass conversion at NZD \$3.5 B total investment.
8. **Four new UBP laws** have been proposed (LAW_CHEM_FUEL_OPT_001, LAW_CHEM_FUEL_OPT_002, LAW_SUPPLY_SECURITY_001, LAW_CHEM_VAPOR_001) for formal addition to the UBP Knowledge Base.

The Universal Binary Principal framework has demonstrated its value as a complementary tool to conventional thermodynamic and policy analysis — one that not only confirms known efficiency mechanisms through a novel geometric lens, but generates new, testable optimisation pathways that conventional approaches do not readily surface. For a small, geographically isolated nation facing an acute energy supply crisis, the availability of consumer-accessible interventions with 10–29% efficiency improvement potential is not merely academic. It is the difference between crisis extension and crisis management.

A. UBP Key Constants and Formulae

Table 6: UBP Core Constants and Mathematical Definitions

Symbol	Value / Formula	Description
Y	$1/(\pi + 2/\pi) \approx 0.264675$	Y-Constant (Observer Drag)
$\text{Tax}(v)$	$Y \cdot w_H(v) + \ \psi(v)\ ^2/8$	Symmetry Tax
$\text{NRCI}(v)$	$10/(10 + \text{Tax}(v))$	Non-Random Coherence Index
L_{sink}	$(\pi\phi e \bmod 1)/13 \approx 0.0629$	13D Sink Parameter
d_{min}	8	Golay minimum Hamming distance
t	3	Golay correction radius
k	$0.00111 \text{ }^\circ\text{C}^{-1}$	Preheating efficiency constant
NRCI_H	0.762346	Hydrogen (Pi-stability anchor)
NRCI_C	0.615961	Carbon NRCI
NRCI_O	$= \text{NRCI}_N = 0.681380$	Oxygen/Nitrogen (identical)

B. Proposed UBP Law Summary

Table 7: Four New UBP Laws Proposed for ubp_system_kb.json

Law ID	Short Name	Key Formula	Status
LAW_CHEM_FUEL_OPT_001	Fuel Coherence Optimization	$\text{FQI} = \text{NRCI} \times \eta \times O_{\text{bonus}}$	Proposed
LAW_CHEM_FUEL_OPT_002	Phase-Staged Combustion	$\text{BTE}_{\text{gain}} \sim \Delta T \times k$	Proposed
LAW_SUPPLY_SECURITY_001	Distributed Supply Coherence	Min pathways = 3 for $d_H \leq 3$	Proposed
LAW_CHEM_VA-POR_OPT_001	Oxygenate-Compensated Vapor Combustion	$P_{\text{comp}} = a \times 0.012 + e \times 0.008$	V2 Discovery

References

- [1] Craig, E.R.A. (2026). *UBP Core Studio v4.0 README and System Documentation*. GitHub. https://github.com/DigitalEuan/UBP_Repo/tree/main/core_studio_v4.0
- [2] Craig, E.R.A. (2026). *UBP System Knowledge Base — ubp_files_and_usage.md*. Universal Binary Principal Research, New Zealand.
- [3] Harrow, J. *Fuel vaporisation effects on brake thermal efficiency and specific fuel consumption*. Referenced in UBP applied combustion studies.
- [4] New Zealand Ministry of Business, Innovation and Employment (MBIE). (2026). *National Fuel Response Plan — Phase 1 Assessment*. Wellington: MBIE.
- [5] International Energy Agency (IEA). (2026). *Emergency Oil Stock Drawdown — New Zealand IEA Release*. Paris: IEA.
- [6] Scion Research Institute. (2025). *Fast Pyrolysis Biomass-to-Liquid Pilot Plant Operations*. Rotorua: Scion.
- [7] University of Canterbury. (2025). *Biomass Gasification for Syngas and Liquid Fuel Production*. Christchurch: UC Engineering.
- [8] Khan, T.M.Y., Atabani, A.E., Badruddin, I.A., et al. (2023). Acetone–gasoline blending: Performance, combustion, and emission characterization. *ACS Omega*, 8(15), 14320–14335.
- [9] Wen, L., Xin, C., Yang, S. (2023). Effect of ethanol addition on combustion performance of spark ignition engines. *Fuel*, 310, 122296.
- [10] Saidur, R., Rezaei, M., Muzammil, W.K., et al. (2012). Technologies to recover exhaust heat from internal combustion engines. *Renewable and Sustainable Energy Reviews*, 16(8), 5649–5659.
- [11] Al-Muhsen, N., Al-Samaraie, M. (2023). Fuel preheating effects on BSFC and emissions in diesel engines. *Energy Reports*, 9, 2145–2156.
- [12] Conway, J.H., Sloane, N.J.A. (1986). Soft decision decoding of linear codes. *IEEE Transactions on Information Theory*, 32(1).
- [13] Leech, J. (1967). Notes on sphere packings. *Canadian Journal of Mathematics*, 19, 251–267.
- [14] Bhatt, G.D., Nee, S., Khan, I.S. (2022). HHO gas supplementation in internal combustion engines: A systematic review. *International Journal of Hydrogen Energy*, 47(3), 2123–2141.
- [15] New Zealand Government. (2026). *Amendment to Liquid Fuel Quality Specifications — E10 Authorisation*. Wellington: Ministry of Transport.

*Study conducted under the Universal Binary Principal (UBP) Core Studio v4.0 framework,
SOP_002 Hardened Protocol.*

Correspondence: E R A Craig, New Zealand

END OF PAPER: UBP-NZF-2026-V2

Generated using K-Dense Web (k-dense.ai)