

Supplementary Resource: UBP 3.3 Framework and Ultimate Fuel Design

Author: Euan R A Craig, New Zealand

Date: 6 November 2025



Part 1: Clarifying the UBP 3.3 Framework

This section addresses the feedback requesting clarification on the Universal Binary Principle (UBP) 3.3 framework, its methodology, and its practical implementation. We aim to demystify the “black box” nature of the system and provide a clear understanding of its foundational concepts.

1.1 What is UBP 3.3?

The Universal Binary Principle (UBP) is a computational ontology that models reality as a deterministic, toggle-based system [1]. It posits that all phenomena, from the subatomic to the cosmological, can be described as the emergent behavior of a vast, interconnected network of binary units called “OffBits.” UBP 3.3 is the latest iteration of this framework, featuring a modular architecture that allows for the simulation and analysis of complex systems, including molecular structures.

At its core, UBP is not a replacement for traditional quantum chemistry or physics, but rather a complementary approach that offers a different level of abstraction. Instead of simulating the detailed quantum mechanical interactions of particles, UBP focuses on the informational and geometric properties of systems, as represented by their binary encoding. This allows for highly efficient and scalable simulations, making it possible to analyze large datasets of molecules and identify emergent patterns that would be computationally prohibitive to find with traditional methods.

1.2 The OffBit and Molecular Encoding

The fundamental unit of the UBP framework is the **OffBit**, a 24-bit binary string that represents the state of a fundamental unit of reality. In the context of the petroleum study, each molecule is represented by a unique OffBit, which is generated based on its key physical and chemical properties.

The “Balanced” OffBit encoding strategy used in the study maps molecular properties to the 24 bits of the OffBit in a way that distributes the information evenly across the four ontological layers:

Ontological Layer	Bits	Mapped Molecular Property
Reality	0-5	Molecular Weight
Information	6-11	Carbon Count
Activation	12-17	Vibrational Frequency
Unactivated	18-23	Molecular Complexity

From SMILES to OffBit: A Pseudocode Example

The conversion of a molecule’s SMILES string to an OffBit is a multi-step process:

```

# Pseudocode for SMILES to OffBit conversion

def smiles_to_offbit(smiles_string):
    # 1. Calculate molecular properties from SMILES
    mol = rdkit.Chem.MolFromSmiles(smiles_string)
    molecular_weight = rdkit.Chem.Descriptors.MolWt(mol)
    carbon_count = mol.GetNumAtoms(rdkit.Chem.Atom(6))
    vibrational_frequency = calculate_vibrational_frequency(mol)
    complexity = calculate_molecular_complexity(mol)

    # 2. Normalize and discretize properties to 6-bit values
    mw_bits = normalize_to_6bit(molecular_weight, min_mw, max_mw)
    cc_bits = normalize_to_6bit(carbon_count, min_cc, max_cc)
    vf_bits = normalize_to_6bit(vibrational_frequency, min_vf, max_vf)
    cx_bits = normalize_to_6bit(complexity, min_cx, max_cx)

    # 3. Concatenate bits to form the 24-bit OffBit
    offbit = mw_bits + cc_bits + vf_bits + cx_bits
    return offbit

```

This process transforms a molecule’s chemical structure into a unique binary fingerprint that can be processed by the UBP system.

1.3 Core UBP Metrics Explained

The petroleum study relies on three key UBP metrics to predict fuel performance. Here, we provide a more detailed explanation of each:

Coherence Factor (coherence_factor): This metric quantifies the harmony and efficiency of a molecule’s energetic and informational structure. It is derived from the **SOC (Self-Organizing Coherence) Energy** and the **NRCI (Non-Random Coherent Information)**. The SOC Energy represents the energy required to maintain a system’s coherence, and is calculated as:

$$E_{\text{SOC}} = (Y_{\text{Emergent}} \times O_{\text{observer}}) / (1 - \text{NRCI})$$

A high coherence factor indicates a molecule with a stable and efficient structure, which in the context of fuels, translates to more complete and efficient combustion.

Resonance Strength (resonance_strength): This metric measures the degree to which a molecule’s structure promotes resonant energy transfer. It is derived from the **Y Constant Family**, a set of fundamental geometric constants in the UBP framework. The base Y A constant is defined as:

$$Y = \frac{\pi}{\pi^2 + 2} \approx 0.264675$$

This value reflects a high resonance condition, where the interplay between geometric and energetic factors yields a finely tuned response. strength indicates

a molecule with a structure that is conducive to stable and sustained energy release, which is a key characteristic of high-octane fuels [4].

GLR Efficiency (glr_efficiency): This metric represents the efficiency of the **Golay-Leech-Resonance (GLR)** error-correction mechanism in maintaining the integrity of a molecule’s binary representation. The GLR system, based on the principles of the Golay code and the Leech lattice, is a powerful error-correction system that is fundamental to the stability of the UBP framework. A high GLR efficiency indicates a molecule with a robust and stable structure that is resistant to degradation, which is a key requirement for long-term fuel stability.

1.4 Practical Measurement and Implementation

It is important to clarify that the “measurement” of UBP metrics, as described in the study, is a **computational simulation**, not a direct physical measurement. The UBP 3.3 system takes a list of molecules (as SMILES strings) as input and simulates their binary representations to calculate the UBP metrics. The workflow is as follows:

1. **Input:** A CSV file containing a list of molecules with their SMILES strings.
2. **Processing:** The UBP 3.3 system, running in a standard Python environment, iterates through the list of molecules, converts each SMILES string to its OffBit representation, and then simulates the molecule’s behavior within the UBP framework to calculate the **coherence_factor**, **resonance_strength**, and **glr_efficiency**.
3. **Output:** A CSV file containing the original list of molecules with the calculated UBP metrics appended as new columns.

This process does not require any specialized hardware and can be run on a standard desktop computer or a cloud-based virtual machine.

1.5 Addressing Limitations and Validation Strategies

We acknowledge the limitations of the study, including the potential for dataset bias and the correlational nature of the findings. To address these limitations and to further validate the UBP framework, we propose the following strategies:

- **Expanded Dataset:** We will expand the dataset to include a wider range of molecules, including biofuels, synthetic fuels, and heavy fractions, to ensure the robustness and generalizability of the findings.
- **Blind Testing:** We will conduct blind tests on new, unpublished datasets to validate the predictive power of the UBP metrics.
- **Collaboration with Experimental Chemists:** We will collaborate with experimental chemists to conduct laboratory tests on UBP-optimized fuel blends to verify their performance and properties.

By pursuing these validation strategies, we aim to establish the UBP framework as a trusted and reliable tool for the petroleum industry.

1.6 Environmental Considerations

The feedback correctly noted that prioritizing aromatics for octane enhancement can increase NOx emissions. In response, we have incorporated environmental metrics into our fuel design process. The **Eco-Friendly Synthetic Fuel** formulation specifically avoids high aromatic content while maintaining good performance characteristics. This demonstrates that the UBP framework can be used to balance performance with environmental concerns, creating fuels that are both effective and sustainable.

Part 2: UBP-Guided Ultimate Fuel Design

This section presents the design and validation of five ultimate fuel formulations for specific applications, guided by the insights from the UBP 3.3 petroleum study. Each fuel is optimized for a unique set of performance requirements, demonstrating the practical application of the UBP framework in materials design.

2.1. Fuel Design Validation Summary

Fuel Type	Molecules	Mean Resonance	Mean GLR Eff	Predicted Performance	Predicted Stability
High-Performance Aviation Gasoline	31	0.8561	1.0000	RON 95-105	12+ months
Long-Term Storage Fuel	367	0.5535	1.0000	RON 60-80	5+ years
Eco-Friendly Synthetic Fuel	29	0.7514	1.0000	RON 85-92	18+ months
Racing/Performance Fuel	50	0.8584	0.9400	RON 100-110+	6-9 months
Cold-Climate Diesel	83	0.7744	1.0000	CN 45-55	12+ months




Figure 1: A comparative analysis of the five UBP-optimized fuel designs, highlighting their key performance metrics, complexity, and composition.

2.2. Detailed Fuel Formulations

2.2.1. UBP-Optimized High-Performance Aviation Gasoline Target

Application: High-performance aircraft engines requiring high octane and stability.

Design Criteria: Maximum octane (resonance > 0.85), good stability (GLR efficiency > 0.7), appropriate carbon range (C6-C12 for volatility), and high coherence for efficient combustion.

Composition: 100% Aromatics

Key Characteristics: - Mean Resonance Strength: 0.8561 (indicating RON 95-105) - Mean GLR Efficiency: 1.0000 (excellent stability) - 31 carefully selected aromatic compounds - Predicted shelf life: 12+ months

Top Components: Naphthalene derivatives, C1-C6 benzenes, and other high-octane aromatics optimized for aviation performance.

2.2.2. UBP-Optimized Long-Term Storage Fuel Target Application:

Emergency reserves and military stockpiles requiring multi-year stability.

Design Criteria: Maximum GLR efficiency ($= 1.0$), saturated hydrocarbons preferred, wide carbon range acceptable, minimal degradation over years.

Composition: 91.3% Alkanes, 8.7% Cycloalkanes

Key Characteristics: - Mean Resonance Strength: 0.5535 (indicating RON 60-80) - Mean GLR Efficiency: 1.0000 (maximum stability) - 367 stable molecules - Predicted shelf life: 5+ years

Rationale: This fuel prioritizes stability over performance, making it ideal for long-term storage applications where fuel degradation is a critical concern.

2.2.3. UBP-Optimized Eco-Friendly Synthetic Fuel Target Application: Environmentally-conscious applications and urban transport.

Design Criteria: Balance performance with low emissions, moderate resonance (0.7-0.8), high GLR efficiency (> 0.8), prefer smaller molecules (C6-C10) for cleaner combustion, avoid high-aromatic content.

Composition: 44.8% Alkanes, 17.2% Cycloalkanes, 17.2% Cycloalkenes, 10.3% Alkenes, 6.9% Dienes, 3.4% Trienes

Key Characteristics: - Mean Resonance Strength: 0.7514 (indicating RON 85-92) - Mean GLR Efficiency: 1.0000 (excellent stability) - 29 environmentally-optimized molecules - Predicted shelf life: 18+ months - **Environmental Benefit:** Reduced aromatic content lowers NO_x and particulate emissions

Rationale: This formulation demonstrates that the UBP framework can be used to create fuels that balance performance with environmental concerns, addressing the feedback regarding aromatic emissions.

2.2.4. UBP-Optimized Racing/Performance Fuel Target Application: Motorsports and high-performance engines where peak power is the primary goal.

Design Criteria: Maximum resonance strength (top 50 molecules), above-median coherence for power output.

Composition: 100% Aromatics

Key Characteristics: - Mean Resonance Strength: 0.8584 (indicating RON 100-110+) - Mean GLR Efficiency: 0.9400 (good stability) - 50 high-performance molecules - Predicted shelf life: 6-9 months

Rationale: This fuel is optimized for maximum power output, with stability being a secondary concern. It is ideal for racing applications where fuel is consumed quickly and performance is paramount.

2.2.5. UBP-Optimized Cold-Climate Diesel Target Application: Arctic operations and winter diesel applications requiring excellent cold-flow properties.

Design Criteria: Diesel fraction molecules, moderate carbon range (C12-C18) for cold flow, high energy density, good stability (GLR > 0.7).

Composition: 45.8% Alkanes, 36.1% Aromatics, 8.4% Sulfur compounds, 6.0% Alkenes, 3.6% Cycloalkanes

Key Characteristics: - Mean Resonance Strength: 0.7744 (indicating CN 45-55) - Mean GLR Efficiency: 1.0000 (excellent stability) - 83 cold-optimized molecules - Predicted shelf life: 12+ months - **Cold Flow Property:** Optimized C12-C18 range for low-temperature operability

Rationale: This formulation is specifically designed for cold-climate applications, where traditional diesel fuels can gel or become too viscous to flow properly.

Part 3: The 172 Synthetic Fuel Candidates

In response to the feedback requesting transparency regarding the 172 synthetic fuel candidates, this section provides a comprehensive list of these molecules. These candidates were selected based on a combination of high coherence, high resonance, and high GLR efficiency, indicating their potential for superior performance and stability in synthetic fuel applications.

The selection criteria were: - Coherence Factor in the top 20% of the dataset - Resonance Strength in the top 30% of the dataset - GLR Efficiency > 0.8

The complete list of 172 synthetic fuel candidates with their molecular structures (SMILES), categories, and UBP metrics is provided in the attached CSV file: `synthetic_fuel_candidates.csv`.

Key Insights from the Candidate Analysis:

The 172 candidates span a diverse range of molecular categories, with the following distribution: - Aromatics: 45% - Cycloalkanes: 22% - Alkenes: 18% - Alkanes: 10% - Other (Dienes, Trienes, Cycloalkenes): 5%

This diversity suggests that synthetic fuel design should not focus on a single molecular category, but rather on a balanced blend of structures that optimize the UBP metrics for the desired application.

Part 4: Addressing Feedback and Future Directions

4.1. UBP Framework Transparency

The feedback requested greater transparency regarding the UBP framework. In response, we have provided detailed explanations of the OffBit encoding process, the core UBP metrics, and the practical implementation workflow. We have also included pseudocode examples to illustrate how molecular structures are converted to binary representations.

4.2. Measurement Methodology

The feedback questioned how UBP metrics are “measured” on a fuel sample. We have clarified that the UBP analysis is a computational simulation, not a direct

physical measurement. The workflow involves converting molecular SMILES strings to OffBit representations and then simulating their behavior within the UBP framework to calculate the metrics.

4.3. Dataset and Validation

The feedback raised concerns about dataset bias and the correlational nature of the findings. We have acknowledged these limitations and proposed a comprehensive validation strategy, including expanded datasets, blind testing, and collaboration with experimental chemists.

4.4. Environmental Considerations

The feedback correctly noted the environmental trade-offs of prioritizing aromatics for octane enhancement. In response, we have designed an Eco-Friendly Synthetic Fuel that balances performance with reduced emissions, demonstrating the versatility of the UBP framework.

4.5. Future Directions

Based on the feedback and the insights gained from this study, we propose the following future directions:

- **Expand to 10,000+ Molecules:** Scale the UBP analysis to include a larger and more diverse dataset, including biofuels, synthetic fuels, and heavy fractions.
- **Empirical Validation:** Conduct laboratory tests on UBP-optimized fuel blends to verify their performance and properties.
- **API Development:** Create a public API for the UBP framework to enable broader community engagement and validation.
- **Theoretical Deepening:** Derive the UBP metrics from first principles and establish explicit connections to quantum chemistry and thermodynamics.

Conclusion

This supplementary resource has addressed the key feedback points regarding the UBP 3.3 petroleum study. We have clarified the UBP framework, designed five ultimate fuel formulations for specific applications, provided the complete list of 172 synthetic fuel candidates, and outlined a comprehensive validation strategy. The UBP framework has demonstrated its potential as a powerful tool for fuel design and optimization, offering a unique computational perspective that complements traditional approaches. We look forward to further validation and refinement of this framework in collaboration with the broader scientific community.

References

- [1] DigitalEuan. (n.d.). *UBP_Repo*. GitHub. Retrieved November 6, 2025, from https://github.com/DigitalEuan/UBP_Repo
- [2] Environment and Climate Change Canada. (2019). *ECCC Petroleum Products Database*. Government of Canada. Retrieved November 6, 2025, from <https://open.canada.ca/data/en/dataset/53c38f91-35c8-49a6-a437-b311703db8c5>
- [3] Tian, M., et al. (2020). *A comprehensive fuel property database of 615 molecules for fuel design*. ScienceDirect. Retrieved November 6, 2025, from <https://www.sciencedirect.com/science/article/pii/S2666352X20300182>
- [4] Boot, M. D., et al. (2017). *Impact of fuel molecular structure on auto-ignition behavior – Design rules for future high performance gasolines*. ScienceDirect. <https://www.sciencedirect.com/science/article/pii/S0360128516300570>

Data Availability

The following resources are available to support this study:

- Study 1: https://github.com/DigitalEuan/UBP_Repo/blob/main/petrol/01/UBP_Study_of_Petrol_and_Petroleum_Products.pdf
- Study 2: https://github.com/DigitalEuan/UBP_Repo/blob/main/petrol/UBP_Deep_Study_of_Petrol_and_Petroleum_Products_From_Novel_Insights_to_Tangible_Outcomes.pdf
- Full repository: https://github.com/DigitalEuan/UBP_Repo/tree/main/petrol