Antigravity ACP Server - Public Docs

Documentation Based on Current Code

Google Antigravity ACP Server

The Antigravity ACP Server provides an implementation of the Agent Client Protocol (ACP) to enable developers to use the Antigravity agent from within IDEs and other developer tools that support ACP. It can be found in the ACP Registry.

1. Supported Authentication Methods

Depending on the IDE (or ACP Client) being used - the Antigravity ACP Server determines the authentication method to use based on what the user selects in the IDE or based on what you specify in your local configuration files - with preference given to what the IDE communicates via ACP. Please ensure your auth method matches the entitlements you have access to.

Authentication Method	Configuration Value (settings.json)	Use Case
Sign in with a Google Account	oauth-personal	Individual developers accessing their Google AI plans.
Sign in with Gemini Enterprise	oauth-business	Developers using Gemini Enterprise subscriptions.
Gemini API Keys	gemini-api-key	Building with the Gemini API using API keys from Google AI Studio.
Gemini Enterprise Agent Platform (via Google API Keys or ADCs)	agent-platform (also accepts “vertex-ai”)	Leveraging a Google Cloud environment using either Google API Keys or Application Default Credentials (ADCs).

2. Server Configuration

The Antigravity ACP Server is configured via configuration files and environment variables. If an option is defined in both places, the environment variable takes precedence.

Configuration Files

The AGY ACP server reads its default settings from a centralized JSON configuration located in $GEMINI_HOME, where $GEMINI_HOME defaults to “~/.gemini/”.

- Settings file Location: $GEMINI_HOME/antigravity-acp/settings.json (i.e. “~/.gemini/antigravity-acp/settings.json” by default).

For Google accounts (using Google AI plans):

```JSON
{
  "auth": {
```

```
    "type": "oauth-personal"
  }
}
```

For Gemini Enterprise:

```JSON
{
  "auth": {
    "type": "oauth-business"
  },
  "gcp": {
    // Corporate Google Cloud Project ID associated with your Gemini Enterprise license [1]
    "project": "<YOUR_GCP_PROJECT_ID>",

    // Google Cloud Region associated with your Gemini Enterprise license (e.g. us-central1) [1]
    "location": "<YOUR_GCP_REGION>"
  }
}
```

[1] Contact your enterprise administrators for details.

For Gemini API:

```JSON
{
  "auth": {
    // Gemini API keys are created with Google AI Studio
    "type": "gemini-api-key"
  }
}
```

For Gemini Enterprise Agent Platform:

```JSON
{
  "auth": {
    "type": "agent-platform"
  }
  "gcp": {
    // Gemini Enterprise Agent Platform is accessed either using Google API Keys or ADCs.
    // Using ADCs requires providing a project ID and location (e.g. us-central1).
    // The Google API key can be provided via environment variable or via ACP.
    // Project ID & location can be provided as environment variables or in settings.
    "project": "<YOUR_GCP_PROJECT_ID>",
    "location": "<YOUR_GCP_REGION>"
  }
}
```

Environment Variables

Antigravity ACP Server can use several variables for configuration and authentication purposes. These can be set directly in the AGY ACP Server's execution environment as environment variables.

- **GEMINI_HOME:** Defines the directory where the Antigravity ACP Server stores active sessions, runtime metadata, and your global configuration file. Defaults to "~/.gemini/".
- **GEMINI_API_KEY:** The API key generated from Google AI Studio. Required only when auth.type is set to gemini-api-key.
- **GOOGLE_API_KEY:** Used for Gemini Enterprise Agent Platform use - alternatively Application Default Credentials (ADCs) can be used, which requires specifying the Google Cloud Project & Location.
- **GOOGLE_CLOUD_PROJECT:** The target Google Cloud Project ID. Used for ADC authentication with **Gemini Enterprise Agent Platform** or for license selection for Gemini Enterprise subscriptions.
- **GOOGLE_CLOUD_LOCATION:** The Google Cloud region (e.g. us-central1). Used for ADC authentication with **Gemini Enterprise Agent Platform** or for license selection for Gemini Enterprise subscriptions.

Agent Platform Users: Visit the Gemini Enterprise Agent Platform documentation for additional instructions and context on getting started.

3. Agent Customization

The Antigravity ACP Server is designed to align with the rest of the Antigravity ecosystem - including the Antigravity CLI and Antigravity 2.0. Global (user-specific) scope configurations and customizations are found in $GEMINI_HOME, which defaults to "~/.gemini/".

Customization Type	Project-Specific Scope	Global (User-Specific) Scope
Agent Skills	<project-root>/.agents/skills/ <project-root>/.gemini/skills/	$GEMINI_HOME/config/skills/ $GEMINI_HOME/antigravity-cli/skills/
Hooks	<project-root>/.agents/hooks.json (also checks .agent/, _agents/, _agent/)	$GEMINI_HOME/config/hooks.json
MCP Servers	Configuration provided by your IDE	Configuration provided by your IDE & $GEMINI_HOME/config/mcp_config.json

4. Additional Information

The Antigravity ACP Server is built using a combination of Google-proprietary technologies and open-source libraries. To facilitate easy auditing and ensure compliance with open-source software distribution standards, the server binary includes a built-in flag to inspect third-party license notices.

To print all third-party licenses and immediately exit the process, run the binary from your terminal with the --notices flag:

```shell
/path/to/agy_acp_server.par --notices
```