

Force.com Source Scanner Results

Job Type: ZIP_UPLOAD

Preset: PortalAll

Scan Id: a0OKX000001JMTX2A4

Description: CloudScan

Email Address: popcrabadmins@salesforce.com

Security Issues: 33

Service Version:
v3.2

Scan Start: 2026-
07-13 22:11:28

Quality Issues: 0

CxEngine: 9.7

Scan End: 2026-
07-14 03:13:05

For any questions about this service, please consult our scanner help page at

<https://security.secure.force.com/security/tools/forcecom/scannerhelp>

(<https://security.secure.force.com/security/tools/forcecom/scannerhelp>)

Query	Group	Issues
Apex SOQL SOSL Security Enforced Usage	Apex Medium Security Risk	11
SOQL SOSL Injection	Apex Critical Security Risk	3
Apex SOQL SOSL User Mode Missing	Apex Medium Security Risk	1
Authenticaton Secrets in http request	Apex Medium Security Risk	18
Disallowed Password APIs	Apex Critical Security Risk	No Issues Found
Stored XSS	Apex Critical Security Risk	No Issues Found
Lightning API Version	Apex Critical Security Risk	No Issues Found
Reflected XSS	Apex Critical Security Risk	No Issues Found
Client DOM Code Injection	JavaScript High Risk	No Issues Found
Client DOM XSS	JavaScript High Risk	No Issues Found
Client DOM Stored XSS	JavaScript High Risk	No Issues Found

Client DOM Stored Code Injection	JavaScript High Risk	No Issues Found
Sharing	Apex Serious Security Risk	No Issues Found
FLS Update	Apex Serious Security Risk	No Issues Found
URL Redirection Attack	Apex Serious Security Risk	No Issues Found
CRUD Delete	Apex Serious Security Risk	No Issues Found
FLS Create	Apex Serious Security Risk	No Issues Found
XSRF	Apex Serious Security Risk	No Issues Found
Client Overly Permissive Message Posting	JavaScript Low Visibility	No Issues Found
DML Statements Inside Loops	Apex Code Quality	No Issues Found
Async Future Method Inside Loops	Apex Code Quality	No Issues Found
Bulkify Apex Methods Using Collections In Methods	Apex Code Quality	No Issues Found
Multiple Forms In Visualforce Page	Apex Code Quality	No Issues Found
Hardcoding Of Trigger New	Apex Code Quality	No Issues Found
Test Methods With No Assert	Apex Code Quality	No Issues Found
Queries With No Where Or Limit Clause	Apex Code Quality	No Issues Found
Multiple Trigger On same sObject	Apex Code Quality	No Issues Found
Hardcoding Ids	Apex Code Quality	No Issues Found
SOSL SOQL Statments Inside Loops	Apex Code Quality	No Issues Found

Query: SOQL SOSL Injection

This query detects user controlled input entering the structure of a SOQL query in Apex. Unlike queries sent via the REST/SOAP API, queries in Apex do not enforce CRUD/FLS checks, and therefore letting the user inject their own SOQL code can lead to unauthorized data access. This is even true if the user can only influence fields in WHERE clauses. To fix this vulnerability, make sure that 1) user controlled data that is in a quoted context is entered into the query via a bound variable, or is otherwise sanitized with `String.escapeSingleQuotes()`. 2) For data that is not quoted it must be of a safe data type, such as integer or Id. 3) All other user data must be checked by manually performing CRUD/FLS checks or matching against a whitelist. This may be a false positive if you perform the sanitization outside of the detected dataflow or if the fieldtype is only controlled by a privileged account (custom settings).

Reference:

https://developer.salesforce.com/docs/atlas.en-us.secure_coding_guide.meta/secure_coding_guide/secure_coding_sql_injection.htm
(https://developer.salesforce.com/docs/atlas.en-us.secure_coding_guide.meta/secure_coding_guide/secure_coding_sql_injection.htm)

SOQL SOSL Injection result path 1:

Similarity Id: -2024209245

Object: objectname in file: classes/ExternalOrgQueryController.cls

```
L 205: String objectName,
```

Object: objectname in file: classes/ExternalOrgQueryController.cls

```
L 212: objectName,
```

Object: objectname in file: classes/DataSeedingService.cls

```
L 13: String objectName,
```

Object: objectname in file: classes/DataSeedingService.cls

```
L 81: objectName +
```

Object: soql in file: classes/DataSeedingService.cls

```
L 77: String soql =
```

Object: soql in file: classes/DataSeedingService.cls

```
L 98: for (SObject s : Database.query(soql, AccessLevel.USER_MODE)) {
```

Object: matchfields in file: classes/ExternalOrgQueryController.cls

```
L 206: List<String> matchFields,
```

Object: matchfields in file: classes/ExternalOrgQueryController.cls

```
L 213: matchFields,
```

Object: matchfields in file: classes/DataSeedingService.cls

```
L 14: List<String> matchFields,
```

Object: matchfields in file: classes/DataSeedingService.cls

```
L 23: matchFields.isEmpty()
```

Object: matchfields in file: classes/DataSeedingService.cls

```
L 57: for (String f : matchFields) {
```

Object: f in file: classes/DataSeedingService.cls

```
L 70: whereClause += f + ' IN (' + String.join(quoted, ',') + ')';
```

Object: whereclause in file: classes/DataSeedingService.cls

```
L 83: whereClause +
```

Object: soql in file: classes/DataSeedingService.cls

```
L 77: String soql =
```

Object: soql in file: classes/DataSeedingService.cls

```
L 98: for (SObject s : Database.query(soql, AccessLevel.USER_MODE)) {
```

Object: soql in file: classes/ExternalOrgQueryController.cls

```
L 121: String soql
```

Object: soql in file: classes/ExternalOrgQueryController.cls

```
L 123: return ExternalOrgQueryService.queryCurrent(soql);
```

Object: soql in file: classes/ExternalOrgQueryService.cls

```
L 177: public static QueryResultWrapper queryCurrent(String soql) {
```

Object: soql in file: classes/ExternalOrgQueryService.cls

```
L 178: return queryCurrent(soql, null);
```

Object: soql in file: classes/ExternalOrgQueryService.cls

```
L 182: String soql,
```

Object: soql in file: classes/ExternalOrgQueryService.cls

```
L 192: String cleanSoql = soql.replaceAll('(?!i)WITH\\s+SECURITY_ENFORCE
```

Object: cleansoql in file: classes/ExternalOrgQueryService.cls

```
L 193: List<SObject> recs = Database.query(cleanSoql, AccessLevel.USER_
```

Query: Apex AuthN SECRETS

Do not use hard-coded secrets in code. See the references for specific guidance on how to securely handle authentication secrets

References:

https://developer.salesforce.com/docs/atlas.en-us.secure_coding_guide.meta/secure_coding_guide/secure_coding_storing_sensitive_data.htm
(https://developer.salesforce.com/docs/atlas.en-us.secure_coding_guide.meta/secure_coding_guide/secure_coding_storing_sensitive_data.htm)
<https://trailhead.salesforce.com/content/learn/modules/secure-secrets-storage/protect-secrets-using-platform-features> (
<https://trailhead.salesforce.com/content/learn/modules/secure-secrets-storage/protect-secrets-using-platform-features>)

Apex AuthN SECRETS result path 1:

Similarity Id: 1509773199

Object: "sess" in file: classes/ExternalOrgQueryControllerTest2.cls

```
L 52: 'sess',
```

Object: sessionId in file: classes/ExternalOrgQueryController.cls

```
L 48: String sessionId,
```

Object: sessionId in file: classes/ExternalOrgQueryController.cls

```
L 55: sessionId,
```

Object: sessionId in file: classes/ExternalOrgDescribeService.cls

```
L 135: String sessionId,
```

Object: sessionId in file: classes/ExternalOrgDescribeService.cls

```
L 179: sessionId,
```

Object: sessionId in file: classes/ExternalOrgDescribeService.cls

```
L 385: String sessionId,
```

Object: sessionId in file: classes/ExternalOrgDescribeService.cls

```
L 408: sessionId,
```

Object: sessionId in file: classes/ExternalOrgDescribeService.cls

```
L 506: String sessionId,
```

Object: sessionId in file: classes/ExternalOrgDescribeService.cls

```
L 521: request.setHeader('Authorization', 'Bearer ' + sessionId);
```

Apex AuthN SECRETS result path 2:

Similarity Id: -620423033

Object: "sess" in file: classes/ExternalOrgQueryControllerTest2.cls

```
L 52: 'sess',
```

Object: sessionId in file: classes/ExternalOrgQueryController.cls

```
L 48: String sessionId,
```

Object: sessionId in file: classes/ExternalOrgQueryController.cls

```
L 55: sessionId,
```

Object: sessionId in file: classes/ExternalOrgDescribeService.cls

```
L 135: String sessionId,
```

Object: sessionId in file: classes/ExternalOrgDescribeService.cls

```
L 170: sessionId,
```

Object: sessionId in file: classes/ExternalOrgDescribeService.cls

```
L 196: String sessionId,
```

Object: sessionId in file: classes/ExternalOrgDescribeService.cls

```
L 228: executeBatchDescribe(sessionId, instanceUrl, neededDescriptions)
```

Object: sessionId in file: classes/ExternalOrgDescribeService.cls

```
L 308: String sessionId,
```

Object: sessionId in file: classes/ExternalOrgDescribeService.cls

```
L 319: sendBatchRequest(sessionId, instanceUrl, batch);
```

Object: sessionId in file: classes/ExternalOrgDescribeService.cls

```
L 329: String sessionId,
```

Object: sessionId in file: classes/ExternalOrgDescribeService.cls

```
L 348: request.setHeader('Authorization', 'Bearer ' + sessionId);
```

Apex AuthN SECRETS result path 3:

Similarity Id: 1863570574

Object: "sess" in file: classes/ExternalOrgServicesTest.cls

```
L 132: 'sess',
```

Object: sessionId in file: classes/ExternalOrgDescribeService.cls

```
L 79: String sessionId,
```

Object: sessionId in file: classes/ExternalOrgDescribeService.cls

```
L 91: request.setHeader('Authorization', 'Bearer ' + sessionId);
```

Apex AuthN SECRETS result path 4:

Similarity Id: 272681186

Object: "sessid" in file: classes/ExternalOrgDmlServiceTest.cls

```
L 44: 'sessId',
```

Object: sessionId in file: classes/ExternalOrgDmlService.cls

```
L 227: String sessionId,
```

Object: sessionId in file: classes/ExternalOrgDmlService.cls

```
L 233: sessionId,
```

Object: sessionid in file: classes/ExternalOrgDmlService.cls

```
L 257: String sessionId,
```

Object: sessionid in file: classes/ExternalOrgDmlService.cls

```
L 273: out.addAll(sendBatch(sessionId, instanceUrl, objectName, chunk,
```

Object: sessionid in file: classes/ExternalOrgDmlService.cls

```
L 279: String sessionId,
```

Object: sessionid in file: classes/ExternalOrgDmlService.cls

```
L 345: req.setHeader('Authorization', 'Bearer ' + sessionId);
```

Apex AuthN SECRETS result path 5:

Similarity Id: -1397556052

Object: "sess" in file: classes/ExternalOrgServicesTest.cls

```
L 81: 'sess',
```

Object: sessionid in file: classes/ExternalOrgQueryService.cls

```
L 91: String sessionId,
```

Object: sessionid in file: classes/ExternalOrgQueryService.cls

```
L 114: request.setHeader('Authorization', 'Bearer ' + sessionId);
```

Apex AuthN SECRETS result path 6:

Similarity Id: -1589476630

Object: "src_sess" in file: classes/DataSeedingServicesTestV2.cls

```
L 46: 'src_sess',
```

Object: sourcesessionid in file: classes/DataSeedingBatch.cls

```
L 43: String sourceSessionId,
```

Object: sourcesessionid in file: classes/DataSeedingBatch.cls

```
L 51: this.sourceSessionId = sourceSessionId;
```

Object: dataseedingbatch in file: classes/DataSeedingServicesTestV2.cls

```
L 45: DataSeedingBatch batch = new DataSeedingBatch(
```

Object: batch in file: classes/DataSeedingServicesTestV2.cls

```
L 60: batch.resolveUserProfiles(userRows);
```

Object: sourcesessionid in file: classes/DataSeedingBatch.cls

```
L 503: sourceSessionId,
```

Object: sessionid in file: classes/ExternalOrgQueryService.cls

```
L 91: String sessionId,
```

Object: sessionid in file: classes/ExternalOrgQueryService.cls

```
L 114: request.setHeader('Authorization', 'Bearer ' + sessionId);
```

Apex AuthN SECRETS result path 7:

Similarity Id: -8047731

Object: "http://schemas.xmlsoap.org/soap/envelop... in file:
classes/ExternalOrgAuthService.cls

```
L 129: 'http://schemas.xmlsoap.org/soap/envelope/'
```

Object: getChildElement in file: classes/ExternalOrgAuthService.cls

```
L 127: Dom.XMLNode body = envelope.getChildElement(
```

Object: body in file: classes/ExternalOrgAuthService.cls

```
L 134: Dom.XMLNode loginResponse = body.getChildElement(
```

Object: loginresponse in file: classes/ExternalOrgAuthService.cls

```
L 153: Dom.XMLNode resultNode = loginResponse.getChildElement(
```

Object: resultnode in file: classes/ExternalOrgAuthService.cls

```
L 161: String sessionId = safeGetText(resultNode, 'sessionId');
```

Object: parent in file: classes/ExternalOrgAuthService.cls

```
L 175: private static String safeGetText(Dom.XMLNode parent, String chi
```



Object: parent in file: classes/ExternalOrgAuthService.cls

```
L 176: Dom.XMLNode child = parent.getChildElement(
```

Object: child in file: classes/ExternalOrgAuthService.cls

```
L 180: return child == null ? null : child.getText();
```

Object: safegettext in file: classes/ExternalOrgAuthService.cls

```
L 161: String sessionId = safeGetText(resultNode, 'sessionId');
```

Object: sessionid in file: classes/ExternalOrgAuthService.cls

```
L 170: loginResult.sessionId = sessionId;
```

Object: loginresult in file: classes/ExternalOrgAuthService.cls

```
L 171: loginResult.serverUrl = serverUrl;
```

Object: loginresult in file: classes/ExternalOrgAuthService.cls

```
L 172: return loginResult;
```

Object: login in file: classes/ExternalOrgQueryService.cls

```
L 40: ExternalOrgAuthService.LoginResult loginResult = ExternalOrgAuthS
```



Object: loginresult in file: classes/ExternalOrgQueryService.cls

```
L 62: request.setHeader('Authorization', 'Bearer ' + loginResult.sessio
```



Apex AuthN SECRETS result path 8:

Similarity Id: -2125843471

Object: "sess" in file: classes/ExternalOrgQueryControllerTest2.cls

```
L 15: 'sess',
```

Object: sessionid in file: classes/ExternalOrgQueryController.cls

```
L 65: String sessionId,
```

Object: sessionid in file: classes/ExternalOrgQueryController.cls

```
L 70: sessionId,
```

Object: sessionid in file: classes/ExternalOrgDescribeService.cls

```
L 543: String sessionId,
```

Object: sessionid in file: classes/ExternalOrgDescribeService.cls

```
L 559: sessionId,
```

Object: sessionId in file: classes/ExternalOrgDescribeService.cls

```
L 506: String sessionId,
```

Object: sessionId in file: classes/ExternalOrgDescribeService.cls

```
L 521: request.setHeader('Authorization', 'Bearer ' + sessionId);
```

Apex AuthN SECRETS result path 9:

Similarity Id: 1519154351

Object: "sessionId" in file: classes/ExternalOrgAuthService.cls

```
L 161: String sessionId = safeGetText(resultNode, 'sessionId');
```

Object: childlocalname in file: classes/ExternalOrgAuthService.cls

```
L 175: private static String safeGetText(Dom.XMLNode parent, String chi
```



Object: childlocalname in file: classes/ExternalOrgAuthService.cls

```
L 177: childLocalName,
```

Object: getchildelement in file: classes/ExternalOrgAuthService.cls

```
L 176: Dom.XMLNode child = parent.getChildElement(
```

Object: child in file: classes/ExternalOrgAuthService.cls

```
L 180: return child == null ? null : child.getText();
```

Object: safegettext in file: classes/ExternalOrgAuthService.cls

```
L 161: String sessionId = safeGetText(resultNode, 'sessionId');
```

Object: sessionId in file: classes/ExternalOrgAuthService.cls

```
L 170: loginResult.sessionId = sessionId;
```

Object: loginresult in file: classes/ExternalOrgAuthService.cls

```
L 171: loginResult.serverUrl = serverUrl;
```

Object: loginresult in file: classes/ExternalOrgAuthService.cls

```
L 172: return loginResult;
```

Object: login in file: classes/ExternalOrgQueryService.cls

```
L 40: ExternalOrgAuthService.LoginResult loginResult = ExternalOrgAuthS
```

Object: loginresult in file: classes/ExternalOrgQueryService.cls

```
L 62: request.setHeader('Authorization', 'Bearer ' + loginResult.sessio
```

Apex AuthN SECRETS result path 10:

Similarity Id: -134631470

Object: "result" in file: classes/ExternalOrgAuthService.cls

```
L 154: 'result',
```

Object: getChildElement in file: classes/ExternalOrgAuthService.cls

```
L 153: Dom.XMLNode resultNode = loginResponse.getChildElement(
```

Object: resultnode in file: classes/ExternalOrgAuthService.cls

```
L 161: String sessionId = safeGetText(resultNode, 'sessionId');
```

Object: parent in file: classes/ExternalOrgAuthService.cls

```
L 175: private static String safeGetText(Dom.XMLNode parent, String chi
```

Object: parent in file: classes/ExternalOrgAuthService.cls

```
L 176: Dom.XMLNode child = parent.getChildElement(
```

Object: child in file: classes/ExternalOrgAuthService.cls

```
L 180: return child == null ? null : child.getText();
```

Object: safegettext in file: classes/ExternalOrgAuthService.cls

```
L 161: String sessionId = safeGetText(resultNode, 'sessionId');
```

Object: sessionId in file: classes/ExternalOrgAuthService.cls

```
L 170: loginResult.sessionId = sessionId;
```

Object: loginresult in file: classes/ExternalOrgAuthService.cls

```
L 171: loginResult.serverUrl = serverUrl;
```

Object: loginresult in file: classes/ExternalOrgAuthService.cls

```
L 172: return loginResult;
```

Object: login in file: classes/ExternalOrgQueryService.cls

```
L 40: ExternalOrgAuthService.LoginResult loginResult = ExternalOrgAuthS
```

Object: loginresult in file: classes/ExternalOrgQueryService.cls

```
L 62: request.setHeader('Authorization', 'Bearer ' + loginResult.sessio
```

Apex AuthN SECRETS result path 11:

Similarity Id: 2124197709

Object: "body" in file: classes/ExternalOrgAuthService.cls

```
L 128: 'Body',
```

Object: getChildElement in file: classes/ExternalOrgAuthService.cls

```
L 127: Dom.XMLNode body = envelope.getChildElement(
```

Object: body in file: classes/ExternalOrgAuthService.cls

```
L 134: Dom.XMLNode loginResponse = body.getChildElement(
```

Object: loginresponse in file: classes/ExternalOrgAuthService.cls

```
L 153: Dom.XMLNode resultNode = loginResponse.getChildElement(
```

Object: resultnode in file: classes/ExternalOrgAuthService.cls

```
L 161: String sessionId = safeGetText(resultNode, 'sessionId');
```

Object: parent in file: classes/ExternalOrgAuthService.cls

```
L 175: private static String safeGetText(Dom.XMLNode parent, String chi
```

Object: parent in file: classes/ExternalOrgAuthService.cls

```
L 176: Dom.XMLNode child = parent.getChildElement(
```

Object: child in file: classes/ExternalOrgAuthService.cls

```
L 180: return child == null ? null : child.getText();
```

Object: safegettext in file: classes/ExternalOrgAuthService.cls

```
L 161: String sessionId = safeGetText(resultNode, 'sessionId');
```

Object: sessionId in file: classes/ExternalOrgAuthService.cls

```
L 170: loginResult.sessionId = sessionId;
```

Object: loginresult in file: classes/ExternalOrgAuthService.cls

```
L 171: loginResult.serverUrl = serverUrl;
```

Object: loginresult in file: classes/ExternalOrgAuthService.cls

```
L 172: return loginResult;
```

Object: login in file: classes/ExternalOrgQueryService.cls

```
L 40: ExternalOrgAuthService.LoginResult loginResult = ExternalOrgAuthS
```

◀  ▶

Object: loginresult in file: classes/ExternalOrgQueryService.cls

```
L 62: request.setHeader('Authorization', 'Bearer ' + loginResult.sessio
```

◀  ▶

Apex AuthN SECRETS result path 12:

Similarity Id: 417345171

Object: "loginresponse" in file: classes/ExternalOrgAuthService.cls

```
L 135: 'loginResponse',
```

Object: getChildElement in file: classes/ExternalOrgAuthService.cls

```
L 134: Dom.XMLNode loginResponse = body.getChildElement(
```

Object: loginresponse in file: classes/ExternalOrgAuthService.cls

```
L 153: Dom.XMLNode resultNode = loginResponse.getChildElement(
```

Object: resultnode in file: classes/ExternalOrgAuthService.cls

```
L 161: String sessionId = safeGetText(resultNode, 'sessionId');
```

Object: parent in file: classes/ExternalOrgAuthService.cls

```
L 175: private static String safeGetText(Dom.XMLNode parent, String chi
```

◀  ▶

Object: parent in file: classes/ExternalOrgAuthService.cls

```
L 176: Dom.XMLNode child = parent.getChildElement(
```

Object: child in file: classes/ExternalOrgAuthService.cls

```
L 180: return child == null ? null : child.getText();
```

Object: safegettext in file: classes/ExternalOrgAuthService.cls

```
L 161: String sessionId = safeGetText(resultNode, 'sessionId');
```

Object: sessionid in file: classes/ExternalOrgAuthService.cls

```
L 170: loginResult.sessionId = sessionId;
```

Object: loginresult in file: classes/ExternalOrgAuthService.cls

```
L 171: loginResult.serverUrl = serverUrl;
```

Object: loginresult in file: classes/ExternalOrgAuthService.cls

```
L 172: return loginResult;
```

Object: login in file: classes/ExternalOrgQueryService.cls

```
L 40: ExternalOrgAuthService.LoginResult loginResult = ExternalOrgAuthS
```



Object: loginresult in file: classes/ExternalOrgQueryService.cls

```
L 62: request.setHeader('Authorization', 'Bearer ' + loginResult.sessio
```



Apex AuthN SECRETS result path 13:

Similarity Id: -1629732128

Object: "sess" in file: classes/UserFieldFilteringTest.cls

```
L 65: 'sess',
```

Object: sessionid in file: classes/ExternalOrgDmlService.cls

```
L 227: String sessionId,
```

Object: sessionid in file: classes/ExternalOrgDmlService.cls

```
L 233: sessionId,
```

Object: sessionid in file: classes/ExternalOrgDmlService.cls

```
L 257: String sessionId,
```

Object: sessionId in file: classes/ExternalOrgDmlService.cls

```
L 273: out.addAll(sendBatch(sessionId, instanceUrl, objectName, chunk,
```

Object: sessionId in file: classes/ExternalOrgDmlService.cls

```
L 279: String sessionId,
```

Object: sessionId in file: classes/ExternalOrgDmlService.cls

```
L 345: req.setHeader('Authorization', 'Bearer ' + sessionId);
```

Apex AuthN SECRETS result path 14:

Similarity Id: 1949638984

Object: "urn:partner.soap.sforce.com" in file:
classes/ExternalOrgAuthService.cls

```
L 178: 'urn:partner.soap.sforce.com'
```

Object: getChildElement in file: classes/ExternalOrgAuthService.cls

```
L 176: Dom.XMLNode child = parent.getChildElement(
```

Object: child in file: classes/ExternalOrgAuthService.cls

```
L 180: return child == null ? null : child.getText();
```

Object: safegettext in file: classes/ExternalOrgAuthService.cls

```
L 161: String sessionId = safeGetText(resultNode, 'sessionId');
```

Object: sessionId in file: classes/ExternalOrgAuthService.cls

```
L 170: loginResult.sessionId = sessionId;
```

Object: loginresult in file: classes/ExternalOrgAuthService.cls

```
L 171: loginResult.serverUrl = serverUrl;
```

Object: loginresult in file: classes/ExternalOrgAuthService.cls

```
L 172: return loginResult;
```

Object: login in file: classes/ExternalOrgQueryService.cls

```
L 40: ExternalOrgAuthService.LoginResult loginResult = ExternalOrgAuthS
```

Object: loginresult in file: classes/ExternalOrgQueryService.cls

```
L 62: request.setHeader('Authorization', 'Bearer ' + loginResult.sessio
```

Apex AuthN SECRETS result path 15:

Similarity Id: 2065411516

Object: "sess" in file: classes/ExternalOrgServicesTest.cls

```
L 98: 'sess',
```

Object: sessionId in file: classes/ExternalOrgQueryService.cls

```
L 136: String sessionId,
```

Object: sessionId in file: classes/ExternalOrgQueryService.cls

```
L 156: request.setHeader('Authorization', 'Bearer ' + sessionId);
```

Apex AuthN SECRETS result path 16:

Similarity Id: 137131212

Object: "urn:partner.soap.sforce.com" in file:
classes/ExternalOrgAuthService.cls

```
L 155: 'urn:partner.soap.sforce.com'
```

Object: getChildElement in file: classes/ExternalOrgAuthService.cls

```
L 153: Dom.XMLNode resultNode = loginResponse.getChildElement(
```

Object: resultnode in file: classes/ExternalOrgAuthService.cls

```
L 161: String sessionId = safeGetText(resultNode, 'sessionId');
```

Object: parent in file: classes/ExternalOrgAuthService.cls

```
L 175: private static String safeGetText(Dom.XMLNode parent, String chi
```

Object: parent in file: classes/ExternalOrgAuthService.cls

```
L 176: Dom.XMLNode child = parent.getChildElement(
```

Object: child in file: classes/ExternalOrgAuthService.cls

```
L 180: return child == null ? null : child.getText();
```

Object: safegettext in file: classes/ExternalOrgAuthService.cls

```
L 161: String sessionId = safeGetText(resultNode, 'sessionId');
```

Object: sessionId in file: classes/ExternalOrgAuthService.cls

```
L 170: loginResult.sessionId = sessionId;
```

Object: loginresult in file: classes/ExternalOrgAuthService.cls

```
L 171: loginResult.serverUrl = serverUrl;
```

Object: loginresult in file: classes/ExternalOrgAuthService.cls

```
L 172: return loginResult;
```

Object: login in file: classes/ExternalOrgQueryService.cls

```
L 40: ExternalOrgAuthService.LoginResult loginResult = ExternalOrgAuthS
```



Object: loginresult in file: classes/ExternalOrgQueryService.cls

```
L 62: request.setHeader('Authorization', 'Bearer ' + loginResult.sessio
```



Apex AuthN SECRETS result path 17:

Similarity Id: -130920509

Object: "sess" in file: classes/DataSeedingServiceTest.cls

```
L 55: 'sess',
```

Object: sessionId in file: classes/DataSeedingService.cls

```
L 11: String sessionId,
```

Object: sessionId in file: classes/DataSeedingService.cls

```
L 90: sessionId,
```

Object: sessionId in file: classes/ExternalOrgQueryService.cls

```
L 91: String sessionId,
```

Object: sessionId in file: classes/ExternalOrgQueryService.cls

```
L 114: request.setHeader('Authorization', 'Bearer ' + sessionId);
```

Apex AuthN SECRETS result path 18:

Similarity Id: 869986200

Object: "dest_sess" in file: classes/DataSeedingServicesTestV2.cls

```
L 48: 'dest_sess',
```

Object: destsessionId in file: classes/DataSeedingBatch.cls

```
L 45: String destSessionId,
```

Object: destsessionId in file: classes/DataSeedingBatch.cls

```
L 53: this.destSessionId = destSessionId;
```

Object: dataseedingbatch in file: classes/DataSeedingServicesTestV2.cls

```
L 45: DataSeedingBatch batch = new DataSeedingBatch(
```

Object: batch in file: classes/DataSeedingServicesTestV2.cls

```
L 60: batch.resolveUserProfiles(userRows);
```

Object: destsessionId in file: classes/DataSeedingBatch.cls

```
L 540: destSessionId,
```

Object: sessionId in file: classes/ExternalOrgQueryService.cls

```
L 91: String sessionId,
```

Object: sessionId in file: classes/ExternalOrgQueryService.cls

```
L 114: request.setHeader('Authorization', 'Bearer ' + sessionId);
```

Query: Apex SOQL SOSL SECURITY ENFORCED USAGE

USER_MODE is recommended for SOQL/SOSL/DML operations. Use of WITH SECURITY_ENFORCED is no longer allowed for AppExchange apps

Reference:

https://developer.salesforce.com/docs/atlas.en-us.apexcode.meta/apexcode/apex_classes_enforce_usermode.htm
(https://developer.salesforce.com/docs/atlas.en-us.apexcode.meta/apexcode/apex_classes_enforce_usermode.htm)

Apex SOQL SOSL SECURITY ENFORCED USAGE
result path 1:

Similarity Id: -758848385

Object: "(?i)with\\s+security_enforced" in file:
classes/ExternalOrgQueryService.cls

```
L 192: String cleanSql = sql.replaceAll('( ?i)WITH\\s+SECURITY_ENFORCE
```

Object: cleansoql in file: classes/ExternalOrgQueryService.cls

```
L 193: List<SObject> recs = Database.query(cleanSoql, AccessLevel.USER_
```



Apex SOQL SOSL SECURITY ENFORCED USAGE
result path 2:

Similarity Id: 1288849195

Object: querycurrent in file: classes/DataSeedingBatch.cls

```
L 156: res = ExternalOrgQueryService.queryCurrent(soql, queryFields);
```

Object: query in file: classes/ExternalOrgQueryService.cls

```
L 193: List<SObject> recs = Database.query(cleanSoql, AccessLevel.USER_
```



Apex SOQL SOSL SECURITY ENFORCED USAGE
result path 3:

Similarity Id: 762656274

Object: querycurrent in file: classes/DataSeedingBatch.cls

```
L 508: sourceRes = ExternalOrgQueryService.queryCurrent(sourceSoql);
```

Object: query in file: classes/ExternalOrgQueryService.cls

```
L 193: List<SObject> recs = Database.query(cleanSoql, AccessLevel.USER_
```



Apex SOQL SOSL SECURITY ENFORCED USAGE
result path 4:

Similarity Id: 39316466

Object: querycurrent in file: classes/DataSeedingBatch.cls

```
L 545: destRes = ExternalOrgQueryService.queryCurrent(destSoql);
```

Object: query in file: classes/ExternalOrgQueryService.cls

```
L 193: List<SObject> recs = Database.query(cleanSoql, AccessLevel.USER_
```



Apex SOQL SOSL SECURITY ENFORCED USAGE
result path 5:

Similarity Id: 1162945227

Object: querycurrent in file: classes/DataSeedingBatch.cls

```
L 606: sourceRes = ExternalOrgQueryService.queryCurrent(sourceSoql);
```

Object: query in file: classes/ExternalOrgQueryService.cls

```
L 193: List<SObject> recs = Database.query(cleanSoql, AccessLevel.USER_
```

Apex SOQL SOSL SECURITY ENFORCED USAGE
result path 6:

Similarity Id: 1150025963

Object: querycurrent in file: classes/DataSeedingBatch.cls

```
L 668: destRes = ExternalOrgQueryService.queryCurrent(destSoql);
```

Object: query in file: classes/ExternalOrgQueryService.cls

```
L 193: List<SObject> recs = Database.query(cleanSoql, AccessLevel.USER_
```

Apex SOQL SOSL SECURITY ENFORCED USAGE
result path 7:

Similarity Id: -101644074

Object: querycurrent in file: classes/DataSeedingService.cls

```
L 556: return ExternalOrgQueryService.queryCurrent(soql);
```

Object: query in file: classes/ExternalOrgQueryService.cls

```
L 193: List<SObject> recs = Database.query(cleanSoql, AccessLevel.USER_
```

Apex SOQL SOSL SECURITY ENFORCED USAGE
result path 8:

Similarity Id: -1378804520

Object: querycurrent in file: classes/DataSeedingServicesTestV2.cls

```
L 182: ExternalOrgQueryService.queryCurrent('SELECT Id FROM Account');
```

Object: query in file: classes/ExternalOrgQueryService.cls

```
L 193: List<SObject> recs = Database.query(cleanSoql, AccessLevel.USER_
```

Apex SOQL SOSL SECURITY ENFORCED USAGE
result path 9:

Similarity Id: 1510189664

Object: querycurrent in file: classes/ExternalOrgQueryController.cls

```
L 123: return ExternalOrgQueryService.queryCurrent(soql);
```

Object: query in file: classes/ExternalOrgQueryService.cls

```
L 193: List<SObject> recs = Database.query(cleanSoql, AccessLevel.USER_
```

Apex SOQL SOSL SECURITY ENFORCED USAGE
result path 10:

Similarity Id: -210323188

Object: querycurrent in file: classes/ExternalOrgQueryService.cls

```
L 178: return queryCurrent(soql, null);
```

Object: query in file: classes/ExternalOrgQueryService.cls

```
L 193: List<SObject> recs = Database.query(cleanSoql, AccessLevel.USER_
```

Apex SOQL SOSL SECURITY ENFORCED USAGE
result path 11:

Similarity Id: 759191736

Object: querycurrent in file: classes/ExternalOrgServicesTest.cls

```
L 117: ExternalOrgQueryService.queryCurrent(null, null);
```

Object: query in file: classes/ExternalOrgQueryService.cls

```
L 193: List<SObject> recs = Database.query(cleanSoql, AccessLevel.USER_
```

Query: Apex SOQL SOSL USER MODE MISSING

USER_MODE is recommended for SOQL or SOSL operations

Reference:

https://developer.salesforce.com/docs/atlas.en-us.apexcode.meta/apexcode/apex_classes_enforce_usermode.htm
(https://developer.salesforce.com/docs/atlas.en-us.apexcode.meta/apexcode/apex_classes_enforce_usermode.htm)

Apex SOQL SOSL USER MODE MISSING result path
1:

Similarity Id: 62105350

Object: select in file: classes/UserFieldFilteringTest.cls

```
L 11: List<Profile> profiles = [SELECT Id FROM Profile LIMIT 1];
```

Object: profiles in file: classes/UserFieldFilteringTest.cls

```
L 12: String validProfileId = profiles.isEmpty()
```

Object: profiles in file: classes/UserFieldFilteringTest.cls

```
L 14: : (String) profiles[0].Id;
```

Object: validprofileid in file: classes/UserFieldFilteringTest.cls

```
L 12: String validProfileId = profiles.isEmpty()
```

Object: validprofileid in file: classes/UserFieldFilteringTest.cls

```
L 19: r1.put('ProfileId', validProfileId);
```

Object: r1 in file: classes/UserFieldFilteringTest.cls

```
L 20: r1.put('UserRoleId', '00E000000000001');
```

Object: r1 in file: classes/UserFieldFilteringTest.cls

```
L 21: r1.put('UserLicenseId', '100000000000001'); // Not a real field b
```



Object: r1 in file: classes/UserFieldFilteringTest.cls

```
L 22: records.add(r1);
```

Object: records in file: classes/UserFieldFilteringTest.cls

```
L 32: records
```

Object: records in file: classes/ExternalOrgDmlService.cls

```
L 22: List<Map<String, Object>> records
```

Object: records in file: classes/ExternalOrgDmlService.cls

```
L 29: if (records == null || records.isEmpty()) {
```

Object: records in file: classes/ExternalOrgDmlService.cls

```
L 47: for (Map<String, Object> rec : records) {
```

Object: rec in file: classes/ExternalOrgDmlService.cls

```
L 51: String oldId = (rec.containsKey('Id') && rec.get('Id') != null)
```

Object: rec in file: classes/ExternalOrgDmlService.cls

```
L 52: ? String.valueOf(rec.get('Id'))
```

Object: oldid in file: classes/ExternalOrgDmlService.cls

```
L 51: String oldId = (rec.containsKey('Id') && rec.get('Id') != null)
```

Object: oldId in file: classes/ExternalOrgDmlService.cls

```
L 54: oldIds.add(oldId);
```

Object: oldids in file: classes/ExternalOrgDmlService.cls

```
L 88: m.oldId = i < oldIds.size() ? oldIds[i] : null;
```

Object: m in file: classes/ExternalOrgDmlService.cls

```
L 89: m.name = i < inputNames.size() ? inputNames[i] : null;
```

Object: m in file: classes/ExternalOrgDmlService.cls

```
L 97: m.success = false;
```

Object: m in file: classes/ExternalOrgDmlService.cls

```
L 107: m.errorMessage = 'Unknown DML error';
```

Object: m in file: classes/ExternalOrgDmlService.cls

```
L 110: out.add(m);
```

Object: out in file: classes/ExternalOrgDmlService.cls

```
L 112: return out;
```

Results are provided through a partnership with Checkmarx. Checkmarx, through its suite of Source Code Analysis tools, provides powerful solutions for identifying, tracking, and fixing technical and logical security flaws. Checkmarx is the first and only company to provide Source Code Analysis for the Force.com platform. For Sales inquiries and pricing information please visit:
<https://www.checkmarx.com/salesforce/> (<https://www.checkmarx.com/salesforce/>)
Additional details and other supported languages can be found on the Checkmarx website - <https://www.checkmarx.com> (<https://www.checkmarx.com>)