

# What's in the database?

EXPLORATORY DATA ANALYSIS IN SQL




**Christina Maimone**  
Data Scientist

# PostgreSQL



















PostgreSQL

# Database client














evanston311	
id	int
priority	varchar(6)
source	varchar(20)
category	varchar(64)
date_created	timestamptz
date_completed	timestamptz
street	varchar(48)
house_num	varchar(12)
zip	char(5)
description	varchar


















fortune500	
 <b>title</b>	varchar
 <b>rank</b>	int
 <b>name</b>	varchar
 <b>ticker</b>	char(5)
 <b>url</b>	varchar
 <b>hq</b>	varchar
 <b>sector</b>	varchar
 <b>industry</b>	varchar
 <b>employees</b>	int
 <b>revenues</b>	int
 <b>revenues_change</b>	real
 <b>profits</b>	numeric
 <b>profits_change</b>	real
 <b>assets</b>	numeric
 <b>equity</b>	numeric

Stack Overflow data was provided by Thinknum <https://www.thinknum.com>


evanston311	
 id	int
 priority	varchar(6)
 source	varchar(20)
 category	varchar(64)
 date_created	timestamptz
 date_completed	timestamptz
 street	varchar(48)
 house_num	varchar(12)
 zip	char(5)
 description	varchar



fortune500	
 title	varchar
 rank	int
 name	varchar
 ticker	char(5)
 url	varchar
 hq	varchar
 sector	varchar
 industry	varchar
 employees	int
 revenues	int
 revenues_change	real
 profits	numeric
 profits_change	real
 assets	numeric
 equity	numeric

Stack Overflow data was provided by Thinknum <https://www.thinknum.com>


evanston311	
id	int
priority	varchar(6)
source	varchar(20)
category	varchar(64)
date_created	timestampz
date_completed	timestampz
street	varchar(48)
house_num	varchar(12)
zip	char(5)
description	varchar



fortune500	
title	varchar
rank	int
name	varchar
ticker	char(5)
url	varchar
hq	varchar
sector	varchar
industry	varchar
employees	int
revenues	int
revenues_change	real
profits	numeric
profits_change	real
assets	numeric
equity	numeric


Stack Overflow data was provided by Thinknum <https://www.thinknum.com>

evanston311	
<b>id</b>	int
<b>priority</b>	varchar(6)
<b>source</b>	varchar(20)
<b>category</b>	varchar(64)
<b>date_created</b>	timestampz
<b>date_completed</b>	timestampz
<b>street</b>	varchar(48)
<b>house_num</b>	varchar(12)
<b>zip</b>	char(5)
<b>description</b>	varchar



Stack Overflow data was provided by Thinknum <https://www.thinknum.com>

evanston311	
<b>id</b>	int
<b>priority</b>	varchar(6)
<b>source</b>	varchar(20)
<b>category</b>	varchar(64)
<b>date_created</b>	timestampz
<b>date_completed</b>	timestampz
<b>street</b>	varchar(48)
<b>house_num</b>	varchar(12)
<b>zip</b>	char(5)
<b>description</b>	varchar



fortune500	
<b>title</b>	varchar
<b>rank</b>	int
<b>name</b>	varchar
<b>ticker</b>	char(5)
<b>url</b>	varchar
<b>hq</b>	varchar
<b>sector</b>	varchar
<b>industry</b>	varchar
<b>employees</b>	int
<b>revenues</b>	int
<b>revenues_change</b>	real
<b>profits</b>	numeric
<b>profits_change</b>	real
<b>assets</b>	numeric
<b>equity</b>	numeric

stackoverflow	
<b>id</b>	int
<b>tag</b>	varchar(30)
<b>date</b>	date
<b>question_count</b>	int
<b>question_pct</b>	double precision
<b>unanswered_count</b>	int
<b>unanswered_pct</b>	double precision

tag_type	
<b>id</b>	int
<b>tag</b>	varchar(30)
<b>type</b>	varchar(30)

Stack Overflow data was provided by Thinknum <https://www.thinknum.com>



# Select a few rows

```
SELECT *  
  FROM company  
LIMIT 5;
```

```
id | exchange | ticker | name | parent_id  
--+-+-----+-----+-----+-----  
1 | nasdaq   | PYPL   | PayPal Holdings, Inc. |  
2 | nasdaq   | AMZN   | Amazon.com, Inc. |  
3 | nasdaq   | MSFT   | Microsoft Corporation |  
4 | nasdaq   | MDB     | MongoDB Inc. |  
5 | nasdaq   | DBX     | Dropbox, Inc. |  
(5 rows)
```

# A few reminders

Code	Note
<code>NULL</code>	missing

# A few reminders

Code	Note
<code>NULL</code>	missing
<code>IS NULL</code> , <code>IS NOT NULL</code>	don't use <code>= NULL</code>

# A few reminders

Code	Note
<code>NULL</code>	missing
<code>IS NULL</code> , <code>IS NOT NULL</code>	don't use <code>= NULL</code>
<code>count(*)</code>	number of rows

# A few reminders

Code	Note
<code>NULL</code>	missing
<code>IS NULL</code> , <code>IS NOT NULL</code>	don't use <code>= NULL</code>
<code>count(*)</code>	number of rows
<code>count(column_name)</code>	number of non- <code>NULL</code> values

# A few reminders

Code	Note
<code>NULL</code>	missing
<code>IS NULL</code> , <code>IS NOT NULL</code>	don't use <code>= NULL</code>
<code>count(*)</code>	number of rows
<code>count(column_name)</code>	number of non- <code>NULL</code> values
<code>count(DISTINCT column_name)</code>	number of different non- <code>NULL</code> values

# A few reminders

Code	Note
<code>NULL</code>	missing
<code>IS NULL</code> , <code>IS NOT NULL</code>	don't use <code>= NULL</code>
<code>count(*)</code>	number of rows
<code>count(column_name)</code>	number of non- <code>NULL</code> values
<code>count(DISTINCT column_name)</code>	number of different non- <code>NULL</code> values
<code>SELECT DISTINCT column_name ...</code>	distinct values, including <code>NULL</code>

# Let's start exploring

EXPLORATORY DATA ANALYSIS IN SQL




# The keys to the database

EXPLORATORY DATA ANALYSIS IN SQL













**Christina Maimone**  
Data Scientist


# Foreign keys













# Foreign keys


- Reference another row
  - In a different table or the same table
  - Via a unique ID
    - >> Primary key column containing unique, non-NULL values
- Values restricted to values in referenced column OR NULL
















evanston311	
 id	int
 priority	varchar(6)
 source	varchar(20)
 category	varchar(64)
 date_created	timestamptz
 date_completed	timestamptz
 street	varchar(48)
 house_num	varchar(12)
 zip	char(5)
 description	varchar



Stack Overflow data was provided by Thinknum <https://www.thinknum.com>


evanston311	
 id	int
 priority	varchar(6)
 source	varchar(20)
 category	varchar(64)
 date_created	timestamptz
 date_completed	timestamptz
 street	varchar(48)
 house_num	varchar(12)
 zip	char(5)
 description	varchar



fortune500	
 <b>title</b>	varchar
 <b>rank</b>	int
 <b>name</b>	varchar
 <b>ticker</b>	char(5)
 <b>url</b>	varchar
 <b>hq</b>	varchar
 <b>sector</b>	varchar
 <b>industry</b>	varchar
 <b>employees</b>	int
 <b>revenues</b>	int
 <b>revenues_change</b>	real
 <b>profits</b>	numeric
 <b>profits_change</b>	real
 <b>assets</b>	numeric
 <b>equity</b>	numeric











Stack Overflow data was provided by Thinknum <https://www.thinknum.com>


evanston311	
<b>id</b>	int
<b>priority</b>	varchar(6)
<b>source</b>	varchar(20)
<b>category</b>	varchar(64)
<b>date_created</b>	timestampz
<b>date_completed</b>	timestampz
<b>street</b>	varchar(48)
<b>house_num</b>	varchar(12)
<b>zip</b>	char(5)
<b>description</b>	varchar



fortune500	
<b>title</b>	varchar
<b>rank</b>	int
<b>name</b>	varchar
<b>ticker</b>	char(5)
<b>url</b>	varchar
<b>hq</b>	varchar
<b>sector</b>	varchar
<b>industry</b>	varchar
<b>employees</b>	int
<b>revenues</b>	int
<b>revenues_change</b>	real
<b>profits</b>	numeric
<b>profits_change</b>	real
<b>assets</b>	numeric
<b>equity</b>	numeric


Stack Overflow data was provided by Thinknum <https://www.thinknum.com>

evanston311	
 id	int
 priority	varchar(6)
 source	varchar(20)
 category	varchar(64)
 date_created	timestamptz
 date_completed	timestamptz
 street	varchar(48)
 house_num	varchar(12)
 zip	char(5)
 description	varchar



Stack Overflow data was provided by Thinknum <https://www.thinknum.com>





Stack Overflow data was provided by Thinknum <https://www.thinknum.com>



# Coalesce function

```
coalesce(value_1, value_2 [, ...])
```

- Operates row by row
- Returns first non-NULL value

# Coalesce function

```
SELECT *  
FROM prices;
```

column_1	column_2
	10
22	
3	4

```
SELECT coalesce(column_1, column_2)  
FROM prices;
```

coalesce
10
22
3

# Time to keep exploring!

EXPLORATORY DATA ANALYSIS IN SQL

# Column Types and Constraints

EXPLORATORY DATA ANALYSIS IN SQL



**Christina Maimone**  
Data Scientist

# Column constraints

- **Foreign key:** value that exists in the referenced column, or NULL
- **Primary key:** unique, not NULL
- **Unique:** values must all be different except for NULL
- **Not null:** NULL not allowed: must have a value
- **Check constraints:** conditions on the values
  - `column1 > 0`
  - `columnA > columnB`

# Data types

## Common

- Numeric
- Character
- Date/Time
- Boolean

## Special
















- Arrays
- Monetary
- Binary
- Geometric
- Network Address
- XML
- JSON
- and more!









# Numeric types: PostgreSQL documentation

**Table 8-2. Numeric Types**

Name	Storage Size	Description	Range
<code>smallint</code>	2 bytes	small-range integer	-32768 to +32767
<code>integer</code>	4 bytes	typical choice for integer	-2147483648 to +2147483647
<code>bigint</code>	8 bytes	large-range integer	-9223372036854775808 to +9223372036854775807
<code>decimal</code>	variable	user-specified precision, exact	up to 131072 digits before the decimal point; up to 16383 digits after the decimal point
<code>numeric</code>	variable	user-specified precision, exact	up to 131072 digits before the decimal point; up to 16383 digits after the decimal point
<code>real</code>	4 bytes	variable-precision, inexact	6 decimal digits precision
<code>double precision</code>	8 bytes	variable-precision, inexact	15 decimal digits precision
<code>smallserial</code>	2 bytes	small autoincrementing integer	1 to 32767
<code>serial</code>	4 bytes	autoincrementing integer	1 to 2147483647
<code>bigserial</code>	8 bytes	large autoincrementing integer	1 to 9223372036854775807

# Types in entity relationship diagrams

fortune500	
 <b>title</b>	varchar
 <b>rank</b>	int
 <b>name</b>	varchar
 <b>ticker</b>	char(5)
 <b>url</b>	varchar
 <b>hq</b>	varchar
 <b>sector</b>	varchar
 <b>industry</b>	varchar
 <b>employees</b>	int
 <b>revenues</b>	int
 <b>revenues_change</b>	real
 <b>profits</b>	numeric
 <b>profits_change</b>	real
 <b>assets</b>	numeric
 <b>equity</b>	numeric





# Casting with CAST()

## Format

```
-- With the CAST function  
SELECT CAST (value AS new_type);
```

## Examples

```
-- Cast 3.7 as an integer  
SELECT CAST (3.7 AS integer);
```

```
4
```

```
-- Cast a column called total as an integer  
SELECT CAST (total AS integer)  
FROM prices;
```

# Casting with ::

## Format

```
-- With :: notation  
SELECT value::new_type;
```

## Examples

```
-- Cast 3.7 as an integer  
SELECT 3.7::integer;
```

```
-- Cast a column called total as an integer  
SELECT total::integer  
FROM prices;
```

# Time to practice!

EXPLORATORY DATA ANALYSIS IN SQL