



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Experiment No.5
Implement Bi-Gram model for the given Text input
Date of Performance:
Date of Submission:



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Aim: Implement Bi-Gram model for the given Text input

Objective: To study and implement N-gram Language Model.

Theory:

A language model supports predicting the completion of a sentence.

Eg:

- Please turn off your cell _____
- Your program does not _____

Predictive text input systems can guess what you are typing and give choices on how to complete it.

N-gram Models:

Estimate probability of each word given prior context.

$P(\text{phone} \mid \text{Please turn off your cell})$

- Number of parameters required grows exponentially with the number of words of prior context.
- An N-gram model uses only $N-1$ words of prior context.
 - Unigram: $P(\text{phone})$
 - Bigram: $P(\text{phone} \mid \text{cell})$
 - Trigram: $P(\text{phone} \mid \text{your cell})$
- The Markov assumption is the presumption that the future behavior of a dynamical system only depends on its recent history. In particular, in a k th-order Markov model, the next state only depends on the k most recent states, therefore an N-gram model is a $(N-1)$ -order Markov model.

N-grams: a contiguous sequence of n tokens from a given piece of text



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Mary was scared because of the terrifying noise. ...

Fig. Example of Trigrams in a sentence



04_DikshantBuwa_Exp4_NLP.ipynb - Colaboratory

```
import nltk, re, pprint, string
from nltk import word_tokenize, sent_tokenize
string.punctuation = string.punctuation + '~'+'''+'.+'''+'''+_-'
string.punctuation = string.punctuation.replace('.', '')
file = open('./dataset.txt', encoding='utf8').read()


file_nl_removed = ""
for line in file:
    line_nl_removed = line.replace("\n", " ")
    file_nl_removed += line_nl_removed
file_p = "".join([char for char in file_nl_removed if char not in string.punctuation])

nltk.download('punkt')
sents = nltk.sent_tokenize(file_p)
print("The number of sentences is", len(sents))

words = nltk.word_tokenize(file_p)
print("The number of tokens is", len(words))

average_tokens = round(len(words)/len(sents))
print("The average number of tokens per sentence is",
      average_tokens)

unique_tokens = set(words)
print("The number of unique tokens are", len(unique_tokens))
```

 [nltk_data] Downloading package punkt to /root/nltk_data...
[nltk_data] Unzipping tokenizers/punkt.zip.
The number of sentences is 981
The number of tokens is 27361
The average number of tokens per sentence is 28
The number of unique tokens are 3039

```
nltk.download('stopwords')
from nltk.util import ngrams
from nltk.corpus import stopwords
stop_words = set(stopwords.words('english'))

[nltk_data] Downloading package stopwords to /root/nltk_data...
[nltk_data] Unzipping corpora/stopwords.zip.
```

```
unigram=[]
bigram=[]
trigram=[]
fourgram=[]
tokenized_text = []

for sentence in sents:
    sentence = sentence.lower()
    sequence = word_tokenize(sentence)
    for word in sequence:
        if (word == '.'):
            sequence.remove(word)
        else:
            unigram.append(word)
            tokenized_text.append(sequence)
            bigram.extend(list(ngrams(sequence, 2)))
            trigram.extend(list(ngrams(sequence, 3)))
            fourgram.extend(list(ngrams(sequence, 4)))

#removes ngrams containing only stopwords
def remove1(x):
    y = []
    for pair in x:
        count = 0
        for word in pair:
            if word in stop_words:
                count = count or 0
            else:
                count = count or 1
        if (count==1):
            y.append(pair)
    return(y)
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

10/11/23, 3:27 PM

04_DikshantBuwa_Exp4_NLP.ipynb - Colaboratory

```
bigram = removal(bigram)
trigram = removal(trigram)
fourgram = removal(fourgram)
freq_bi = nltk.FreqDist(bigram)
freq_tri = nltk.FreqDist(trigram)
freq_four = nltk.FreqDist(fourgram)
print("Most common n-grams without stopword removal and without add-1 smoothing: \n")
print("Most common bigrams: ", freq_bi.most_common(5))
print("\nMost common trigrams: ", freq_tri.most_common(5))
print("\nMost common fourgrams: ", freq_four.most_common(5))

Most common n-grams without stopword removal and without add-1 smoothing:

Most common bigrams: [(['said', 'the'], 209), (['said', 'alice'], 115), (['the', 'queen'], 65), (['the', 'king'], 60), (['a', 'lit

Most common trigrams: [(['the', 'mock', 'turtle'], 51), (['the', 'march', 'here'], 30), (['said', 'the', 'king'], 29), (['the', 'w

Most common fourgrams: [(['said', 'the', 'mock', 'turtle'], 19), (['she', 'said', 'to', 'herself'], 16), (['a', 'minute', 'on', 't

<

from nltk.corpus import stopwords
stop_words = set(stopwords.words('english'))

print("Most common n-grams with stopword removal and without add-1 smoothing: \n")
unigram_sw_removed = [p for p in unigram if p not in stop_words]
fdist = nltk.FreqDist(unigram_sw_removed)
print("Most common unigrams: ", fdist.most_common(10))
bigram_sw_removed = []
bigram_sw_removed.extend(list(ngrams(unigram_sw_removed, 2)))
fdist = nltk.FreqDist(bigram_sw_removed)
print("\nMost common bigrams: ", fdist.most_common(10))

Most common n-grams with stopword removal and without add-1 smoothing:

Most common unigrams: [(['said', 462), (['alice', 385), (['little', 128), (['one', 101), (['like', 85), (['know', 85), (['would', 83), (['

Most common bigrams: [(['said', 'alice'], 122), (['mock', 'turtle'], 54), (['march', 'here'], 31), (['said', 'king'], 29), (['thou

<

ngrams_all = {1:[], 2:[], 3:[], 4:[]}
for i in range(4):
    for each in tokenized_text:
        for j in ngrams(each, i+1):
            ngrams_all[i+1].append(j)
ngrams_voc = {1:set([]), 2:set([]), 3:set([]), 4:set([])}
for i in range(4):
    for gram in ngrams_all[i+1]:
        if gram not in ngrams_voc[i+1]:
            ngrams_voc[i+1].add(gram)
total_ngrams = {1:-1, 2:-1, 3:-1, 4:-1}
total_voc = {1:-1, 2:-1, 3:-1, 4:-1}
for i in range(4):
    total_ngrams[i+1] = len(ngrams_all[i+1])
    total_voc[i+1] = len(ngrams_voc[i+1])

ngrams_prob = {1:[], 2:[], 3:[], 4:[]}
for i in range(4):
    for ngram in ngrams_voc[i+1]:
        tlist = [ngram]
        tlist.append(ngrams_all[i+1].count(ngram))
        ngrams_prob[i+1].append(tlist)

for i in range(4):
    for ngram in ngrams_prob[i+1]:
        ngram[-1] = (ngram[-1]+1)/(total_ngrams[i+1]+total_voc[i+1])

print("Most common n-grams without stopword removal and with add-1 smoothing: \n")
for i in range(4):
    ngrams_prob[i+1] = sorted(ngrams_prob[i+1], key = lambda x:x[1], reverse = True)

print("Most common unigrams: ", str(ngrams_prob[1][:10]))
print("\nMost common bigrams: ", str(ngrams_prob[2][:10]))
print("\nMost common trigrams: ", str(ngrams_prob[3][:10]))
print("\nMost common fourgrams: ", str(ngrams_prob[4][:10]))

Most common n-grams without stopword removal and with add-1 smoothing:

Most common unigrams: [(['the'], 0.05590462224968249), (['and'], 0.02900490852298081), (['to'], 0.02478289225277177), (['a'], 0.02478289225277177), (['the'], 0.02478289225277177), (['of'], 0.02478289225277177), (['in'], 0.02478289225277177), (['on'], 0.02478289225277177), (['at'], 0.02478289225277177), (['by'], 0.02478289225277177)

Most common bigrams: [(['said', 'the'], 0.0053395713087035016), (['of', 'the'], 0.0033308754354293268), (['said', 'alice'], 0.0029
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

10/11/23, 3:27 PM

04_DikshantBuwa_Exp4_NLP.ipynb - Colaboratory

```
Most common trigrams: [[('the', 'mock', 'turtle'), 0.001143837575064341], [('the', 'march', 'hare'), 0.0006819031697498955], [('sa  
Most common fourgrams: [[('said', 'the', 'mock', 'turtle'), 0.00043521782652217433], [('she', 'said', 'to', 'herself'), 0.00036993  
  
str1 = 'after that alice said the'  
str2 = 'alice felt so desperate that she was'  
  
token_1 = word_tokenize(str1)  
token_2 = word_tokenize(str2)  
ngram_1 = {1:[], 2:[], 3:[]} #to store the n-grams formed  
ngram_2 = {1:[], 2:[], 3:[]}  
for i in range(3):  
    ngram_1[i+1] = list(ngrams(token_1, i+1))[-1]  
    ngram_2[i+1] = list(ngrams(token_2, i+1))[-1]  
print("String 1: ", ngram_1, "\nString 2: ", ngram_2)  
  
String 1: {1: ('the',), 2: ('said', 'the'), 3: ('alice', 'said', 'the')}  
String 2: {1: ('was',), 2: ('she', 'was'), 3: ('that', 'she', 'was')}  
  
for i in range(4):  
    ngrams_prob[i+1] = sorted(ngrams_prob[i+1], key = lambda x:x[1], reverse = True)  
  
pred_1 = {1:[], 2:[], 3:[]}  
for i in range(3):  
    count = 0  
    for each in ngrams_prob[i+2]:  
        if each[0][-1] == ngram_1[i+1]:  
            #to find predictions based on highest probability of n-grams  
  
            count +=1  
            pred_1[i+1].append(each[0][-1])  
            if count ==5:  
                break  
    if count<5:  
        while(count!=5):  
            pred_1[i+1].append("NOT FOUND")  
#if no word prediction is found, replace with NOT FOUND  
count +=1  
for i in range(4):  
    ngrams_prob[i+1] = sorted(ngrams_prob[i+1], key = lambda x:x[1], reverse = True)  
  
pred_2 = {1:[], 2:[], 3:[]}  
for i in range(3):  
    count = 0  
    for each in ngrams_prob[i+2]:  
        if each[0][-1] == ngram_2[i+1]:  
            count +=1  
            pred_2[i+1].append(each[0][-1])  
            if count ==5:  
                break  
    if count<5:  
        while(count!=5):  
            pred_2[i+1].append("")  
            count +=1  
  
the probability models of bigrams, trigrams, and fourgrams\n")  
  
predictions: {} \nFourgram model predictions: {} \n".format(pred_1[1], pred_1[2], pred_1[3]))  
was-\n")  
predictions: {} \nFourgram model predictions: {} \n".format(pred_2[1], pred_2[2], pred_2[3]))  
  
Next word predictions for the strings using the probability models of bigrams, trigrams, and fourgrams  
  
String 1 - after that alice said the-  
  
Bigram model predictions: ['queen', 'king', 'gryphon', 'mock', 'hatter']  
Trigram model predictions: ['king', 'hatter', 'mock', 'caterpillar', 'gryphon']  
Fourgram model predictions: ['NOT FOUND', 'NOT FOUND', 'NOT FOUND', 'NOT FOUND', 'NOT FOUND']  
  
String 2 - alice felt so desperate that she was-  
  
Bigram model predictions: ['a', 'the', 'not', 'that', 'going']  
Trigram model predictions: ['now', 'quite', 'a', 'walking', 'beginning']  
Fourgram model predictions: ['now', 'ready', 'walking', 'losing', 'in']
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Conclusion:

The N-gram language model is a simple and widely used approach for natural language processing tasks, such as text generation and speech recognition. It operates by analyzing the statistical relationships between words in a given text, with "N" representing the number of preceding words considered for prediction. While N-gram models are easy to implement and computationally efficient, they have limitations in capturing long-range dependencies and understanding context. As a result, they may struggle with handling more complex language tasks compared to more advanced models like recurrent neural networks or transformer-based models. In conclusion, N-gram language models are a valuable tool for certain applications but may fall short in tasks that require a deeper understanding of language and context.