




Untitled2.ipynb ☆ ☁
Edit View Insert Runtime Tools Help
Cells + Code + Text ▶ Run all

Files
↑ ↻ 📁 🔍
..
intel_dataset
sample_data
intel-image-classification.zip

Best Model: MobileNetV2
Best Accuracy: 77.9 %

```
[71] ✓ 3m ▶ !pip install tensorflow matplotlib pandas

import tensorflow as tf
import numpy as np
import matplotlib.pyplot as plt
from tensorflow.keras import layers, models
from tensorflow.keras.applications import MobileNetV2, ResNet50, EfficientNetB0
import gc

print("TensorFlow Version:", tf.__version__)
print("GPU Available:", tf.config.list_physical_devices('GPU'))

# =====
# LOAD AND FILTER CIFAR-10 FOR ANIMALS ONLY
# =====

(X_train_full, y_train_full), (X_test_full, y_test_full) = tf.keras.datasets.cifar10.load_data()

# CIFAR-10 Original Labels:
# 0: airplane, 1: automobile, 2: bird, 3: cat, 4: deer, 5: dog, 6: frog, 7: horse, 8: ship, 9: truck
# Keeping only animal indices: 2, 3, 4, 5, 6, 7
ANIMAL_INDICES = [2, 3, 4, 5, 6, 7]
class_names = ['Bird', 'Cat', 'Deer', 'Dog', 'Frog', 'Horse']

# Map old labels to new sequential labels (0 to 5)
label_mapping = {old_idx: new_idx for new_idx, old_idx in enumerate(ANIMAL_INDICES)}

def filter_animals(X, y):
    # Get mask of elements that match our animal indices
    mask = np.isin(y, ANIMAL_INDICES).flatten()
    X_filtered = X[mask]
    y_filtered = y[mask].flatten()

    # Remap labels to be 0, 1, 2, 3, 4, 5
    y_remapped = np.array([label_mapping[old_idx] for old_idx in y_filtered])
    return X_filtered, y_remapped

X_train_animals, y_train_animals = filter_animals(X_train_full, y_train_full)
```

How can I install Python libraries?

Load data from Google Drive

Show an example of training

What can I help you build?

Gemini 2.5 Flash ▶

Disk 64.35 GB available

ables Terminal

Search

11:31 AM T4 (Python 3)

ENG IN 11:35 04-06-2026