

ex43

-----

<!-- password field ==> used fore accepting data from user with hidden format  
use case => password, opt,  
passcode, card pin, cvv etc...

==> by using input we can create  
Syn:- <input type="password" ... />

==> dot symbol or \* symbol

==> eye symbol not sup browsers

except edge browser

-->

<!-- example on "input" tag -->

<!DOCTYPE html>

<html lang="en">

<head>

<title>Ex43</title>

<link rel="icon" href="logo1.png"/>

</head>

<body>

<h3>demo on password fields

<label>enter password</label>

<input type="password" id="pwd" name="pwd"/>

<br>

<label>enter cvv</label>

<input type="password" id="cv" name="cv" maxlength="3"/>

</body>

</html>

ex44

-----

<!--

number field ==> used to type numeric values only

==> 0 to 9

e

use case => phone, pincode, age,

height, ....

Syn:- <input type="number" ... />

-->

<!-- example on "input" tag -->

<!DOCTYPE html>

<html lang="en">

<head>

<title>Ex44</title>

<link rel="icon" href="logo1.png"/>

</head>

<body>

<h3>demo on number fields</h3>

<input type="number" id="n1" name="n1"/>

<br>

<input type="number" id="n2" name="n2" min="1" max="100"/>

<br>

<input type="number" id="n3" name="n3" min="0" max="300" step="10"/>

</body>

</html>

ex45

-----

<!--

hidden field ==> an invisble text field with init value

==> used to perform session mang/session

tracking

==> every hidden should have name & value

attributes

Syn:- <input type="hidden" ... />

Note: while submitting with regular data, hidden fields also sending to server  
-->

```
<!-- example on "input" tag -->
<!DOCTYPE html>
<html lang="en">
  <head>
    <title>Ex45</title>
    <link rel="icon" href="logo1.png"/>
  </head>
  <body>
    <h3>demo on hidden fields</h3>
    <input type="hidden" name="hf1" value="true"/>
    <input type="hidden" name="hf2" value="1"/>
  </body>
</html>
```

ex46

```
-----
<!--
  buttons ==> reset, submit, image
reset button ==> this button used to clear input fields (values)
                  ==> cases filter, application forms
                  ==> input fields (which we want to clear) &
reset button should with in the same "form" tag
                  Syn:-      <input type="reset" .../>
```

Note: reset button details are not sending to server

```
-->
<!-- example on "input" tag -->
<!DOCTYPE html>
<html lang="en">
  <head>
    <title>Ex46</title>
    <link rel="icon" href="logo1.png"/>
  </head>
  <body>
    <h3>demo on reset button </h3>
    <form>
      <input type="text"/> <br>
      <input type="number"/> <br>
      <input type="password"/> <br>
      <input type="reset" value="Clear All"/>
    </form>
    <input type="text"/> <!-- its not cleared -->
  </body>
</html>
```