

DOTA2024:8

Defense of the Ancients

Eighth topic - Infrastructure

Hugh Anderson

National University of Singapore
School of Computing

July, 2024



OPINIONS ON INTERNET PRIVACY

THE PHILOSOPHER:

"PRIVACY" IS AN IMPRACTICAL WAY TO THINK ABOUT DATA IN A DIGITAL WORLD SO UNLIKE THE ONE IN WHICH OUR SOCI-

SO BORED.



THE CRYPTO NUT:

MY DATA IS SAFE BEHIND SIX LAYERS OF SYMMETRIC AND PUBLIC-KEY ALGORITHMS.

WHAT DATA IS IT?

MOSTLY ME EMAILING WITH PEOPLE ABOUT CRYPTOGRAPHY.



THE CONSPIRACIST:

THESE LEAKS ARE JUST THE TIP OF THE ICEBERG. THERE'S A WAREHOUSE IN UTAH WHERE THE NSA HAS THE ENTIRE ICEBERG.

I DON'T KNOW HOW THEY GOT IT THERE.



THE NIHILIST:

JOKES ON THEM, GATHERING ALL THIS DATA ON ME AS IF ANYTHING I DO MEANS ANYTHING.



THE EXHIBITIONIST:

MMMM? I SURE HOPE THE NSA ISN'T WATCHING ME BITE INTO THESE JUICY STRAWBERRIES!!

OOPS I DRIPPED SOME ON MY SHIRT! BETTER TAKE IT OFF. GOOGLE, ARE YOU THERE? GOOGLE, THIS LOTION FEELS SOOOO GOOD.



THE SAGE:

I DON'T KNOW OR CARE WHAT DATA *ANYONE* HAS ABOUT ME.

DATA IS IMAGINARY. THIS BURRITO IS REAL.



Outline

1 Authentication, logging in...

- Banking systems, Public key infrastructure
- Authentication without passing passwords

2 Other infrastructural building blocks

- Voting, coin flipping, oblivious transfer
- Hardware ... IoT, DVD, DNS...

Case study 1: SWIFT

SWIFT is for sending money from bank to bank...

Society for Worldwide International Financial Telecommunications.

It was set up a long time ago (before PK and before PKI). The system had an unusual set of constraints. Banks did not trust the system (i.e. they did not want dishonest SWIFT people to steal from them), and authenticity was independent of confidentiality because some countries forbade cryptography (!)

Systems also had to enforce non-repudiation, and had to support the control of transactions under some policy or other (two-controls, balancing of books).

Now it is used over e-mail...

Case study 1: SWIFT

SWIFT mechanisms

- **Authentication:** Messages have a MAC (Message Authentication Code - a keyed hash function) attached. Banks would exchange Keys for the MAC in face-to-face meetings, or via third channels (certainly not via SWIFT). As a result SWIFT took no part in authentication.
- **Non-repudiation:** Countries log messages at a regional processing centre (RGP), before sending on to SWIFT. RGPs are more or less independent.
- **Confidentiality:** Used proprietary encryption devices, keys were hand-carried for distribution.
- **Dual controls:** Roles were separated - one clerk entered data, another checked and transmitted it.

Case study 1: SWIFT

We saw this before... What has gone wrong?

For 20 years it ran well without any external fraud. Since 1996 SWIFT has used PK cryptography (so it may suffer from PK flaws or attacks).

Most frauds have an insider bypassing a dual control somehow. Stanley Rifkin, bank computer consultant, got hold of an authorization code, and used this over a telephone to authorize the purchase of \$10M worth of diamonds.

In February 2016, attackers tried to steal US\$951 Million from Bangladesh Bank, the central bank of Bangladesh, using the SWIFT network. Five transactions worth \$101 million were withdrawn from a Bangladesh Bank account at the Federal Reserve Bank of New York, with \$20M traced to Sri Lanka (since recovered) and \$81M to the Philippines.

2016 Bangladesh Bank heist

From Wikipedia, the free encyclopedia



It has been suggested that *Nasir Hossain Zohir* be merged into this article. [[Discuss](#)] ([Proposed since June 2016](#))

In February 2016, instructions to steal US\$951 Million from Bangladesh Bank, the central bank of Bangladesh, were issued via the SWIFT network. Five transactions issued by hackers, worth \$101 million and withdrawn from a Bangladesh Bank account at the Federal Reserve Bank of New York, succeeded, with \$20M traced to Sri Lanka (since recovered) and \$81M to the Philippines. The Federal Reserve Bank of NY blocked the remaining 36 transactions, amounting to \$850 million, at the request of Bangladesh Bank.^[1]




The Federal Reserve Bank of New York

Contents [hide]

- 1 Background
- 2 Events
 - 2.1 Attempted fund diversion to Sri Lanka
 - 2.2 Funds diverted to the Philippines
- 3 Investigations
 - 3.1 Bangladesh
 - 3.2 Philippines

Reminder: Man-in-the-middle for Public Keys

Motivation for PKI:



Reminder: Man-in-the-middle for Public Keys

Motivation for PKI:

How to ensure that keys belong to Bob?

*Need some **trusted authority/heirarchy** to certify that keys are OK.*

How to **trust** the Authority?

*Authority's **public credentials** are already resident on your machine*

What does the Authority do?

It digitally signs a certificate using the CA's private key. The certificate binds a public key and the identity of the user together.

Authorities: No single heirarchy:

Anyone or thing that you consider acceptable could **sign** a certificate.

For money and **commercial** interests, we want a bit more **trust**:

*There are many **certifying authorities** - Verisign, Entrust and so on.
Your browser comes pre-loaded with their public keys.*

Case study 2: PKI

Summary:

The overall mechanism provides **certificates** that contain **public keys, bound to identities** (web sites for example). Certifying authorities provide some **level of trust**, providing certificates.

How is it used? ... In **SSL** for example

Main points...

- We have to trust (certifying) authorities.
- We may not know WHO our computer trusts.
- Bad certificates originally had no way of being discarded. Even now the work-around is awkward.


Case study 3: WeakDH

June 2013: Snowden releases NSA documents...

... and in them we discover that [NSA](#) has been [routinely listening](#) in on skype calls, and intercepting IPsec and https:// conversations.

My colleague Martin suggests that, in this day and age, most people couldn't care less. Maybe he is right. But in any case, [how can it be done?](#)

October 2015: Plausible explanation... <https://weakdh.org/>



You can test your server using the tool below, or by using the [Qualsys SSL Server Test](#). If you have information on how to patch other software, please [let us know](#).

Server Test

Test A Server

Go

Warning! This site supports export-grade Diffie-Hellman key exchange and is vulnerable to the Logjam attack. You need to disable export cipher suites.


IP	Connected	TLS	Insecure DHE_EXPORT	DHE	Chrome
137.132.1.144	✓	✓	Supported!	1024-bits	1024-bits

Using a Strong DH Group

You will first need to generate a new Diffie-Hellman group, regardless of the server software you use. Modern browsers.

Case study 3: large scale monitoring of IPsec

Architecture of an NSA system from leaked document



Notice the diagram is clearly indicating the IKE (Internet Key Exchange), and the **use of IPsec** - the AH and ESP packets.

There is so much supporting material, that it is clear that this is **not FUD**, but is a **real mechanism**, in use since at least 2009.

It relies on the use of the **fixed large primes** used in **Diffie-Hellman** key exchange software.


Case study 3: large scale monitoring of IPSec

What are the steps?

- During initial setup of the link, **downgrade** the Diffie-Hellman key exchange to one using smaller (**EXPORT-GRADE**) bitsize primes.
- Send IKE (Internet Key Exchange) values to supercomputer, which **returns actual keys** within 15 minutes.
 - October 2015 paper succeeds in 70 seconds: **logjam** - a mitm downgrade to 512 bit primes.

Solved $y = g^x \bmod p$ discrete log problem? ... No.

Common (NFS) algorithm can use **pre-computation**, for a **specific prime**, of 3 out of the 4 steps:




Case study 3: large scale monitoring of IPSec

Solutions? (From the paper)

- **Browser** - check you have the updates which stop *you* being vulnerable
- **Server...**
 - **Disable Export Cipher Suites.** There is little downside in disabling them.
 - **Deploy (Ephemeral) Elliptic-Curve Diffie-Hellman (ECDHE).** No known feasible cryptanalytic attacks
 - **Use a Strong, Diffie Hellman Group.** Use 2048-bit or stronger Diffie-Hellman groups with "safe" primes.

Case study 4: The DNS


A heirarchy, root servers, domains, local...



Forms a tree, and a new request at a leaf has to traverse the tree.
A distributed database, with distributed caching of recent name requests.
Plenty of opportunity to inject in false entries.

Challenge response

Challenge response protocol for password checking...



Challenge-response protocol

When a client wishes to use a resource...

... it requests a connection and **negotiates** the **protocol**.

In the reply to this request the server generates and appends an 8 byte, **random** value - this is stored in the server after the reply is sent and is known as the **challenge** - **different** for every client connection.

The **client** then uses the hashed password (16 byte values described above), appended with 5 null bytes, as three 56 bit DES keys, to encrypt the challenge 8 byte value, forming a 24 byte value known as the **response**. This calculation is done on *both* hashes of the user's password, and *both* responses are returned to the server, giving two 24 byte values.

Challenge-response protocol

The server then...

... reproduces the above calculation, using its own value of the 16 byte hashed password and the challenge value that it kept during the initial protocol negotiation.

It then **checks** to see if the 24 byte value it calculates matches the 24 byte value returned to it from the client. If these **values match** exactly, then the client knew the correct password and is allowed access.

There are good points about this:

- The server never knows or stores the *cleartext* of the users password - just the 16 byte hashed values derived from it.
- The cleartext password or 16 byte hashed values are never transmitted over the network - thus increasing security.

Challenge-response protocol

However, there is also a bad side:

- The 16 byte hashed values are a "password equivalent". You cannot derive the users password from them, but they can be used in a modified client to gain access to a server.
- The initial protocol negotiation is generally insecure, and can be hijacked in a range of ways. One common hijack involves convincing the server to allow clear-text passwords.
- Despite functionality added to NT to protect unauthorized access to the SAM, the mechanism is trivially insecure

Attacks on Windows (NT) systems...

Even *without* network access, it is possible by various means to access the SAM password hashes, and *with* network access it is easy.

The attack considered here is the use of either a dictionary, or brute force attack directly on the password hashes (which must be first collected somehow).

Kerberos/Cerberus



What is it?

Kerberos is a network **authentication** protocol. It provides strong authentication for client/server applications using symmetric or public key cryptography.

Kerberos is freely available in source form, and also is in commercial products (Windows uses Kerberos for login).


Authentication... and encryption.

Client and server use Kerberos to prove their identity, and encrypt all of their communications. There is a Key Distribution Center (KDC)

Kerberos uses a Needham-Schroeder symmetric key protocol.

Kerberos

Sequence of messages for granting tickets



Kerberos

Notation

A key $K_{x,y}$ is a session key shared by both x and y .
When we encrypt a message M using the key $K_{x,y}$ we write it as $E(K_{x,y}, M)$.

Sequence of messages for granting tickets

When a client first authenticates to Kerberos, she:

- 1 Talks to KDC, to get a *Ticket Granting Ticket*.
- 2 Uses that to talk to the *Ticket Granting Service* and get a particular ticket for a particular service.
- 3 Uses that ticket, to interact with the server.

This way a user doesn't have to reenter passwords every time they wish to connect to a Kerberized service.

Note that if the Ticket Granting Ticket is *compromised*, an attacker can only masquerade as a user until the *ticket expires*.

Kerberos protocol

Two sorts of credentials: tickets and authenticators:

A *ticket* $T_{c,s}$ contains the client's *name* and network *address*, the server's name, a *timestamp* and a *session key*, encrypted with the server's secret key (so that the client is unable to modify it).

An *authenticator* $A_{c,s}$ contains the client's *name*, a *timestamp* and an optional *extra session key*, encrypted with the session key shared between the client and the server.

Alice wants session key for communication with Bob:

- 1 Alice sends message to Ted containing her identity, Ted's TGS identity, and one-time value $(n) : \{a, tgs, n\}$.
- 2 Ted responds with a key encrypted with Alice's secret key (which Ted knows), and a ticket encrypted with the TGS secret key:
 $E(K_a, \{K_{a,tgs}, n\}) \ E(K_{tgs}, T_{a,tgs})$.
Alice now has ticket and session key: $E(K_{tgs}, T_{a,tgs}), K_{a,tgs}$
- 3 Alice can prove her identity to the TGS, as she has session key $K_{a,tgs}$, and Ticket Granting Ticket: $E(K_{tgs}, T_{a,tgs})$.

Kerberos protocol

Later, Alice can ask the TGS for a specific service ticket:

- 1 When Alice wants a ticket for a specific service (say with Bob), she sends an *authenticator* along with the *Ticket Granting Ticket* to the TGS: $E(K_{a,tgs}, A_{a,b}) E(K_{tgs}, T_{a,tgs}), b, n$.
- 2 The TGS responds with a suitable key and a ticket: $E(K_{a,tgs}, \{K_{a,b}, n\}) E(K_b, T_{a,b})$.
- 3 Alice can now use an authenticator and ticket directly with Bob: $E(K_{a,b}, A_{a,b}) E(K_b, T_{a,b})$.

Properties of the protocol - weaknesses -

Host security: Kerberos makes no provisions for host security; it assumes that it is running on *trusted* hosts with an *untrusted* network.

KDC compromises: Kerberos uses a principal's password (encryption key) as the fundamental proof of identity.

Salt: This is an additional input to the one-way hash algorithm.

Voting protocols

A voting protocol is one in which...

...independent systems vote in a kind of election..

We may want to put conditions on this. For example, afterwards we might want to check that the vote was correct, or that each voter only got a single vote. Systems should be corruption-proof.

Voting systems are commonly found in computer systems. For example, if we had multiple servers being used for redundancy, then the servers might vote to see who is in charge.

Too-simple voting systems may be subject to attack. For example, a protocol like first-to-the-post may result in always choosing only one server, or even worse, be tricked by a fast-responder. (Consider the DHCP attack in the “Topic5” videos).

Voting protocols

Voting using public key encryption...

If Alice votes v_A , then she broadcasts:

$$R_A(R_B(R_C(E_A(E_B(E_C(v_A)))))))$$

where

- 1 R_A is a random encoding function which adds a random string to a message before encrypting it with A 's public key:

$$R_A(m) \equiv E(K_{A_{\text{pub}}}, m + \text{rand}())$$

- 2 E_A is public key encryption with A 's public key: $E_A(m) \equiv E(K_{A_{\text{pub}}}, m)$.

Each voter then engages in a process of signing and decrypting and rebroadcasting one level of every message/vote.

At the end of the protocol, each voter has a complete signed audit trail and is ensured of the validity of the vote.

First round...

One round...

Who	Receives and removes one level...	and sends on (with sigs)...
Alice:	$R_A^1(R_B^1(R_C^1(E_A^1(E_B^1(E_C^1(v_1))))))$	$\rightarrow R_B^1(R_C^1(E_A^1(E_B^1(E_C^1(v_1)))))$
	$R_A^2(R_B^2(R_C^2(E_A^2(E_B^2(E_C^2(v_2))))))$	$\rightarrow R_B^2(R_C^2(E_A^2(E_B^2(E_C^2(v_2)))))$
	$R_A^3(R_B^3(R_C^3(E_A^3(E_B^3(E_C^3(v_3))))))$	$\rightarrow R_B^3(R_C^3(E_A^3(E_B^3(E_C^3(v_3)))))$
Bob:	$R_B^1(R_C^1(E_A^1(E_B^1(E_C^1(v_1)))))$	$\rightarrow R_C^1(E_A^1(E_B^1(E_C^1(v_1))))$
	$R_B^2(R_C^2(E_A^2(E_B^2(E_C^2(v_2)))))$	$\rightarrow R_C^2(E_A^2(E_B^2(E_C^2(v_2))))$
	$R_B^3(R_C^3(E_A^3(E_B^3(E_C^3(v_3)))))$	$\rightarrow R_C^3(E_A^3(E_B^3(E_C^3(v_3))))$
Charles:	$R_C^1(E_A^1(E_B^1(E_C^1(v_1))))$	$\rightarrow E_A^1(E_B^1(E_C^1(v_1)))$
	$R_C^2(E_A^2(E_B^2(E_C^2(v_2))))$	$\rightarrow E_A^2(E_B^2(E_C^2(v_2)))$
	$R_C^3(E_A^3(E_B^3(E_C^3(v_3))))$	$\rightarrow E_A^3(E_B^3(E_C^3(v_3)))$

In the first round (after 3 transfers) - each voter has agreed that their vote has been counted. If not, they do not continue.

To show agreement, voters sign the votes they forward.

Second round...

Then actually discover the votes...

Who	Receives and removes one level...	and sends on (with sigs)...
Alice:	$E_A^1(E_B^1(E_C^1(v_1)))$	$\rightarrow E_B^1(E_C^1(v_1))$
	$E_A^2(E_B^2(E_C^2(v_2)))$	$\rightarrow E_B^2(E_C^2(v_2))$
	$E_A^3(E_B^3(E_C^3(v_3)))$	$\rightarrow E_B^3(E_C^3(v_3))$
Bob:	$E_B^1(E_C^1(v_1))$	$\rightarrow E_C^1(v_1)$
	$E_B^2(E_C^2(v_2))$	$\rightarrow E_C^2(v_2)$
	$E_B^3(E_C^3(v_3))$	$\rightarrow E_C^3(v_3)$
Charles:	$E_C^1(v_1)$	$\rightarrow v_1$
	$E_C^2(v_2)$	$\rightarrow v_2$
	$E_C^3(v_3)$	$\rightarrow v_3$

Only Alice can remove her level of encryption, but anyone can check that it was done correctly (by re-encrypting).

In the second round, someone can tamper with the vote, but at the end each vote can be re-encrypted, and checked against the set of signatures. The tamperer will be found.

Tossing a coin

Lets pretend we are gambling...

Alice and Bob want to toss a coin, so adopt the following first steps:

- 1 Alice calculates two primes p, q and calculates $N = pq$, sends N to Bob. $N = 35 = 5 * 7$
- 2 If Bob can factorize the number, then Bob wins a coin toss.
- 3 Bob selects random x , and sends $y = x^2 \bmod N$ to Alice.
 $y = 31^2 \bmod 35 = 16$
- 4 Alice calculates the four square roots of 16:

$$\begin{array}{rclclcl} 4^2 \bmod 35 & = & 16 & 31^2 \bmod 35 & = & 16 \\ 24^2 \bmod 35 & = & 16 & 11^2 \bmod 35 & = & 16 \end{array}$$

This is easy for Alice, as she knows the prime factors of N . She then sends one of these back to Bob.

Tossing a coin

So what does Bob do?

If Bob receives x or $-x$, then he learns nothing, but if Bob receives either of the other values:

$$\begin{aligned}\text{GCD}(24 + 31, 35) &= \text{GCD}(55, 35) \\ &= 5\end{aligned}$$

Bob can calculate a factor, and Alice is unable to tell she has divulged the factor.

Note that...

... If you know two different square roots of a number modulo $N = pq$, you can find the factors of N .

Alice can compute square roots knowing p, q ?

Yes. When Alice receives the value $y = x^2 \bmod n$, she calculates $\sqrt{y} \bmod p$ and $\sqrt{y} \bmod q$. She then uses these two values in the Chinese Remainder Theorem to find a root. Using the example in class, $y = 16$, and Alice knows $p = 5$ and $q = 7$. She computes $\sqrt{16} \bmod 5$ and $\sqrt{16} \bmod 7$, noting that $16 = 1 \bmod 5$ and $16 = 2 \bmod 7$:

$$\begin{aligned}\sqrt{1} \bmod 5 &= \pm 1 \\ \sqrt{2} \bmod 7 &= \pm 4\end{aligned}$$

and then CRT helps find x :

$$\begin{aligned}x \bmod 5 &= 1 & \& & x \bmod 7 &= 4 & \implies & x &= 11 \\ x \bmod 5 &= 1 & \& & x \bmod 7 &= -4 & \implies & x &= 31\end{aligned}$$

We have the four square roots of $16 \bmod 35$: ± 11 and ± 31 .

Example of a square root algorithm modulo an odd prime...

If $p \equiv 3 \bmod 4$ then $x = y^{\frac{p+1}{4}} \bmod p$.

For example, if $p = 3851$ and $y = 3298$, then $x = 3298^{\frac{3852}{4}} \bmod 3851 = 231$.

Contract signing and oblivious transfer

Scenario: signing contracts can be difficult:

If one party signs the contract, the other may not. We have one party bound by the contract, and the other not.

In addition, both may sign, and then one may say "*I didn't sign any contract!*" afterwards.

Use oblivious transfer...

In an oblivious transfer, randomness is used to convince participants of the fairness of some transaction

In the coin-tossing example, Alice knows the prime factors of a large number, and if Bob can factorize the number, then Bob wins a coin toss. Alice will either divulge one of the prime factors to Bob, or not, with equal probability. Alice is unable to tell if she has divulged the factor, and so the coin toss is fair.

Alice is "oblivious" - she is unaware if she has revealed a secret.

Contract signing

Use oblivious transfer for contract signing...

Oblivious transfer used for contract-signing where the following points are important:

- Up to a certain point neither party is bound
- After that point both parties are bound
- Either party can prove that the other party signed

Alice and Bob pre-agree on some probability difference that they will live with (say 5%), and then exchange (say 1000) signed oblivious-transfer messages, each possibly transferring a bit of information. They are becoming “more” bound by a contract with ever-increasing probability - perhaps each successfully received bit is worth 1% to the receiver.

What if someone tries to terminate early?

In the event of early termination of the contract, either party can take the messages they have to an adjudicator, who chooses a random probability value (42% say) before looking at the messages.

If messages are over 42% then both parties are bound. If less then both parties are free.


(a): IoT

A well known IoT device...

The **Particle Photon** is a popular IoT development kit that is relatively inexpensive, at US\$19.

STM32F205
120Mhz ARM
Cortex M3
microcontroller

Broadcom
BCM43362
Wi-Fi chip



1MB flash
memory


128KB RAM,
preloaded
with Particle
firmware

Open sourced
hardware and
software

(a): IoT

Single token needed for access...

Users can associate multiple Particle devices to their Particle account. The access token is required to use the Cloud API provided by Particle and it is considered secret and should not be shared.



(a): Accessing the IoT device

The device access is via the “Particle cloud API”

Whenever a user sends an instruction to the photon, the user has to supply a device ID, and the access token. The Particle cloud will authenticate the token and device ID before relaying instructions to the device.

The access token is all-powerful! With the token, you can list out all the device IDs. i.e. you do not need to know the device ID to send instructions. As a result, getting the access token ... gets you the photon!

Acquiring the access token...

Students identified at mechanisms to get an access:


- Social Engineering
 - Man-in-the-middle attacks
-

They were effective mechanisms, and could be used to get the access token for any number of photons, nearby or remote. The students even found access tokens through google!

(a): IoT

Single token needed for access...

An attacker can **build a modified firmware** that **publishes the stored Wi-Fi credentials**. The attacker can then flash the firmware using the Particle Cloud onto the Photon device. Firmware flashing takes only a short while and **does not overwrite the current user application** installed on the device. This allows the attacker to compromise the Photon device **without disrupting its usual functions**.



(a): An attack on IoT and photons

My students engineered this nasty attack

And they are talking to the manufacturers to come up with a resolution. What can be done to mitigate it?

- Limit the access token capabilities.
- Two factor authentication
- Authenticate the clients who initiate software updates...

The firmware steals WiFi credentials for the remote network near the photon. This is obviously pretty serious.

.
BAD STUDENTS!

Poster and papers, responsible disclosure...

IoT Hacking: Attacking the Photon

Ang Kang Seng, Chew Yung Chung, Juliana Seng, Mei Feng, Tan Qiu Hao, Joel

1. Introduction

Internet of Things (IoT) is the convergence of information and communication technologies (ICT) with physical objects, enabling them to be connected to the Internet and exchange data with other devices. This has led to the development of a wide range of IoT applications, from smart homes to industrial automation. However, the rapid growth of IoT has also led to a corresponding increase in security risks. This paper presents a comprehensive survey of IoT security threats and vulnerabilities, and discusses the challenges of securing IoT systems.

2. Photon Platform

The Photon platform is a low-cost, open-source IoT platform based on the Raspberry Pi. It is designed to be easy to use and to support a wide range of IoT applications. This paper describes the architecture of the Photon platform and discusses the security challenges it faces.

3. Attacking the Photon

This section describes the various attacks that can be performed on the Photon platform. These include:

- Denial of Service (DoS):** Attacking the Photon's network connectivity.
- Man-in-the-Middle (MitM):** Intercepting and modifying data transmitted between the Photon and other devices.
- Malware:** Installing malicious software on the Photon.
- Physical Access:** Gaining physical access to the Photon and its components.

4. Defending the Photon

This section discusses the various techniques that can be used to defend the Photon platform against attacks. These include:

- Network Security:** Using firewalls, intrusion detection systems, and other network security measures.
- Application Security:** Using secure coding practices and other application security measures.
- Physical Security:** Using tamper-resistant hardware and other physical security measures.

5. Conclusion

The Photon platform is a powerful tool for developing IoT applications. However, it is also a target for attackers. This paper has presented a comprehensive survey of the security challenges facing the Photon platform and discussed the techniques that can be used to defend against these challenges.

IoT Hacking: Attacking the

Ang Kang Seng National University of Singapore 21 Lower Kent Ridge Rd. 110627 485 8045528 a0123456@nus.edu.sg	Chew Yung Chung National University of Singapore 21 Lower Kent Ridge Rd. 110627 485 8045528 a0123456@nus.edu.sg	Tan Qiu Hao, Joel National University of Singapore 21 Lower Kent Ridge Rd. 110627 485 8045528 a0123456@nus.edu.sg	Juliana Seng National University of Singapore 21 Lower Kent Ridge Rd. 110627 485 8045528 a0123456@nus.edu.sg
--	--	--	---

ABSTRACT

The Internet of Things (IoT) is becoming increasingly prevalent in our daily lives, enabling a wide range of applications from smart homes to industrial automation. However, the rapid growth of IoT has also led to a corresponding increase in security risks. This paper presents a comprehensive survey of IoT security threats and vulnerabilities, and discusses the challenges of securing IoT systems. The paper is organized as follows: Section 1 introduces the background of IoT and the Photon platform. Section 2 describes the various attacks that can be performed on the Photon platform. Section 3 discusses the techniques that can be used to defend the Photon platform against attacks. Section 4 concludes the paper.

Categories and Subject Descriptors

C.2.2 [Computer Systems, Hardware]: Network Hardware; C.2.3 [Computer Systems, Hardware]: Network Software; C.2.4 [Computer Systems, Hardware]: Network Architecture; C.2.5 [Computer Systems, Hardware]: Network Security

General Terms

Security

Keywords

IoT, Photon, security, attacks, defense

1. INTRODUCTION

The Internet of Things (IoT) is the convergence of information and communication technologies (ICT) with physical objects, enabling them to be connected to the Internet and exchange data with other devices. This has led to the development of a wide range of IoT applications, from smart homes to industrial automation. However, the rapid growth of IoT has also led to a corresponding increase in security risks. This paper presents a comprehensive survey of IoT security threats and vulnerabilities, and discusses the challenges of securing IoT systems.

The Photon platform is a low-cost, open-source IoT platform based on the Raspberry Pi. It is designed to be easy to use and to support a wide range of IoT applications. This paper describes the architecture of the Photon platform and discusses the security challenges it faces. The paper is organized as follows: Section 1 introduces the background of IoT and the Photon platform. Section 2 describes the various attacks that can be performed on the Photon platform. Section 3 discusses the techniques that can be used to defend the Photon platform against attacks. Section 4 concludes the paper.

IoT Hacking: Attacking the Photon

Ang Kang Seng National University of Singapore 21 Lower Kent Ridge Rd. 110627 485 8045528 a0123456@nus.edu.sg	Chew Yung Chung National University of Singapore 21 Lower Kent Ridge Rd. 110627 485 8045528 a0123456@nus.edu.sg	Tan Qiu Hao, Joel National University of Singapore 21 Lower Kent Ridge Rd. 110627 485 8045528 a0123456@nus.edu.sg	Juliana Seng National University of Singapore 21 Lower Kent Ridge Rd. 110627 485 8045528 a0123456@nus.edu.sg
--	--	--	---

ABSTRACT

The Internet of Things (IoT) is becoming increasingly prevalent in our daily lives, enabling a wide range of applications from smart homes to industrial automation. However, the rapid growth of IoT has also led to a corresponding increase in security risks. This paper presents a comprehensive survey of IoT security threats and vulnerabilities, and discusses the challenges of securing IoT systems. The paper is organized as follows: Section 1 introduces the background of IoT and the Photon platform. Section 2 describes the various attacks that can be performed on the Photon platform. Section 3 discusses the techniques that can be used to defend the Photon platform against attacks. Section 4 concludes the paper.

Categories and Subject Descriptors

C.2.2 [Computer Systems, Hardware]: Network Hardware; C.2.3 [Computer Systems, Hardware]: Network Software; C.2.4 [Computer Systems, Hardware]: Network Architecture; C.2.5 [Computer Systems, Hardware]: Network Security

General Terms

Security

Keywords

IoT, Photon, security, attacks, defense

1. INTRODUCTION

The Internet of Things (IoT) is the convergence of information and communication technologies (ICT) with physical objects, enabling them to be connected to the Internet and exchange data with other devices. This has led to the development of a wide range of IoT applications, from smart homes to industrial automation. However, the rapid growth of IoT has also led to a corresponding increase in security risks. This paper presents a comprehensive survey of IoT security threats and vulnerabilities, and discusses the challenges of securing IoT systems.

The Photon platform is a low-cost, open-source IoT platform based on the Raspberry Pi. It is designed to be easy to use and to support a wide range of IoT applications. This paper describes the architecture of the Photon platform and discusses the security challenges it faces. The paper is organized as follows: Section 1 introduces the background of IoT and the Photon platform. Section 2 describes the various attacks that can be performed on the Photon platform. Section 3 discusses the techniques that can be used to defend the Photon platform against attacks. Section 4 concludes the paper.

(b): Media and DVD security

What is the point of DVD regions?

The DVD CSS is a [Content Scrambling System](#) - data encryption scheme, developed by commercial interests to [stop copying](#)... but it is [easy to copy](#) a DVD: CSS only prevents decrypting, changing and re-recording.

The CSS algorithm details are a trade secret. There is a master set of 400 [keys](#) stored [on every DVD](#), and the DVD player uses these to generate a key needed to decrypt data from the disc.

LINUX and the CSS

Linux users were excluded from access to CSS licenses because of the open-source nature of Linux.

The source code for decoding DVDs is available on a T-shirt, because in October 1999, hobbyists/hackers in Europe cracked the CSS algorithm.

Since then DVD industry players have been trying to prevent distribution of any software

(b): DVD security

What do we learn?

The lesson to learn from this is that *security-through-obscurity* is a very poor strategy.

The source code and detailed descriptions for a CSS descrambler is available at: <http://www-2.cs.cmu.edu/~dst/DeCSS/Gallery/>

Description of the key/descrambling process:

First one must have a master key, which is unique to the DVD player manufacturer. It is also known as a player key. The player reads an encrypted disk key from the DVD, and uses its player key to decrypt the disk key. Then the player reads the encrypted title key for the file to be played. (The DVD will likely contain multiple files, typically 4 to 8, each with its own title key.) It uses the decrypted disk key (DK) to decrypt the title key. Finally, the decrypted title key, TK, is used to descramble the actual content.

(b): DVD security

Confusion and diffusion...

```
#define m(i) (x[i]^s[i+84])<<
unsigned char x[5],y,s[2048];main(n){for(read(0,x,5);read(0,s,n=2048);
write(1,s ,n))if(s[y=s[13]%8+20]/16%4==1){int i=m(1)17^256+m(0)8,k=m(2)
0,j=m(4)17^m(3)9^k *2-k%8^8,a=0,c=26;for(s[y]--16;--c;j*=2)
a=a*2^i&1,i=i/2^j&1<<24;for(j=127;++j<n ;c=c>y)c+=y=i^i/8^i>>4^
i>>12,i=i>>8^y<<17,a^=a>>14,y=a^a*8^a<<6,a=a>>8^y<<9,k=s [j],k="7
Wo~'G_\216"[k&7]+2^"cr3sfw6v;*k+>/n."[k>>4]*2^k*257/8,s[j]=k^(k&k
*2&34) *6^c+~y;}}
```

Summary

Many opportunities for manipulation:

- ① We looked at four large infrastructural systems:
 - ① SWIFT, a worldwide banking mechanism. Happily there have only been isolated attacks, and it is still largely working.
 - ② PKI, which has a history of worrisky attacks, with BAD certificates issued by “authorities”.
 - ③ How the (US) NSA has been messing with Diffie Hellman, to do large scale monitoring of supposedly secure https and IKE.
 - ④ The DNS.
- ② We looked at the general idea of challenge-response, to perform authentication without having to reveal passwords, along with Kerberos, a strong challenge-response system.
- ③ We then looked at some other infrastructural things, and how they might be done:
 - ① Voting systems
 - ② Coin flipping
 - ③ contract signing with oblivious transfer.
- ④ Finally, we looked at some hardware - IoT devices, and DVDs, and the security in them (or perhaps lack of security in them).