
#### Depth First Search:

- Looke for the goal state/node among all the successor/children of the tue siblings of the node.

Fringe is implementes as LIFO.



#### Evaluation:

Complete: Does it always find sol-

No, if my not find the Solution in case if search space is infinite & contains loops.

optimal/admissible:

No, it may not be appinal because:

- It expand deepest nose first.
- If it expand entire sub-tree even right contains goal note at some depth d'.

## Time complexity:

- let d be the max depth of search free.
- Root has b successor and each note at each level has again b successor.
  - Worst care expand all the node except node at depth d'
    - Total voice y energled:


6+62+63+64+---+6d = 0(6d)

### space complexity:


- DFS need to store only single path from roof to leaf ware

- It also stores remaining unexpanded sibling nades for each vote on the path.
- once a node has been expanded it can be remove from a memory as soon as its descendents have been fully explored.
- so, for state space with branching factor 'b' & depth 'd', it stores of only:

  0 (bd) nodes




Step 2! Remore A from fringe. Expand A & put ite successor in fart of fringe.



Fringe


B C

step 3: Node Bis removed & its successor are placed in fort ext fringe.




# Fringe DFC

step 4: Now node so is removed from the fringe & its successor are push in front of fringe.



Fringe CFEC

step 5: Renne node/state c from the foringe and its thild 4 is pushed in font of foringe.




Fringe GFEC

Step 6:
Here, Mode by is expanded and
found to be goal node. Finally,
algorithm fearningtes reprint


ABDCG

### Practice:

1.



Start Stete: P & broal state: V



stort node: A broal node: by