



Guidewire InsuranceSuite™ for Guidewire Cloud

Configuration Parameters

Release: 2025.11.0



© 2025 Guidewire Software, Inc.

For information about Guidewire trademarks, visit <https://www.guidewire.com/legal-notices>.

Guidewire Proprietary & Confidential — DO NOT DISTRIBUTE

Product Name: Guidewire InsuranceSuite for Guidewire Cloud

Product Release: 2025.11.0

Document Name: Configuration Parameters

Document Revision: 27-January-2026

Contents

Support.....	15
1 Application configuration parameters.....	17
Working with configuration parameters.....	17
Adding custom parameters to the application.....	17
Configuration parameter behaviors.....	17
View configuration parameters on a running server.....	19
Access configuration parameters in Gosu.....	19
Adding custom MIME types.....	19
Account parameters.....	20
AccountsWithdrawnAfterMonths.....	20
Approval parameters.....	20
BulkInvoiceApprovalPattern.....	20
PaymentApprovalPattern.....	20
RecoveryApprovalPattern.....	21
RecoveryReserveApprovalPattern.....	21
ReserveApprovalPattern.....	21
Archive parameters.....	21
ArchiveDaysRetrievedBeforeArchive	21
ArchiveDefaultRecheckDays.....	21
ArchiveEnabled.....	21
ArchivePolicyPeriodDays.....	22
ArchivePolicyTermDays.....	22
ArchiveRecentJobCompletionDays.....	22
AssignClaimToRetriever.....	22
DaysClosedBeforeArchive.....	22
DaysRetrievedBeforeArchive.....	23
DomainGraphKnownUnreachableTables.....	23
MaxNumberOfArchivedEntitiesToRestore.....	23
PolicySystemArchivingEnabled.....	23
RestorePattern.....	24
SnapshotEncryptionUpgradeChunkSize.....	24
Assignment parameters.....	24
AssignmentQueuesEnabled.....	24
ExposureWWLEnabled.....	24
WeightedAssignmentEnabled.....	24
WeightedAssignmentGlobalDefaultWeight.....	24
Asynchronous quoting parameters.....	25
AsynchronousQuotingEnabled.....	25
Autopilot workflow parameters.....	25
AutopilotUserRoleAssignment.....	25
Batch process parameters.....	25
BatchProcessHistoryPurgeDaysOld.....	25
MaxCatastropheClaimFinderSearchResults.....	25
Bulk invoice activity pattern parameters.....	25
BulkInvoiceItemValidationFailedPattern.....	25

BulkInvoiceUnableToStopPattern.....	26
BulkInvoiceUnableToVoidPattern.....	26
Business calendar parameters.....	26
BusinessDayDemarcation.....	26
BusinessDayEnd.....	26
BusinessDayStart.....	26
BusinessWeekEnd.....	26
HolidayList (obsolete).....	26
IsFridayBusinessDay.....	27
IsMondayBusinessDay.....	27
IsSaturdayBusinessDay.....	27
IsSundayBusinessDay.....	27
IsThursdayBusinessDay.....	27
IsTuesdayBusinessDay.....	27
IsWednesdayBusinessDay.....	27
MaxAllowedDate.....	27
MinAllowedDate.....	28
Business rules parameters.....	28
BizRulesCacheStaleTimeMinutes.....	28
BizRulesDeploymentEnabled.....	28
BizRulesDeploymentId.....	28
BizRulesEnabled.....	29
BizRulesExposureDisabledWhenIncidentOnly.....	29
BizRulesImportBootstrapRules.....	29
BizRulesLeafSearchNumOfHops.....	30
BulkLoadRuleHeadByIdCacheEnabled.....	30
OnlineJavadocPrefix.....	30
PreloadBizRulesBeansCacheEnabled.....	30
Cache parameters.....	31
ActivityPatternCacheMaxDuration.....	31
ChargePatternCacheRefreshIntervalSecs.....	31
ExchangeRatesCacheRefreshIntervalSecs.....	31
GlobalCacheActiveTimeMinutes.....	31
GlobalCacheDetailedStats.....	32
GlobalCacheReapingTimeMinutes.....	32
GlobalCacheSizeMegabytes.....	32
GlobalCacheSizePercent.....	32
GlobalCacheStaleTimeMinutes.....	32
GlobalCacheStatsRetentionPeriodDays.....	33
GlobalCacheStatsWindowMinutes.....	33
GroupCacheRefreshIntervalSecs.....	33
PlanOrderCacheRefreshIntervalSecs.....	33
ResetGlobalCacheOnSwitchFromReadOnlyToNormal.....	33
ScriptParametersRefreshIntervalSecs.....	34
TAccountPatternCacheRefreshIntervalSecs.....	34
ZoneCacheRefreshIntervalSecs.....	34
Catastrophe heat map parameters.....	34
CatastropheClaimHeatMapCacheRefreshSecs.....	34
CatastrophePolicyLocationHeatMapCacheRefreshSecs.....	34
HeatMapCredential.....	34
HeatMapPolicyLocationDemo.....	35

HeatMapServiceTemplate.....	35
Claim health indicator and metric parameters.....	35
ClaimHealthCalcMaxLossDateInYears.....	35
InitialReserveAllowedPeriod.....	35
MaxClaimResultsPerClaimHealthCalcBatch.....	35
Cloud API parameters.....	35
AllowedCompositeRequestTags.....	36
EnableWorkersCompMainInjuryIncidentInCloudAPI.....	36
GiveInternalUsersFullPermissionsInCommonActivitiesApi.....	36
GiveProducerAccessToAllExposures.....	36
MaximumAllowedNumberOfBatchSubRequests.....	36
MaximumAllowedNumberOfCompositeSubRequests.....	36
RequireExposuresToBeNewLossWhenSubmittingWithCloudAPI.....	37
RestAPIsGeneratingByPolicyLine.....	37
RestJobRecoveryExpirationDate.....	37
RestJobRecoveryMaxResults.....	37
RoleNameCacheStaleTimeMinutes.....	37
Data destruction parameters.....	37
ContactDestructionRequestAgeForPurgingResults.....	38
DataDestructionMaxWaitForBlockingMessagesToFinish.....	38
PersonalDataDestructionEnabled.....	38
KeepPurgedRootForDays.....	38
Deduction parameters.....	38
BackupWithholdingTypeCode.....	39
CalculateBackupWithholdingDeduction.....	39
StandardWithholdingRate.....	39
Desktop and team parameters.....	39
ActivityStatisticsWindowSize.....	39
CanceledActivityRetentionWindow.....	39
OtherWorkOrdersStatisticsWindowSize.....	39
RenewalsStatisticsWindowSize.....	40
SearchActivityThresholdDays.....	40
SubmissionsStatisticsWindowSize.....	40
TeamScreenTabVisibilityRowCountCutoff.....	41
Document creation and document management parameters.....	41
DisplayDocumentEditUploadButtons.....	41
DocumentContentDispositionMode.....	41
DocumentTemplateDescriptorXSDLocation.....	41
FinalDocumentsNotEditable.....	41
MaximumFileUploadCount.....	41
MaximumFileUploadSize.....	42
MaximumTotalUploadSize.....	42
Environment parameters.....	42
AddressDeletionDelay.....	42
AddressVerificationFailureAsError.....	42
AllowStartupInDevelopmentModeWithDomainGraphErrors.....	42
CollapseFutureInvoicesUponCancellation.....	43
CommissionRemainderTreatment.....	43
CreateSmartReinstatementSnapshotItems.....	43
CurrentEncryptionPlugin.....	43
DaysBeforeAccountIsConsideredInactive.....	44

DeprecatedEventGeneration.....	44
EnableAddressVerification.....	44
EnableChargeProRataTxCreation.....	44
EnableBatchPayments.....	45
EnableInternalDebugTools.....	45
EntityValidationOrder.....	45
ExternalIDPrefix.....	45
GosuSampleDataMethod.....	45
IBillingCenterAPICDCENumRetries.....	46
IncludeClosedPoliciesInAccountAggregateBalances.....	46
InvoicePeriodCutoff.....	46
InvoicePeriodDueCutoff.....	46
KeyGeneratorRangeSize.....	46
MemoryUsageMonitorIntervalMins.....	47
PASEffectiveTime.....	47
PolicyClosureBufferDays.....	47
PublicIDPrefix.....	47
ResourcesMutable.....	47
RetainDebugInfo.....	48
ScopedVariableSupportedForAllCapturedRequests.....	48
StrictDataTypes.....	48
TwoDigitYearThreshold.....	49
UnreachableCodeDetection.....	49
UnrestrictedUserName.....	49
UseOldStylePreUpdate.....	49
WarnOnImplicitCoercion.....	50
WebResourcesDir.....	50
Equity warning parameters.....	50
DefaultEquityBuffer.....	50
EnableEquityWarnings.....	50
Financial activity pattern parameters.....	50
CheckDeniedPattern.....	50
CheckUnableToStopPattern.....	50
CheckUnableToVoidPattern.....	50
ClaimOrExposureUnableToClosePattern.....	51
LastPaymentReminderPattern.....	51
RecoveryDeniedPattern.....	51
Financial parameters.....	51
AllowMultipleLineItems.....	51
AllowMultiplePayments.....	51
AllowNegativeManualChecks.....	51
AllowNoPriorPaymentSupplement.....	52
AllowPaymentsExceedReservesLimits.....	52
AllowTransactionDenyWhenSubmitted.....	52
CheckAuthorityLimits.....	52
CheckUnappliedAmountAfterEveryPayment.....	52
CloseClaimAfterFinalPayment.....	53
CloseExposureAfterFinalPayment.....	53
EnableMulticurrencyReserving.....	53
EnforceNonCustomAuthorityLimitProfilesCannotHaveDuplicateNames.....	53
Financials.....	53

InstantPaymentIntegrationEnabled.....	54
NewCustomCommissionPayableCalculatorEnabled.....	54
ProRataCalculationRemainderTreatment.....	54
PaymentLogThreshold.....	55
PaymentRecodeValidationExtensionFields.....	55
PaymentRoundingMode.....	55
RecoveryRecodeValidationExtensionFields.....	55
ReserveRoundingMode.....	56
SetReservesByTotalIncurred.....	56
UseDeductibleHandling.....	56
UseDeprecatedExchangeRates.....	57
UseRecoveryReserves.....	57
Geocoding parameters.....	57
ProximityRadiusSearchDefaultMaxResultCount.....	57
ProximitySearchOrdinalMaxDistance.....	58
UseGeocodingInAddressBook.....	58
UseGeocodingInPrimaryApp.....	58
UseMetricDistancesByDefault.....	58
Globalization parameters.....	58
AlwaysShowPhoneWidgetRegionCode.....	58
DefaultApplicationBaseCurrencies.....	59
DefaultApplicationCurrency.....	59
DefaultApplicationLanguage.....	59
DefaultApplicationLocale.....	59
DefaultCountryCode.....	60
DefaultNANPACountryCode.....	60
DefaultPhoneCountryCode.....	60
DefaultRoundingMode.....	60
MulticurrencyDisplayMode.....	61
MultiSettlementCurrencyHandlingEnabled	61
High Volume Quoting configuration.....	61
HVQEnabled.....	62
HVQServer.....	62
MaxHVQSearchResults.....	62
Integration parameters.....	62
BillingSystemArchiveEnabled.....	63
BillingSystemArchivePolicyPeriodDays.....	63
BillingSystemURL.....	63
ClaimSystemURL.....	63
ContactAutoSyncBundleCommitSize.....	64
ContactAutoSyncWorkItemChunkSize.....	64
DefaultXmlExportIEncryptionId.....	64
EnableCreditCardCollectionUI.....	64
EnableCustomBilling.....	65
EnableMetroIntegration.....	65
HighRiskAssessmentCategories.....	65
InboundPaymentIntegrationEnabled.....	65
InstantaneousContactAutoSync.....	65
ISOPropertiesFileName.....	65
KeepCompletedMessagesForDays.....	66
LockPrimaryEntityDuringMessageHandling.....	66

MetroPropertiesFileName.....	66
PaymentSystemURL.....	66
PluginStartupTimeout.....	66
PolicySystemURL.....	66
Itemized charges and commissions parameters.....	67
EnableChargeBreakdownCommissionable.....	67
EnableChargeBreakdowns.....	67
Job expiration parameters.....	68
JobExpirationCreateDateThreshold.....	68
JobExpirationEffDateThreshold.....	69
JobExpireCheckAudit.....	69
JobExpireCheckCancellation.....	69
JobExpireCheckIssuance.....	69
JobExpireCheckPolicyChange.....	69
JobExpireCheckReinstatement.....	69
JobExpireCheckRenewal.....	70
JobExpireCheckRewrite.....	70
JobExpireCheckSubmission.....	70
JobExpireCheckTestJob.....	70
Job-related parameters.....	70
AllowedDaysBeforeOrAfterPolicyStartDate.....	70
MaximumPolicyCreationYearDelta.....	70
MaxRecentAccounts.....	71
MaxRecentPoliciesAndJobs.....	71
MaxSubmissionsToCreate.....	71
MinimumPolicyCreationYear.....	71
PatternCacheMaxDuration.....	71
PolicyChangeMaxQuotes.....	71
PurgeTemporaryPolicyPeriodsAfterDays.....	71
PurgeTemporaryPolicyPeriodsEnabled.....	71
RenewalMaxQuotes.....	72
RenewalProcessLeadTime.....	72
SubmissionMaxQuotes.....	72
JSON, Swagger, and REST parameters.....	72
OverrideJSONMappingWarnings.....	72
OverrideJSONSchemaWarnings.....	72
OverrideRESTSchemaWarnings.....	72
PreloadRestServletConfig.....	73
Lookup table parameters.....	73
AvailabilityContextCacheEntryExpirationTime.....	73
AvailabilityContextCacheSize.....	73
UsePolicyPeriodReferenceDateForOfferingAvailability.....	73
Miscellaneous parameters.....	74
AdminDataImporterExporterEnabled.....	74
AdminExportRecordPurgeEnabled.....	74
AdminImportRecordPurgeEnabled.....	74
AccountNumberSequenceGeneratorOnInitEnabled.....	74
AllowShortCircuitMatchingBean.....	74
BulkInsertSelectCardinalityEstimatorHint.....	75
BusinessRuleOverridesEnabled.....	75
ClusterClockChangeDelaySeconds.....	75

ClaimLossDateDemarcation.....	75
ConsistencyCheckerThreads.....	75
ConfigurationServiceEnabled.....	75
DefaultDiffDateFormat.....	75
DisableDomainGraphSupport.....	76
EnableClaimNumberGeneration.....	76
EnableClaimSnapshot.....	76
EnablePreLoader.....	76
EnableStatCoding.....	76
EquityDatingIncludeWriteoffs.....	77
ExportUserDataEnabled.....	77
ExternallyVisibleProducerCodes.....	77
IgnoreLeapDayForEffDatedCalc.....	77
ImportUserDataEnabled.....	78
InitialSampleDataSet.....	78
MaintainPolicyValidationLevelOnPolicyChange.....	78
MaxCachedClaimSnapshots.....	79
MaximumXmlExportSize.....	79
MaxStatCodesInDropdown.....	79
MaxTAccountsInConsistencyCheck.....	79
MaxTransactionsInConsistencyCheck.....	79
PhoneNumberStrictValidation.....	79
PreloadSystemTableToCacheForFasterSynchronization.....	79
ProfilerDataPurgeDaysOld.....	80
RewriteMaxQuotes.....	80
StructuredLoggerLightLoggingEnabled.....	80
StructuredLoggerRemoveCRLFEnabled.....	80
TenantId.....	80
TransactionIdPurgeDaysOld.....	80
WorkflowLogPurgeRowLimit.....	80
Multicurrency parameters.....	81
DefaultApplicationBaseCurrencies.....	81
DefaultApplicationCurrency.....	81
MulticurrencyDisplayMode.....	81
BillingAPIWizardsEnabled.....	82
MulticurrencyDedicatedUIEnabled.....	82
Parallel rating parameters.....	82
EnableCPDTOParallelRating.....	82
ParallelizedRatingEnabled.....	82
ParallelRatingTimeoutPerCoverable.....	83
MaxRatingThreadPoolSize.....	83
Parallel product model synchronization parameters.....	83
MaxProductModelSyncThreadPoolSize.....	83
MinNumberOfCoverablesToParallelizeProductModelSync.....	84
ParallelizedProductModelSyncEnabled.....	84
ParallelProductModelSyncTimeoutPerCoverable.....	84
Policy exception parameters.....	84
BoundPolicyThresholdDays.....	84
ClosedPolicyThresholdDays.....	84
OpenPolicyThresholdDays.....	85
Policy purge parameters.....	85

TruncatePoliciesEnabled.....	85
TruncatePoliciesChunkSize.....	85
TruncatePoliciesMinimumTimeToRecheckDays.....	85
TruncatePoliciesMinimumThresholdYears.....	85
Print settings parameters.....	85
DefaultContentDispositionMode.....	86
PrintCsvDefaultBaseFileExtension.....	86
PrintCsvMimeType.....	86
PrintDefaultBaseFileName.....	86
PrintFontFamilyName.....	86
PrintFontSize.....	86
PrintFOPUserConfigFile.....	86
PrintHeaderFontSize.....	86
PrintLineHeight.....	87
PrintListViewBlockSize.....	87
PrintListViewFontSize.....	87
PrintMarginBottom.....	87
PrintMarginLeft.....	87
PrintMarginRight.....	87
PrintMarginTop.....	87
PrintMaxNestedListViewSize.....	87
PrintMaxPDFInputFileSize.....	87
PrintPageHeight.....	88
PrintPageWidth.....	88
PrintPdfDefaultBaseFileExtension.....	88
PrintPdfMimeType.....	88
Product model parameters.....	88
CoverableCacheEnabled.....	88
ExternalProductModelDirectory.....	88
ProductModelClassCacheConcurrencyLevel.....	89
StrictProductModelIdUniquenessChecking.....	89
Quote purging configuration parameters.....	89
PruneAndPurgeJobsEnabled.....	90
PruneVersionsDefaultRecheckDays.....	90
PruneVersionsPolicyTermDays.....	90
PruneVersionsPolicyTermDaysCheckDisabled.....	90
PruneVersionsRecentJobCompletionDays.....	90
PurgeJobsDefaultRecheckDays.....	90
PurgeJobsPolicyTermDays.....	91
PurgeJobsPolicyTermDaysCheckDisabled.....	91
PurgeJobsRecentJobCompletionDays.....	91
PurgeOrphanedPolicyPeriodsEnabled.....	91
PurgePolicyTermsEnabled.....	91
Rating Management parameters.....	91
EnableRateRoutinesJar.....	92
OverriddenTableArgsLabelSimple.....	92
PurgeRateBookExportResultEnabled.....	92
PurgeWorksheetsEnabled.....	92
RateBookCacheEntryLifetimeSecs.....	92
RateBookCacheUpdateIntervalSecs.....	93
RateBookExportResultAgeForPurging.....	93

RateBookPreloadEnabled.....	93
RateRoutineIndexingThreshold.....	93
RateRoutinesJarFile.....	94
RateRoutinesUpdateJarFile.....	94
RateTableCacheConcurrency.....	95
RateTableCacheEntryLifetimeSecs.....	95
RateTableCacheMaxSize.....	95
RateTableCacheUpdateIntervalSecs.....	96
RateTableDefinitionCacheEntryLifetimeSecs.....	96
RateTableDefinitionCacheUpdateIntervalSecs.....	96
RateTableManagementNormalizationRowLimit.....	96
RateTableManagementNormalizationRowThreshold.....	97
RatingWorksheetContainerAgeForPurging.....	97
SmallRateTableRowLimit.....	97
Risk assessment parameters.....	97
MultipleLocationRiskAssessmentEnabled.....	97
PurgeRiskAssessmentTempStoreDays.....	98
RiskAssessmentIntegrationEnabled.....	98
RiskAssessmentThumbnailMapEnabled.....	98
SingleLocationRiskAssessmentEnabled.....	98
SpotlightInteractiveServiceURL.....	98
SpotlightLoginURL.....	98
SpotlightRiskAssessmentServiceURL.....	98
SpotlightThumbnailMapURL.....	98
Scheduler and workflow parameters.....	98
IdleClaimThresholdDays.....	99
SchedulerEnabled.....	99
SeparateIdleClaimExceptionMonitor.....	99
WorkflowLogDebug.....	99
WorkflowLogPurgeDaysOld.....	99
WorkflowPurgeDaysOld.....	99
WorkflowStatsIntervalMins.....	99
Search parameters.....	100
FreeTextSearchEnabled.....	100
MaxActivitySearchResults.....	100
MaxBulkInvoiceSearchResults.....	100
MaxCheckSearchResults.....	100
MaxClaimSearchResults.....	101
MaxContactSearchResults.....	101
MaxContactDocumentSearchResults.....	101
MaxDocTemplateSearchResults.....	101
MaxDuplicateContactSearchResults.....	101
MaxNoteSearchResults.....	101
MaxPolicySearchResults.....	101
MaxRecoverySearchResults.....	102
MaxSearchResults.....	102
PolicySearchMaxResult.....	102
Seasonal coverage parameters.....	102
ApplySeasonalDiffItemsFirst.....	102
Security parameters.....	102
AbsoluteMaxSessionLength.....	103

EnableAbsoluteMaxSessionLength.....	103
EnableDownlinePermissions.....	103
ExternalUserAccess.....	103
FailedAttemptsBeforeLockout.....	104
LockoutPeriod.....	104
LoginRetryDelay.....	104
MaxACLParameters.....	104
MaxPasswordLength.....	105
MinPasswordLength.....	105
ProducerCodeCyclesAllowed.....	105
RestrictContactPotentialMatchToPermittedItems.....	105
RestrictSearchesToPermittedItems.....	105
SessionTimeoutSecs.....	105
SingleSignOnAuthenticationEnabled.....	105
UseACLPermissions.....	106
Segmentation parameters.....	106
ClaimSegment.....	106
ClaimStrategy.....	106
ExposureSegment.....	106
ExposureStrategy.....	106
Service request parameters.....	106
ServiceRequestAPIMaxDaysKeepActiveWithoutInvoice.....	107
ServiceRequestAPIMaxMessageResults.....	107
ServiceRequestAPIMaxSearchResults.....	107
Servlet parameters.....	107
EnableInfoServlet.....	107
EnableVerbosePingServlet.....	107
Side-by-side quoting parameters.....	107
RenewalMaxSideBySideQuotes.....	108
SideBySide.....	108
SubmissionMaxSideBySideQuotes.....	108
PolicyChangeMaxSideBySideQuotes.....	108
SideBySideTwoStepQuotingEnabled.....	108
MaxParallelQuotingThreads.....	108
Smart Communications for PolicyCenter parameters.....	108
DocumentProductionIntegrationEnabled.....	109
DocumentProductionBindingType.....	109
Statistics, team, and dashboard parameters.....	109
AddIndexHintForLossDate.....	109
AgingStatsFirstDivision.....	109
AgingStatsSecondDivision.....	109
AgingStatsThirdDivision.....	110
CalculateLitigatedClaimAgingStats.....	110
DashboardIncurredLimit.....	110
DashboardShowByCoverage.....	110
DashboardShowByLineOrLoss.....	110
DashboardWindowPeriod.....	110
GroupSummaryShowUserGlobalWorkloadStats.....	110
UserStatisticsWindowSize.....	111
Test framework parameters.....	111
DefaultTestProductCode.....	111

Two-step quoting parameters.....	111
TwoStepQuotingEnabled.....	111
User interface parameters.....	111
ActionsShortcut.....	112
AutoCompleteLimit.....	112
HidePolicyObjectsWithNoCoveragesForLossTypes.....	112
HighlyLinkedContactThreshold.....	112
IgnorePolicyTotalPropertiesValue.....	112
IgnorePolicyTotalVehiclesValue.....	112
ListViewPageSizeDefault.....	113
MaxBrowserHistoryItems (obsolete).....	113
MaxChooseByCoverageMenuItems.....	113
MaxChooseByCoverageTypeMenuItems.....	113
MaxClaimantsInClaimListViews.....	113
MaxTeamSummaryChartUserBars.....	113
QuickJumpShortcut.....	113
RequestReopenExplanationForTypes.....	114
ShowCurrentPolicyNumberInSelectPolicyDialog.....	114
ShowFixedExposuresInLossDetails.....	114
ShowNewExposureChooseByCoverageMenuForLossTypes.....	114
ShowNewExposureChooseByCoverageTypeMenuForLossTypes.....	114
ShowNewExposureMenuForLossTypes.....	115
UISkin.....	115
WebUIAJAXTimeout.....	115
Web services parameters.....	115
WebservicesHideDetails.....	116
WebservicesHideListPage.....	116
Work queue parameters.....	116
AppEventsMarkForSyncChunkSize.....	116
EnableWorkQueueValidation.....	116
EventMigratableWorkItemPriorityForOpenClaims.....	117
EventMigratableWorkItemPriorityForUpdatedClaims.....	117
FullPayDiscountPolicyPeriodsPerWorkItem.....	117
FundsAllotmentAccountsPerWorkItem.....	117
InstrumentedWorkerInfoPurgeDaysOld.....	117
PaymentRequestsPerWorkItem.....	117
WorkItemCreationBatchSize.....	118
WorkItemPriorityMultiplierSecs.....	118
WorkItemRetryLimit.....	118
WorkQueueHistoryMaxDownload.....	119
WorkQueueThreadPoolMaxSize.....	119
WorkQueueThreadPoolMinSize.....	119
WorkQueueThreadsKeepAliveTime.....	119

Support

For assistance, visit the Guidewire Community.

Guidewire customers

<https://community.guidewire.com>

Guidewire partners

<https://partner.guidewire.com>

Application configuration parameters

This topic covers the application configuration parameters, which are static values that you use to control various aspects of system operation. For example, you can control business calendar settings, cache management, and user interface behavior through the use of configuration parameters, along with much more.

Working with configuration parameters

You set application configuration parameters in the file `config.xml`. You can find this file in the Guidewire Studio **Project** tool window, under **configuration > config**.

This file generally contains entries in the following format:

```
<param name="param_name" value="param_value" />
```

Each entry sets the parameter named *param_name* to the value specified by *param_value*.

The `config.xml` file in the base configuration contains all available parameters. To set a parameter, edit the file, locate the parameter, and change its value. Application configuration parameters are case-insensitive. If a parameter does not appear in the file, the default value is used, if the parameter has one.

Adding custom parameters to the application

You cannot add new or additional configuration parameters to `config.xml`. If you want to add custom parameters to your configuration, consider defining script parameters. You can access the values of script parameters in Gosu code at runtime. For more information, see “Script parameters”.

Configuration parameter behaviors

The configuration parameters in `config.xml` may implement the following behaviors:

Behavior	Summary	More information
Required	You must supply a value.	“Required” on page 18
Set for server	You can set a different value for different servers in a cluster.	“Set for server” on page 18
Dynamic	You can change the parameter value on a running server.	“Dynamic” on page 18
Permanent	Once you start the server, you cannot change the parameter value.	“Permanent” on page 18

Behavior	Summary	More information
Semi-permanent	Once you start the server, you can change the parameter value only in limited ways.	"Semi-permanent" on page 18
Nullable	The parameter value is allowed to be null.	"Nullable" on page 18

Required

Guidewire designates certain configuration parameters as *required*, which means that you must supply a value for that parameter.

Configuration parameters that are required have *Required: Yes* in their parameter descriptions.

Set for server

Guidewire designates certain configuration parameters as possible for the parameter value to vary on different servers in a cluster.

Configuration parameters that can be set per server have *Set for server: Yes* in their parameter descriptions.

Do not add a configuration parameter that is not designated as *Set for server: Yes* to a local configuration file. If you do so, the application prints a warning message in the configuration log file when the application server starts. For example:

```
WARN Illegal parameter specified in a local config file (will be ignored): XXXXXXXX
```

Note: For information on server environments, see the *InsuranceSuite Server Administration*.

Dynamic

Guidewire designates certain configuration parameters as *dynamic*. This indicates that Guidewire permits you to change this value on a running application server through management integration. The discussion of configuration parameters indicates this by adding *Dynamic: Yes* to the parameter description.

See *Plugins, Prebuilt Integrations, and SOAP APIs*.

Permanent

Guidewire specifies several configuration parameter values as *permanent*. After you set the value of a permanent parameter and start the production application server, you cannot change the parameter's value. An example is the `DefaultApplicationLocale` configuration parameter. If you set the value of this parameter on a production server and then start the server, you are unable to change the value thereafter.

Guidewire stores these values in the database and checks the value at server start up. If an application server value does not match a database value, the application throws an error.

Semi-permanent

Guidewire specifies a limited number of configuration parameter values as *semi-permanent*. After you set the value of a semi-permanent parameter and start the production application server, you can change the value of the parameter only once to a specified value.

Nullable

The parameter value is allowed to be null.

View configuration parameters on a running server

About this task

You can view the configuration parameters and their values that are in effect on a running application server. To change the values dynamically, you can create a management integration plugin.

Procedure

1. Open the **Server Tools** page of the application server.
2. In the sidebar, click **Info Pages > Configuration**.

Results

See *Plugins, Prebuilt Integrations, and SOAP APIs*.

Access configuration parameters in Gosu

Procedure

To access a configuration parameter in Gosu code, use the following syntax:

Platform

```
gw.api.system.PLConfigParameters
```

ClaimCenter

```
gw.api.system.CCConfigParameters
```

PolicyCenter

```
gw.api.system.PCConfigParameters
```

BillingCenter

```
gw.api.system.BCConfigParameters
```

Example

For example:

```
var businessDayEnd = gw.api.system.PLConfigParameters.BusinessDayEnd.Value  
var forceUpgrade   = gw.api.system.PLConfigParameters.ForceUpgrade.Value
```

Adding custom MIME types

About this task

Perform the following steps to add application support for a new MIME type (Multipurpose Internet Mail Extension).

Note: Guidewire restricts uploads of files with text/html and application/octet-stream MIME types.

Procedure

1. If necessary, add the MIME type to the configuration of the application server. This step is dependent on the configuration requirements of the application server.
For example, Tomcat stores MIME type information in the `web.xml` configuration file in a series of `<mime-mapping>` tags. Verify that the needed MIME type exists in the appropriate file. If necessary, add it.

2. Add the new MIME type to the application `config.xml` file in the `<mimetyperemapping>` section.
 - For the `name` attribute, specify the name of the MIME type, such as `text/plain`.
 - For the `extensions` attribute, specify the file extensions used by the MIME type. If the MIME type is used by more than one file extension, separate each extension with a “|” character. The application uses this information to associate MIME types and file extensions. If retrieving a file extension from a MIME type, the application uses the first extension in the list. If retrieving a MIME type from a file extension, the application uses the first `<mimetype>` entry associated with the extension.
 - For the `icon` attribute, specify the image to use for documents of the MIME type. For example, Tomcat assumes the images are stored in the `tomcat/webapps/xx/resources/images` directory.
 - If you want to prevent users from uploading the MIME type to the application, set the `restrictUploads` attribute to `true`.
3. Create a description for the MIME type. The description is stored in the `displaykey` files. The definition has a prefix of `Mimetype`. (notice the prefix-terminating period) followed by the MIME type name attribute specified in the type’s definition in the `config.xml` `<mimetyperemapping>` section. Any non-alphanumeric character in the name must be replaced with an underscore character. For example, the `text/plain` MIME type would have a `displaykey` description of `Mimetype.text_plain`.

Account parameters

PolicyCenter provides the following configuration parameters in the `config.xml` file related to approval activities.

For information on editing `config.xml` and setting configuration parameters, see “Working with configuration parameters” on page 17.

`AccountsWithdrawnAfterMonths`

This parameter is one of the factors that Account Withdraw Evaluation batch processing uses to evaluate whether to change an account's status to withdrawn. If the creation time or origination date of the account is greater than this value in months, then the account can be withdrawn.

Applies to: PolicyCenter

Default: 37 months

Approval parameters

Guidewire provides the following configuration parameters in the `config.xml` file related to approval activities.

Applies to: ClaimCenter

`BulkInvoiceApprovalPattern`

Name of the activity pattern to use if creating bulk invoice approval activities.

Applies to: ClaimCenter

Required: Yes

`PaymentApprovalPattern`

Name of an approval activity pattern to use if creating payment approval activities.

Applies to: ClaimCenter

Required: Yes

RecoveryApprovalPattern

Name of the activity pattern to use if creating recovery approval activities.

Applies to: ClaimCenter

Required: Yes

RecoveryReserveApprovalPattern

Name of the activity pattern to use if creating recovery reserve approval activities.

Applies to: ClaimCenter

Required: Yes

ReserveApprovalPattern

Name of the approval activity pattern to use if creating reserve approval activities.

Applies to: ClaimCenter

Required: Yes

Archive parameters

See "Enabling archiving" in *Data Archiving*.

Guidewire provides the following configuration parameters in the `config.xml` file that relate to archiving.

ArchiveDaysRetrievedBeforeArchive

For BillingCenter, the minimum number of days that must pass after restoring a policy period before it is possible to archive the policy period again.

For PolicyCenter, the minimum number of days that must pass after restoring a policy term before it is possible to archive the term again.

Applies to: PolicyCenter, BillingCenter

Default: 90

ArchiveDefaultRecheckDays

For BillingCenter, the minimum number of days that must pass before reconsidering a policy period for archiving after a previous check did not identify the policy period as an archiving candidate.

For PolicyCenter, the minimum number of days that must pass before reconsidering a policy term for archiving after a previous check did not identify the policy term as an archiving candidate.

Applies to: PolicyCenter, BillingCenter

Default: 30

ArchiveEnabled

A Boolean string that specifies whether archiving is enabled or disabled. If set to `true`, an archive storage area must be implemented. An archive storage area can be implemented as a database, a regular file on a storage system, or some other desired method of storage. The application base configuration does not provide an archive storage area.

This parameter also controls the creation of indexes on the `ArchivePartition` column. If you set the value of this parameter to `true`, the application creates a non-unique index on the `ArchivePartition` column for `Extractable` entities.

In ClaimCenter, if the Extractable entity is Keyable, ClaimCenter creates a unique index on the ID and ArchivePartition columns.

In PolicyCenter, ArchiveEnabled controls whether or not the domain graph is started. If this parameter and DisableDomainGraphSupport are both true, the server will not start.

The value of ArchiveEnabled is semi-permanent, meaning that after you start the production server, you can change the value of this parameter from false to true, but not the converse.

WARNING: After you set ArchiveEnabled to true and start the server, you cannot change the value again. If you reset the value to false, the server will not start.

Default: false

Required: Yes

Permanent: Semi-permanent

ArchivePolicyPeriodDays

Minimum numbers of days that must pass after a policy period is closed before it is eligible for archiving. The parameter value is also used to determine whether an invoice or distribution can be safely included in the freeze set.

Assigning the parameter a value lower than the default setting is not recommended.

Applies to: BillingCenter

Default: 731 (two years)

ArchivePolicyTermDays

Minimum number of days that must pass before the policy periods associated with a given policy term can be archived.

Applies to: PolicyCenter

Default: 366

ArchiveRecentJobCompletionDays

Minimum number of days that must pass after a job is closed before archiving the associated policy term. Jobs are associated with policy periods.

Applies to: PolicyCenter

Default: 90

AssignClaimToRetriever

Specifies to whom ClaimCenter assigns a retrieved claim:

- true assigns the claim to the user who retrieved the claim.
- false assigns a retrieved claim to the original group and user who owned it.

If it is not possible to reassign the claim to the original user, ClaimCenter assigns the retrieved claim to the supervisor of the group. If ClaimCenter cannot reassign the retrieved claim to the original group, ClaimCenter assigns the claim to defaultowner.

Applies to: ClaimCenter

Default: false

DaysClosedBeforeArchive

ClaimCenter bases archive eligibility on the entity.DateEligibleForArchive field. For an archivable entity to be eligible for archiving, its DateEligibleForArchive property must be a non-null date and time that is not later than the current system date and time. In general, ClaimCenter calculates the DateEligibleForArchive value using the following formula:

$\text{DateEligibleForArchive} = \text{DaysClosedBeforeArchive (in days)} + \text{current system date}$

Applies to: ClaimCenter

Default: 30

DaysRetrievedBeforeArchive

Used by the implementation of the IArchiveSource plugin in the base configuration to set the DateEligibleForArchive field on Claim as it retrieves a claim from the archive store. ClaimCenter calculates the DateEligibleForArchive value using the following formula:

$\text{DateEligibleForArchive} = \text{DaysRetrievedBeforeArchive (in days)} + \text{current system date}$

Applies to: ClaimCenter

Default: 100

DomainGraphKnownUnreachableTables

Use to define a comma-separated list of relative names of entity types that are linked to the graph through a nullable foreign key. This can be problematic because the entity can become unreachable from the graph if the foreign key is null. Naming the type in this configuration parameter suppresses the warning that would otherwise be generated for the type by the domain graph validator

Default: None

MaxNumberOfArchivedEntitiesToRestore

A numeric value that sets the maximum limit of input entity numbers that a user can enter at one time in the **Bulk Restore** screen. This limits the number of archived entities to you can restore in a single operation.

In PolicyCenter, it is possible to restore multiple policy terms using a single policy number.

Default: 2000

PolicySystemArchivingEnabled

It is possible to include archived policies in the ClaimCenter **Policy Select** search and the FNOL wizard **Find Policy** search. However, the policy system must retrieve any archived policies before ClaimCenter can use them. Configuration parameter PolicySystemArchivingEnabled controls whether you can include archived policies in searches.

This configuration parameter has the following valid settings:

PolicySystemArchivingEnabled	Meaning
true	The policy search result from both FNOL and policy select excludes archived policies.
false	If you also check Include Archived Policies in FNOL policy search or in the policy select screen, ClaimCenter includes archived policies in the search result. ClaimCenter also does the following: • Sets the Address, City, State, and postal code fields to blank for archived policies • Displays a Status column

Applies to: ClaimCenter

Default: false

RestorePattern

Code of the activity pattern that ClaimCenter uses to create retrieval activities. Upon retrieving a claim, ClaimCenter creates two activities:

- One activity for the retriever of the claim
- One activity for the assigned user of the claim, if different from the retriever

Applies to: ClaimCenter

Default: restore

SnapshotEncryptionUpgradeChunkSize

Limits the number of claim snapshots that ClaimCenter upgrades during a change to the encryption plugin or during a change to encrypted fields. Set this parameter to 0 to disable the limit.

Applies to: ClaimCenter

Default: 50000

Assignment parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to assignment.

For information on editing `config.xml` and setting configuration parameters, see “Working with configuration parameters” on page 17.

AssignmentQueuesEnabled

Whether to display the application interface portions of the assignment queue mechanism. If you turn this on, you cannot turn it off again while working with the same database.

Default: false

ExposureWWLEnabled

Whether to enable exposure assignment load balancing.

Applies to: ClaimCenter

Default: false

WeightedAssignmentEnabled

Whether to enable assignment load balancing.

Applies to: ClaimCenter

Default: false

WeightedAssignmentGlobalDefaultWeight

The global default weight of all assignable entities that do not match any classifications.

Applies to: ClaimCenter

Default: 10

Minimum: 0

Asynchronous quoting parameters

Guidewire provides configuration parameters in the `config.xml` file that relate to asynchronous quoting.

`AsynchronousQuotingEnabled`

If set to `true`, quoting for large policies runs asynchronously as a background process.

Applies to: PolicyCenter

Default: `false`

Autopilot workflow parameters

Guidewire provides a configuration parameter in the `config.xml` file that enables support for Autopilot workflows in PolicyCenter.

`AutopilotUserRoleAssignment`

Enables support for the Autopilot Workflow service for PolicyCenter. If set to `true`, loads Autopilot user data during server startup and assigns eligible items to this user.

Default: `false`

Batch process parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to batch processing.

`BatchProcessHistoryPurgeDaysOld`

Number of days to retain batch process history before the application deletes it.

Default: 45

`MaxCatastropheClaimFinderSearchResults`

Maximum number of claims that ClaimCenter relates to a single catastrophe in the `CatClaimFinder` batch process (used to find catastrophe-related claims).

Applies to: ClaimCenter

Default: 1000

Bulk invoice activity pattern parameters

Guidewire provides the following configuration parameters in the `config.xml` file that are used to create activities for bulk invoicing.

For information on editing `config.xml` and setting configuration parameters, see “Working with configuration parameters” on page 17.

`BulkInvoiceItemValidationFailedPattern`

Name of the activity pattern to use in creating an activity to alert about a failure during processing of a bulk invoice item.

Applies to: ClaimCenter

Required: Yes

BulkInvoiceUnableToStopPattern

Name of the activity pattern to use if creating an activity to alert that ClaimCenter was unable to stop a bulk invoice. More technically, it was not possible to update the status from Pending-stop or Stopped to Issued or Cleared.

Applies to: ClaimCenter

Required: Yes

BulkInvoiceUnableToVoidPattern

Name of the activity pattern to use in creating an activity to alert that ClaimCenter was unable to void a bulk invoice. More technically, it was not possible to update the status from Pending-void or Voided to Issued or Cleared.

Applies to: ClaimCenter

Required: Yes

Business calendar parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to defining a business calendar.

BusinessDayDemarcation

The time at which a business day begins.

Default: 12:00 AM

Set for server: Yes

BusinessDayEnd

Indicates the time at which the business day ends.

Default: 5:00 PM

Set for server: Yes

BusinessDayStart

Indicates the time at which the business day starts.

Default: 8:00 AM

Set for server: Yes

BusinessWeekEnd

The day of the week considered to be the end of the business week.

Default: Friday

Set for server: Yes

HolidayList (obsolete)

This parameter is obsolete. Do not use it. Previously, you would use this to generate a comma-delimited list of dates to consider as holidays. Instead, use the **Administration** screen within the application to manage the official designation of holidays. Guidewire retains this configuration parameter to facilitate upgrade from older versions of the application.

IsFridayBusinessDay

Indicates whether Friday is a business day.

Default: true

Set for server: Yes

IsMondayBusinessDay

Indicates whether Monday is a business day.

Default: true

Set for server: Yes

IsSaturdayBusinessDay

Indicates whether Saturday is a business day.

Default: false

Set for server: Yes

IsSundayBusinessDay

Indicates whether Sunday is a business day.

Default: false

Set for server: Yes

IsThursdayBusinessDay

Indicates whether Thursday is a business day.

Default: true

Set for server: Yes

IsTuesdayBusinessDay

Indicates whether Tuesday is a business day.

Default: true

Set for server: Yes

IsWednesdayBusinessDay

Indicates whether Wednesday is a business day.

Default: true

Set for server: Yes

MaxAllowedDate

The latest date allowed to be used.

Default: 2200-12-31

Set for server: Yes

MinAllowedDate

The earliest date allowed to be used.

Default: 1800-01-01

Set for server: Yes

Business rules parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to the business rules. Business rules, which you manage through the application **Administration** tab, are distinct from Gosu rules, which you manage through Guidewire Studio.

BizRulesCacheStaleTimeMinutes

Time (in minutes) that PolicyCenter retains rule data in the RuleVersion cache before it considers cached items to be stale and thus eligible for reaping.

PolicyCenter initializes the RuleVersion cache once, at server start up. It then rebuilds the cache every time the following entities change:

- RuleHead
- RuleVersion
- Rule

Applies to: ClaimCenter, PolicyCenter

Default: 60

Minimum: 1

Maximum: 120

Set for server: Yes

BizRulesDeploymentEnabled

Determines whether it is necessary to explicitly deploy a business rule before the application can evaluate the rule. If you set the value of this parameter to `true`, you must also provide a value for configuration parameter `BizRulesDeploymentId`.

IMPORTANT: Always set this parameter to `true` in a production environment.

Do not attempt to set this parameter to `true` in a non-production environment. If you do so, the server generates an error and does not start. In a non-production environment, with the value of this parameter set to `false`, the application evaluates all enabled and valid rules at runtime, including rules in the draft state.

ClaimCenter ignores this parameter if the value of parameter `BizRulesEnabled` is `false`.

Applies to: ClaimCenter, PolicyCenter

Default: `false`

BizRulesDeploymentId

Unique string identifier of the server to which you intend to deploy the business rules. There is no default value for this parameter. If the value of `BizRulesDeploymentEnabled` is `true`, then you must supply a value for this parameter. Otherwise, the server generates an error during server start and refuses to start. the application ignores this configuration parameter if the value of `BizRulesDeploymentEnabled` is `false`.

It is possible to change the value of this parameter through a server restart. However, if you change the value of `BizRulesDeploymentId`, the application does not update already deployed rule versions.

Guidewire recommends, in a production environment, that you have a single `BizRulesDeploymentId` value for the entire production cluster. This action guarantees that all nodes in the cluster use the same `BizRulesDeploymentId` parameter value. Using the same value on all cluster nodes ensures that rule deployment works consistently across all nodes in the cluster. You can choose any name for this value if you use only a single application production cluster. For example, if all nodes in a cluster point to a single database, you can use the database ID as the `BizRulesDeploymentId` value.

However, if you use multiple production clusters, each separate cluster must have its own unique value for this configuration parameter. The application expressly does not permit you to import business rules from another cluster instance that has the same `BizRulesDeploymentId` value as the cluster instance into which you are importing the rules.

The application associates the `BizRulesDeploymentId` value (name) with a rule during its deployment. Thus, if you deploy the rule in one production cluster, the name appears along with the rule version number in other production clusters to identify that the rule was deployed in a particular production cluster. For example, if the value of `BizRulesDeploymentId` is `GW100-A`, the rule version appears as `1.GW100-A` in all other production clusters.

Applies to: ClaimCenter, PolicyCenter

Default: None

[See also](#)

- *Administration Guide*

BizRulesEnabled

Determines whether the application enables the use of activity business rules. If set to `true`, the application displays the **Business Rules** screens in the **Administration** tab to users with the appropriate privileges.

Applies to: ClaimCenter

Default: `true`

BizRulesExposureDisabledWhenIncidentOnly

Determines whether the ClaimCenter business rules create exposures for incident-only claims. Set this parameter to one of the following Boolean values.

<code>true</code>	ClaimCenter does not trigger the Exposure rules if the claim is marked as incident-only.
<code>false</code>	ClaimCenter triggers the exposure rules for incident-only claims.

Applies to: ClaimCenter

Default: `true`

BizRulesImportBootstrapRules

Whether the application imports the business rules located in folder `config/import/bizrules` on starting the application server with an empty database. Set the value of this parameter to `true` to import the files located in the `bizrules` folder.

IMPORTANT: Guidewire recommends that you set the value of this configuration parameter to `true` in a non-production test environment only.

Applies to: ClaimCenter, PolicyCenter

Default: `false`

[See also](#)

- *InsuranceSuite Business Rules Administration*

BizRulesLeafSearchNumOfHops

Maximum number of hops for a leaf search to search through in suggesting matching results. This parameter refers to the autocomplete feature of the **Rule Condition** editor on the **Business Rules** detail screens.

In the following expression, A is the root, B is a single hop, and C is a leaf.

```
A.B.C
```

The following example illustrates a two hop expression, with the root being `office` and `PhoneNumber` the leaf.

```
office.ConferenceRooms[0].Table.PhoneNumber
```

Applies to: ClaimCenter, PolicyCenter

Default: 3

BulkLoadRuleHeadByIdCacheEnabled

The Rule Head cache stores the RuleHead IDs for all business rules used in the application. If not configured to do otherwise, the application populates this cache using multiple database queries. The use of multiple queries can greatly impact the performance of the business rules. However, if you set this configuration parameter to `true`, the application uses a single database query to bulk load the cache, thereby significantly improving the performance of the business rules.

This parameter can take the following values:

- `true` - the application uses a single query to populate the Rule Head cache.
- `false` - the application uses multiple queries to populate the Rule Head cache.

Note: For information on how to bulk load the Rule Head cache at server start, see the *Administration Guide*.

Applies to: ClaimCenter, PolicyCenter

Default: `true`

OnlineJavadocPrefix

Prefix to a URL for Javadoc. Override the default URL to point a different Javadoc location. For example, use this value to point to a local Javadoc instance.

IMPORTANT: Do not use file protocol to define this value due to JavaScript security issues.

Applies to: ClaimCenter

Default: <https://docs.oracle.com/en/java/javase/11/docs/api/>

PreloadBizRulesBeansCacheEnabled

The Rule Entities cache stores the entities that comprise the entire rule graph for all rule versions that can possibly execute in the application. If not configured to do otherwise, the application populates this cache using multiple database queries. The use of multiple queries can greatly impact the performance of the business rules. However, if you set this configuration parameter to `true`, the application uses a single database query to bulk load the cache, thereby significantly improving the performance of the business rules.

This parameter can take the following values:

- `true` - the application uses a single query to preload the Rule Entities cache with business rule entities from the database.

- `false` - the application uses multiple queries during rule execution to fetch the necessary business rule entities.

Note: For information on how to bulk load the Rule Entities cache at server start, see the *Administration Guide*.

Applies to: ClaimCenter, PolicyCenter

Default: `true`

Cache parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to the application cache.

For information on editing `config.xml` and setting configuration parameters, see “Working with configuration parameters” on page 17.

See also

- *InsuranceSuite Server Administration*

ActivityPatternCacheMaxDuration

Upper bound on how long caches of activity pattern entities are allowed to exist without refresh, measured in seconds.

Applies to: ClaimCenter

Default: 86400

ChargePatternCacheRefreshIntervalSecs

The time between refreshes of the charge pattern cache, in seconds. This integer value must be 0 or greater.

Applies to: BillingCenter

Default: 3600

ExchangeRatesCacheRefreshIntervalSecs

The time between refreshes of the `ExchangeRateSet` cache, in seconds. This integer value must be 0 or greater. See the *Administration Guide* for more information.

Default: 600

GlobalCacheActiveTimeMinutes

Time period (in minutes) in which the application considers cached items as *active*, meaning that Guidewire recommends that the cache give higher priority to preserve these items. You can think of this as the period during which the application is using one or more items very heavily. For example, this can be the length of time that a user stays on a page. The maximum value for this parameter is the smaller of 15 and the value of `GlobalCacheStaleTimeMinutes`.

IMPORTANT: The value of `GlobalCacheActiveTimeMinutes` must be less than that of `GlobalCacheReapingTimeMinutes`. If the value of `GlobalCacheActiveTimeMinutes` is greater than that of `GlobalCacheReapingTimeMinutes`, the cache does not start.

See the *InsuranceSuite Server Administration* for more information.

Default: 5

Minimum: 1

Maximum: 15

Set for server: Yes

GlobalCacheDetailedStats

Configuration parameter `GlobalCacheDetailedStats` determines whether to collect detailed statistics for the global cache. Detailed statistics are data that the application collects to explain why items are evicted from the cache. The application collects basic statistics, such as the miss ratio, regardless of the value of this parameter.

In the base configuration, Guidewire sets the value of the `GlobalCacheDetailedStats` parameter to `false`. Set the parameter to `true` to help tune your cache.

At runtime, use the **Management Beans** page to enable the collection of detailed statistics for the global cache. If you disable the `GlobalCacheDetailedStats` parameter, the application does not display the **Evict Information** and **Type of Cache Misses** graphs.

Default: `false`

Dynamic: Yes

Required: Yes

GlobalCacheReapingTimeMinutes

Time (in minutes) since the last use before the application considers cached items to be eligible for reaping. You can think of this as the period during which the application is most likely to reuse an entity. See *InsuranceSuite Server Administration* for more information.

IMPORTANT: The value of `GlobalCacheReapingTimeMinutes` must be greater than that of `GlobalCacheActiveTimeMinutes`. If the value of `GlobalCacheActiveTimeMinutes` is greater than that of `GlobalCacheReapingTimeMinutes`, the cache does not start.

Default: 15

Minimum: 1

Maximum: 15

Set for server: Yes

GlobalCacheSizeMegabytes

The amount of space to allocate to the global cache. If you specify this value, it takes precedence over `GlobalCacheSizePercent`. See the *InsuranceSuite Server Administration* for more information.

Default: 25

Nullable: Yes

Set for server: Yes

GlobalCacheSizePercent

The percentage of the heap to allocate to the global cache. See the *InsuranceSuite Server Administration* for more information.

Default: 15

Set for server: Yes

GlobalCacheStaleTimeMinutes

Time (in minutes) since the last write before the application considers cached items to be stale and thus eligible for reaping. See the *Administration Guide* for more information.

Default: 60

Minimum: 1

Maximum: 120

Set for server: Yes

Dynamic: Yes

GlobalCacheStatsRetentionPeriodDays

Time period (in days), in addition to today, for how long the application preserves statistics for historical comparison. See *InsuranceSuite Server Administration* for more information.

Default: 7

Minimum: 2

Maximum: 365

Set for server: Yes

GlobalCacheStatsWindowMinutes

Time period (in minutes). The application uses this parameter for the following purposes:

- To define the period of time to preserve the reason for which the application evicts an item from the cache, after the event occurred. If a cache miss occurs, the application looks up the reason and reports the reason in the **Cache Info** page.
- To define the period of time to display statistics on the chart on the **Cache Info** page.

See the *InsuranceSuite Server Administration* for more information.

Default: 30

Minimum: 2

Maximum: 120

Set for server: Yes

GroupCacheRefreshIntervalSecs

The time in seconds between refreshes of the group cache. This integer value must be 0 or greater. See the *Administration Guide* for more information.

Default: 600

PlanOrderCacheRefreshIntervalSecs

The time between refreshes of the plan order cache, in seconds. This integer value must be 0 or greater.

Applies to: BillingCenter

Default: 600

ResetGlobalCacheOnSwitchFromReadOnlyToNormal

Whether to reset global cache when switching from Read-Only to Normal mode.

Default: false

ScriptParametersRefreshIntervalSecs

The time between refreshes of the script parameter cache, in seconds. This integer value must be 0 or greater. See the *Administration Guide* for more information.

Default: 600

TAccountPatternCacheRefreshInternalSecs

The time between refreshes of the charge pattern cache, in seconds. This integer value must be 0 or greater.

Applies to: BillingCenter

Default: 3600

ZoneCacheRefreshIntervalSecs

The time between refreshes of the zone cache, in seconds. See the *Administration Guide* for more information.

Default: 86400

Catastrophe heat map parameters

Before you can use the **Catastrophe Search** page and its catastrophe heat map, you must enable the functionality. For details, see *InsuranceSuite Server Administration*.

Guidewire provides the following configuration parameters in the `config.xml` file that relate to the catastrophe map.

For information on editing `config.xml` and setting configuration parameters, see “Working with configuration parameters” on page 17.

Applies to: ClaimCenter

CatastropheClaimHeatMapCacheRefreshSecs

Set the interval (in seconds) at which the catastrophe heat map will refresh claim information from the database into the cache. A smaller interval will provide more up-to-date information, but will impact performance.

Applies to: ClaimCenter

Default: 3600

CatastrophePolicyLocationHeatMapCacheRefreshSecs

Set the interval (in seconds) at which the catastrophe heat map will refresh policy information from the database into the cache. A smaller interval will provide more up-to-date information, but will impact performance.

Applies to: ClaimCenter

Default: 3600

HeatMapCredential

Set this configuration parameter to the credential associated with heat maps you obtained during the licensing process. This parameter is passed to the map service, such as Bing Maps or Azure Maps, and used in the “HeatMapServiceTemplate” on page 35 parameter.

Applies to: ClaimCenter

Default: None

HeatMapPolicyLocationDemo

Enable the display of policy locations for demonstration purposes in the catastrophe heat map and the **Policy Locations** tab in the **Administration > Business Settings > Catastrophe Details** screen.

Applies to: ClaimCenter

Default: false

HeatMapServiceTemplate

Set to the fully qualified name of the Gosu template map service to use (such as Bing Maps or Azure Maps) for heat maps in the catastrophe search screen. For example, `gw.api.heatmap.BingMap2`.

Applies to: ClaimCenter

Default: *None*

Claim health indicator and metric parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to the claim metrics.

For information on editing `config.xml` and setting configuration parameters, see “Working with configuration parameters” on page 17.

Applies to: ClaimCenter

ClaimHealthCalcMaxLossDateInYears

Maximum number of years to look back to find claims on which to calculate metrics and indicators. This parameter strictly limits the number of claims found for the `ClaimHealthCalcuation` batch process.

Applies to: ClaimCenter

Default: 2

InitialReserveAllowedPeriod

Number of days that new initial reserves contribute to the initial reserve sum of the `Percent * Reserve Change Claim Metric` calculation after ClaimCenter creates the first initial reserve. An initial reserve is a reserve that ClaimCenter creates during creation of a claim or exposure. It is also the first set of reserves that ClaimCenter creates on the claim or exposure if there are no previous reserves for those entities.

Applies to: ClaimCenter

Default: 3

MaxClaimResultsPerClaimHealthCalcBatch

Maximum number of claims for each invocation of the `ClaimHealthCalculation` batch process to calculate metrics and indicators. This parameter strictly limits the number of claims that can be processed at a single time. The `ClaimHealthCalculation` batch process calculates the claim metrics and indicators for found claims.

Applies to: ClaimCenter

Default: 1000

Cloud API parameters

Guidewire provides the following configuration parameters in the `config.xml` file related to Cloud API.

For information on editing `config.xml` and setting configuration parameters, see “Working with configuration parameters” on page 17.

AllowedCompositeRequestTags

A comma-separated list of tags that will be allowed as the `requestTag` value of a Composite API request. Values not present in this list are ignored and not sent as metric tags. Tag names must start with a letter, consist of alphanumeric characters or underscores, and are limited to at most 150 characters. The list of allowed tags is limited to 100 unique values.

Dynamic: Yes

EnableWorkersCompMainInjuryIncidentInCloudAPI

Whether to provide access to the `mainWorkersCompInjuryIncident` property on the `InjuryIncident` schema.

When this is set to true, workers' compensation claims must be submitted within the context of a composite request. There must be a "main" injury incident, and it must be included in the injury incidents collection endpoint.

When this is set to false, workers' compensation claims can be submitted outside of a composite request. But, future calls will not have access to the `mainWorkersCompInjuryIncident` property.

Applies to: ClaimCenter

Default: true

GiveInternalUsersFullPermissionsInCommonActivitiesApi

This parameter determines which activities an internal user can view when calling the GET `/common/v1/activities` endpoint.

When true, internal users can access all activities they have permission to access according to their Access Control Lists.

When false, internal users can view only activities that are explicitly assigned to them.

Applies to: ClaimCenter

Default: true

GiveProducerAccessToAllExposures

If true, a caller who is accessing exposures the Cloud API and who is using the `producerCodes` resource access strategy has a privileged view of all exposures where the claimant is a contact with at least one producer accessible role ("*first-party exposures*"). They have a restricted view of all other exposures ("*third-party exposures*").

If false, the caller still has a privileged view of all first-party exposures. But, they cannot access third-party exposures.

Applies to: ClaimCenter

Default: true

MaximumAllowedNumberOfBatchSubRequests

The maximum number of subrequests allowed in a Cloud API batch request.

Default: 100

MaximumAllowedNumberOfCompositeSubRequests

The maximum number of subrequests allowed in a Cloud API composite request.

Default: 100

RequireExposuresToBeNewLossWhenSubmittingWithCloudAPI

For claims submitted through Cloud API, this controls which validation level any exposures on the claim must reach for the submit to succeed.

- If set to false, exposures must reach Load Save only. (This matches the behavior of the New Claim wizard.)
- If set to true, exposures must reach New Loss Completion. (This matches the behavior of the Cloud API releases from 2020.05 (Aspen) through 2024.02 (Jasper).)

Applies to: ClaimCenter

Default: true

RestAPIsGeneratingByPolicyLine

When false, LOB-specific endpoints are generated at the product level. When true, LOB-specific endpoints are generated at the policy line level. If you have multi-line products that share one or more sets of LOB-specific endpoints, set this value to true.

Applies to: PolicyCenter

Default: true

RestJobRecoveryExpirationDate

The number of days past the current date when a job becomes too old to be recoverable.

Applies to: PolicyCenter

Default: 7

RestJobRecoveryMaxResults

The maximum number of jobs that are returned by the /recover-new-jobs endpoint.

Applies to: PolicyCenter

Default: 5

RoleNameCacheStaleTimeMinutes

Time (in minutes) since the last bean change to Roles to consider the RoleNameCache stale. When the cache is considered stale, the application reloads it.

Set for server: Yes

Default: 60

Minimum: 1

Maximum: 720

Dynamic: Yes

Data destruction parameters

Guidewire provides configuration parameters in the config.xml file that relate to destruction of data. In the base configuration of the application, data destruction is not enabled. You must set configuration parameters to enable data destruction.

[See also](#)

- “Data destruction configuration parameters”
- “Working with configuration parameters” on page 17

ContactDestructionRequestAgeForPurgingResults

Used by the RemoveOldContactDestructionRequest work queue to determine the age of PersonalDataDestructionRequest objects that have a status of Finished. In the base configuration, this parameter is set to 10 days.

Default: 10

[See also](#)

- *Plugins, Prebuilt Integrations, and SOAP APIs*

DataDestructionMaxWaitForBlockingMessagesToFinish

Used by the DestroyContactForPersonalData work queue to determine the maximum number of seconds to wait for Solr messages in the queue to clear before retrying personal data destruction purging requests. Personal data destruction requests will retry every second until the queue is clear or the parameter threshold is reached. In the base configuration, this parameter is 60 seconds.

This parameter only applies if Solr free-text search and personal data destruction is enabled. The purpose of this parameter is to allow the Solr message queue to complete removal of purged contacts from the Solr index, which must be performed before the personal data destruction work queue can start.

If purging of claim and contact data is unsuccessful, it is recommended you increase the number of seconds in the parameter to allow the Solr message queue to clear. For example, if you set this parameter to 180 seconds, the purge request will retry every second for three minutes. Likewise, setting the parameter to 0 will bypass the Solr message queue check altogether and attempt to purge immediately.

Applies to: ClaimCenter

Default: 60

PersonalDataDestructionEnabled

Set this parameter to true to enable destruction of personal data. In the base configuration, this parameter is false.

PolicyCenter won't start if both PersonalDataDestructionEnabled and DisableDomainGraphSupport parameters are true.

Default: false

[KeepPurgedRootForDays](#)

Used by the PurgeOldPurgedRootInfo work queue to determine the age of PurgeOldPurgedRootInfo objects. In the base configuration, this parameter is set to 180 days.

Applies to: PolicyCenter

Default: 180

[See also](#)

- *Plugins, Prebuilt Integrations, and SOAP APIs*

Deduction parameters

Guidewire provides the following configuration parameters in the config.xml file that relate to deductions.

Applies to: ClaimCenter

BackupWithholdingTypeCode

The typecode in the DeductionType typelist for backup withholding. The default is `irs`. You must define this parameter for the backup withholding plugin to work. Also, this parameter must also correspond to a valid DeductionType typecode.

Applies to: ClaimCenter

Default: `irs`

CalculateBackupWithholdingDeduction

Whether ClaimCenter calculates backup withholding for applicable checks.

Applies to: ClaimCenter

Default: `true`

StandardWithholdingRate

Standard backup withholding rate, as defined by the U.S. Internal Revenue Service, for use by the backup withholding plugin. The number is a percentage. (For example, 28.0 means 28.0 percent.) The backup withholding plugin does not work if you do not define this parameter.

Applies to: ClaimCenter

Default: `28.0`

Desktop and team parameters

Guidewire provides the following configuration parameters in `config.xml` that relate to the **Desktop** and **Team** tabs.

Applies to: PolicyCenter

ActivityStatisticsWindowSize

Time window to capture activity statistics.

Applies to: PolicyCenter

Default: `0`

CanceledActivityRetentionWindow

Minimum number of days that must pass after the activity has been canceled before it can be retired.

Applies to: PolicyCenter

Default: `30`

OtherWorkOrdersStatisticsWindowSize

Time window that the **Team** tab uses to calculate statistics for work orders other than renewals and submissions. Possible values are:

0	Use this week as the window, defined as the start of the current business week until now.
-1	Use this month as the window, defined as the start of the current month until now.
Any positive integer N The window is the last N days of activity, including the current day.	

Applies to: PolicyCenter

Default: 0

[See also](#)

- *Configuration Guide*
- *Application Guide*

RenewalsStatisticsWindowSize

Time window that the **Team** tab uses to calculate renewal statistics. Possible values are:

0	Use this week as the window, defined as the start of the current business week until now.
-1	Use this month as the window, defined as the start of the current month until now.
Any positive integer N The window is the last N days of activity, including the current day.	

Applies to: PolicyCenter

Default: 0

[See also](#)

- *Configuration Guide*
- *Application Guide*

SearchActivityThresholdDays

This parameter controls the threshold within which an activity must have been modified to qualify a job as being assigned to a user. The `UpdateTime` field on an activity contains a timestamp of when the activity was last modified. The activity must have been modified within `SearchActivityThresholdDays` days before the current date.

Applies to: PolicyCenter

Default: 366

[See also](#)

- *Configuration Guide*
- *Application Guide*

SubmissionsStatisticsWindowSize

Time window that the **Team** tab uses to calculate submission statistics. Possible values are:

0	Use this week as the window, defined as the start of the current business week until now.
-1	Use this month as the window, defined as the start of the current month until now.
Any positive integer N The window is the last N days of activity, including the current day.	

Applies to: PolicyCenter

Default: 0

[See also](#)

- *Configuration Guide*
- *Application Guide*

TeamScreenTabVisibilityRowCountCutoff

This parameter sets the maximum number of rows on the **Team** tab screens. Increasing this parameter potentially increases the amount of time that PolicyCenter takes to render the **Team** screens. If the results exceed the value of this parameter, then PolicyCenter displays a message on that screen and does not display the results.

If you select an individual user, PolicyCenter always displays the filtered results even if the number of results exceeds the cutoff parameter.

Applies to: PolicyCenter

Default: 200

- *Configuration Guide*
- *Application Guide*

Document creation and document management parameters

Guidewire provides configuration parameters in the `config.xml` file that relate to document creation and management.

DisplayDocumentEditUploadButtons

Whether the **Documents** list displays **Edit** and **Upload** buttons. Set this parameter to `false` if the `IDocumentContentSource` integration mechanism does not support it.

Default: `true`

DocumentContentDispositionMode

The Content-Disposition header setting to use when the application returns document content directly to the browser. Supported settings are `inline` and `attachment`.

Default: `inline`

DocumentTemplateDescriptorXSDLocation

The path to the XSD file that the application uses to validate document template descriptor XML files. Specify this location relative to the following directory:

```
modules/configuration/config/resources/doctemplates
```

FinalDocumentsNotEditable

Indicates whether documents with Final status can be transferred by using the Asynchronous implementation of the `IDocumentContentSource` plugin. A value of `false` indicates that documents with Final status can be transferred. A value of `true` indicates that documents with Final status cannot be transferred.

Default: `false`

MaximumFileUploadCount

The maximum number of document content files that can be listed and uploaded at once. The number of files listed for upload can affect the performance of the upload screen.

Default: 200

MaximumFileUploadSize

The maximum allowable size in megabytes for a document file that you can upload to the server. Attempting to upload a file larger than this size results in failure. Because the uploaded document must be handled on the server, this parameter protects the server from possible memory consumption problems.

ClaimCenter default: 25 MB

PolicyCenter default: 150 MB

BillingCenter default: 20 MB

MaximumTotalUploadSize

The maximum allowable total size in megabytes per session for documents uploads that are pending commitment to the document management system. Because multiple documents can be uploaded at once, this value also provides control of the overall size of an upload and protects the server from possible memory consumption problems.

ClaimCenter default: 25 MB

PolicyCenter default: 150 MB

BillingCenter default: 20 MB

Environment parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to the application environment.

For information on editing `config.xml` and setting configuration parameters, see “Working with configuration parameters” on page 17.

AddressDeletionDelay

Sets the amount of time to wait (in minutes) before an `AddressDeleteWorkQueue` work item deletes an address marked as potentially orphaned. During an entity bundle commit, it is possible for an address to become orphaned if there is no longer an entity that points to the address.

ClaimCenter manages the `AddressDeleteWorkQueue` work queue internally. It is not possible to either schedule this work queue or to run it from the ClaimCenter user interface.

Applies to: ClaimCenter

Default: 1

AddressVerificationFailureAsError

Set to `true` to have address verification failures shown as errors instead of warnings. This parameter has no effect if `EnableAddressVerification` is set to `false`.

Applies to: ClaimCenter, PolicyCenter

Default: `false`

[See also](#)

- “`EnableAddressVerification`” on page 44

AllowStartupInDevelopmentModeWithDomainGraphErrors

Whether the application can be started in development mode while there are domain graph errors.

Set this parameter to `true` if you wish to do development work before fixing domain graph errors.

This parameter is ignored when running in production mode. The application can't be started in production mode while there are domain graph errors. This is true even if archiving has been disabled.

Applies to: BillingCenter, PolicyCenter

Default: false

CollapseFutureInvoicesUponCancellation

Whether to collapse future invoices into a single invoice any time that BillingCenter receives a cancellation billing instruction.

Applies to: BillingCenter

Default: true

CommissionRemainderTreatment

How to distribute the remainder amount for a commission in pro rata calculations. Valid values are:

- overweightFromFront
- overweightFromBack
- overweightFirst
- overweightLast
- writeoff

Applies to: BillingCenter

Default: writeoff

Note: In previous releases, Guidewire called the `CommissionRemainderTreatment` configuration parameter `AgencyBillCommissionRemainderTreatment`.

CreateSmartReinstatementSnapshotItems

Whether to have BillingCenter create cancellation snapshots of invoice items on policies that are about to be canceled before any other cancellation processing occurs.

Applies to: BillingCenter

Default: true

CurrentEncryptionPlugin

Set this value to the name of the plugin that you intend to use to manage encryption. This plugin implements the `IEncryption` plugin interface. Typically, a Guidewire installation has only a single implementation of an encryption plugin interface. However, you can decide to implement a different encryption algorithm using a different implementation of the encryption interface as part of an upgrade process. In this case, you must retain your old encryption plugin implementation in order to support the upgrade and any archived items that use the previous implementation.

To support multiple implementations of the encryption plugin, the application provides the `CurrentEncryptionPlugin` configuration parameter. Set this configuration parameter to the value of the `EncryptionIdentifier` property of the encryption plugin currently in use.

- If you do not provide a value for this configuration parameter or if the value is an empty string, data is unencrypted.
- If you provide a value for this configuration parameter that does not match the value of the `EncryptionIdentifier` property of an encryption plugin implementation, the server cannot start.

- If you create multiple implementations of the encryption plugin interface, you must name each plugin implementation individually and uniquely. The application retrieves the name of the plugin from the `EncryptionIdentifier` property.

IMPORTANT: InsuranceSuite applications don't provide a production-level encryption algorithm. You must determine the best method to encrypt your data and implement it.

Default: None

[See also](#)

- For information on using the Plugins Registry editor, see “Using the Plugins Registry editor”.
- *Plugins, Prebuilt Integrations, and SOAP APIs*

DaysBeforeAccountIsConsideredInactive

Number of days to wait before deciding that this account is inactive. Batch process `AccountInactivityBatchProcess` uses this value to determine whether an account is inactive.

Applies to: BillingCenter

Default: 60

DeprecatedEventGeneration

Whether to use the now-deprecated event logic that had previously been available.

Applies to: ClaimCenter, PolicyCenter

Default: false

EnableAddressVerification

Set this value to true to enable address verification warnings. Address verification checks that all the fields match each other based on the zone data.

This parameter works in concert with the `AddressVerificationFailureAsError` parameter to show either a warning or an error, as follows:

- If `EnableAddressVerification` is true and `AddressVerificationFailureAsError` is false, the application shows a warning message if verification against zone data fails.
- If `EnableAddressVerification` is true and `AddressVerificationFailureAsError` is true, the application shows an error message if verification against zone data fails.
- If `EnableAddressVerification` is false, the application does not verify the address based on zone data.

Applies to: ClaimCenter, PolicyCenter

Default: false

[See also](#)

- “`AddressVerificationFailureAsError`” on page 42

EnableChargeProRataTxCreation

Specify whether to create `ChargeProRataTX` entities.

WARNING: Guidewire recommends tracking earned premium in the policy administration system and not in BillingCenter. Consequently, Guidewire recommends against enabling this option.

BillingCenter normally creates ChargeProRataTx entities when a Charge is created with a ChargePattern subtype of ProRataCharge. The entities are subsequently processed by the ChargeProRataTx batch process to track earned premium. If you do not use BillingCenter to track earned premium, the ChargeProRataTx entities are not needed. When EnableChargeProRataTxCreation is set to false, ChargeProRataTx entities are not created.

If EnableChargeProRataTxCreation is set to false, it cannot be enabled again at a later time. Because the default setting is false, the parameter can be set to true only when initially deploying BillingCenter.

The EnableChargeProRataTxCreation parameter and ChargeProRataTx batch process are used only to track earned premium. If you do not use BillingCenter to track earned premium, leave the parameter set to false, and do not run the batch process. Any existing ChargeProRataTx entities not processed by the ChargeProRataTx batch process are ignored by BillingCenter.

Applies to: BillingCenter

Default: false

EnableBatchPayments

Enable creation, posting, and reversing of batch payments.

Applies to: BillingCenter

Default: false

EnableInternalDebugTools

Make internal debug tools available to developers.

Default: false

Set for server: Yes

EntityValidationOrder

Order in which to execute validation if validating multiple entities. ClaimCenter validates all other validatable entities not specified in this list after all listed entities, in no particular order.

Note: Guidewire does not guarantee that the application validates entities of a given type (such as the exposures on a claim) in any deterministic order with respect to one another.

Applies to: ClaimCenter

Default: Policy, Claim, Exposure, Matter, TransactionSet

ExternalIDPrefix

The prefix to use for external IDs generated by the application. Generated external IDs will be of the form *prefix:id* where *id* is the actual ID for the entity. Guidewire strongly recommends that you set this parameter to different values in production and test environments to allow for the clean import and export of data between applications.

This prefix must not exceed 9 characters in length. Use only letters and numbers. Do not use space characters, colon characters, or any other characters that other applications might process or escape specially.

Applies to: PolicyCenter

Required: Yes

Default: pcext

GosuSampleDataMethod

Method on Gosu class DataSets.gs that creates sample data.

Applies to: BillingCenter

Default: createBillingCenterSampleData

IBillingCenterAPICDCENumRetries

The number of times BillingCenter retries billing instructions in the case of a ConcurrentDataChangeException. This integer value must be 1 or greater.

Applies to: BillingCenter

Default: 50

IncludeClosedPoliciesInAccountAggregateBalances

Whether BillingCenter includes closed policies in the totals returned by the balance methods for an account.

Applies to: BillingCenter

Default: false

InvoicePeriodCutoff

Specifies the time of day that invoices become billable. The Invoice batch process considers an invoice to be billable if it meets both of the following criteria:

- Its bill date is on or before the current date.
- The batch process is run on or after the InvoicePeriodCutoff time.

Applies to: BillingCenter

Default: 12:00 AM

InvoicePeriodDueCutoff

Specifies the time of day that invoices become due. The InvoiceDue batch process considers an invoice to be due if its due date is before the current date and the batch process runs on or after the InvoicePeriodDueCutoff time.

Applies to: BillingCenter

Default: 12:00 AM

KeyGeneratorRangeSize

The number of key identifiers (as a block) that the server obtains from the database with each request. This integer value must be 0 or greater.

As you create a new application object such as a Policy, the application assigns it a key, or unique public identifier. To ensure that keys are unique, the server requests an available key from the application database. If every server in a cluster queried the database each time it needed a single key, performance would degrade.

Instead, use this configuration parameter to obtain a block of keys with a single request. For example, a server can reserve a block of 100 keys, and then assign each key without needing to query the database again. The server continues to assign the keys from a block until it uses all keys in that block.

In the base configuration, Guidewire sets the default value of this parameter to 100. For small test environments, this value is likely large enough to prevent frequent database queries for more keys. It is also small enough to not waste too many keys that the server reserves but never uses.

However, for large production systems, the value of this parameter needs to be much larger. For example, for a production database with 20,000 concurrent users, try setting this value to 2000.

As the server shuts down, it discards keys that are allocated but are unused. As keys are 64-bit integers, wasting a few keys is not an issue.

Default: 100

MemoryUsageMonitorIntervalMins

How often the application server logs memory usage information, in minutes. This is often useful for identifying memory problems.

To disable the memory monitor, do one of the following:

- Set this parameter to 0.
- Remove this parameter from `config.xml`.

Default: 0

PASEffectiveTime

Effective time to use in the Policy Administration System (PAS). The PAS uses this value as the default time for any passed-in date.

Applies to: BillingCenter

Default: 12:01 AM

PolicyClosureBufferDays

Specifies the number of days past a policy period's expiration date before the period will be considered for closure. For flat-canceled policy periods, the parameter specifies the number of days past the period's effective date before the period will be considered for closure.

Applies to: BillingCenter

Default: 60

PublicIDPrefix

The prefix to use for public IDs generated by the application. Generated public IDs are of the form *prefix:id*. This *id* is the actual entity ID. Guidewire strongly recommends that you set this parameter to different values in production and test environments to allow for the clean import and export of data between applications.

This `PublicIDPrefix` must not exceed 9 characters in length. Use only letters and numbers. Do not use space characters, colon characters, or any other characters that other applications might process or escape specially. Do not specify a two-character value. Guidewire reserves for itself all public IDs that start with a two-character ID and then a colon.

IMPORTANT: Guidewire reserves two-character public ID prefixes for its own current or future use.

Required: Yes

Default: *None*

ResourcesMutable

Indicates whether resource are mutable (modifiable) on this server. If you connect Studio to a remote server (on which this parameter set to `true`), then Studio pushes resource changes to the remote server as you save local changes. Guidewire strongly recommends that you set this value to `false` on a production server to prevent changes to the configuration resources directory.

See also “RetainDebugInfo” on page 48.

Studio Read-only Mode

If you set the value of `ResourcesMutable` to `false` in `config.xml` on a particular application server and then restart the associated Studio, that Studio becomes effectively read-only. In this context, read-only means:

- It is not possible to modify a Studio-managed resource. For example, this applies to files that you open in the Gosu or Rules editor.
- If it is possible to modify a Studio-managed resource, it is not possible to save any modification you make to that resource. For example, this applies to files that you open in the PCF editor.

To indicate the read-only status:

- Studio displays a padlock icon on the status bar that is visible only if Studio is in read-only mode. If you click the icon, Studio displays a modal message box indicating the reason why it is in read-only mode.
- Studio disables the **Save** button any time that Studio is in read-only mode.
- Studio changes the **Save** button tooltip in read-only mode to display the reason that save is not active in this mode. This is the same message that Studio shows if you click the padlock icon on the status bar.

Setting the value of configuration parameter `ClusteringEnabled` to `true` provides the same Studio read-only behavior.

Default: `true`

WARNING: Guidewire recommends that you always set this configuration parameter to `false` in a production environment. Setting this parameter to `true` has the potential to modify resources on a production server in unexpected and possibly damaging ways.

RetainDebugInfo

Whether the production server retains debugging information. This parameter facilitates debugging from Studio without a type system refresh.

- If set to `true`, the application does not clear debug information after compilation.
- If set to `false`, the server does not retain sufficient debugging information to enable debugging. As a production server does not recompile types, it is not possible to regenerate any debugging information.

Applies to: ClaimCenter, PolicyCenter

Default: `false`

[See also](#)

- “`ResourcesMutable`” on page 47

ScopedVariableSupportedForAllCapturedRequests

Whether `RequestVar` objects are available from threads originating from web services and Gosu servlets.

Default: `false`

StrictDataTypes

Controls whether the application uses legacy behavior for configuring data types, through the use of the `fieldvalidators.xml` file.

- Set this value to `false` to use legacy behavior. This is useful for older installations that upgrade but want to preserve the previous functionality.
- Set this value to `true` to implement the modern behavior.

StrictDataTypes = true

If you set the `StrictDataTypes` value to `true`, then the application:

- Does not permit decimal values to exceed the scale required by the data type. The setter throws a `gw.datatype.DataTypeException` if the scale is greater than that allowed by the data type. You are responsible for rounding the value, if necessary.
- Validates field validator formats in both the application user interface and in the field setter.
- Validates numeric range constraints in both the application user interface and in the field setter.

StrictDataTypes = false

If you set the `StrictDataTypes` value to `false`, then the application:

- Auto-rounds decimal values to the appropriate scale, using the `RoundHalfUp` method. For example, setting the value 5.045 on a field with a scale of 2 sets the value to 5.05.
- Validates field validator formats in the interface but not at the setter level. For example, the application does not permit a field with a validator format of `[0-9]{3}-[0-9]{2}-[0-9]{4}` to have the value 123-45-A123 in the interface. However, it is possible to set a field to that value in Gosu code, for example. This enables you to bypass the validation set in the interface.
- Validates numeric range constraints in the interface, but not at the setter level. For example, Guidewire does not allow a field with a maximum value of 100 to have the value 200 in the interface. However, you can set the field to this value in Gosu rules, for example. This enables you to bypass the validation set in the interface.

Default: `true`

TwoDigitYearThreshold

The threshold year value for determining whether to resolve a two-digit year to the earlier or later century.

Default: 50

UnreachableCodeDetection

Determines whether the Gosu compiler generates errors if it detects unreachable code or missing return statements.

Applies to: ClaimCenter, PolicyCenter

Default: `true`

UnrestrictedUserName

InsuranceSuite applications don't evaluate permissions for the unrestricted user. As a consequence of the application bypassing permission checking, the unrestricted user has access to the entire application. Thus, an unrestricted user behaves as if it has all permissions.

In the base configuration, the application defines user `su` user as the unrestricted user. To set the unrestricted user to a different user, set the value of the `UnrestrictedUserName` parameter to that user's login name.

Default: `su`

UseOldStylePreUpdate

Determines whether to apply the preupdate rule set prior to committing a bundle.

Applies to: ClaimCenter

Default: `true`

WarnOnImplicitCoercion

A value of true indicates that the Gosu compiler generates warnings if it determines that an implicit coercion is occurring in a program.

Default: true

WebResourcesDir

Specifies the location of the Web resources directory under the root of the Tomcat configuration directory.

Default: resources

Equity warning parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to equity warnings.

Applies to: BillingCenter

DefaultEquityBuffer

System default for the threshold number of days of preferred equity for newly created payment plans.

Applies to: BillingCenter

Default: 30

EnableEquityWarnings

System default for whether equity warnings are enabled or disabled for newly created payment plans.

Applies to: BillingCenter

Default: true

Financial activity pattern parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to financial activity patterns.

Applies to: ClaimCenter

CheckDeniedPattern

Name of the activity pattern to use if creating an alert that a down-stream system has denied a check.

Applies to: ClaimCenter

Required: Yes

CheckUnableToStopPattern

Name of the activity pattern to use if creating an alert that ClaimCenter cannot stop a check.

Applies to: ClaimCenter

Required: Yes

CheckUnableToVoidPattern

Name of the activity pattern to use if creating an alert that ClaimCenter cannot void a check.

Applies to: ClaimCenter

Required: Yes

ClaimOrExposureUnableToClosePattern

Name of the activity pattern to use if a claim or an exposure cannot be closed.

Applies to: ClaimCenter

Required: Yes

LastPaymentReminderPattern

Name of the activity pattern to use if creating an alert to signal the approach of the last payment in a set of recurrence checks.

Applies to: ClaimCenter

Required: Yes

RecoveryDeniedPattern

Name of the activity pattern to use if creating an alert that a down-stream system has denied a recovery.

Applies to: ClaimCenter

Required: Yes

Financial parameters

Guidewire provides the following parameters in the `config.xml` file to help configure how the application works with monetary amounts.

Applies to: ClaimCenter, BillingCenter

AllowMultipleLineItems

Whether to allow multiple line items in a transaction. See also `UseDeductibleHandling`.

Applies to: ClaimCenter

Default: true

AllowMultiplePayments

Whether to allow a single check to reflect multiple payments.

Applies to: ClaimCenter

Default: true

AllowNegativeManualChecks

Use to set the ability to create negative checks manually. The following values are valid:

- `true` – Allow user to create negative checks manually.
- `false` – Disable the ability to create negative checks manually.

The default ClaimCenter behavior is to not allow manual checks to be negative. If you need the ability to create negative checks manually, then you must explicitly set this parameter to `true`.

Applies to: ClaimCenter

Default: false

AllowNoPriorPaymentSupplement

Whether to allow a user to create supplemental payments on a closed claim or exposure with no prior payments.

Applies to: ClaimCenter

Default: false

AllowPaymentsExceedReservesLimits

If true, a user can submit payments that exceed available reserves up to the amount limited by the `paymentsexceedreserves` authority limits. Otherwise, ClaimCenter does not allow partial or final payments that exceed reserves.

Applies to: ClaimCenter

Default: false

AllowTransactionDenyWhenSubmitted

Determines when transactions can be denied. The following values are valid:

- true – A check or recovery can be denied in Submitting/Requesting, Submitted, or Requested status.
- false – A check or recovery can be denied only in Submitting/Requesting status.

Applies to: ClaimCenter

Default: false

[See also](#)

- "Booking date for the Transaction entity" in the *Configuration Guide*

CheckAuthorityLimits

Controls whether ClaimCenter checks authority during approval processing of a TransactionSet.

Applies to: ClaimCenter

Default: true

CheckUnappliedAmountAfterEveryPayment

When redistributing an unapplied fund, BillingCenter checks to see if the unapplied fund amount is positive before processing any payments. If the amount is not positive, no redistribution occurs. When this parameter is set to false, this is the only time the unapplied fund amount is checked. When this is set to true, the unapplied fund amount is checked before processing any payments, and it is checked again after each payment is processed. If the unapplied amount is not positive after the processing of any given payment, BillingCenter stops the redistribution of that unapplied fund.

Setting this parameter to true may improve performance for redistributions with a large number of payments and a small amount of money in the unapplied fund to redistribute.

Applies to: BillingCenter

Default: false

CloseClaimAfterFinalPayment

If true, ClaimCenter attempts to automatically close a claim if a final payment closes the last open exposure.

Applies to: ClaimCenter

Default: true

CloseExposureAfterFinalPayment

If true, ClaimCenter attempts to automatically close the exposure of a Final payment when that payment's Check is escalated.

Applies to: ClaimCenter

Default: true

EnableMulticurrencyReserving

Whether to enable multicurrency reserving support. Note that this parameter is not intended to be used by non-Gosu classes, or to be accessed directly. Use `CCConfigUtil.EnableMulticurrencyReserving` instead.

If you set this parameter to true, you must also set `MulticurrencyDisplayMode` to `MULTIPLE`.

IMPORTANT: The `EnableMultiCurrencyReserving` parameter setting is semi-permanent. After you set `EnableMultiCurrencyReserving` to true and then start the server, you cannot change the value again.

Applies to: ClaimCenter

Default: false

Set for server: No

EnforceNonCustomAuthorityLimitProfilesCannotHaveDuplicateNames

Enforces that the name of each non-custom Authority Limit Profile is unique. In the ClaimCenter user interface, a custom Authority Limit Profile is only created for a specific user. A non-custom profile can be created as a new Authority Limit Profile in the ClaimCenter user interface or in InsuranceSuite Cloud API. Non-custom profiles are associated with a role that applies to multiple ClaimCenter users.

For backwards compatibility with earlier versions of ClaimCenter, it is recommended you disable this parameter.

Applies to: ClaimCenter

Default: true

Financials

Specifies the level of financials functionality that is available in the application. Available options are `view` for read-only values or `entry` to enable editing the financial values directly in ClaimCenter.

ClaimCenter supports the following values:

Value	Description
entry	financials entry
view	financials view (read-only)

Default: entry

InstantPaymentIntegrationEnabled

If true, the **Instant** payment method is enabled in the ClaimCenter check wizard and quick check wizard. This payment method is known as the instant disbursements feature in ClaimCenter. The **Instant** payment method option requires an integration with an external payment gateway system to issue an instant payment such as a prepaid card, debit card, or Zelle money transfer directly to an individual person.

Applies to: ClaimCenter

Default: false

Set for server: No

NewCustomCommissionPayableCalculatorEnabled

Most commissions become payable at a specific point in time that BillingCenter can easily identify. For example, if a commission plan's payable criteria is "On first payment received", BillingCenter marks the commission as payable when the first payment is received.

However, commission can also be earned on the date that a policy period becomes effective or expires. These dates are not tied to any billing activity. Therefore, BillingCenter cannot *immediately* identify that the commission is earned. To mark the commission as earned, BillingCenter periodically runs one of the following batch processes:

- Date Based Commission Payable Calculations
- Commission Payable Calculations

Both of these batch processes determine which commission is payable. For insurers who enter production using a Jasper release (2024.02.0) or later, Guidewire recommends the Date Based Commission Payable Calculations batch process. This batch process executes more quickly. This is because it can more easily filter out commission items for which there is no need to determine if commission is payable, such as commission items that have already been earned.

This original Commission Payable Calculations batch process remains for backwards compatibility for insurers who entered production using an Innsbruck release (2023.10.0) or earlier and who have custom logic which depends on the original Commission Payable Calculations behavior.

The NewCustomCommissionPayableCalculatorEnabled application configuration parameter controls which batch process gets used.

- When set to true, Date Based Commission Payable Calculations is used. This is the default.
- When set to false, Commission Payable Calculations is used.

Applies to: BillingCenter

Default: true

ProRataCalculationRemainderTreatment

Specifies how to distribute any remaining amount resulting from a pro rata calculation.

Assumptions cannot be made concerning the order in which invoice items are processed. As a hypothetical example, if the same group of invoice items are paid twice, the first or last paid item may differ in each operation.

- `overweightFromFront`: Distribute remainder amount pro rata beginning with the first invoice item.
- `overweightFromBack`: Distribute remainder amount pro rata beginning with the last invoice item.
- `overweightFirst`: Distribute entire remainder amount to the first invoice item.
- `overweightLast`: Distribute entire remainder amount to the last invoice item.

Applies to: BillingCenter

Default: `overweightFromFront`

PaymentLogThreshold

ClaimCenter logs payments greater than this threshold. This integer value must be 0 or greater.

Applies to: ClaimCenter

Default: 500

Dynamic: Yes

PaymentRecodeValidationExtensionFields

The list of one or more extension fields used in payment recode validation. The value of each field must be *type.extensionFieldName* where *type* can only be Payment or TransactionLineItem. Separate each field with commas as delimiters.

Example: `Payment.MyPmtField_Ext,TransactionLineItem.TLIField_Ext`

Applies to: ClaimCenter

Default: *None*

PaymentRoundingMode

Use to set the rounding mode for conversion of amounts among TransactionAmount, ClaimAmount, and ReportingAmount columns on the TransactionLineItem entity for Payment transactions. The available choices are a subset of those supported by `java.math.RoundingMode`, namely:

- UP
- DOWN
- CEILING
- FLOOR
- HALF_UP
- HALF_DOWN
- HALF_EVEN

Guidewire strongly recommends that you use one of the following:

- HALF_UP
- HALF_EVEN

You can access this value in Gosu code by using the following method:

```
gw.api.util.CCCurrencyUtil.getRoundingMode(Payment)
```

Applies to: ClaimCenter

Default: HALF_UP

Permanent: No

[See also](#)

- *Globalization Guide*

RecoveryRecodeValidationExtensionFields

The list of one or more extension fields used in recovery recode validation. The value of each field must be *type.extensionFieldName* where *type* can only be Recovery or TransactionLineItem. Separate each field with commas as delimiters.

Example: `Recovery.MyRecoveryField_Ext,TransactionLineItem.TLIField_Ext`

Applies to: ClaimCenter

Default: *None*

ReserveRoundingMode

Use to set the rounding mode for conversion of amounts among TransactionAmount, ClaimAmount, and ReportingAmount columns on the TransactionLineItem entity for Reserve transactions.

The available choices are a subset of those supported by `java.math.RoundingMode`, namely:

- UP
- DOWN
- CEILING
- FLOOR
- HALF_UP
- HALF_DOWN
- HALF_EVEN

Guidewire strongly recommends that you use one of the following:

- HALF_UP
- HALF_EVEN

You can access this value in Gosu code by using the following method:

```
gw.api.util.CCCurrencyUtil.getRoundingMode(Reserve)
```

Applies to: ClaimCenter

Default: HALF_UP

Permanent: No

[See also](#)

- *Globalization Guide*

SetReservesByTotalIncurred

Specifies the way in which you modify reserves in the ClaimCenter interface.

- If set to true, the user can set the **Total Incurred** values
- If set to false, the user can set the **Available Reserves** values.

Applies to: ClaimCenter

Default: false

UseDeductibleHandling

Whether to use deductible handling. If this value is true, then AllowMultipleLineItems must be true as well.

Applies to: ClaimCenter

Default: true

[See also](#)

- *Application Guide*

UseDeprecatedExchangeRates

IMPORTANT: ClaimCenter has two plugins for managing exchange rates: `IExchangeRateSetPlugin` (deprecated) and `IFXRatePlugin`. The `IExchangeRateSetPlugin` is only for use if you are on ClaimCenter 2024.11 or earlier. If you are starting with or updating to 2025.03, Guidewire recommends that you use the `IFXRatePlugin` plugin.

To use the `IFXRatePlugin` plugin, set `UseDeprecatedExchangeRates` to `false`.

- If you are updating to 2025.03, Guidewire recommends you set `UseDeprecatedExchangeRates` to `false`.

This parameter determines which plugin is used for newly created exchange rates. Once created, an exchange rate continues to use whichever model it was first stored in.

The plugins are associated with two distinct data models in ClaimCenter:

ExchangeRate data model

This is the legacy data model that is supported by the deprecated `IExchangeRateSetPlugin` plugin.

ExchangeRateInUse data model

This is the current data model that is supported by the `IFXRatePlugin` plugin.

If this parameter is `true`, newly created exchange rates are stored in the legacy `ExchangeRate` data model. If `false`, newly created exchange rates are stored in the `ExchangeRateInUse` data model.

The value of `UseDeprecatedExchangeRates` is semi-permanent, meaning that after you start the production server, you can change the value of this parameter from `false` to `true`, but not the converse.

WARNING: After you set `UseDeprecatedExchangeRates` to `true` and start the server, you cannot change the value again. If you reset the value to `false`, the server will not start.

Applies to: ClaimCenter

Default: `true`

Permanent: Semi-permanent

UseRecoveryReserves

Whether to use recovery reserve transactions in financial calculations. If you set this parameter to `false`, and then later set it back to `true`, consider creating offsetting recovery reserves for your existing recoveries. In addition, changing the parameter from `false` to `true` generates database consistency check errors, which you may ignore.

Applies to: ClaimCenter

Default: `true`

Geocoding parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to geocoding.

Applies to: ClaimCenter, PolicyCenter

ProximityRadiusSearchDefaultMaxResultCount

The maximum number of results to return if performing a *radius* (within *n* miles or kilometers) proximity search. This parameter has no effect on *ordinal* (nearest *n* items) proximity searches. This parameter in ClaimCenter does not have to match the value of the corresponding parameter in the ContactManager `config.xml` file.

Applies to: ClaimCenter, PolicyCenter

Default: 1000

ProximitySearchOrdinalMaxDistance

A distance that provides an approximate bound to improve performance of an *ordinal* (nearest *n* items) proximity search. This distance is in miles, unless you set `UseMetricDistancesByDefault` to `true`. This parameter has no effect on *radius* (within *n* miles or kilometers) proximity searches or walking-the-group-tree-based proximity assignment.

Default: 300

IMPORTANT: If the setting for this configuration parameter differs between ContactManager and ClaimCenter, it is possible for the application to display distance-related messages incorrectly. Additionally, the search can return results that are farther away than the distance specified.

UseGeocodingInAddressBook

Set to `true` if you have the application integrated with ContactManager and ContactManager has geocoding enabled for vendors. This setting enables vendor search in the application and ContactManager user interfaces.

Applies to: ClaimCenter

Default: `false`

UseGeocodingInPrimaryApp

If `true`, ClaimCenter enables proximity search for users in the assignment user interface.

If `true`, PolicyCenter enables searching for nearby locations in the Reinsurance Management user interface.

ContactManager does not respond to this parameter.

Applies to: ClaimCenter, PolicyCenter

Default: `false`

UseMetricDistancesByDefault

If `true`, ClaimCenter uses kilometers and metric distances instead of miles and United States distances for driving distance or directions. Set this parameter identically in both ClaimCenter and ContactManager.

If `true`, PolicyCenter uses kilometers and metric distances instead of miles and United States distances for location searches. Set this parameter identically in both PolicyCenter and ContactManager.

Default: `false`

Globalization parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to globalization.

For information on editing `config.xml` and setting configuration parameters, see “Working with configuration parameters” on page 17.

AlwaysShowPhoneWidgetRegionCode

Whether the phone number widget in the application user interface always displays a selector for phone region codes.

Default: `false`

Set for server: Yes

DefaultApplicationBaseCurrencies

A comma-separated list of currencies that can be used as an exchange rate's base currency.

Applies to: PolicyCenter, BillingCenter, ClaimCenter

Default: The value of the DefaultApplicationCurrency configuration parameter.

[See also](#)

- *BillingCenter Configuration*
- *ClaimCenter Configuration*
- *PolicyCenter Configuration*

DefaultApplicationCurrency

Default currency for the application. You must set configuration parameter DefaultApplicationCurrency to a typecode contained in the Currency typelist, even if you configure the application with a single currency. Guidewire applications that share currency values must have the same DefaultApplicationCurrency setting in their respective config.xml files. The default currency is sometimes known in ClaimCenter as the *reporting currency*, or in PolicyCenter as the *preferred* currency.

IMPORTANT: This parameter setting is permanent. Once you set the parameter and then start the server, you cannot change the value.

Default: usd

Permanent: Yes

Note: This parameter is also included in the ContactManager config.xml file in the base application, so it can be set for ContactManager. Ensure it matches the setting in other InsuranceSuite applications.

[See also](#)

- “The default currency”

DefaultApplicationLanguage

The display language that a user sees if they have not specified another language for the application. The language must be enabled and the specified language displays only for display keys that are defined for that language.

IMPORTANT: This parameter setting is permanent. Once you set the parameter and then start the server, you cannot change the value.

Default: en_US

Permanent: Yes

[See also](#)

- *Globalization Guide*

DefaultApplicationLocale

Default locale for regional formats in the application. You must set configuration parameter DefaultApplicationLocale to a typecode contained in the LocaleType typelist.

IMPORTANT: This parameter setting is permanent. Once you set the parameter and then start the server, you cannot change the value.

Default: en_US

Permanent: Yes

See also

- *Globalization Guide*

DefaultCountryCode

The default ISO country code that the application uses if the country for an address is not set explicitly. The application also uses the value of this parameter as the default country code for new addresses that it creates. The country code must be a valid ISO country code that exists as a typecode in the Country typelist.

See the following page to search a list of ISO country codes:

<https://www.iso.org/obp/ui>

DefaultNANPACountryCode

The default country code for region 1 phone numbers. If the area code is not in the `nanpa.properties` map file, then it defaults to the value configured with this parameter.

Default: US

DefaultPhoneCountryCode

The default ISO country code used for phone data.

Default: None

DefaultRoundingMode

Sets the default rounding mode for:

ClaimCenter

Money and currency amount calculations.

PolicyCenter

Monetary amount calculations.

BillingCenter

Monetary amount calculations, except as noted below:

IMPORTANT: This parameter does not influence rounding when a charge is distributed across multiple invoice items or when a commission is distributed across multiple item commissions. BillingCenter expects charge remainders and commission remainders to always be positive. Therefore, BillingCenter always rounds down when distributing a charge or commission across multiple items, regardless of how the `DefaultRoundMode` parameter is set.

The available choices are a subset of those supported by `java.math.RoundingMode`, namely:

- UP
- DOWN
- CEILING
- FLOOR
- HALF_UP
- HALF_DOWN
- HALF_EVEN

Guidewire strongly recommends that you use one of the following:

- HALF_UP
- HALF_EVEN

You can access this value in Gosu code by using the following method:

```
gw.api.util.CurrencyUtil.getRoundingMode()
```

IMPORTANT: This parameter setting is permanent. Once you set the parameter and then start the server, you cannot change the value.

Default: HALF_UP

Permanent: Yes

[See also](#)

- “PaymentRoundingMode” on page 55
- “ReserveRoundingMode” on page 56
- *Globalization Guide*

MulticurrencyDisplayMode

Determines whether multicurrency is enabled for the application. The following are allowed values for MulticurrencyDisplayMode:

- SINGLE
- MULTIPLE

In the base configuration of the application, the value is set to SINGLE. The configuration parameter behavior is semi-permanent, which means you can change the value to MULTIPLE once only. After you change the value to MULTIPLE, you cannot later change it back to SINGLE. If you change the value back to SINGLE, subsequent attempts to start the server fail.

Default: SINGLE

Permanent: Semi-permanent

[See also](#)

- “Enabling multicurrency”

MultiSettlementCurrencyHandlingEnabled

Determines whether Advanced Product Designer App creates additional codegen artifacts to enable multicurrency policies with multiple settlement currencies.

Applies to: PolicyCenter

Default: false

[See also](#)

- “Enabling multicurrency”

High Volume Quoting configuration

It is common for an insurance company to need to handle large volumes of incoming quote requests from anonymous or guest users. As a consequence, the server that supports the quote requests needs to be able to provide near-linear scaling to handle the volume of incoming requests.

One way to manage a large volume of quote requests is to implement an additional set of PolicyCenter servers to specifically handle anonymous quote requests. These servers are in addition to the system of record PolicyCenter servers that comprise the PolicyCenter cluster. Typically, the high volume quoting servers are not members of the PolicyCenter cluster so as to avoid latency issues created by cluster channel communications. In addition, these servers do not actually persist the generated quotes to an RDBMS in the standard table structure. Instead, the purpose of the quote servers is to generate a quote document that one can later import into the PolicyCenter system of record and bind there, if required.

To support this separation of functionality and purpose, Guidewire provides a way to designate a server as a High Volume Quoting (HVQ) server. In this way, it is possible to distinguish between HVQ servers and system of record servers. Server instances designated as HVQ allow only certain types of operations. For example, HVQ servers permit quote generation using a specific API or quote storage, but do not support archiving.

To manage this separation of functionality, Guidewire provides multiple configuration parameters in `config.xml` that you can set to indicate whether the server instance is system of record or HVQ.

Applies to: PolicyCenter

HVQEnabled

This Boolean parameter has the following meanings:

`true` Server is in a High Volume Quoting environment

`false` Server has no support for High Volume Quoting

The value of this Boolean parameter is managed through the `ExternalConfigurationProperties` interface. The default value is `false`. Guidewire recommends that you do not alter or set the value of this parameter.

Applies to: PolicyCenter

Default: `false`

HVQServer

This Boolean parameter has the following meanings:

`true` Server is a High Volume Quoting server

`false` Server is a system of record server

This `config.xml` parameter is deprecated. Guidewire recommends that you do not alter or set the value of this parameter.

Applies to: PolicyCenter

MaxHVQSearchResults

This Integer parameter limits the number of High Volume Quoting search results available from the system of record. Currently, Guidewire limits this parameter to a value of 100.

Applies to: PolicyCenter

Integration parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to how multiple Guidewire applications integrate with each other.

For information on editing `config.xml` and setting configuration parameters, see “Working with configuration parameters” on page 17.

BillingSystemArchiveEnabled

IMPORTANT: Guidewire must enable archiving before the archiving functionality is available.

Whether or not the archiving is enabled in the billing system. This parameter needs to match billing system settings for archiving.

Applies to: PolicyCenter

Default: false

BillingSystemArchivePolicyPeriodDays

IMPORTANT: Guidewire must enable archiving before the archiving functionality is available.

The minimum number of days after the term end date before the billing policy period is archived. This value must be less than or equal to the setting in the billing system. Guidewire recommends setting the value to be equal and keeping the value of `BillingSystemArchivePolicyPeriodDays` synchronized with the value of `ArchivePolicyPeriodDays` in `BillingCenter`.

This parameter is used to decide whether to check the billing system for the archiving flag. A negative value disables this check, and `PolicyCenter` ignores the archiving flag when determining whether to call the billing system API. This parameter is applicable only if the `BillingSystemArchiveEnabled` parameter is true.

Applies to: PolicyCenter

Default: -1

BillingSystemURL

URL to use in `ExitPoint` PCF pages that view items in the billing system.

- If integrating Guidewire `PolicyCenter` with Guidewire `BillingCenter`, then set this parameter to the `BillingCenter` base URL (for example, `http://server/bc`). In this case, the exit points add the appropriate `BillingCenter` entry point.
- If integrating with a non-Guidewire billing system, then you need to modify the `ExitPoint` PCF to set up the parameters required by that system.
- If you omit this parameter or if you set it to an empty string, then `PolicyCenter` hides the buttons in the interface that take you to the exit points.

Applies to: PolicyCenter

Default: Empty string

ClaimSystemURL

URL to use in `ExitPoint` PCF pages that view items in the claims system.

- If integrating Guidewire `PolicyCenter` with Guidewire `ClaimCenter`, then set this parameter to the `ClaimCenter` base URL (for example, `http://server/cc`). In this case, the exit points add the appropriate `ClaimCenter` entry point.
- If integrating with a non-Guidewire claim system, then you need to modify the `ExitPoint` PCF to set up the parameters required by that system.
- If you omit this parameter or if you set it to an empty string, then `PolicyCenter` hides the buttons in the interface that take you to the exit points.

Applies to: PolicyCenter

Default: Empty string

ContactAutoSyncBundleCommitSize

If you integrate ClaimCenter with ContactManager, it is necessary to synchronize contacts stored by the two Guidewire applications. Batch process ContactAutoSync controls this synchronization.

It is common to have a large number of local instances of each contact in Guidewire ClaimCenter, one for each claim that uses that contact. To improve the performance of synchronizing the ClaimCenter contacts that match a single AddressBookUID, the parameter ContactAutoSyncBundleCommitSize specifies the maximum number of contacts in a single bundle commit.

Note: Parameter ContactAutoSyncBundleCommitSize is meaningful only if ClaimCenter is integrated with ContactManager.

Applies to: ClaimCenter

Default: 15

[See also](#)

- “ContactAutoSyncWorkItemChunkSize” on page 64
- *Contact Management Guide*

ContactAutoSyncWorkItemChunkSize

If you integrate ClaimCenter with ContactManager, it is necessary to synchronize the contacts stored by the two Guidewire applications. Batch process ContactAutoSync controls this synchronization.

It is common to have a large number of local instances of each contact in Guidewire ClaimCenter, one for each claim that uses that contact. During contact synchronization between ClaimCenter and ContactManager, ClaimCenter processes the table for highly linked contacts. If the number of contacts linked to a single AddressBookUID is greater than the value of ContactAutoSyncWorkItemChunkSize, ClaimCenter divides these contacts into smaller groups of contacts. This process is known as *chunking*. ClaimCenter then creates a work item to process each chunk of contacts.

Note: Parameter ContactAutoSyncWorkItemChunkSize is meaningful only if ClaimCenter is integrated with ContactManager.

Applies to: ClaimCenter

Default: 400

[See also](#)

- “ContactAutoSyncBundleCommitSize” on page 64
- *Contact Management Guide*

DefaultXmlExportIEncryptionId

The unique encryption ID of an encryption plugin. If archiving is enabled, the application uses the encryption plugin to encrypt any encrypted fields during XML serialization.

Default: null (no encryption)

EnableCreditCardCollectionUI

If true, a set of demonstration screens to collect tokenized credit card information is enabled. This inbound payments reference feature includes a solution that simulates a PCI-compliant integration with a payment gateway.

Applies to: PolicyCenter

Default: false

Set for server: No

EnableCustomBilling

Enables the deprecated **Custom Billing Options** functionality on the **Payment** screen. This parameter is provided for backwards compatibility only.

Default: false

EnableMetroIntegration

Whether to enable Metropolitan Reporting Bureau integration. If `true`, there is a working integration that sends messages from ClaimCenter to the Metropolitan Reporting Bureau service (requesting Metropolitan reports).

Applies to: ClaimCenter

Default: false

Set for server: Yes

In the base configuration, ClaimCenter sets the `EnableMetroIntegration` parameter to `true` in the `config.xml` file.

HighRiskAssessmentCategories

This parameter is used if you integrate with Guidewire Analytics Manager to enable Embedded Analytics predictions in ClaimCenter. Separate each field with semicolons (;) as delimiters.

Applies to: ClaimCenter

Default: high;warning;reject;very high;needs attention;error;action required

[See also](#)

- "Configuring high-risk predictions" in the *Configuration Guide*

InboundPaymentIntegrationEnabled

This parameter determines whether the user interface elements that support the inbound payment integration solution are accessible to users.

Applies to: BillingCenter

Default: false

InstantaneousContactAutoSync

Whether to process contact automatic synchronization in ClaimCenter at the time of receiving the notification:

- If you set `InstantaneousContactAutoSync` to `false`, ClaimCenter synchronizes contacts only while running the `ContactAutoSync` batch process.
- If you set `InstantaneousContactAutoSync` to `true`, the `ContactAutoSync` worker activates automatically as ClaimCenter receives autosync events and immediately updates all ClaimCenter copies of a contact stored in `ContactManager`.

Applies to: ClaimCenter

Default: true

[See also](#)

- *Contact Management Guide*

ISOPropertiesFileName

Name of the ISO properties file in the `modules/configuration/config/iso` configuration directory.

Applies to: ClaimCenter

Default: ISO.properties

Set for server: Yes

KeepCompletedMessagesForDays

Number of days after which the application purges old messages in the message history table.

Default: 90

LockPrimaryEntityDuringMessageHandling

Deprecated. Do not attempt to use.

MetroPropertiesFileName

Name of the Metropolitan properties file in the `modules/configuration/config/metro` configuration directory. ClaimCenter uses this files to set up fields in the XML messages sent to the Metropolitan Reporting Bureau. See `EnableMetroIntegration` as well.

Applies to: ClaimCenter

Default: Metro.properties

Set for server: Yes

PaymentSystemURL

URL to use in ExitPoint PCF pages that view items in a payment system.

- If integrating Guidewire PolicyCenter with Guidewire BillingCenter, then set this parameter to the BillingCenter base URL (for example, `http://server/bc`). In this case, the exit points add the appropriate BillingCenter entry point.
- If integrating with a non-Guidewire billing system, then you need to modify the ExitPoint PCF to set up the parameters required by that system.
- If you omit this parameter or if you set it to an empty string, then PolicyCenter hides the buttons in the interface that take you to the exit points.

Note: Guidewire configures this parameter in the base configuration to work with a demonstration payment system. For more details, see *Plugins, Prebuilt Integrations, and SOAP APIs*.

Applies to: PolicyCenter

Default: pc

PluginStartupTimeout

OSGi plugins startup timeout (in seconds). The `PluginConfig` component waits for at most this time for all required OSGi plugins to start. The `PluginConfig` component reports an error for each OSGi plugin that does not start after this timeout has expired.

Default: 60

PolicySystemURL

URL to use in ClaimCenter ExitPoint PCF pages that view items in the policy system.

- If integrating Guidewire ClaimCenter with Guidewire PolicyCenter, then set this parameter to the PolicyCenter base URL (for example, `http://server/pc`). In this case, the exit points add the appropriate PolicyCenter entry point.
- If integrating with a non-Guidewire policy system, then you need to modify the ExitPoint PCF to set up the parameters required by that system.
- If you omit this parameter or if you set it to an empty string, then ClaimCenter hides the buttons in the interface that take you to the exit points.

Applies to: ClaimCenter

Default: Empty string

Itemized charges and commissions parameters

Guidewire provides the following configuration parameters in `config.xml` that relate to itemized charges and commissions.

Applies to: PolicyCenter

`EnableChargeBreakdownCommissionable`

Set this Boolean parameter to `true` if the billing system to which PolicyCenter sends billing information supports partially commissionable charges. This parameter takes effect if the `EnableChargeBreakdowns` parameter is also set to `true`.

The billing system might need to pay commission to an agent on only a portion of a charge amount, such as the portion of the charge that is premium and not the portion that is tax.

To integrate PolicyCenter with BillingCenter, set the value of `EnableChargeBreakdownCommissionable` as follows:

- To keep the default behavior, which is to not send commissionable information, set `EnableChargeBreakdownCommissionable` to `false`.
- To send commissionable information to BillingCenter release 2020.11, set `EnableChargeBreakdownCommissionable` to `true`.
- For BillingCenter release 2020.05, BillingCenter release 10.1.0, or previous releases of BillingCenter, set `EnableChargeBreakdownCommissionable` to `false` because these releases of BillingCenter do not support commissionable information in charge breakdowns.

Applies to: PolicyCenter

Default: `false`

`EnableChargeBreakdowns`

Set this Boolean parameter to `true` to instruct PolicyCenter to send itemized billing information to the billing system. If this parameter is `true`, you can control support for partially commissionable charges by using the `EnableChargeBreakdownCommissionable` parameter.

The billing system might need to send information to a customer about the items that make up the total of a charge amount, such as the costs for each coverage attached to a risk unit. The base configuration of PolicyCenter supports charge breakdowns for product lines that are created by using Advanced Product Designer. You can also define charge breakdown categories for product lines that are provided in the base configuration or that you design by using Product Designer. In the base configuration, the personal auto line demonstrates the use of these categories.

Applies to: PolicyCenter

Default: `false`

Job expiration parameters

Guidewire provides the following configuration parameters in `config.xml` that relate to how PolicyCenter handles jobs.

Applies to: PolicyCenter

PolicyCenter provides a **Job Expire** (`jobexpire`) batch process that moves jobs from the **New**, **Draft**, or **Quote** status to the **Expired** status. This process first examines all jobs that have a **New**, **Draft**, or **Quote** status. From this set of jobs, the batch process expires the jobs that meet all of the following criteria:

- The job meets the expiration threshold.
- The job meets the creation threshold.
- The `job.canExpireJob` method returns `true` for that job type.

In the base configuration, this process moves Submission jobs to the **Expired** status if all of the following are true:

- The job status is either **New**, **Draft**, or **Quote**.
- The job is at least seven days past the effective date of the policy.

Setting the expiration and creation thresholds – Modify the following parameters to configure the expiration and creation thresholds. If you enable both parameters, the job must meet both thresholds.

- “`JobExpirationEffDateThreshold`” – The number of days past the policy effective date before the batch process `JobExpire` expires a job.
- “`JobExpirationCreateDateThreshold`” – The number of days past the job creation date before batch process `JobExpire` expires a job.

Expiring different job types – You can also enable expiration for job types other than Submission. To facilitate this process, PolicyCenter provides a number of Boolean configuration parameters of the following pattern:

```
JobExpireCheckJobType
```

Job types – For this configuration parameter, `JobType` can be any of the following:

- Audit
- Cancellation
- Issuance
- PolicyChange
- Reinstatement
- Renewal
- Rewrite
- Submission
- TestJob

To enable the expiration of a particular job type, set `JobExpireCheckJobType` to `true` for that particular job type.

JobExpirationCreateDateThreshold

Number of days past the job creation date before batch process `JobExpire` expires a job. Batch process `JobExpire` first examines all jobs meeting the date criteria set by this parameter. In addition to this threshold, the job must also meet the `JobExpirationEffDateThreshold` threshold. The batch process then expires those jobs for which `job.canExpireJob` is `true`.

The job creation date is specified in `Job.CreateTime`.

A value of -1 disables this parameter.

IMPORTANT: Setting the create date threshold to a negative number effectively disables create date checking, as it is not possible to create a job with a future create date. Disabling `JobExpirationCreateDateThreshold` does not disable `JobExpirationEffDateThreshold`.

Applies to: PolicyCenter

Default: -1

JobExpirationEffDateThreshold

Number of days past the job effective date before batch process `JobExpire` expires a job. Batch process `JobExpire` first examines all jobs meeting the date criteria set by this parameter. In addition to this threshold, the job must also meet the `JobExpirationCreateDateThreshold` threshold. The batch process then expires those jobs for which `job.canExpireJob` is true.

The job effective date is the `EditEffectiveDate` of a `PolicyPeriod` on the `Job`. If the job has more than one policy period, then each active policy period on the job must meet the threshold. You access the active policy periods on the job through the `Job.ActivePeriods` array.

A negative value means that the batch process expires unbound jobs by that number of days before their effective date is reached. For example, a value of -5 for this parameter indicates that jobs expire five days before their effective date.

Applies to: PolicyCenter

Default: 7

JobExpireCheckAudit

Set to true to enable PolicyCenter to expire this job type. For audit jobs, you must override the `canExpireJob` method in the `gw.job.AuditProcess` class and modify it to return true. You can find this class in the **Classes** folder in Studio.

Applies to: PolicyCenter

Default: false

JobExpireCheckCancellation

Set to true to enable PolicyCenter to expire this job type.

Applies to: PolicyCenter

Default: false

JobExpireCheckIssuance

Set to true to enable PolicyCenter to expire this job type.

Applies to: PolicyCenter

Default: false

JobExpireCheckPolicyChange

Set to true to enable PolicyCenter to expire this job type.

Applies to: PolicyCenter

Default: false

JobExpireCheckReinstatement

Set to true to enable PolicyCenter to expire this job type.

Applies to: PolicyCenter

Default: false

JobExpireCheckRenewal

Set to true to enable PolicyCenter to expire this job type.

Applies to: PolicyCenter

Default: false

JobExpireCheckRewrite

Set to true to enable PolicyCenter to expire this job type.

Applies to: PolicyCenter

Default: false

JobExpireCheckSubmission

Set to true to enable PolicyCenter to expire this job type.

Applies to: PolicyCenter

Default: true

JobExpireCheckTestJob

Set to true to enable PolicyCenter to expire this job type.

Applies to: PolicyCenter

Default: false

Job-related parameters

Guidewire provides the following configuration parameters in `config.xml` that relate to PolicyCenter jobs.

Applies to: PolicyCenter

AllowedDaysBeforeOrAfterPolicyStartDate

Number of days, before or after a given policy period `StartDate`, to search for a non-canceled bound `PolicyPeriod` on which to base the renewal.

For example, if you need to rewrite a canceled policy with an earlier start date, the most recent bound period is the canceled period. To renew such a policy, it must be possible to identify the rewrite. This parameter establishes the windows in which to search for a rewritten policy.

- If the policy term is 6 months or longer, then the default of 90 days is acceptable.
- If the policy term is shorter, then use a smaller number for this parameter.

Applies to: PolicyCenter

Default: 90

MaximumPolicyCreationYearDelta

Value, which added to the current year, represents the maximum year to use during policy creation. This integer value must be 0 or greater.

Applies to: PolicyCenter

Default: 1

MaxRecentAccounts

Maximum number of recent accounts that PolicyCenter shows in the **Account** tab.

Applies to: PolicyCenter

Default: 5

MaxRecentPoliciesAndJobs

Maximum number of recent policies and jobs that PolicyCenter shows in the **Policy** tab.

Applies to: PolicyCenter

Default: 8

MaxSubmissionsToCreate

Maximum number of submissions that PolicyCenter can create at one time in the **New Submission** page.

Applies to: PolicyCenter

Default: 20

MinimumPolicyCreationYear

Minimum (earliest) year to use during policy creation. This integer value must be 1000 or greater.

Applies to: PolicyCenter

Default: 1000

PatternCacheMaxDuration

Upper bound on how long PolicyCenter allows caches of pattern entities to exist without refresh, measured in seconds.

Applies to: PolicyCenter

Default: 86400

PolicyChangeMaxQuotes

Maximum number of allowable quotes for a policy change.

Applies to: PolicyCenter

Default: 3

PurgeTemporaryPolicyPeriodsAfterDays

Minimum number of days that must pass before a temporary policy period can be purged.

Applies to: PolicyCenter

Default: 14

PurgeTemporaryPolicyPeriodsEnabled

Enables Purge Temporary Policy Periods batch processing. If `false`, the work queue will not remove any temporary policy periods.

Applies to: PolicyCenter

Default: false

RenewalMaxQuotes

Maximum number of allowable quotes for a renewal.

Applies to: PolicyCenter

Default: 3

RenewalProcessLeadTime

Lead time (in number of days) before the state non-renewal notification deadline to start renewals.

Applies to: PolicyCenter

Default: 165

SubmissionMaxQuotes

Maximum number of allowable quotes for a submission.

Applies to: PolicyCenter

Default: 3

JSON, Swagger, and REST parameters

Guidewire provides the following configuration parameters in file `config.xml` that relate to JSON, Swagger, and the REST API framework.

For information on editing `config.xml` and setting configuration parameters, see “Working with configuration parameters” on page 17.

OverrideJSONMappingWarnings

Determines how the REST framework handles JSON mapping warnings:

- ON - Enable all warning categories for JSON mapping validations
- OFF - Disable all warning categories for JSON mapping validations
- DEFAULT - Defer to `suppress-warnings` properties of the individual JSON mappings

Default: DEFAULT

OverrideJSONSchemaWarnings

Determines how the REST framework handles JSON schema warnings:

- ON - Enable all warning categories for JSON schema validations
- OFF - Disable all warning categories for JSON schema validations
- DEFAULT - Defer to `x-gw-suppress-warnings` properties of the individual JSON schemas

Default: DEFAULT

OverrideRESTSchemaWarnings

Determines how the REST API framework handles schema warnings:

- ON - Enable all warning categories for REST Swagger schema validations
- OFF - Disable all warning categories for REST Swagger schema validations
- DEFAULT - Defer to x-gw-suppress-warnings properties of the individual REST Swagger schemas

Default: DEFAULT

PreloadRestServletConfig

Determines whether the application preloads the REST servlet configuration:

- true - the application preloads the REST servlet configuration during servlet initialization.
- false - the application lazily loads the REST servlet configuration on the first request to the servlet.

Setting the value of this configuration parameter to true ensures that the application loads all the configuration needed for the REST servlet to process requests during initial servlet initialization.

Default: false

Set for server: Yes

Lookup table parameters

Applies to: PolicyCenter

For information on editing config.xml and setting configuration parameters, see “Working with configuration parameters” on page 17.

AvailabilityContextCacheEntryExpirationTime

Lookup Table Manager uses a cache to improve performance of Product Model availability lookups. Cache entries expire after a period of inactivity defined by this configuration parameter. Specify the expiration time in minutes. Consider the performance impact before reducing the expiration time. Cache misses may result if entries have been flushed.

Applies to: PolicyCenter

Default: 1440 minutes (1 hour)

Required: No

AvailabilityContextCacheSize

The maximum size of the cache holding AvailabilityContexts after a lookup.

Applies to: PolicyCenter

Default: 1000

Required: Yes

UsePolicyPeriodReferenceDateForOfferingAvailability

Whether to use written date or effective date for offerings availability. If true, use effective date. If false, use written date.

Applies to: PolicyCenter

Default: false

Required: No

Miscellaneous parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to various miscellaneous application features.

For information on editing `config.xml` and setting configuration parameters, see “Working with configuration parameters” on page 17.

AdminDataImporterExporterEnabled

Whether the feature-rich admin data import and export tools are enabled. If `false`, the legacy data import and export tools are enabled.

Default: `true`

AdminExportRecordPurgeEnabled

Whether admin export records are periodically purged from the database.

Default: `true`

AdminImportRecordPurgeEnabled

Whether admin import records are periodically purged from the database.

Default: `true`

AccountNumberSequenceGeneratorOnInitEnabled

Enables calls to the `INumberGenerator` plugin implementation to set an account number when creating a new account.

- `true` - When an account is initialized, `BillingCenter` generates an account number by calling the `INumberGenerator` plugin.
- `false` - When an account is initialized, `BillingCenter` does not call the `INumberGenerator` plugin. This is appropriate when custom code sets the account number and you want to improve performance by disabling the unneeded call to the `INumberGenerator` plugin. However, when committing the associated bundle, if the account number is still `NULL`, `BillingCenter` will call the `INumberGenerator` plugin to generate an account number when calling the `beforeInsert` method.

Applies to: `BillingCenter`

Default: `false`

AllowShortCircuitMatchingBean

When `PolicyCenter` merges duplicate entities during a policy change, it executes a database query that performs poorly for large policies. To improve performance, set `AllowShortCircuitMatchingBean` to `true`. If

`AllowShortCircuitMatchingBean` is set to `true`, you must implement the interface `ShortCircuitLogicalMatcher` on every entity for a line-of-business (LOB) that implements `LogicalMatcher` in order to gain the performance benefit for that LOB. You can address one LOB at a time. The `ShortCircuitLogicalMatcher` has only one method that you must implement, `matchingHash`. `matchingHash` must be a unique hash of the bean, but when hashed it must be the logical match of the bean. For example, for a vehicle the hash must be a hash of the Vehicle Identification Number (VIN) only and not VIN and color as the color of the car can change, but the car is still logically the same vehicle.

Applies to: `PolicyCenter`

Default: `false`

Set for server: Yes

Dynamic: Yes

BulkInsertSelectCardinalityEstimatorHint

Comma-separated list of tables to force PRE2014 cardinality estimator hint in BulkInsertSelectPreparedStatementHandler.

Default: empty

BusinessRuleOverridesEnabled

Whether or not business rule overrides are enabled. If true, business rule overrides are applied by the relevant business process if their criteria are met. If false, business rule overrides are never applied. Regardless of the value of this configuration parameter, business rule overrides can be created and managed in the user interface by users with administrator privileges.

Applies to: BillingCenter

Default: true

ClusterClockChangeDelaySeconds

Use with the (Internal Tools) Testing System Clock functionality. The parameter controls how long the cluster waits to ensure all members have received the clock update request and are prepared for the time change. The application saves the offset in the database, which provides a stable value across server and cluster restarts. The value must be an integer from 0 to 30.

See also the following documentation for more information on how this parameter interacts with the ITestingClock plugin:

Default: 30

ClaimLossDateDemarcation

Default time for a claim's loss date when it is not specified in the FNOL. Set this to match the default time at which the policy administration system sets the effective date of the policy.

Applies to: ClaimCenter

Default: 12:00 AM

Set for server: Yes

ConsistencyCheckerThreads

Number of threads to use when running the consistency checker.

Default: 1

ConfigurationServiceEnabled

This configuration parameter is for Guidewire internal use only. Do not use.

DefaultDiffDateFormat

Sets the default format for dates in the difference tree user interface. Valid formats mirror the Java default date formats:

- short
- medium
- long
- full

Applies to: PolicyCenter

Default: short

DisableDomainGraphSupport

All PolicyCenter environments are expected to have valid data models. However, in rare situations, you might want to upgrade a PolicyCenter environment that does not yet have a valid data model. If there are compelling business reasons not to correct the data model during the upgrade, you can disable domain graph support by setting the `DisableDomainGraphSupport` parameter to `true`.

Guidewire strongly recommends that you resolve domain graph issues at the earliest opportunity to minimize the upgrade cost of the changes required to achieve a valid data model.

You cannot disable domain graph support if you are using quote purging, quote cloning, and personal data destruction. These features require domain graph support. Therefore, PolicyCenter will not start if `DisableDomainGraphSupport` is `true` and `PersonalDataDestructionEnabled` is `true` as well.

Applies to: PolicyCenter

Default: false

EnableClaimNumberGeneration

Whether to enable automatic claim number generation (through an external plugin). If you enable claim number generation, then you must also provide an external Claim Number Generator plugin. If enabled, claim number generation must succeed in order for a claim to be added through either the New Claim wizard or the integration tools. This does not affect claims added through staging tables.

Applies to: ClaimCenter

Default: true

EnableClaimSnapshot

Whether to create snapshots for imported and created claims. The claim snapshot contains a version of the claim data before any automated processing by ClaimCenter.

Applies to: ClaimCenter

Default: true

EnablePreLoader

Whether the application enables preloading of classes, types, and so on found in the contents of the `preload.txt` file across modules.

Extensive preloading can significantly increase startup time, so it can be useful to disable this for some servers, such as when running tests.

Default: true

Set for server: Yes

EnableStatCoding

Whether to enable statistical coding support.

Applies to: ClaimCenter

Default: true

EquityDatingIncludeWriteoffs

Whether to consider policy write-offs in equity dating calculations while calculating the policy equity and paid through date.

Applies to: BillingCenter

Default: false

ExportUserDataEnabled

You can export various types of administrative (admin) data in XML and Excel file format from the following application screen:

Administration > Utilities > Export Data

If enabled, the exported data can also include user information, along with additional related information such as user credentials, user settings, and user contacts. However, by default, Guidewire disables the export of user-related admin data through the application screen, by setting the default value for this configuration parameter to `false`. Thus, while this parameter is `false`, it is possible to view user-related data within the application, but it is not possible export that data into an XML file.

Default: false

Dynamic: Yes

ExternallyVisibleProducerCodes

A comma-separated list of producer codes that can be accessed externally, such as through an API. The producer codes can be from any organization.

Applies to: PolicyCenter

Default: ""

Dynamic: No

IgnoreLeapDayForEffDatedCalc

In the default configuration, the `IgnoreLeapDayForEffDatedCalc` parameter determines whether PolicyCenter ignores a leap day in the following calculations:

- Calculating scalable properties
- Prorating premiums for policies that are less than a full term

The following table describes the values for the `IgnoreLeapDayForEffDatedCalc` parameter:

Value	Description
true	PolicyCenter does not include the leap day while calculating the values for scalable properties or prorated premiums.
false	PolicyCenter includes the leap day while calculating the scalable property amount or prorated premium.

In the default configuration, some scalable properties are `OverrideAmount` on the `Cost` entity and `ScalableBasisAmount` on the `GLExposure` entity.

Applies to: PolicyCenter

Default: true

Leap Days and Prorated Premiums Example

Assume that PolicyCenter needs to rate a policy change that affects the entire month of February in a year that includes a leap day. If `IgnoreLeapDayForEffDatedCalc` is `true`, PolicyCenter ignores the leap day and prorates the premium for 28 days. If `false`, PolicyCenter includes the leap day and prorates the premium for 29 days.

PolicyCenter prorates the premium in the proration plugin. It is possible to override the `IgnoreLeapDayForEffDatedCalc` parameter by a parameter on the plugin.

ImportUserDataEnabled

You can import various types of administrative (admin) data in XML and Excel file format from the following application screen:

Administration > Utilities > Import Data

If enabled, the imported data can also include user information, along with additional related information such as user credentials, user settings, and user contacts. However, by default, Guidewire disables the import of user-related admin data through an XML file, by setting the default value for this configuration parameter to `false`. Thus, while this parameter is `false`, it is not possible import user data as part of an XML file import. If you attempt to do so, the application ignores all user-related data during the file import process.

Default: `true`

Dynamic: Yes

InitialSampleDataSet

Optional set of sample data to load at server start up. This value must be a typecode from the `SampleDataSet` typelist, or `null`. In the base application configuration, valid typecodes are:

Typecode	Description
Tiny	Just a few users like <code>aapplegate</code> , good for test purposes.
Small	A small community model and a few sample Accounts and Policies, useful for local development.
Large	A large, full dataset useful for application demonstrations and manual Quality Assurance.

Set value to `Tiny`, `Small`, or `Large`, corresponding to the dataset that you want to load:

- If there is no sample data loaded as the server starts, the application loads the sample dataset that you specify.
- If there is sample data, the application does nothing.

Applies to: PolicyCenter

Default: *None*

Set for server: Yes

MaintainPolicyValidationLevelOnPolicyChange

If `true`, any time that you change or refresh the policy for a claim, ClaimCenter validates the new policy at the level of the old policy. If `false`, ClaimCenter validates the new policy at the `newLoss` level. In either case, a validation failure causes ClaimCenter to revert the policy refresh or change.

Applies to: ClaimCenter

Default: `true`

MaxCachedClaimSnapshots

Limits the number of claim snapshots that ClaimCenter caches in memory. This integer value must be 0 or greater, but less than ten (10).

Applies to: ClaimCenter

Default: 3

Minimum: 0

Maximum: 10

MaximumXmlExportSize

This configuration parameter is for Guidewire internal use only. Do not use.

MaxStatCodesInDropdown

Maximum number of statistics codes to show in the statistics code picker drop-down.

Applies to: ClaimCenter

Default: 20

MaxTAccountsInConsistencyCheck

Maximum number of T-accounts to process in a query at one time. Set this parameter only if encountering performance issues with very large databases.

Applies to: BillingCenter

Default: 0 (disabled)

MaxTransactionsInConsistencyCheck

Maximum number of transactions to process in a query at one time. Set this parameter only if encountering performance issues with very large databases.

Applies to: BillingCenter

Default: 0 (disabled)

PhoneNumberStrictValidation

Controls how stringent the phone number validator PhoneValidator is.

- If set to `true`, the application uses the `libphonenumber` validator to perform a more stringent validation on phone numbers for syntax and correctness. For example, numbers with unregistered prefixes are rejected.
- If set to `false`, the application performs very little validation on phone numbers.

Default: `false`

PreloadSystemTableToCacheForFasterSynchronization

Enables or disables the pre-load of system tables at server start. To enable pre-loading, set this parameter to `true`. Pre-loading the system tables at server start allows for faster synchronization and faster server startup times. However, be aware that the use of system table pre-loading can require the application to allocate additional heap space.

Applies to: PolicyCenter

Default: `true`

Required: Yes

ProfilerDataPurgeDaysOld

Number of days to keep profiler data before the application deletes it.

Default: 30

RewriteMaxQuotes

Maximum number of allowable quotes for a rewrite.

Applies to: PolicyCenter

Default: 3

StructuredLoggerLightLoggingEnabled

Determines whether light logging or standard logging is enabled for the Structured Logger. By default, standard logging is enabled. Light logging reduces the number of parameters set in the LogData object for output to JSON.

Default: false

Dynamic: Yes

Required: Yes

StructuredLoggerRemoveCRLFEnabled

Determines whether carriage return characters are removed from the log message. By default, this is disabled. This is useful to be enabled for local development environments and generally is disabled for GWCP-deployed environments.

Default: false

Dynamic: Yes

Required: Yes

TenantId

The tenant identifier with which the server runs.

Set for server: Yes

TransactionIdPurgeDaysOld

Number of days to keep external transaction ID records before they can be deleted.

Default: 30

WorkflowLogPurgeRowLimit

Number of workflow logs to delete in a single commit of a delete transaction to the database. This parameter controls how many rows in table WorkflowLogs that batch process PurgeWorkflowLogs deletes in one commit to the database. A value of 0 means to delete all available rows in the table in a single database commit.

Default: 250000

Minimum: 0

Maximum: 1000000

Multicurrency parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to various multicurrency application features.

Applies to: BillingCenter

DefaultApplicationBaseCurrencies

A comma-separated list of currencies that can be used as an exchange rate's base currency.

Applies to: PolicyCenter, BillingCenter, ClaimCenter

Default: The value of the `DefaultApplicationCurrency` configuration parameter.

[See also](#)

- *BillingCenter Configuration*
- *ClaimCenter Configuration*
- *PolicyCenter Configuration*

DefaultApplicationCurrency

Default currency for the application. You must set configuration parameter `DefaultApplicationCurrency` to a typecode contained in the `Currency` typelist, even if you configure the application with a single currency. Guidewire applications that share currency values must have the same `DefaultApplicationCurrency` setting in their respective `config.xml` files. The default currency is sometimes known in ClaimCenter as the *reporting currency*, or in PolicyCenter as the *preferred* currency.

IMPORTANT: This parameter setting is permanent. Once you set the parameter and then start the server, you cannot change the value.

Default: `usd`

Permanent: Yes

Note: This parameter is also included in the `ContactManager config.xml` file in the base application, so it can be set for `ContactManager`. Ensure it matches the setting in other InsuranceSuite applications.

[See also](#)

- “The default currency”

MulticurrencyDisplayMode

Determines whether multicurrency is enabled for the application. The following are allowed values for `MulticurrencyDisplayMode`:

- `SINGLE`
- `MULTIPLE`

In the base configuration of the application, the value is set to `SINGLE`. The configuration parameter behavior is semi-permanent, which means you can change the value to `MULTIPLE` once only. After you change the value to `MULTIPLE`, you cannot later change it back to `SINGLE`. If you change the value back to `SINGLE`, subsequent attempts to start the server fail.

Default: `SINGLE`

Permanent: Semi-permanent

[See also](#)

- “Enabling multicurrency”

BillingAPIWizardsEnabled

BillingCenter has two sets of wizards that can be used to simulate the receipt of billing requests from a PAS. One set, the "mono-currency set", can simulate billing requests only for policies that use a single currency. The other set, the "multicurrency set", can simulate billing requests for policies that use either a single currency or multiple currencies. The multicurrency set makes use of the enhanced version of the Billing API released in BillingCenter 2023.06.0 (the "Hakuba" release).

The `BillingAPIWizardsEnabled` setting determines which set of wizards are used.

- When `false`, the mono-currency wizards are used.
- When `true`, the multicurrency wizards are used.

Applies to: BillingCenter

Default: `true`

MulticurrencyDedicatedUIEnabled

When multicurrency is enabled, this determines how the user interface renders splinter accounts, policy periods, and producers.

- `true` - Splinter accounts, policy periods, and producers are hidden from the user interface. Financial information about the splinters are aggregated in the user interface at the primary account, policy period, and producer levels.
- `false` - Splinter accounts, policy periods, and producers are visible in the user interface. There is no aggregation of financial information for a primary account, policy period, or producer and its splinters.

Applies to: BillingCenter

Default: `true`

Parallel rating parameters

Guidewire provides the following configuration parameters in the `config.xml` file related to parallel rating.

Applies to: PolicyCenter

`EnableCPDTOParallelRating`

Enable parallel rating using data transfer objects (DTOs) for commercial property. This parameter also enables access to Rating Management components in the sample data, such as rate table and rate routines, that use DTOs. These components are included in the small sample dataset and are provided for demonstration purposes.

Applies to: PolicyCenter

Default: `false`

Required: No

Dynamic: Yes

ParallelizedRatingEnabled

Enable or disable parallel rating. If `true`, parallel rating is enabled for each line of business which supports parallel rating. If `false`, parallel rating is disabled.

Applies to: PolicyCenter

Default: `true`

Required: No

ParallelRatingTimeoutPerCoverable

The number of milliseconds per coverable to wait for parallel rating to complete. Because the timeout is per coverable, policies with a large number of coverables will have a longer timeout than smaller policies. This timeout applies to all lines of business that implement parallel rating.

The number of milliseconds per coverable to wait for parallel rating to complete. Because the timeout is per coverable, policies with a large number of coverables will have a longer timeout than smaller policies. This timeout applies to all lines of business that implement parallel rating.

For example, when quoting a policy with 10 coverables and using the default timeout of 20 seconds per coverable, the server times out on rating 200 seconds after it starts. When the timeout is reached, the application displays an error to the user and attempts to stop the rating thread.

Applies to: PolicyCenter

Default: 20000 milliseconds

Required: No

MaxRatingThreadPoolSize

Maximum number of threads spawned during parallel rating. The optimum number of threads depends upon how many tasks the typical policy generates and how long each task takes to complete. The optimum number of threads also depends upon the number of available processors, the typical number of users, and competition for processors from other application features which also implement parallel rating. As a starting point, set the initial value to the number of available processors in your environment. Be aware that other processes or the application features that use parallel processing, such as product model availability, may be competing for processors. Perform benchmark testing to better determine the maximum number of threads.

Applies to: PolicyCenter

Default: 4

Minimum: 1

Maximum: none

Required: No

Parallel product model synchronization parameters

Guidewire provides the following configuration parameters in the `config.xml` file related to parallel product model synchronization.

Applies to: PolicyCenter

MaxProductModelSyncThreadPoolSize

Maximum number of threads spawned during parallel product model synchronization. The maximum number of threads depends upon the number of available processors, the typical number of users, and competition for processors from other PolicyCenter features. As a starting point, set the initial value to the number of available processors in your environment. Be aware that other processes or PolicyCenter features that use parallel processing may be competing for processors. Perform benchmark testing to better determine the maximum number of threads.

Applies to: PolicyCenter

Default: 4

Dynamic: Yes

MinNumberOfCoverablesToParallelizeProductModelSync

The minimum number of coverables on a policy period required to take advantage of parallel product model synchronization. This parameter is used in the `shouldParallelizeProductModelAvailabilitySync` method of the policy period enhancement, `PolicyPeriodBaseEnhancement.gsx`.

Default: 25

Dynamic: Yes

ParallelizedProductModelSyncEnabled

If true, parallel product model synchronization is enabled.

Default: false

Dynamic: Yes

ParallelProductModelSyncTimeoutPerCoverable

The number of milliseconds per coverable to wait for parallel product model synchronization to complete. Because the timeout is per coverable, policies with a large number of coverables will have a longer timeout than smaller policies.

For example, when synchronizing the product model on a policy with 10 coverables and using the default timeout of 20 seconds per coverable, the server times out 200 seconds after it starts. When the timeout is reached, PolicyCenter displays an error to the user and attempts to stop the synchronization thread.

A value of -1 implies no timeout and the queue waits until synchronization completes or the session times out. This is not recommended.

Default: 2500

Dynamic: Yes

Policy exception parameters

Guidewire provides the following configuration parameters in `config.xml` that limit how many days must pass before the Policy Exception Rules run a second time on any given `PolicyPeriod` entity.

Applies to: PolicyCenter

BoundPolicyThresholdDays

The minimum number of days that must pass before the Policy Exception Rules run again on a bound `PolicyPeriod` entity. This integer value must be 0 or greater.

Applies to: PolicyCenter

Default: 14

Dynamic: Yes

ClosedPolicyThresholdDays

The minimum number of days that must pass before the Policy Exception Rules run again on a closed `PolicyPeriod` entity. This integer value must be 0 or greater.

Applies to: PolicyCenter

Default: 14

Dynamic: Yes

OpenPolicyThresholdDays

The minimum number of days that must pass before the Policy Exception Rules run again on an open PolicyPeriod entity. This integer value must be 0 or greater.

Applies to: PolicyCenter

Default: 1

Dynamic: Yes

Policy purge parameters

Guidewire provides configuration parameters in the `config.xml` file that relate to purging policy data older than a pre-defined retention period.

Applies to: PolicyCenter

TruncatePoliciesEnabled

If set to `true`, a work queue to truncate policy data is enabled. If you then run the **Purge Policy Terms** batch process, the system deletes policy data that is older than the threshold defined in the system table `policy_term_retention_threshold_configs`.

Applies to: PolicyCenter

Default: `false`

TruncatePoliciesChunkSize

Defines the number of policy IDs to store for each work item for the truncation work queue. This parameter can be used to ensure that database performance is not affected during a policy purge.

Applies to: PolicyCenter

Default: 50

TruncatePoliciesMinimumTimeToRecheckDays

Defines the minimum number of days that must pass before a policy is rechecked for truncation. This parameter can be used to ensure that database performance is not affected by repeated purges of policy data.

Applies to: PolicyCenter

Default: 30

TruncatePoliciesMinimumThresholdYears

Defines the minimum number of years that must pass before a term can be removed. This value is not used to calculate the term removal date, but is instead provided as a safety check for your configuration. An exception is thrown if the purge plugin (`PCPurgePlugin.gs`) returns a threshold below this value. If you set this value to 0, then no policy data will be purged.

Applies to: PolicyCenter

Default: 1

Print settings parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to printing from the application.

For information on editing `config.xml` and setting configuration parameters, see “Working with configuration parameters” on page 17.

DefaultContentDispositionMode

The Content-Disposition header setting to use when the application returns file content directly to the browser. This parameter applies to printed and exported content. It does not apply to documents. For documents, use the `DocumentContentDispositionMode` parameter. Supported settings are `inline` and `attachment`.

Default: attachment

PrintCsvDefaultBaseFileExtension

Default base output file extension for CSV documents.

Default: csv

PrintCsvMimeType

MIME type used for generated CSV output files.

Default: application/excel

PrintDefaultBaseFileName

Default base output file name for output generation.

Default: Print

PrintFontFamilyName

Use to configure FOP settings for printing non-U.S. character sets. (FOP refers to the Apache Formatting Objects Processor.) Set this value to the name of the font family for custom fonts as defined in your FOP user configuration file. For more information, refer to <http://xmlgraphics.apache.org/fop/>

Default: san-serif

PrintFontSize

Font size of standard print text.

Default: 10pt

PrintFOPUserConfigFile

Path to FOP user configuration file, which contains settings for printing non-U.S. character sets. (FOP refers to the Apache Formatting Objects Processor.) Enter a fully qualified path to a valid FOP user configuration file. There is no default. However, a typical value for this parameter is the following:

```
C:\fopconfig\fop.xconf
```

For more information, refer to <http://xmlgraphics.apache.org/fop/>

Default: None

PrintHeaderFontSize

Font size of headers in print text.

Default: 16pt

PrintLineHeight

Total size of a line of print text.

Default: 14pt

PrintListViewBlockSize

Use to set the number of elements in a list view to print as a block. This parameter splits the list into blocks of this size, with a title page introducing each block of elements. A large block size consumes more memory during printing, which can cause performance issues. For example, attempting to print a block of several thousand elements can potentially cause an out-of-memory error.

Default: 20

PrintListViewFontSize

Font size of text within a list view.

Default: 10pt

PrintMarginBottom

Bottom margin size of print page.

Default: 0.5in

PrintMarginLeft

Left margin size of print page.

Default: 1in

PrintMarginRight

Right margin size of print page.

Default: 1in

PrintMarginTop

Top margin size of print page.

Default: 0.5in

PrintMaxNestedListViewSize

When printing a list view that is nested inside a detail view, the list view is truncated to the number of rows set by this parameter. Nested lists cause the PDF generator to consume additional memory, so this parameter prevents long nested lists from causing memory problems.

Default: 100

PrintMaxPDFInputFileSize

During PDF printing, the application first creates an intermediate XML file as input to a PDF generator. If the input is very large, the PDF generator can run out of memory.

Value	Purpose
Negative	A negative value indicates that there is no limit on the size of the XML input file to the PDF generator.
Non-negative	A non-negative value limits the size of the XML input file to the set value (in megabytes). If a user attempts to print a PDF file that is larger in size than this value, the application generates an error.

Default: -1

PrintPageHeight

Total print height of page.

Default: 8.5in

PrintPageWidth

Total print width of page.

Default: 11in

PrintPdfDefaultBaseFileExtension

Default base output file extension for PDF documents.

Default: 11in

PrintPdfMimeType

MIME type used for generated PDF output files.

Default: application/pdf

Product model parameters

Guidewire provides the following configuration parameters in `config.xml` that relate to the PolicyCenter product model.

Applies to: PolicyCenter

CoverableCacheEnabled

Whether the cache that holds jurisdictions and reference dates for coverables is enabled.

Applies to: PolicyCenter

Default: false

ExternalProductModelDirectory

Specifies the directory from which to load product model availability data. PolicyCenter loads the information in this directory at server startup time or if requested through the Server Tools **Product Model Info** screen. For the load to succeed, all of the following must be true:

- The parameter specifies a directory accessible to the application server.
- The directory is not in the deployment directory.
- The directory contains a complete product model definition that only defines existing patterns.
- The directory contains at least one lookup XML file ending in `-lookups.xml`.

- The XML files in the directory are all valid.

If this parameter is blank, PolicyCenter loads availability data from the standard configuration module at server startup time. Any attempt to reload the data through the Server Tools **Product Model Info** screen then fails with an error message.

Applies to: PolicyCenter

Default: None

Dynamic: No

[See also](#)

- *Product Model Guide*
- *InsuranceSuite Server Administration*

ProductModelClassCacheConcurrencyLevel

To fine tune performance, use this parameter to adjust the concurrency level of the product model class cache. This cache is lazy-loaded when product model pattern objects, such as coverage patterns, are instantiated. See `com.google.common.cache.CacheBuilder#concurrencyLevel` for more information about caches and concurrency levels. The minimum value is 1. The maximum value is 100.

Applies to: PolicyCenter

Default: 10

Dynamic: No

[StrictProductModelIdUniquenessChecking](#)

Whether to check product model code identifier, `CodeIdentifier`, for uniqueness for all the product model objects.

Guidewire recommends that all product model code identifiers be unique. However, this is not strictly enforced.

Regardless of the setting of this parameter, `Product`, `PolicyLinePattern`, and `CoveragePattern` must have unique code identifiers. If they are not unique, PolicyCenter will not compile.

If `StrictProductModelIdUniquenessChecking` is true, PolicyCenter throws an error if two product model patterns of any type share the same code identifier.

If the parameter is false, PolicyCenter logs a warning if two product model patterns of the following types have the same identifier:

- | | |
|----------------------------------|---------------------------------|
| • <code>Product</code> | • <code>ConditionPattern</code> |
| • <code>PolicyLinePattern</code> | • <code>ExclusionPattern</code> |
| • <code>CoveragePattern</code> | • <code>QuestionSet</code> |

Even with warnings, PolicyCenter will start. To be more compliant with the recommendation that all code identifiers be unique, you can fix these issues.

Applies to: PolicyCenter

Default: true

Quote purging configuration parameters

This topic describes quote purging configuration parameters related to *purging* jobs and *pruning* policy periods.

Purging removes jobs after a specified length of time has passed. The jobs must meet the purging criteria.

Pruning removes deselected policy periods attached to a job. The selected policy period is specified by the `SelectedVersion` property on the `Job` entity. Deselected policy periods are any policy periods attached to the job that are not the `SelectedVersion`.

Applies to: PolicyCenter

[See also](#)

- *Configuration Guide*
- *Application Guide*

PruneAndPurgeJobsEnabled

Specifies whether the Purge batch process is enabled.

Applies to: PolicyCenter

Default: false

[See also](#)

- "Enable quote purging batch processes" in *Configuration Guide*

PruneVersionsDefaultRecheckDays

The minimum number of days that must pass after failing a purging check before reconsidering the deselected policy periods on the job for pruning.

Applies to: PolicyCenter

Default: 30

PruneVersionsPolicyTermDays

The minimum number of days that must pass after a job's selected policy period has ended before the deselected policy periods on the job are eligible for pruning. This parameter is ignored if `PruneVersionsPolicyTermDaysCheckDisabled` is true.

Applies to: PolicyCenter

Default: 30

PruneVersionsPolicyTermDaysCheckDisabled

If true, then disable the `PruneVersionsPolicyTermDays` parameter. Setting this parameter to true does not disable pruning closed jobs.

Applies to: PolicyCenter

Default: false

PruneVersionsRecentJobCompletionDays

The minimum number of days that must pass after a job is closed before the deselected policy periods on the job are eligible for pruning.

Applies to: PolicyCenter

Default: 210

PurgeJobsDefaultRecheckDays

The minimum number of days that must pass after failing a purging check before a job is reconsidered for purging.

Applies to: PolicyCenter

Default: 30

PurgeJobsPolicyTermDays

The minimum number of days that must pass after the end of a job's selected policy period before the job is eligible for purging. This parameter is ignored if `PurgeJobsPolicyTermDaysCheckDisabled` is `true`.

Applies to: PolicyCenter

Default: 30

PurgeJobsPolicyTermDaysCheckDisabled

If `true`, then disable the `PurgeJobsPolicyTermDays` parameter. Setting this parameter to `true` does not disable purging closed jobs.

Applies to: PolicyCenter

Default: `false`

PurgeJobsRecentJobCompletionDays

The minimum number of days that must pass after a job is closed before the job is eligible for purging.

Applies to: PolicyCenter

Default: 210

PurgeOrphanedPolicyPeriodsEnabled

Specifies whether the Purge Orphaned Policy Periods batch process is enabled.

Applies to: PolicyCenter

Default: `false`

[See also](#)

- "Enable quote purging batch processes" in *Configuration Guide*

PurgePolicyTermsEnabled

If `true`, unbound renewal and rewrite policy transactions are considered for purging. If `false`, disable policy terms for renewal and rewrite policy transactions are not considered for purging. This parameter only applies to these two policy transaction types.

Applies to: PolicyCenter

Default: `false`

Rating Management parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to Guidewire Rating Management.

IMPORTANT: To determine whether your Guidewire PolicyCenter license agreement includes Guidewire Rating Management, contact your Guidewire sales representative. Using Rating Management within PolicyCenter requires an additional license key. For instructions on obtaining and installing this key, contact your Guidewire support representative.

Applies to: PolicyCenter

EnableRateRoutinesJar

Set this Boolean parameter to true if you want rate routines to be preloaded from the rate routines JAR file at system startup. This parameter also enables the **Generate JAR File** and **Download JAR File** buttons on the **Rate Books** screen.

If you enable this parameter, then you must also specify the location in the RateRoutinesJarFile parameter.

Applies to: PolicyCenter

Default: false

Set for server: Yes

Dynamic: Yes

[See also](#)

- *Configuration Guide*

OverriddenTableArgsLabelSimple

You can speed up rate table preloading by setting the parameter OverriddenTableArgsLabelSimple to true. (The RateBookPreloadEnabled parameter must also be true.)

When true, when viewing a rate routine on the Rate Routine screen, parameters in rate routine steps may appear as ellipses (...).

Applies to: PolicyCenter

Default: false

Set for server: Yes

Dynamic: Yes

PurgeRateBookExportResultEnabled

If true, enable Purge Rate Book Export Result batch processing.

Applies to: PolicyCenter

Default: true

Set for server: No

PurgeWorksheetsEnabled

Enable the Purge Rating Worksheets batch process.

Applies to: PolicyCenter

Default: false

Set for server: No

[See also](#)

- *Configuration Guide*

RateBookCacheEntryLifetimeSecs

The maximum time in seconds that a non-active rate book can stay in the rate book cache without being refreshed.

Applies to: PolicyCenter

Default: 3600

Minimum: 1

Maximum: 2592000 (30 days)

Set for server: Yes

[See also](#)

- "Improving performance of rate tables loaded in memory" in *Configuration Guide*

RateBookCacheUpdateIntervalSecs

The time in seconds after which the rate book cache is rebuilt: all non-active rate books are refreshed and any rate books added after the last update are added to the cache.

Applies to: PolicyCenter

Default: 86400

Minimum: 1

Maximum: 2592000 (30 days)

Set for server: Yes

[See also](#)

- "Improving performance of rate tables loaded in memory" in *Configuration Guide*

RateBookExportResultAgeForPurging

Purge Rate Book Export Result batch processing removes from the PolicyCenter database RateBookExportResult Excel and XML files that have been around for more days than this parameter.

Applies to: PolicyCenter

Default: 60

Set for server: No

RateBookPreloadEnabled

This parameter determines whether to load Rating Management components on system startup. If true, PolicyCenter loads all rate books and their associated rate routines and rate tables on system startup.

Note: Unrelated to whether this parameter is true or false, PolicyCenter always preloads some parts of rate books that load quickly. After this, PolicyCenter writes this message to the log file:

```
INFO Application.Rating.RateTableManagement Preloading all ratebooks
```

Therefore, this message is not an indication of the RateBookPreloadEnabled parameter setting.

Applies to: PolicyCenter

Default: true

Set for server: Yes

[See also](#)

- *Configuration Guide*

RateRoutineIndexingThreshold

When editing a long rate routine, you can edit the rate routine by section. A long rate routine has more steps than the value of the indexing threshold, the RateRoutineIndexingThreshold parameter.

Applies to: PolicyCenter

Default: 150

Set for server: No

Dynamic: Yes

RateRoutinesJarFile

Specify the file system location of the rate routines JAR file. May be an absolute path or path relative to the web application root. For allowed locations, see *Plugins, Prebuilt Integrations, and SOAP APIs*. Guidewire recommends that you deploy the JAR file in the following location:

```
modules/configuration/plugins/Gosu/lib/rateroutines.jar
```

For example, if you are running PolicyCenter under Apache Tomcat and the WAR file expands into `TOMCAT_HOME/webapps/pc`, where `TOMCAT_HOME` is the Tomcat root directory, then set `RateRoutinesJarFile` to `webapps/pc/modules/configuration/plugins/Gosu/lib/rateroutines.jar`.

If the directory does not exist, PolicyCenter attempts to create it. If the file exists, it must be a valid JAR file. If the file does not exist, PolicyCenter creates it if `EnableRateRoutinesJar` is true. If the JAR does not exist at startup, PolicyCenter compiles all rate routines in the rate books returned by the `RateBookPreloadPlugin` to the JAR. To avoid this delay during startup, deploy the JAR file to the production system when you build PolicyCenter.

Applies to: PolicyCenter

Default: Empty string

Set for server: Yes

Dynamic: Yes

[See also](#)

- “Precompile rate routines JAR file”

RateRoutinesUpdateJarFile

Specify the location of the rate routines JAR file that is updated dynamically while PolicyCenter is running. If you specify this parameter, PolicyCenter modifies the file referred to by it whenever an update event happens. If you do not specify this parameter, PolicyCenter updates the file pointed to by `RateRoutinesJarFile`.

Note:

You must use this parameter if you are running PolicyCenter on Windows Server.

For allowed locations, see *Plugins, Prebuilt Integrations, and SOAP APIs*. Guidewire recommends that you deploy the JAR file in the following location:

```
modules/configuration/plugins/Gosu/lib/rateroutines_update.jar
```

If the directory does not exist, PolicyCenter attempts to create it.

Applies to: PolicyCenter

Default: Empty string

Set for server: Yes

Dynamic: Yes

Modify the startup process

If you specify `RateRoutinesUpdateJarFile`, the JAR file must not exist at system startup. If it exists, PolicyCenter throws an exception and fails to start. Therefore, perform these steps before starting the server:

1. If the file specified by `RateRoutinesUpdateJarFile` exists, then copy it to the file specified by `RateRoutinesJarFile`.
2. Delete the file specified by `RateRoutinesUpdateJarFile`.
3. Start the server.

For example, the following Windows shell script starts the server on Tomcat:

```
SET ROUTINES_JAR = %TOMCAT_HOME%\webapps\pc\modules\configuration\plugins\gosu\lib\rateroutines.jar
SET UPDATE_JAR=%TOMCAT_HOME%\webapps\pc\modules\configuration\plugins\gosu\lib\rateroutines_update.jar
IF EXIST %UPDATE_JAR% {
    del %ROUTINES_JAR%
    ren %UPDATE_JAR% %ROUTINES_JAR%
}
%TOMCAT_HOME%\bin\startup.bat
```

RateTableCacheConcurrency

Provides guidance on the maximum number of concurrent operations on the rate table cache.

Applies to: PolicyCenter

Default: 8

Minimum: 1

Maximum: 32

Set for server: Yes

[See also](#)

- "Improving performance of rate tables loaded in memory" in *Configuration Guide*

RateTableCacheEntryLifetimeSecs

The maximum time in seconds for which a rate table in a non-active rate book can stay in the rate table cache without being refreshed.

Applies to: PolicyCenter

Default: 600

Minimum: 1

Maximum: 2592000 (30 days)

Set for server: Yes

[See also](#)

- "Improving performance of rate tables loaded in memory" in *Configuration Guide*

RateTableCacheMaxSize

The maximum number of rate tables that can be in the rate table cache. For no limit, set to -1. To disable rate table caching, set to 0.

Applies to: PolicyCenter

Default: -1

Set for server: Yes

[See also](#)

- "Improving performance of rate tables loaded in memory" in *Configuration Guide*

RateTableCacheUpdateIntervalSecs

The time in seconds after which the rate table cache is cleared.

Applies to: PolicyCenter

Default: 3600

Minimum: 1

Maximum: 2592000 (30 days)

Can change value on running server: true

[See also](#)

- "Improving performance of rate tables loaded in memory" in *Configuration Guide*

RateTableDefinitionCacheEntryLifetimeSecs

The maximum number of seconds that a cache entry can remain in the cache without being refreshed.

Applies to: PolicyCenter

Default: 3600

Minimum: 1

Maximum: 2592000 (30 days)

Set for server: Yes

[See also](#)

- "Improving performance of rate tables loaded in memory" in *Configuration Guide*

RateTableDefinitionCacheUpdateIntervalSecs

The time in seconds after which the rate table definition cache is cleared.

Applies to: PolicyCenter

Default: 86400

Minimum: 0

Maximum: 2592000 (30 days)

Set for server: Yes

[See also](#)

- "Improving performance of rate tables loaded in memory" in *Configuration Guide*

RateTableManagementNormalizationRowLimit

PolicyCenter determines whether to normalize a rate table if the table contains this many rows or more.

If the number of rows in the normalized table would exceed this limit, the table is automatically marked as non-normalizable. PolicyCenter stores the non-normalized version of the table.

Applies to: PolicyCenter

Default: 5000

Set for server: No

Dynamic: Yes

[See also](#)

- *Configuration Guide*

RateTableManagementNormalizationRowThreshold

If the number of rows in the normalized table would exceed this threshold, the user is given the option to store a non-normalized version of the table.

Applies to: PolicyCenter

Default: 1000

Set for server: No

Dynamic: Yes

[See also](#)

- *Configuration Guide*

RatingWorksheetContainerAgeForPurging

The Purge Rating Worksheets batch process uses this parameter as one factor in determining if a worksheet container can be purged. To be considered for purging, the worksheet container's job must have been completed at least RatingWorksheetContainerAgeForPurging days.

Applies to: PolicyCenter

Default: 90

Set for server: No

[See also](#)

- "Purge Rating Worksheet batch process"

SmallRateTableRowLimit

Before importing rate tables, PolicyCenter scans the import file. The scan does not examine rate tables with more rows than specified in SmallRateTableRowLimit.

Applies to: PolicyCenter

Set for server: No

Dynamic: Yes

Risk assessment parameters

Risk assessment parameters enable you to set the URL for log in to Guidewire Spotlight and to access risk assessment services.

You must change the default URL, `example.com`, to enable testing or using Spotlight services.

[See also](#)

- *Configuration Guide*
- *Application Guide*

MultipleLocationRiskAssessmentEnabled

Specify whether multiple location risk assessment calls can be made to Spotlight.

Default: false

PurgeRiskAssessmentTempStoreDays

Minimum number of days that must pass after temporary risk assessment objects has been created before the objects can be eligible for purging.

Default: 30

See also

- *Administration Guide*

RiskAssessmentIntegrationEnabled

Enable or disable access to all Spotlight services from PolicyCenter.

Default: false

RiskAssessmentThumbnailMapEnabled

Enable or disable access to Spotlight thumbnail map service.

Default: false

SingleLocationRiskAssessmentEnabled

Specify whether single location risk assessment calls may be made to Spotlight.

Default: false

SpotlightInteractiveServiceURL

Specifies the URL to the Spotlight interactive service. This service provides interactive access to Spotlight.

Default: http://example.com

SpotlightLoginURL

Specifies the URL to the Spotlight login screen.

Default: http://example.com

SpotlightRiskAssessmentServiceURL

Specifies the URL to the Spotlight risk assessment service.

Default: http://example.com

SpotlightThumbnailMapURL

Specifies the URL to the Spotlight thumbnail map service.

Default: http://example.com

Scheduler and workflow parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to batch process scheduler and workflow.

For information on editing `config.xml` and setting configuration parameters, see “Working with configuration parameters” on page 17.

IdleClaimThresholdDays

ClaimCenter schedules claims that have not been touched (including edits or exception checks) for this many days for exception detection. This integer value must be 0 or greater.

Applies to: ClaimCenter

Default: 7

Dynamic: Yes

SchedulerEnabled

Whether to enable the internal batch process application scheduler.

Dynamic: Yes

SeparateIdleClaimExceptionMonitor

If true, run exception monitoring rules for idle cases at a separate time.

Applies to: ClaimCenter

Default: true

WorkflowLogDebug

Configuration parameter WorkflowLogDebug takes a Boolean value:

- If set to true, the application outputs the ordinary verbose system workflow log messages from the Guidewire server to the workflow log.
- If set to false, the application does not output any of the ordinary system messages.

The setting of this parameter does not have any effect on calls to log workflow messages made by customers. Therefore, all customer log messages are output. If customers experience too many workflow messages being written to the `xx_workflowlog` table, Guidewire recommends that you set this parameter to false.

Default: true

WorkflowLogPurgeDaysOld

Number of days to retain workflow log information before PurgeWorkflowLogs batch processing deletes it.

Default: 30

WorkflowPurgeDaysOld

Number of days to retain workflow information before PurgeWorkflows batch processing deletes it.

Default: 60

WorkflowStatsIntervalMins

Aggregation interval in minutes for workflow timing statistics. Statistics such as the mean, standard deviation, and similar statistics used in reporting on the execution of workflow steps all use this time interval. A value of 0 disables statistics reporting.

Default: 60

Search parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to searching.

For information on editing `config.xml` and setting configuration parameters, see “Working with configuration parameters” on page 17.

FreeTextSearchEnabled

Whether to enable the free-text search feature. Setting the `FreeTextSearchEnabled` parameter to `true` enables the free-text plugins for indexing and search. Setting the parameter to `true` also enables the display of the following user interface screens, which use free-text search, :

ClaimCenter

Search > Claims > Search by Contact

PolicyCenter

Search Policies > Basic

screen, which uses free-text search.

Applies to: ClaimCenter, PolicyCenter

Default: `false`

IMPORTANT: Change the value of this parameter only in a development environment that uses the application installed locally. Do not change the value of this parameter in an environment that uses the application on Guidewire Cloud. In that environment, you enable free-text search in Guidewire Home.

[See also](#)

- "Guidewire Advance Search configuration parameters and files" in *Configuration Guide*

MaxActivitySearchResults

Maximum number of activities that ClaimCenter returns in a search. If the number to return is greater than this value, ClaimCenter prompts the user to narrow the search parameters. This integer value must be 1 or greater.

Applies to: ClaimCenter

Default: 300

MaxBulkInvoiceSearchResults

Maximum number of bulk invoices that ClaimCenter returns in a search. If the number to return is greater than this value, ClaimCenter prompts the user to narrow the search parameters. This integer value must be 1 or greater.

Applies to: ClaimCenter

Default: 300

MaxCheckSearchResults

Maximum number of checks that ClaimCenter returns in a search. If the number to return is greater than this value, ClaimCenter prompts the user to narrow the search parameters. This integer value must be 1 or greater.

Applies to: ClaimCenter

Default: 300

MaxClaimSearchResults

Maximum number of results that ClaimCenter returns for a claim search. This integer value must be 1 or greater. If the number of results to return is greater than this value, ClaimCenter prompts the user to narrow the search parameters.

Applies to: ClaimCenter

Default: 300

MaxContactSearchResults

Maximum number of contacts that the application returns in a search. If the number to return is greater than this value, then the application prompts the user to narrow the search parameters. This integer value must be 1 or greater.

Default (BillingCenter, PolicyCenter): 100

Default (ClaimCenter): 300

MaxContactDocumentSearchResults

The maximum number of contact documents search results retrieved from ContactManager.

Applies to: ClaimCenter

Default: 100

MaxDocTemplateSearchResults

Maximum number of document templates that ClaimCenter returns in a search. If the number to return is greater than this value, then ClaimCenter prompts the user to narrow the search parameters. This integer value must be 1 or greater.

Applies to: ClaimCenter

Default: 50

MaxDuplicateContactSearchResults

Maximum number of duplicate results to return from a contact search. This integer value must be 0 or greater.

Applies to: ClaimCenter

Default: 25

MaxNoteSearchResults

Maximum number of notes that ClaimCenter returns in a search. If the number to return is greater than this value, ClaimCenter prompts the user to narrow the search parameters. This integer value must be 0 or greater. A value of 0 indicates that there is no limit on the search.

Applies to: ClaimCenter

Default: 25

MaxPolicySearchResults

Maximum number of policies that ClaimCenter returns in a search. If the number to return is greater than this value, then ClaimCenter prompts the user to narrow the search parameters. This integer value must be 1 or greater.

Applies to: ClaimCenter

Default: 25

MaxRecoverySearchResults

Maximum number of policies that ClaimCenter returns in a search. If the number to return is greater than this value, then ClaimCenter prompts the user to narrow the search parameters. This integer value must be 1 or greater.

Applies to: ClaimCenter

Default: 300

MaxSearchResults

Maximum number of results that BillingCenter search screens will return. If the number of search results is greater than this value, BillingCenter prompts the user to narrow the search parameters. To specify that the number of search results is not limited, set this parameter to -1.

You can also override the `MaxSearchResults` parameter for individual search screens. Each search screen that uses the `MaxSearchResults` configuration parameter has a corresponding `maxSearchResults` PCF property. To set a different search result limit for a particular screen, edit the `maxSearchResults` PCF property for that screen.

The contact search screen and the payment search screen do not use the `MaxSearchResults` configuration parameter. The contact search screen uses `MaxContactSearchResults`. The payment search screen includes multiple result tabs and does not limit the number of search results.

Applies to: BillingCenter

Default: 300

[See also](#)

- “Configuring search functionality for BillingCenter”

PolicySearchMaxResult

Number of maximum results to return from a database policy search. This parameter has no effect on free-text policy search.

Default: 300

[See also](#)

- “Configuring search functionality for PolicyCenter and ClaimCenter”

Seasonal coverage parameters

Guidewire provides configuration parameters in the `config.xml` file that relate to seasonal coverages on coverables.

Applies to: PolicyCenter

ApplySeasonalDiffItemsFirst

If true, when applying changes to a preempted policy period or a future policy period, **DiffItems** related to seasonal data or seasonal date ranges are applied first, allowing the policy period to be resliced before the remaining **DiffItems** are applied.

Applies to: PolicyCenter

Default: false

Security parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to application security.

For information on editing `config.xml` and setting configuration parameters, see “Working with configuration parameters” on page 17.

AbsoluteMaxSessionLength

The maximum number of minutes that an active session is maintained, regardless of user activity. A request with a session that was created a greater number of minutes ago than this setting is immediately invalidated and all in-progress work is lost.

Default: 600

Set for server: Yes

EnableAbsoluteMaxSessionLength

Whether to enforce an absolute maximum session length, regardless of user activity. If an active authenticated session passes the `AbsoluteMaxSessionLength` number of minutes, the session is invalidated immediately and all in-progress work is lost.

Default: false

Set for server: Yes

EnableDownlinePermissions

If `UseACLPermissions` is true, then setting this parameter to true means that supervisors inherit permissions on an object that has been added for a supervised user or group.

Default: true

ExternalUserAccess

Indicate which groups and producer codes are available to external users. In order of increasing access, values are:

- **FULLYRESTRICTED** – External users can be assigned to groups only within their organization. Users inherit producer codes from their groups. In addition, external users can be assigned producer codes from their organization.
- **PROTECTINTERNAL** – External users can be assigned to any external groups. Users inherit producer codes from their groups. In addition, external users can be assigned producer codes from any external organization.
- **ALLOWINTERNAL** – External users can be assigned to any groups, internal or external. Users inherit producer codes from their groups. In addition, external users can be assigned producer codes from internal or external organizations.

Note: You can change the value only to increase access. The server will not start if you set `ExternalUserAccess` to a value that decreases access. For example, if you change the value to `ALLOWINTERNAL`, and start the server, you cannot change it back to `FULLYRESTRICTED` or `PROTECTINTERNAL`. If you drop the database, in development or test mode for example, then you can decrease access.

Applies to: PolicyCenter

Default: FULLYRESTRICTED

Permanent: Semi-permanent

[See also](#)

- *Application Guide*

FailedAttemptsBeforeLockout

Number of failed attempts that the application permits before locking out a user. For example, setting this value to 3 means that the third unsuccessful try locks the account from further repeated attempts. This integer value must be 1 or greater. A value of -1 disables this feature.

Default: 3

Minimum: -1

LockoutPeriod

Length of time in seconds for which the application locks a user account. A value of -1 indicates that a system administrator must manually unlock a locked account.

Default: -1

LoginRetryDelay

Time in milliseconds before a user can retry after an unsuccessful login attempt. This integer value must be 0 or greater.

Default: 0

Minimum: 0

MaxACLParameters

Maximum number of users and groups to directly include in search queries that check the claim access control list. Beyond this maximum limit, ClaimCenter stores users and groups in database tables. You must then use an additional join in the query to check the claim access control list.

Checking the claim access control list can involve a large number of groups and users. For example, if `EnableDownlinePermissions` is true, someone who supervises many groups and users has access to control lists that contain any of their supervisees. Including all these groups and users in the query can be done directly by including them as parameters to the query. Or, you can store them in database tables and doing extra joins in the query.

For small numbers of groups and users, direct parameters are the best choice. For large numbers, in the range of thousands, the extra join can be better. This parameter, `MaxACLParameters`, determines the point at which the query code switches from using direct parameters to using extra joins.

The `MaxACLParameters` can take the following values.

In summary, Guidewire recommends that most ClaimCenter installations use the default value of -1, which chooses the best value for the current database type.

A value of -1 or less

Use the appropriate default for the current database. Thus, ClaimCenter chooses the best value, as determined by Guidewire performance testing, for the current type of database.

A value of 0

Always use parameters, and never use a join in a query.

A value of +1 or greater

Use that value as a threshold. If the number of groups and users is less than the threshold, then a query uses parameters. If the number is larger the threshold, a query uses database tables and extra joins.

Applies to: ClaimCenter

Default: -1

MaxPasswordLength

New passwords must be no more than this many characters long. This integer value must be 0 or greater.

Default: 16

MinPasswordLength

New passwords must be at least this many characters long. For security purposes, Guidewire recommends that you set this value to 8 or greater. This integer value must be 0 or greater. If 0, then the application doesn't require a password. (Guidewire does not recommend this.)

Default: 8

Minimum: 0

ProducerCodeCyclesAllowed

Whether the user can induce cycles in the producer code graph through the user interface or import. For example, producer code C has parent B, and B has parent A. If `true`, the user can set A's parent to A, B, or C.

Applies to: PolicyCenter

Default: false

RestrictContactPotentialMatchToPermittedItems

Whether the application restricts the match results from a contact search screen to those that the user has permission to view.

Default: true

RestrictSearchesToPermittedItems

On contact search screens, whether the application restricts the results of a search to those that the user has permission to view. This does not affect other searches in the application.

Default: true

SessionTimeoutSecs

The number of seconds of user inactivity after which the browser session expires.

This parameter sets the session expiration timeout globally for all application browser sessions. For more information on controlling the session timeout, see the *Administration Guide*. Also see the parameters “AbsoluteMaxSessionLength” on page 103 and “EnableAbsoluteMaxSessionLength” on page 103.

Default: 10800

Minimum: 300

Maximum: 604800

SingleSignOnAuthenticationEnabled

Whether authentication is done through external single sign-on (SSO).

Default: false

Set for server: Yes

UseACLPermissions

Whether to use the ACL permission model.

- If false, the privilege that a user holds applies to every claim.
- If true, the ClaimAccess table controls claim access.

Applies to: ClaimCenter

Default: true

Segmentation parameters

Guidewire provides the following configuration parameters in the config.xml file that relate to claim and exposure segmentation.

Applies to: ClaimCenter

ClaimSegment

Default value to set the Segment field to on a claim, if ClaimCenter cannot determine another segment.

Applies to: ClaimCenter

Required: Yes

ClaimStrategy

The default value to set the Strategy field to on a claim, if ClaimCenter cannot determine another strategy.

Applies to: ClaimCenter

Required: Yes

ExposureSegment

Default value to set the Segment field to on an exposure, if ClaimCenter cannot determine another segment.

Applies to: ClaimCenter

Required: Yes

ExposureStrategy

Default value to set the Strategy field on an exposure, if ClaimCenter cannot determine another strategy.

Applies to: ClaimCenter

Required: Yes

Service request parameters

Guidewire provides the following configuration parameters in the config.xml file that relate to claim and exposure segmentation.

For information on editing config.xml and setting configuration parameters, see “Working with configuration parameters” on page 17.

ServiceRequestAPIMaxDaysKeepActiveWithoutInvoice

Maximum number of days that a service request will be considered active by the ServiceRequestAPI when it is work complete but has no valid invoices.

Applies to: ClaimCenter

Default: 90

Set for server: Yes

ServiceRequestAPIMaxMessageResults

Maximum number of service request messages returned through the ServiceRequestAPI web service.

Applies to: ClaimCenter

Default: 50

Set for server: Yes

ServiceRequestAPIMaxSearchResults

Maximum number of service requests returned by a search performed through the ServiceRequestAPI web service.

Applies to: ClaimCenter

Default: 250

Set for server: Yes

Servlet parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to servlets.

For information on editing `config.xml` and setting configuration parameters, see “Working with configuration parameters” on page 17.

EnableInfoServlet

Whether to enable the `info` servlet that provides a list of the components in the application and their version numbers. For information about this servlet, see *Plugins, Prebuilt Integrations, and SOAP APIs*.

Applies to: ClaimCenter, PolicyCenter

Default: false

EnableVerbosePingServlet

Whether to enable the `ping` servlet that serves ping information. See *Plugins, Prebuilt Integrations, and SOAP APIs* for more information on this servlet.

Default: false

Side-by-side quoting parameters

Guidewire provides the following configuration parameters in `config.xml` that relate to side-by-side quoting.

PolicyCenter provides a number of configuration parameters related to the display of side-by-side quotes in the PolicyCenter interface. For a discussion of side-by-side quoting, see the *Application Guide*.

Applies to: PolicyCenter

RenewalMaxSideBySideQuotes

Sets an upper limit on the number of versions to show on a side-by-side quote page for a policy renewal.

Applies to: PolicyCenter

Default: 4

SideBySide

Determines whether validation warnings block **Quote All** in side-by-side quoting.

In the default configuration, **Quote All** in the **Side by Side Quoting** screen does not produce quotes when there are validation warnings. This is to prevent PolicyCenter from generating invalid quotes. Guidewire expects that the default implementation is suitable for most implementations.

Applies to: PolicyCenter

Default: true

[See also](#)

- For more information about setting this parameter, see *Configuration Guide*.

SubmissionMaxSideBySideQuotes

Sets an upper limit on the number of versions to show on a side-by-side quote page for a policy submission.

Applies to: PolicyCenter

Default: 4

PolicyChangeMaxSideBySideQuotes

Sets an upper limit on the number of versions to show on a side-by-side quote page for a policy change.

Applies to: PolicyCenter

Default: 4

SideBySideTwoStepQuotingEnabled

Enables two-step quoting in side-by-side policy transactions in all policy lines that implement side-by-side quoting.

Applies to: PolicyCenter

Default: true

MaxParallelQuotingThreads

Determines the maximum number of threads to use when quoting side-by-side versions. PolicyCenter creates a thread for each side-by-side version up to the maximum specified by this parameter.

Applies to: PolicyCenter

Default: 3

Smart Communications for PolicyCenter parameters

Guidewire provides the following configuration parameters in `config.xml` that relate to Smart Communications for PolicyCenter.

Applies to: PolicyCenter

DocumentProductionIntegrationEnabled

Enable or disable Smart Communications for PolicyCenter.

Applies to: PolicyCenter

Default: false

DocumentProductionBindingType

Specifies when Smart Communications for PolicyCenter creates documents. Values are:

- EARLY – Early binding
- EARLY_DEFERRED – Early deferred binding
- LATE – Late binding

EARLY_DEFERRED and LATE require additional configuration.

Applies to: PolicyCenter

Default: EARLY

Statistics, team, and dashboard parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to ClaimCenter statistics, the **Team** tab, and the **Dashboard**.

Applies to: ClaimCenter

AddIndexHintForLossDate

Applies only when running on an Oracle database. When true, improves the performance of a particular database query that is executed on the **Desktop Activities** screen. This parameter enables a database hint on the index `Claim.claimu7u`. Therefore, if you modify this index, then you may have better performance on the **Desktop Activities** screen by setting this parameter to false, thereby disabling the hint.

Applies to: ClaimCenter

Default: true

AgingStatsFirstDivision

Number of days to use in calculating the first claim aging bucket. This bucket includes claims between 0 and `AgingStatsFirstDivision` days old. This integer value must be 0 or greater.

Applies to: ClaimCenter

Default: 30

AgingStatsSecondDivision

Number of days to use in calculating the second claim aging bucket. This bucket includes claims between `AgingStatsFirstDivision + 1` and `AgingStatsSecondDivision` days old. This integer value must be 0 or greater.

Applies to: ClaimCenter

Default: 60

AgingStatsThirdDivision

Number of days to use in calculating the third claim aging bucket. This bucket includes claims between `AgingStatsSecondDivision + 1` and `AgingStatsThirdDivision` days old. The last bucket includes all claims older than `AgingStatsThirdDivision` days. This integer value must be 0 or greater.

Applies to: ClaimCenter

Default: 120

CalculateLitigatedClaimAgingStats

Whether to show the number of litigated claims on the **Aging** subtab of the **Team** tab.

Applies to: ClaimCenter

Default: true

DashboardIncurredLimit

Total incurred amount above which ClaimCenter counts the claim as over-the-limit in executive dashboard calculations.

Applies to: ClaimCenter

Default: 1000000

DashboardShowByCoverage

Whether the **Dashboard** shows claim information subtotaled by coverage.

Applies to: ClaimCenter

Default: true

DashboardShowByLineOrLoss

Whether the **Dashboard** shows claim information subtotaled by line of business or loss type.

Applies to: ClaimCenter

Default: true

DashboardWindowPeriod

Number of days to use for executive dashboard calculations that depends on a specific time period.

Applies to: ClaimCenter

Default: 30

GroupSummaryShowUserGlobalWorkloadStats

Whether to show individual user global workload statistics along with the standard statistics in the **Team Summary** page.

Applies to: ClaimCenter

Default: true

UserStatisticsWindowSize

Time window for calculating user statistics. Set this value to the number of previous days to include in the calculation. For example, set it to 10 to calculate statistics for the last 10 days, including today. You can also set this parameter to one of the following special values:

Value	Description
0	This week, defined as the start of the current business week up to and including today.
-1	This month, defined as the start of the current month up to and including today.

Applies to: ClaimCenter

Default: 0

Test framework parameters

Guidewire provides the following configuration parameter in the `config.xml` file that relates to InsuranceSuite Behavior Testing Framework tests and GUnit tests.

Applies to: PolicyCenter

DefaultTestProductCode

The product code that the job builder class `JobBuilder` uses to create a job. InsuranceSuite Behavior Testing Framework tests and GUnit tests use this builder to test job behavior.

Applies to: PolicyCenter

Default: PersonalAuto

Set for server: Yes

Two-step quoting parameters

Guidewire provides configuration parameters in the `config.xml` file that relate to two-step quoting.

Applies to: PolicyCenter

TwoStepQuotingEnabled

If true, then two-step quoting is enabled in PolicyCenter. In the base configuration, each policy line has its own property that determines whether two-step quoting is available for that policy line when two-step quoting is enabled in PolicyCenter.

Applies to: PolicyCenter

Default: true

User interface parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to the application interface.

For information on editing `config.xml` and setting configuration parameters, see “Working with configuration parameters” on page 17.

ActionsShortcut

The keyboard shortcut to use for the **Actions** button.

Default: A

AutoCompleteLimit

The maximum number of autocomplete suggestions to show.

Default: 10

HidePolicyObjectsWithNoCoveragesForLossTypes

It is possible to add a coverage at either the Policy level, or, directly on the covered item (a vehicle, for example). This parameter applies to coverages applied at the Policy level, rather than those coverages applied to individual items covered in the policy. It affects the individual coverage submenus in the ClaimCenter **Actions** > **New Exposure** > **Choose by Coverage** submenu. To remove (hide) empty Vehicle and Property submenus for a specific loss type, add that loss type to the list.

Applies to: ClaimCenter

Default: *None*

HighlyLinkedContactThreshold

Use to improve application performance related to viewing a contact in the ClaimCenter **Address Book** tab or through the **Claim Summary** page. Attempting to view a contact with a large number of links can create performance issues. If a user is viewing a highly linked contact, then ClaimCenter issues a warning if the user clicks on a card that can result in an expensive query. The user must click another button before viewing the contact's related claims, activities, exposures or matters as these views put a heavy load on the database. This parameter sets the threshold value for the number of links to a contact that generates the warning.

Note: If you set the threshold value to 0, then ClaimCenter considers no contact to be highly linked.

Applies to: ClaimCenter

Default: *None*

IgnorePolicyTotalPropertiesValue

If true, the policy properties screens suppress the message telling the user whether all the properties that appear on the policy have been downloaded to the ClaimCenter policy snapshot.

- Set this value to true if the policy plugin is not capable of returning a meaningful value for `Policy.TotalProperties`.
- Set this value to false otherwise.

Applies to: ClaimCenter

Default: false

IgnorePolicyTotalVehiclesValue

If true, the policy vehicles screens suppress the message telling the user whether all the vehicles that appear on the policy have been downloaded to the ClaimCenter policy snapshot.

- Set this value to true if the policy plugin is not capable of returning a meaningful value for `Policy.TotalVehicles`.
- Set this value to false otherwise.

Applies to: ClaimCenter

Default: false

ListViewPageSizeDefault

The default number of entries that the application displays in each page in a list view, if the page does not explicitly specify this value. This integer value must be at least 1.

Default: 15

Minimum: 1

MaxBrowserHistoryItems (obsolete)

This parameter is obsolete. Do not use it.

MaxChooseByCoverageMenuItems

Maximum number of vehicles or properties that ClaimCenter displays in the **New Exposure > Choose by Coverage** menu. If the number to return exceeds this limit, ClaimCenter prompts the user to use the **Coverage Type** menu instead. This integer value must be 1 or greater.

Applies to: ClaimCenter

Default: 15

MaxChooseByCoverageTypeMenuItems

Maximum number of coverage types that ClaimCenter displays in the **New Exposure > Choose by Coverage Type** menu. If the number to return exceeds this limit, ClaimCenter splits the coverage types into alphabetic submenus. This integer value must be 1 or greater.

Applies to: ClaimCenter

Default: 15

MaxClaimantsInClaimListViews

Maximum number of claimants to list for each claim in a list view. This integer value must be 0 or greater. If set to 0, ClaimCenter does not impose a limit.

Applies to: ClaimCenter

Default: 0

MaxTeamSummaryChartUserBars

Maximum number of users to show in the chart on the **Team Summary** page. Set this parameter to 0 to remove the chart entirely. Otherwise, the chart displays statistics for the top N users, and groups the others into a bar labeled **All Other Users**. This integer value must be 0 or greater.

Applies to: ClaimCenter

Default: 10

QuickJumpShortcut

The keyboard shortcut to use to activate the QuickJump box.

Default: / (forward slash)

RequestReopenExplanationForTypes

The set of reopenable entities for which, if reopened, ClaimCenter displays a screen for the user to enter a reason and note. Enter as a comma-separated list.

Applies to: ClaimCenter

Default: Claim,Exposure,Matter

ShowCurrentPolicyNumberInSelectPolicyDialog

Whether to populate the select policy dialog with the policy number for the current policy for a claim.

Applies to: ClaimCenter

Default: false

ShowFixedExposuresInLossDetails

Works with ShowNewExposureMenuForLossTypes.

- If true, claims that do not have the **New Exposure** menu have a fixed list of exposures that can be shown through tabs on the **Claim Loss** page.
- If false, claims that do not have the **New Exposure** menu have a fixed list of exposures that can be shown through separate top-level page links in the claim file.

Applies to: ClaimCenter

Default: false

ShowNewExposureChooseByCoverageMenuForLossTypes

In the base application configuration, the ClaimCenter **Actions > New Exposure** menu contains two submenus, one of which is the **Choose By Coverage** submenu. Use this parameter to specify for which loss types you can access the **Choose By Coverage** submenu. Guidewire recommends that omit WC from the list of loss types.

In modifying this parameter:

- Deleting one of the default parameter values removes the **Choose by Coverage** submenu for that loss type.
- Adding a value to the default parameter values list adds a **Choose by Coverage** submenu for that loss type. Add your new loss type typecode to the existing comma-separated list of values.

IMPORTANT: If you add a new value to the list of loss types in this configuration parameter, then you must also add that value to configuration parameter ShowNewExposureMenuForLossTypes.

This caveat applies also if you modify one of the typefilters on the LossType typelist.

Applies to: ClaimCenter

Default: AUTO,PR,GL,TRAV

ShowNewExposureChooseByCoverageTypeMenuForLossTypes

In the base application configuration, the ClaimCenter **Actions > New Exposure** menu contains two submenus, one of which is the **Choose By Coverage Type** submenu. Use this parameter to specify for which loss types you can access the **Choose By Coverage** submenu.

In modifying this parameter:

- Deleting one of the default parameter values removes the **Choose by Coverage Type** submenu for that loss type.

- Adding a value to the default parameter values list adds a **Choose by Coverage Type** submenu for that loss type. Add your new loss type typecode to the existing comma-separated list of values.

IMPORTANT:

If you add a new value to the list of loss types in this configuration parameter, then you must also add that value to configuration parameter `ShowNewExposureMenuForLossTypes`.

This caveat applies also if you modify one of the typefilters on the `LossType` typelist.

Applies to: ClaimCenter

Default: AUTO,PR,GL,TRAV

ShowNewExposureMenuForLossTypes

Use to specify the ClaimCenter **Actions > New Exposure** menu for a specific loss type. Essentially, this parameter determines for which loss types it is possible to create a new exposure.

In modifying this parameter:

- Deleting one of the default parameter values removes the **New Exposure** menu for that loss type. Removing the **New Exposure** menu for a loss type also hides the **Exposures** step in the **New Claim** wizard for that loss type.
- Adding a value to the default parameter values list adds a **Choose by Coverage Type** submenu for that loss type. Add your new loss type typecode to the existing comma-separated list of values.

IMPORTANT:

If you add a new value to the list of loss types in `ShowNewExposureMenuForLossTypes`, you must also add that value to one, or both, of the following configuration parameters:

- `ShowNewExposureChooseByCoverageMenuForLossTypes`
- `ShowNewExposureChooseByCoverageTypeMenuForLossTypes`

This requirement also applies if you modify one of the typefilters on the `LossType` typelist.

Applies to: ClaimCenter

Default: AUTO,PR,GL,TRAV

UISkin

Name of the application interface skin to use.

Default: theme-9

WebUIAJAXTimeout

Number of seconds that the application web client waits after issuing a call to the application server. If the server doesn't respond within this time, the web client assumes that the server is offline, terminates all connections, and displays an error. You might want to increase this value if you are performing data-intensive operations that take a long time to process.

Default: 600

Web services parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to web services.

For information on editing `config.xml` and setting configuration parameters, see “Working with configuration parameters” on page 17.

WebservicesHideDetails

Whether to hide the detailed WSDL and XSD information about web services that the application provides at the following URL:

```
SERVER_URL/WEB_APP_NAME/ws/WEB_SERVICE_PACKAGE/WEB_SERVICE_CLASS_NAME?WSDL
```

Default: true

WebservicesHideListPage

Whether to hide the list of web services that the application provides at the following URL:

```
SERVER_URL/WEB_APP_NAME/ws
```

For more information about web services, see *Plugins, Prebuilt Integrations, and SOAP APIs*.

Default: true

Work queue parameters

Guidewire provides the following configuration parameters in the `config.xml` file that relate to the work queue.

For information on editing `config.xml` and setting configuration parameters, see “Working with configuration parameters” on page 17.

AppEventsMarkForSyncChunkSize

Sets the number of entities generated for each work item in the App Events mark `all syncables` work queue. Minimum value is 1, maximum value is 1000.

Applies to: PolicyCenter

Default: 100

Minimum: 1

Maximum: 1000

EnableWorkQueueValidation

Specifies whether to perform bundle validation on BillingCenter-specific work queues.

Bundle validation helps to preserve data consistency when entities are updated. This goal is achieved by defining and running validation rules on every commit.

Validation rules are not supported for all entities. For the list of entities that can trigger validation rules, see the *Gosu Rules Guide*.

This parameter affects BillingCenter-specific work queues only. Guidewire platform work queues, such as Activity Escalation, Group/User Exception, and Contact Auto Sync, always perform validation, regardless of the parameter setting.

Validation can significantly impact performance. For that reason, enabling validation is not recommended unless the situation requires it.

The BillingCenter base configuration does not define any validation rules. Accordingly, the default setting of the `EnableWorkQueueValidation` parameter is `false`.

Applies to: BillingCenter

Default: false

EventMigratableWorkItemPriorityForOpenClaims

This is an integer value used by the internal plugin implementation `IEventMigratablePriorityPlugin` to specify the priority of a work item. The default value of this parameter is set to a higher number to prioritize work items associated with the migration of open claims in the `CCEventMigratableWorkQueue` work queue.

For more information on prioritizing migrated claims, refer to "Prioritizing the migration order" in the *App Events for Developers* documentation.

Applies to: ClaimCenter

Default: 300

EventMigratableWorkItemPriorityForUpdatedClaims

This is an integer value used by the internal plugin implementation `IEventMigratablePriorityPlugin` to specify the priority of a work item. The default value of this parameter is set to a higher number to prioritize work items associated with the migration of updated claims in the `CCEventMigratableWorkQueue` work queue.

For more information on prioritizing migrated claims, refer to "Prioritizing the migration order" in the *App Events for Developers* documentation.

Applies to: ClaimCenter

Default: 200

FullPayDiscountPolicyPeriodsPerWorkItem

For the Full Pay Discount work queue, specifies the number of `PolicyPeriod` objects to process per work item.

The optimal number depends on the execution cost of the Policy Period plugin's `applyFullPayDiscount` method, the total number of `PolicyPeriod` objects to process, and the number of worker threads employed. Smaller numbers enable greater parallelism, but can increase the administrative costs of running the queue. Larger numbers reduce administrative costs, but also reduce parallelism.

Applies to: BillingCenter

Default: 10

FundsAllotmentAccountsPerWorkItem

For the Funds Allotment work queue, specifies the number of `Account` objects to process per work item.

The optimal number depends on the execution cost of the Funds Tracking plugin's `allotFunds` method, the total number of `Account` objects to process, and the number of worker threads employed. Smaller numbers enable greater parallelism, but can increase administrative costs of running the queue. Larger numbers reduce administrative costs, but also reduce parallelism.

Applies to: BillingCenter

Default: 10

InstrumentedWorkerInfoPurgeDaysOld

Number of business days to retain instrumentation information for a worker instance before the application deletes it.

Default: 45

PaymentRequestsPerWorkItem

For the Payment Request work queue, specifies the number of `PaymentRequest` objects to process per work item.

The optimal number depends on the execution cost of processing a single work item, the total number of `PaymentRequest` objects to process, and the number of worker threads employed. Smaller numbers enable greater parallelism, but can increase administrative costs of running the queue. Larger numbers reduce administrative costs, but also reduce parallelism.

In the base configuration, the cost to process a single `PaymentRequest` object is small. In production configurations, messaging costs could substantially increase the cost and justify a smaller number.

Applies to: BillingCenter

Default: 50

WorkItemCreationBatchSize

The maximum number of work items for a work queue writer to create for each transaction.

Default: 100

WorkItemPriorityMultiplierSecs

Used to calculate the `AvailableSince` field for new work items. For new work items without a priority, the application sets `AvailableSince` to the current time. Later, the application checks out work items from the work queue in ascending order by `AvailableSince`, so work items without a priority are checked out in the order they were created.

You can assign a priority to new work items by implementing the Work Item Priority plugin (`IWorkItemPriorityPlugin`). For new work items with a priority, the application sets `AvailableSince` according to the following formula:

```
workItem.AvailableSince = CurrentTime - (workItem.Priority * WorkItemPriorityMultiplierSecs)
```

Work items with higher priorities have earlier `AvailableSince` values than work items with lower priorities. Therefore, work items with higher priorities are checked out before ones with lower priorities because their `AvailableSince` values are earlier.

Priority influences the calculation of `AvailableSince` only at the time work items are created. If a worker throws an exception while processing a work item, the application reverts the status of the work item from checkedout to available. At the same time, the application resets `AvailableSince` according to the following formula:

```
workItem.AvailableSince = CurrentTime + RetryInterval
```

Work items are retried in the order they encounter exceptions, irrespective of priority.

IMPORTANT: Prioritization affects only work items of type `WorkflowWorkItem` or its derivatives.

Default: 600

WorkItemRetryLimit

The maximum number of times that the application retries an orphaned or failed work item.

Guidewire logs a `ConcurrentDataChangeException` generated by workers at different levels depending on context. If the `ConcurrentDataChangeException` occurs on processing the work items, the application logs the error only if the number of attempts exceeds the configured value of the `WorkItemRetryLimit`. Otherwise, the application logs the debug message instead.

The value for `WorkItemRetryLimit` applies to all work queues unless overridden in `work-queue.xml` by `retryLimit` for specific work queues.

Default: 3

WorkQueueHistoryMaxDownload

The maximum number of `ProcessHistory` entries to consider when producing the Work Queue History download. The valid range is from 1 to 525600. (The maximum of 525,600 is $60 \times 24 \times 365$, which is one writer running every minute for a year.)

Default: 10000

WorkQueueThreadPoolMaxSize

Maximum number of threads in the work queue thread pool. This must be greater than or equal to “`WorkQueueThreadPoolMinSize`”. All threads that are not core threads are additional on-demand threads. The application terminates any idle on-demand threads after the period of time defined by configuration parameter `WorkQueueThreadsKeepAliveTime`.

Default: 50

Set for server: Yes

WorkQueueThreadPoolMinSize

Minimum number of core threads in the work queue thread pool.

Default: 0

Set for server: Yes

WorkQueueThreadsKeepAliveTime

Keep alive timeout (in seconds) for additional on-demand threads in the work queue thread pool. An additional on-demand thread is terminated if it is idle for more than the time specified by this parameter.

Default: 60

Set for server: Yes

