



**RAJALAKSHMI
ENGINEERING COLLEGE**
An AUTONOMOUS Institution
Affiliated to ANNA UNIVERSITY, Chennai

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

LAB MANUAL

CS23431 – OPERATING SYSTEMS

(REGULATION 2023)

**RAJALAKSHMI ENGINEERING COLLEGE
Thandalam, Chennai-602015**

Name: Dilli Ganesh B

Register No: 231801057

Year / Branch / Section: 2nd / AI&DS / FA

Semester: IV

Academic Year: 2024 - 2025

INDEX

| Exp.No | Title | Page No |
|--------|---|---------|
| 1a | Installation and Configuration of Linux. | 4 |
| 1b | Basic Linux Commands. | 9 |
| 2a | Shell script - Arithmetic Operation -using expr command Basic Calculator. | 27 |
| 2b | Shell script - Check leap year using if-else. | 31 |
| 3a | Shell script - Reverse the number using while loop. | 32 |
| 3b | Shell script - Fibonacci series using for loop. | 33 |
| 4a | Text processing using Awk script - Employee average pay. | 34 |
| 4b | Text processing using Awk script - Results of an examination. | 36 |
| 5 | System calls –fork(), exec(), getpid(),opendir(), readdir(). | 38 |
| 6a | FCFS | 41 |
| 6b | SJF | 43 |
| 6c | Priority | 46 |
| 6d | Round Robin | 48 |
| 7 | Inter-process Communication using Shared Memory. | 51 |
| 8 | Producer Consumer using Semaphores. | 55 |
| 9 | Bankers Deadlock Avoidance algorithms. | 58 |
| 10a | Best Fit | 61 |
| 10b | First Fit | 63 |
| 11a | FIFO | 65 |

| | | |
|-----|---|----|
| 11b | LRU | 67 |
| 11c | Optimal | 70 |
| 12 | File Organization Technique- single and Two level directory. | 73 |

Ex No: 1a
Date: 28/1/25

INSTALLATION AND CONFIGURATION OF LINUX


AIM:



To install and configure Linux operating system in a Virtual Machine.


INSTALLATION/CONFIGURATION STEPS:



1. Install the required packages for virtualization
`dnf install xen virt-manager qemu libvirt`
2. Configure xend to start up on boot
`systemctl enable virt-manager. service`
3. Reboot the machine
Reboot
4. Create a Virtual machine by first running virt-manager
virt-manager &
5. Click on File and then click to connect to localhost
6. In the base menu, right-click on the localhost (QEMU) to create a new VM
7. Select Linux ISO image
8. Choose puppy-linux.iso then the kernel version
9. Select CPU and RAM limits
10. Create default disk image to 8 GB
11. Click finish to create the new VM with PuppyLinux.


OUTPUT:











RESULT:

The Linux OS is Installed and Configured.

Ex No: 1b
Date: 1/2/2025

BASIC LINUX COMMANDS

1.1 GENERAL PURPOSE COMMANDS

1. The 'date' command:

The date command displays the current date with day of week, month, day, time (24 hours clock) and the year.

SYNTAX: \$ date

The date command can also be used with following format.

| Format | Purpose | Example |
|--------|--|--------------|
| + %m | To display only month | \$ date + %m |
| + %h | To display month name | \$ date + %h |
| + %d | To display day of month | \$ date + %d |
| + %y | To display last two digits of the year | \$ date + %y |
| + %H | To display Hours | \$ date + %H |
| + %M | To display Minutes | \$ date + %M |
| + %S | To display Seconds | \$ date + %S |

2. The echo' command:

The echo command is used to print the message on the screen.

SYNTAX: \$ echo

EXAMPLE: \$ echo "God is Great"

3. The 'cal' command:

The cal command displays the specified month or year calendar.

SYNTAX: \$ cal [month] [year]

EXAMPLE: \$ cal Jan 2012

4. The 'bc' command:

2116231801033

CS23431

Unix offers an online calculator and can be invoked by the command bc.

SYNTAX: \$ bc

EXAMPLE: bc -l

16/4

5/2

5. The 'who' command

The who command is used to display the data about all the users who are currently logged into the system.

SYNTAX: \$ who

6. The 'who am i' command

The who am i command displays data about login details of the user.

SYNTAX: \$ who am i

7. The 'id' command

The id command displays the numerical value corresponding to your login.

SYNTAX: \$ id

8. The 'tty' command

The tty (teletype) command is used to know the terminal name that we are using.

SYNTAX: \$ tty

9. The 'clear' command

The clear command is used to clear the screen of your terminal.

SYNTAX: \$ clear

10. The 'man' command

The man command gives you complete access to the Unix commands.

SYNTAX: \$ man [command]

11. The 'ps' command

The ps command is used to the process currently alive in the machine with the 'ps' (process status) command, which displays information about process that are alive when you run the command. 'ps;' produces a snapshot of machine activity.

SYNTAX: \$ ps

EXAMPLE: \$ ps

\$ ps -e

\$ps -aux

12. The 'uname' command

The uname command is used to display relevant details about the operating system on the standard output.

-m -> Displays the machine id (i.e., name of the system hardware)

-n -> Displays the name of the network node. (host name)

-r -> Displays the release number of the operating system.

-s -> Displays the name of the operating system (i.e., system name)

-v -> Displays the version of the operating system.
-a -> Displays the details of all the above five options.
SYNTAX: \$ uname [option]
EXAMPLE: \$ uname -a

1.2 DIRECTORY COMMANDS

1. The 'pwd' command:

The pwd (print working directory) command displays the current working directory. SYNTAX: \$ pwd

2. The 'mkdir' command:

The mkdir is used to create an empty directory in a disk.

SYNTAX: \$ mkdir dirname

EXAMPLE: \$ mkdir receee

3. The 'rmdir' command:

The rmdir is used to remove a directory from the disk. Before removing a directory, the directory must be empty (no files and directories).

SYNTAX: \$ rmdir dirname

EXAMPLE: \$ rmdir receee

4. The 'cd' command:

The cd command is used to move from one directory to another.

SYNTAX: \$ cd dirname

EXAMPLE: \$ cd receee

5. The 'ls' command:

The ls command displays the list of files in the current working directory.

SYNTAX: \$ ls

EXAMPLE: \$ ls

\$ ls -l

\$ ls -a

1.3 FILE HANDLING COMMANDS

1. The 'cat' command:

The cat command is used to create a file.

SYNTAX: \$ cat > filename

EXAMPLE: \$ cat > rec

2. The 'Display contents of a file' command:

The cat command is also used to view the contents of a specified file.

SYNTAX: \$ cat filename

3. The 'cp' command:

The cp command is used to copy the contents of one file to another and copies the file from one place to another.

SYNTAX: \$ cp oldfile newfile

EXAMPLE: \$ cp cse ece

4. The 'rm' command:

The rm command is used to remove or erase an existing file

SYNTAX: \$ rm filename

EXAMPLE: \$ rm rec

\$ rm -f rec

Use option -fr to delete recursively the contents of the directory and its subdirectories.

5. The 'mv' command:

The mv command is used to move a file from one place to another. It removes a specified file from its original location and places it in specified location.

SYNTAX: \$ mv oldfile newfile

EXAMPLE: \$ mv cse eee

6. The 'file' command:

The file command is used to determine the type of file.

SYNTAX: \$ file filename

EXAMPLE: \$ file receee

7. The 'wc' command:

The wc command is used to count the number of words, lines and characters in a file. SYNTAX: \$ wc filename

EXAMPLE: \$ wc receee

8. The 'Directing output to a file' command:

The ls command lists the files on the terminal (screen). Using the redirection operator '>' we can send the output to file instead of showing it on the screen.

SYNTAX: \$ ls > filename

EXAMPLE: \$ ls > cseeee

9. The 'pipes' command:

The Unix allows us to connect two commands together using these pipes. A pipe (|) is an mechanism by which the output of one command can be channeled into the input of another command. SYNTAX: \$

command1 | command2

EXAMPLE: \$ who | wc -l

10. The 'tee' command:

While using pipes, we have not seen any output from a command that gets piped into another command. To save the output, which is produced in the middle of a pipe, the tee command is very useful. SYNTAX: \$

command | tee filename

EXAMPLE: \$ who | tee sample | wc -l

11. The 'Metacharacters of unix' command:

Metacharacters are special characters that are at higher and abstract level compared to most of other characters in Unix. The shell understands and interprets these metacharacters in a special way. * - Specifies number of characters

?- Specifies a single character

[]- used to match a whole set of file names at a command line.

! – Used to Specify Not

EXAMPLE:

\$ ls r** - Displays all the files whose name begins with 'r'

\$ ls ?kkk - Displays the files which are having 'kkk', from the second characters irrespective of the first character.

\$ ls [a-m] – Lists the files whose names begins alphabets from 'a' to 'm'

\$ ls [!a-m] – Lists all files other than files whose names begins alphabets from 'a' to 'm'

12. The 'File permissions' command:

File permission is the way of controlling the accessibility of file for each of three users namely Users, Groups and Others.

There are three types of file permissions are available, they are

r-read

w-write

x-execute

The permissions for each file can be divided into three parts of three bits each.

| | |
|------------------|--|
| First three bits | Owner of the file |
| Next three bits | Group to which the owner of the file belongs |
| Last three bits | Others |

EXAMPLE: \$ ls college

-rwxr-xr-- 1 Lak std 1525 jan10 12:10 college

Where,

-rwx The file is readable, writable and executable by the owner of the file.

Lak Specifies Owner of the file.

r-x Indicates the absence of the write permission by the Group owner of the file. Std Is the Group Owner of the file.

r-- Indicates read permissions for others.

13. The 'chmod' command:

2116231801033

CS23431

The chmod command is used to set the read, write and execute permissions for all categories of users for file.

SYNTAX: \$ chmod category operation permission file

| Category | Operation | permission |
|----------|---------------------|------------|
| u-users | + assign | r-read |
| g-group | -Remove | w-write |
| o-others | = assign absolutely | x-execute |
| a-all | | |

EXAMPLE:

\$ chmod u -wx college

Removes write & execute permission for users for 'college' file.

\$ chmod u +rw, g+rw college

Assigns read & write permission for users and groups for 'college' file.

\$ chmod g=wx college

Assigns absolute permission for groups of all read, write and execute permissions for 'college' file.

14. The 'Octal Notations' command:

The file permissions can be changed using octal notations also. The octal notations for file permission are

| | |
|------------------|---|
| Read permission | 4 |
| Write permission | 2 |

EXAMPLE:

\$ chmod 761 college

| | |
|--------------------|---|
| Execute permission | 1 |
|--------------------|---|

Assigns all permission to the owner, read and write permissions to the group and only executable permission to the others for 'college' file.

1.4 GROUPING COMMANDS

1. The 'semicolon' command:

The semicolon(;) command is used to separate multiple commands at the command line. SYNTAX: \$ command1;command2;command3.....;commandn

EXAMPLE: \$ who;date

2. The '&&' operator:

The '&&' operator signifies the logical AND operation in between two or more valid Unix commands.It means that only if the first command is successfully executed, then the next command will executed.

SYNTAX: \$ command1 && command && command3.....&&commandn EXAMPLE: \$ who && date.

3. The '||' operator:

The '||' operator signifies the logical OR operation in between two or more valid Unix commands.It means, that only if the first command will happen to be un successfully,it will continue to execute next commands.

SYNTAX: \$ command1 || command || command3.....||commandn

EXAMPLE: \$ who || date

1.5 FILTERS

1. The head filter

It displays the first ten lines of a file.

SYNTAX: \$ head filename

EXAMPLE: \$ head college Display the top ten lines.

\$ head -5 college Display the top five lines.

2. The tail filter

It displays ten lines of a file from the end of the file.

SYNTAX: \$ tail filename

EXAMPLE: \$ tail college Display the last ten lines.

\$tail -5 college Display the last five lines.

3. The more filter:

The pg command shows the file page by page.

SYNTAX: \$ ls -l | more

4. The 'grep' command:

This command is used to search for a particular pattern from a file or from the standard input and display those lines on the standard output. "Grep" stands for "global search for regular expression."

SYNTAX: \$ grep [pattern] [file_name]

EXAMPLE: \$ cat> student

Arun cse

Ram ece

Kani cse

\$ grep "cse" student

Arun cse

Kani cse

5. The 'sort' command:

The sort command is used to sort the contents of a file. The sort command reports only to the screen, the actual file remains unchanged.

SYNTAX: \$ sort filename

EXAMPLE: \$ sort college

OPTIONS:

| Command | Purpose |
|-----------------|---|
| Sort -r college | Sorts and displays the file contents in reverse order |
| Sort -c college | Check if the file is sorted |
| Sort -n college | Sorts numerically |
| Sort -m college | Sorts numerically in reverse order |

| | |
|-----------------|---|
| Sort -u college | Remove duplicate records |
| Sort -l college | Skip the column with +1 (one) option.Sorts according to second column |

6. The 'nl' command:

The nl filter adds lines numbers to a file and it displays the file and not provides access to edit but simply displays the contents on the screen.

SYNTAX: \$ nl filename

EXAMPLE: \$ nl college

7. The 'cut' command:

We can select specified fields from a line of text using cut command.

SYNTAX: \$ cut -c filename

EXAMPLE: \$ cut -c college

OPTION:

-c – Option cut on the specified character position from each line.

1.5 OTHER ESSENTIAL COMMANDS

1. free

Display amount of free and used physical and swapped memory system. synopsis- free [options]

example

```
[root@localhost ~]# free -t
```

```
total used free shared buff/cache available Mem: 4044380 605464 2045080 148820 1393836 3226708 Swap:
2621436 0 2621436
Total: 6665816 605464 4666516
```

2. top

It provides a dynamic real-time view of processes in the system.

synopsis- top [options]

example

```
[root@localhost ~]# top
```

```
top - 08:07:28 up 24 min, 2 users, load average: 0.01, 0.06, 0.23
```

```
Tasks: 211 total, 1 running, 210 sleeping, 0 stopped, 0 zombie
```

```
%Cpu(s): 0.8 us, 0.3 sy, 0.0 ni, 98.9 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
```

```
KiB Mem : 4044380 total, 2052960 free, 600452 used, 1390968 buff/cache KiB Swap: 2621436 total,
```

```
2621436 free, 0 used. 3234820 avail Mem PID USER PR NI VIRT RES SHR S %CPU %MEM TIME+
```

```
COMMAND
```

```
1105 root 20 0 175008 75700 51264 S 1.7 1.9 0:20.46 Xorg 2529 root 20 0 80444 32640 24796 S 1.0 0.8
0:02.47 gnome-term
```

3. ps

It reports the snapshot of current processes

synopsis- ps [options]

example

```
[root@localhost ~]# ps -e
```

```
PID TTY TIME CMD
```

```
1 ? 00:00:03 systemd
```

```
2 ? 00:00:00 kthreadd
```

```
3 ? 00:00:00 ksoftirqd/0
```

4. vmstat

It reports virtual memory statistics

synopsis- vmstat [options]

example

```
[root@localhost ~]# vmstat
```

```
procs -----memory----- ---swap-- -----io----- -system-- -----cpu--- -- r b swpd free buff cache si so bi bo
in cs us sy id wa st 0 0 0 1879368 1604 1487116 0 0 64 7 72 140 1 0 97 1 0
```

5. df

It displays the amount of disk space available in file-system.

```
2116231801033
```

CS23431

Synopsis- df [options]

example

```
[root@localhost ~]# df
```

```
Filesystem 1K-blocks Used Available Use% Mounted on
```

```
devtmpfs 2010800 0 2010800 0% /dev tmpfs 2022188 148 2022040 1% /dev/shm tmpfs 2022188 1404  
2020784 1% /run /dev/sda6 487652 168276 289680 37% /boot
```

6. ping

It is used to verify that a device can communicate with another on network. PING stands for Packet Internet Groper.

synopsis- ping [options]

```
[root@localhost ~]# ping 172.16.4.1
```

```
PING 172.16.4.1 (172.16.4.1) 56(84) bytes of data.
```

```
64 bytes from 172.16.4.1: icmp_seq=1 ttl=64 time=0.328 ms
```

```
64 bytes from 172.16.4.1: icmp_seq=2 ttl=64 time=0.228 ms
```

```
64 bytes from 172.16.4.1: icmp_seq=3 ttl=64 time=0.264 ms 64 bytes from 172.16.4.1: icmp_seq=4 ttl=64  
time=0.312 ms
```

```
--- 172.16.4.1 ping statistics ---
```

```
4 packets transmitted, 4 received, 0% packet loss, time 3000ms rtt min/avg/max/mdev =
```

```
0.228/0.283/0.328/0.039 ms
```

7. ifconfig

It is used to configure network interface.

synopsis- ifconfig [options]

example

```
root@localhost ~]# ifconfig
```

```
enp2s0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500 inet 172.16.6.102 netmask  
255.255.252.0 broadcast 172.16.7.255 inet6 fe80::4a0f:cfff:fe6d:6057 prefixlen 64 scopeid 0x20<link>  
ether 48:0f:cf:6d:60:57 txqueuelen 1000 (Ethernet)
```

```
RX packets 23216 bytes 2483338 (2.3 MiB)
```

```
RX errors 0 dropped 5 overruns 0 frame 0
```

```
TX packets 1077 bytes 107740 (105.2 KiB)
```

```
TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0 8.
```

traceroute

It tracks the route the packet takes to reach the destination. synopsis- traceroute [options]

example

```
[root@localhost ~]# traceroute www.rajalakshmi.org
```

```
traceroute to www.rajalakshmi.org (220.227.30.51), 30 hops max, 60 byte packets 1 gateway (172.16.4.1)  
0.299 ms 0.297 ms 0.327 ms 2
```

```
220.225.219.38 (220.225.219.38) 6.185 ms 6.203 ms 6.189 ms
```

OUTPUT:

```
[student@localhost ~]$ date +%m
01
[student@localhost ~]$ date +%h
Jan
[student@localhost ~]$ date +%d
25
[student@localhost ~]$ date +%y
25
[student@localhost ~]$ date +%H
09
[student@localhost ~]$ date +%M
21
[student@localhost ~]$ date +%S
26
[student@localhost ~]$ echo "Hello World"
Hello World
[student@localhost ~]$ echo "Hi"
Hi
[student@localhost ~]$ bc
bc 1.06.95
Copyright 1991-1994, 1997, 1998, 2000, 2004, 2006 Free Software Foundation, Inc.
This is free software with ABSOLUTELY NO WARRANTY.
For details type `warranty'.
15*25
375
524*965
505660
quit
[student@localhost ~]$ who
student pts/0      2025-01-25 08:12 (:0)
student pts/1      2025-01-25 09:20 (:0)
[student@localhost ~]$ who am i
student pts/1      2025-01-25 09:20 (:0)
[student@localhost ~]$ id
uid=1000(student) gid=1000(student) groups=1000(student) context=unconfined_u:unconfined_r:unconfined_t:s0-s0:c0.c1023
[student@localhost ~]$ tty
/dev/pts/1
[student@localhost ~]$ man
what manual page do you want?
[student@localhost ~]$ ps
  PID TTY          TIME CMD
 2125 pts/1    00:00:00 bash
 2161 pts/1    00:00:00 ps
```

```
[student@localhost ~]$ ps
  PID TTY          TIME CMD
 2125 pts/1    00:00:00 bash
 2161 pts/1    00:00:00 ps
[student@localhost ~]$ ps -e
  PID TTY          TIME CMD
   1 ?        00:00:01 systemd
   2 ?        00:00:00 kthreadd
   4 ?        00:00:00 kworker/0:0H
   6 ?        00:00:00 mm_percpu_wq
   7 ?        00:00:00 ksoftirqd/0
   8 ?        00:00:00 rcu_sched
   9 ?        00:00:00 rcu_bh
  10 ?       00:00:00 migration/0
  11 ?       00:00:00 watchdog/0
  12 ?       00:00:00 cpuhp/0
  13 ?       00:00:00 cpuhp/1
  14 ?       00:00:00 watchdog/1
  15 ?       00:00:00 migration/1
  16 ?       00:00:00 ksoftirqd/1
  18 ?       00:00:00 kworker/1:0H
  19 ?       00:00:00 cpuhp/2
  20 ?       00:00:00 watchdog/2
  21 ?       00:00:00 migration/2
  22 ?       00:00:00 ksoftirqd/2
  24 ?       00:00:00 kworker/2:0H
  25 ?       00:00:00 cpuhp/3
  26 ?       00:00:00 watchdog/3
  27 ?       00:00:00 migration/3
  28 ?       00:00:00 ksoftirqd/3
  30 ?       00:00:00 kworker/3:0H
  31 ?       00:00:00 kdevtmpfs
  32 ?       00:00:00 netns
  34 ?       00:00:01 kworker/2:1
  35 ?       00:00:00 oom_reaper
  36 ?       00:00:00 writeback
  37 ?       00:00:00 kcompactd0
  38 ?       00:00:00 ksmd
  39 ?       00:00:00 crypto
  40 ?       00:00:00 kintegrityd
  41 ?       00:00:00 bioset
  42 ?       00:00:00 kblockd
  44 ?       00:00:01 kworker/0:1
  46 ?       00:00:00 kworker/0:1
```

```

44 ? 00:00:01 kworker/0:1
45 ? 00:00:00 ata_sff
46 ? 00:00:00 md
47 ? 00:00:00 devfreq_wq
48 ? 00:00:00 watchdogd
50 ? 00:00:00 kauditd
51 ? 00:00:00 kswapd0
52 ? 00:00:00 bioset
99 ? 00:00:00 kthrotld
100 ? 00:00:00 acpi_thermal_pm
101 ? 00:00:00 scsi_eh_0
102 ? 00:00:00 scsi_tmf_0
103 ? 00:00:00 scsi_eh_1
104 ? 00:00:00 scsi_tmf_1
105 ? 00:00:00 scsi_eh_2
106 ? 00:00:00 scsi_tmf_2
107 ? 00:00:00 scsi_eh_3
108 ? 00:00:00 scsi_tmf_3
109 ? 00:00:00 scsi_eh_4
110 ? 00:00:00 scsi_tmf_4
115 ? 00:00:00 dm_bufio_cache
116 ? 00:00:00 ipv6_addrconf
150 ? 00:00:00 bioset
151 ? 00:00:00 bioset
209 ? 00:00:01 kworker/1:2
355 ? 00:00:00 kworker/0:1H
357 ? 00:00:00 kworker/1:1H
363 ? 00:00:00 kworker/3:1H
366 ? 00:00:00 i915/signal:0
367 ? 00:00:00 i915/signal:1
368 ? 00:00:00 i915/signal:2
369 ? 00:00:00 i915/signal:4
391 ? 00:00:00 kworker/2:1H
428 ? 00:00:00 kdmflush
429 ? 00:00:00 bioset
441 ? 00:00:00 kdmflush
442 ? 00:00:00 bioset
459 ? 00:00:00 jbd2/dm-0-8
460 ? 00:00:00 ext4-rsv-conver
544 ? 00:00:00 systemd-journal
573 ? 00:00:00 systemd-udevd
612 ? 00:00:00 irq/32-me1_me
652 ? 00:00:00 jbd2/sda6-8

```

```

460 ? 00:00:00 ext4-rsv-conver
544 ? 00:00:00 systemd-journal
573 ? 00:00:00 systemd-udevd
612 ? 00:00:00 irq/32-me1_me
652 ? 00:00:00 jbd2/sda6-8
653 ? 00:00:00 ext4-rsv-conver
656 ? 00:00:00 kdmflush
658 ? 00:00:00 bioset
668 ? 00:00:00 jbd2/dm-2-8
669 ? 00:00:00 ext4-rsv-conver
692 ? 00:00:00 rpciod
693 ? 00:00:00 xprtiod
695 ? 00:00:00 auditd
714 ? 00:00:00 alsactl
715 ? 00:00:00 mcelog
716 ? 00:00:00 ModemManager
718 ? 00:00:00 sssd
719 ? 00:03:15 avahi-daemon
720 ? 00:00:00 irqbalance
721 ? 00:00:00 dbus-daemon
723 ? 00:00:00 avahi-daemon
727 ? 00:00:00 gsaprox
735 ? 00:00:00 rsyslogd
736 ? 00:00:00 smartd
738 ? 00:00:00 firewalld
743 ? 00:00:00 rtkit-daemon
748 ? 00:00:00 abrt-d
753 ? 00:00:00 chronyd
764 ? 00:00:00 sssd-be
768 ? 00:00:00 abrt-dump-journ
769 ? 00:00:00 abrt-dump-journ
770 ? 00:00:00 abrt-dump-journ
771 ? 00:00:00 sssd_nss
772 ? 00:00:00 accounts-daemon
773 ? 00:00:00 systemd-logind
788 ? 00:00:00 NetworkManager
789 ? 00:00:00 polkitd
820 ? 00:00:00 crond
821 ? 00:00:00 atd
823 ? 00:00:00 sddm
884 tty1 00:00:13 Xorg
1013 ? 00:00:01 udiskd
1019 ? 00:00:00 upowerd
1060 ? 00:00:00 sddm-baloon

```

```

1013 ? 00:00:01 udiskd
1019 ? 00:00:00 upowerd
1058 ? 00:00:00 sddm-helper
1062 ? 00:00:00 systemd
1064 ? 00:00:00 (sd-pam)
1075 ? 00:00:00 kwalllet5
1078 ? 00:00:00 startkde
1097 ? 00:00:00 dbus-daemon
1102 ? 00:00:00 ssh-agent
1143 ? 00:00:00 start_kdeinit
1144 ? 00:00:00 kdeinit5
1145 ? 00:00:00 klauncher
1148 ? 00:00:01 kded5
1161 ? 00:00:00 kaccess
1166 ? 00:00:00 kwrapper5
1171 ? 00:00:00 dconf-service
1173 ? 00:00:00 ksmserver
1178 ? 00:00:00 kglobalaccel5
1183 ? 00:00:00 mission-control
1185 ? 00:00:00 colord
1191 ? 00:00:13 kwin_x11
1205 ? 00:00:00 kscreen_backend
1210 ? 00:00:00 baloo_file
1212 ? 00:00:00 kdeconnectd
1214 ? 00:00:01 krunner
1216 ? 00:00:15 plasmashell
1217 ? 00:00:00 polkit-kde-auth
1218 ? 00:00:00 xembedsniproxy
1269 ? 00:00:01 kworker/3:0
1279 ? 00:00:00 pulseaudio
1296 ? 00:00:00 abrt-applet
1298 ? 00:00:00 korgac
1299 ? 00:00:00 org_kde_powerde
1328 ? 00:00:00 kactivitymanage
1371 ? 00:00:00 at-spi-bus-laun
1381 ? 00:00:00 dbus-daemon
1386 ? 00:00:00 at-spi2-registr
1446 ? 00:00:00 abrt-dbus
1452 ? 00:00:00 akonadi_control
1456 ? 00:00:00 akonadi_server
1459 ? 00:00:02 mysqld
1499 ? 00:00:00 akonadi_akonote
1500 ? 00:00:00 akonadi_archive

```

```

1499 ? 00:00:00 akonadi_akonote
1500 ? 00:00:00 akonadi_archive
1501 ? 00:00:00 akonadi_birtida
1502 ? 00:00:00 akonadi_contact
1503 ? 00:00:00 akonadi_followu
1504 ? 00:00:00 akonadi_ical_re
1507 ? 00:00:00 akonadi_indexin
1510 ? 00:00:00 akonadi_maildir
1529 ? 00:00:00 akonadi_maildis
1530 ? 00:00:00 akonadi_mailfil
1531 ? 00:00:00 akonadi_migrati
1532 ? 00:00:00 akonadi_newmail
1533 ? 00:00:00 akonadi_sendlat
1601 ? 00:00:00 kuiserver5
1605 ? 00:00:00 cupsd
1607 ? 00:00:06 packagekitd
1838 ? 00:00:00 kworker/3:1
1845 ? 00:00:00 kworker/2:2
1939 ? 00:00:00 kworker/u8:0
1942 ? 00:00:00 kworker/u8:3
1952 ? 00:00:00 kworker/0:2
1960 ? 00:00:00 kworker/u8:1
2004 ? 00:00:13 amarok
2008 ? 00:00:00 kdeinit4
2010 ? 00:00:00 klauncher
2012 ? 00:00:00 kded4
2014 ? 00:00:00 gam_server
2057 ? 00:00:00 knotifyd
2067 ? 00:00:00 kio_http_cache_
2114 ? 00:00:00 kworker/1:0
2121 ? 00:00:00 konsole
2125 pts/1 00:00:00 bash
2158 ? 00:00:00 kworker/1:1
2162 pts/1 00:00:00 ps
[student@localhost ~]$ ps -aux
USER      PID %CPU %MEM    VSZ   RSS TTY      STAT START   TIME COMMAND
root         1  0.0  0.1 32260 10376 ?        Ss   08:01   0:01 /usr/lib/systemd/systemd --switched-root --system --deserialize 24
root         2  0.0  0.0      0   0 ?        S    08:01   0:00 [kthreadd]
root         4  0.0  0.0      0   0 ?        S<   08:01   0:00 [kworker/0:0H]
root         6  0.0  0.0      0   0 ?        S<   08:01   0:00 [mm_percpu_wq]
root         7  0.0  0.0      0   0 ?        S    08:01   0:00 [ksoftirqd/0]
root         8  0.0  0.0      0   0 ?        S    08:01   0:00 [rcu_sched]
root         9  0.0  0.0      0   0 ?        S    08:01   0:00 [rcu_bh]
root        10  0.0  0.0      0   0 ?        S    08:01   0:00 [migration/0]

```

| USER | PID | %CPU | %MEM | VSZ | RSS | TTY | STAT | START | TIME | COMMAND |
|------|-----|------|------|-------|-------|-----|------|-------|------|--|
| root | 1 | 0.0 | 0.1 | 32260 | 10376 | ? | Ss | 08:01 | 0:01 | /usr/lib/systemd/systemd --switched-root --system --deserialize 24 |
| root | 2 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [kthreadd] |
| root | 4 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [kworker/0:0H] |
| root | 6 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [mm_percpu_wq] |
| root | 7 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [ksoftirqd/0] |
| root | 8 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [rcu_sched] |
| root | 9 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [rcu_bh] |
| root | 10 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [migration/0] |
| root | 11 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [watchdog/0] |
| root | 12 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [cpuhp/0] |
| root | 13 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [cpuhp/1] |
| root | 14 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [watchdog/1] |
| root | 15 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [migration/1] |
| root | 16 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [ksoftirqd/1] |
| root | 18 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [kworker/1:0H] |
| root | 19 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [cpuhp/2] |
| root | 20 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [watchdog/2] |
| root | 21 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [migration/2] |
| root | 22 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [ksoftirqd/2] |
| root | 24 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [kworker/2:0H] |
| root | 25 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [cpuhp/3] |
| root | 26 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [watchdog/3] |
| root | 27 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [migration/3] |
| root | 28 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [ksoftirqd/3] |
| root | 30 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [kworker/3:0H] |
| root | 31 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [kdevtmpfs] |
| root | 32 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [netns] |
| root | 34 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:01 | [kworker/2:1] |
| root | 35 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [oom_reaper] |
| root | 36 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [writeback] |
| root | 37 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [kcompactd] |
| root | 38 | 0.0 | 0.0 | 0 | 0 | ? | SH | 08:01 | 0:00 | [ksmd] |
| root | 39 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [crypto] |
| root | 40 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [kintegrityd] |
| root | 41 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [bioset] |
| root | 42 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [kblockd] |
| root | 44 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:01 | [kworker/0:1] |
| root | 45 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [ata_sff] |
| root | 46 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [md] |
| root | 47 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [devfreq_wq] |
| root | 48 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [watchdogd] |
| root | 50 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [kauditd] |

| | | | | | | | | | | |
|------|-----|-----|-----|-------|------|---|----|-------|------|-----------------------------------|
| root | 50 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [kauditd] |
| root | 51 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [kswapd0] |
| root | 52 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [bioset] |
| root | 99 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [kthrotld] |
| root | 100 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [acpi_thermal_pm] |
| root | 101 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [scsi_eh_0] |
| root | 102 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [scsi_tmf_0] |
| root | 103 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [scsi_eh_1] |
| root | 104 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [scsi_tmf_1] |
| root | 105 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [scsi_eh_2] |
| root | 106 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [scsi_tmf_2] |
| root | 107 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [scsi_eh_3] |
| root | 108 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [scsi_tmf_3] |
| root | 109 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [scsi_eh_4] |
| root | 110 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [scsi_tmf_4] |
| root | 115 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [dm_bufio_cache] |
| root | 116 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [ipv6_addrconf] |
| root | 150 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [bioset] |
| root | 151 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [bioset] |
| root | 209 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:01 | [kworker/1:2] |
| root | 355 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [kworker/0:1H] |
| root | 357 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [kworker/1:1H] |
| root | 363 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [kworker/3:1H] |
| root | 366 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [i915/signal:0] |
| root | 367 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [i915/signal:1] |
| root | 368 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [i915/signal:2] |
| root | 369 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [i915/signal:4] |
| root | 391 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [kworker/2:1H] |
| root | 428 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [kdmflush] |
| root | 429 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [bioset] |
| root | 441 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [kdmflush] |
| root | 442 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [bioset] |
| root | 459 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [jbd2/dm-0-8] |
| root | 460 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [ext4-rsv-conver] |
| root | 544 | 0.0 | 0.1 | 42756 | 9240 | ? | Ss | 08:01 | 0:00 | /usr/lib/systemd/systemd-journald |
| root | 573 | 0.0 | 0.0 | 23956 | 8028 | ? | Ss | 08:01 | 0:00 | /usr/lib/systemd/systemd-udev |
| root | 612 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [irq/32-mei_me] |
| root | 652 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [jbd2/sda6-8] |
| root | 653 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [ext4-rsv-conver] |
| root | 656 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [kdmflush] |
| root | 658 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [bioset] |
| root | 668 | 0.0 | 0.0 | 0 | 0 | ? | S | 08:01 | 0:00 | [jbd2/dm-2-8] |
| root | 669 | 0.0 | 0.0 | 0 | 0 | ? | Sc | 08:01 | 0:00 | [ext4-rsv-conver] |


```

root 693 0.0 0.0 0 0 ? Sc 00:01 0:00 [xrtiod]
root 695 0.0 0.0 20388 1908 ? Sscl 00:01 0:00 /sbin/auditd
root 714 0.0 0.0 4112 1384 ? Sns 00:01 0:00 /usr/sbin/alsactl -s -n 19 -c -E ALSA_CONFIG_PATH=/etc/alsa/alsactl.conf --initfile=/lib/alsa/init/00main rdmaemo
root 715 0.0 0.0 11100 2080 ? Ss 00:01 0:00 /usr/sbin/mcelog --ignoreudev -daemon --foreground
root 716 0.0 0.1 50948 8392 ? Ssl 00:01 0:00 /usr/sbin/ModemManager
root 718 0.0 0.1 30864 8220 ? Ss 00:01 0:00 /usr/sbin/sssd -l -f
root 719 1.0 0.0 34632 7480 ? Ss 00:01 1:15 avahi-daemon: running [linux-2.local]
root 720 0.0 0.0 14192 1384 ? Ssl 00:01 0:00 /usr/sbin/lrgbalance --foreground
dbus 721 0.0 0.0 40312 5520 ? Ssl 00:01 0:00 /usr/bin/dbus-daemon --system --address=systemd: --nofork --nopidfile --systemd-activation --syslog-only
avahi 723 0.0 0.0 31204 276 ? S 00:01 0:00 avahi-daemon: chroot helper
root 727 0.0 0.0 48856 3352 ? Ssl 00:01 0:00 /usr/sbin/gssproxy -D
root 735 0.0 0.0 66048 5808 ? Ssl 00:01 0:00 /usr/sbin/rsyslogd -n
root 736 0.0 0.0 5972 3096 ? Ss 00:01 0:00 /usr/sbin/smartd -n -q never
root 738 0.0 0.3 43212 26920 ? Ssl 00:01 0:00 /usr/bin/python3 -Es /usr/sbin/firewalld --nofork --nopid
rtkit 743 0.0 0.1 24164 3300 ? Snscl 00:01 0:00 /usr/libexec/rtkit-daemon
root 748 0.0 0.1 63192 8468 ? Ssl 00:01 0:00 /usr/sbin/abrtfd -s
chrony 753 0.0 0.0 22396 3356 ? S 00:01 0:00 /usr/sbin/chronyd
root 764 0.0 0.1 38936 9236 ? S 00:01 0:00 /usr/libexec/sss/sss_be --domain implicit_files --uid 0 --gid 0 --debug-to-files
root 768 0.0 0.1 70260 9576 ? Ss 00:01 0:00 /usr/bin/abrt-dump-journal-coops -fxtb
root 769 0.0 0.1 70224 8068 ? Ss 00:01 0:00 /usr/bin/abrt-dump-journal-coops -fxtb
root 770 0.0 0.1 70224 9412 ? Ss 00:01 0:00 /usr/bin/abrt-dump-journal-core -D -l -f -e
root 771 0.0 0.3 44304 32760 ? S 00:01 0:00 /usr/libexec/sss/sss_nss --uid 0 --gid 0 --debug-to-files
root 772 0.0 0.1 66456 8548 ? Ssl 00:01 0:00 /usr/libexec/accounts-daemon
root 773 0.0 0.0 20680 8196 ? Ss 00:01 0:00 /usr/lib/systemd/systemd-logind
root 788 0.0 0.2 83628 17480 ? Ssl 00:01 0:00 /usr/sbin/NetworkManager --no-daemon
polkitd 789 0.0 0.1 104200 15588 ? Ssl 00:01 0:00 /usr/lib/polkit-1/polkitd --no-debug
root 820 0.0 0.0 14776 3380 ? S 00:01 0:00 /usr/sbin/crond -n
root 821 0.0 0.0 18104 2368 ? Ss 00:01 0:00 /usr/sbin/atd -f
root 823 0.0 0.1 73100 13760 ? Ssl 00:01 0:00 /usr/bin/sddm
root 884 0.2 0.6 103248 56960 tty1 Ssl+ 00:01 0:13 /usr/libexec/Xorg -nolisten tcp -auth /var/run/sddm/(28a38881-c890-485f-a7f8-244d759105bf) -background none -nor
root 1013 0.0 0.1 68208 10052 ? Ssl 00:01 0:01 /usr/libexec/udisks2/udisksd
root 1019 0.0 0.0 46296 6272 ? Ssl 00:01 0:00 /usr/libexec/upowerd
root 1050 0.0 0.1 61400 14076 ? S 00:12 0:00 /usr/libexec/kf5/start_kdeinit --socket /tmp/sddm-auth856c3439-eebd-4e78-a691-1f03713da942 --id 1 --start /usr/bin/sta
student 1062 0.0 0.0 20164 7616 ? Ss 00:12 0:00 /usr/lib/systemd/systemd --user
student 1064 0.0 0.0 51884 2404 ? S 00:12 0:00 (sd-pam)
student 1075 0.0 0.4 139196 33828 ? S 00:12 0:00 /usr/bin/kwalletd5 --pam-login 4 17
student 1078 0.0 0.0 5784 3092 ? S 00:12 0:00 /bin/sh /usr/bin/startkde
student 1097 0.0 0.0 33988 5088 ? Ssl 00:12 0:00 /usr/bin/dbus-daemon --session --address=systemd: --nofork --nopidfile --systemd-activation --syslog-only
student 1102 0.0 0.0 10644 528 ? Ss 00:12 0:00 /usr/bin/ssh-agent /bin/sh -c exec -l /bin/bash -c "/usr/bin/startkde"
student 1143 0.0 0.1 44460 4440 ? Ss 00:12 0:00 /usr/lib/kf5/start_kdeinit --kded +kcmnit_startup
student 1144 0.0 0.1 64524 8120 ? Ss 00:12 0:00 kdeinit5; Running...
student 1145 0.0 0.3 122860 32328 ? S 00:12 0:00 /usr/libexec/kf5/klauncher --fd=9
student 1148 0.0 0.7 277396 58832 ? S 00:12 0:01 kded5 [kdeinit5]
student 1161 0.0 0.1 143444 31160 ? S 00:13 0:00 /usr/bin/kcxs...

```

```

student 1173 0.0 0.4 146560 38380 ? S 00:12 0:00 /usr/bin/kwserver
student 1178 0.0 0.3 123464 31244 ? S 00:12 0:00 /usr/bin/kglobalaccel5
student 1183 0.0 0.1 50076 11780 ? S 00:12 0:00 /usr/libexec/mission-control-5
colord 1185 0.0 0.1 53116 11664 ? Ssl 00:12 0:00 /usr/libexec/colord
student 1191 0.3 0.9 316792 79436 ? S 00:12 0:13 kwin_x11
student 1205 0.0 0.2 80824 17476 ? S 00:12 0:00 /usr/libexec/kf5/kscreen_backend_launcher
student 1210 0.0 0.2 1125568 17704 ? Sml 00:12 0:00 /usr/bin/baloo_file
student 1212 0.0 0.4 151940 40124 ? S 00:12 0:00 /usr/libexec/kdeconnectd
student 1214 0.0 1.2 1385220 99496 ? S 00:12 0:01 /usr/bin/krunner
student 1216 0.3 2.5 1018156 218240 ? S 00:12 0:15 /usr/bin/plasmashell
student 1217 0.0 0.4 157596 35264 ? S 00:12 0:00 /usr/libexec/kf5/polkit-kde-authentication-agent-1
student 1218 0.0 0.3 129832 30440 ? S 00:12 0:00 /usr/bin/xembedsniproxy
root 1269 0.0 0.0 0 0 ? S 00:12 0:01 [kworker/3:0]
student 1279 0.0 0.1 1404256 10852 ? Scl 00:12 0:00 /usr/bin/pulseaudio --start --log-target=syslog
student 1296 0.0 0.2 78068 23864 ? S 00:12 0:00 /usr/bin/abrt-applet
student 1298 0.0 0.7 349124 65560 ? S 00:12 0:00 /usr/bin/korgac
student 1299 0.0 0.4 151000 35044 ? S 00:12 0:00 /usr/libexec/org.kde.powersdevil
student 1328 0.0 0.4 193268 35960 ? S 00:12 0:00 /usr/bin/kactivitymanagerd start-daemon
student 1371 0.0 0.0 48172 7160 ? Ssl 00:12 0:00 /usr/libexec/at-spi-bus-launcher
student 1381 0.0 0.0 33240 4668 ? S 00:12 0:00 /bin/dbus-daemon --config-file=/usr/share/defaults/at-spi2/accessibility.conf --nofork --print-address 3
student 1386 0.0 0.0 30076 6560 ? S 00:12 0:00 /usr/libexec/at-spi2-registryd --use-gnome-session
root 1446 0.0 0.0 55488 8116 ? S 00:12 0:00 /usr/sbin/abrt-dbus -t133
student 1452 0.0 0.1 130748 31828 ? S 00:12 0:00 /usr/bin/akonadi_control
student 1456 0.0 0.3 344100 20140 ? S 00:12 0:00 akonadiserwer
student 1459 0.0 0.6 526992 55356 ? S 00:12 0:02 /usr/libexec/mysqld --defaults-file=/home/student/.local/share/akonadi/mysql.conf --datadir=/home/student/.local
student 1499 0.0 0.4 145168 36240 ? S 00:12 0:00 /usr/bin/akonadi_akonotes_resource --identifier akonadi_akonotes_resource_0
student 1500 0.0 0.7 345544 64868 ? S 00:12 0:00 /usr/bin/akonadi_archivemail_agent --identifier akonadi_archivemail_agent
student 1501 0.0 0.4 150136 38044 ? S 00:12 0:00 /usr/bin/akonadi_birthdays_resource --identifier akonadi_birthdays_resource
student 1502 0.0 0.4 144812 36384 ? S 00:12 0:00 /usr/bin/akonadi_contacts_resource --identifier akonadi_contacts_resource_0
student 1503 0.0 0.4 160816 39700 ? S 00:12 0:00 /usr/bin/akonadi_followupreminder_agent --identifier akonadi_followupreminder_agent
student 1504 0.0 0.4 151472 38864 ? S 00:12 0:00 /usr/bin/akonadi_ical_resource --identifier akonadi_ical_resource_0
student 1507 0.0 0.4 154560 40440 ? Sml 00:12 0:00 /usr/bin/akonadi_indexing_agent --identifier akonadi_indexing_agent
student 1510 0.0 0.4 145168 35732 ? S 00:12 0:00 /usr/bin/akonadi_maildir_resource --identifier akonadi_maildir_resource_0
student 1529 0.0 0.4 155640 37248 ? S 00:12 0:00 /usr/bin/akonadi_maildispatcher_agent --identifier akonadi_maildispatcher_agent
student 1530 0.0 0.8 351476 67804 ? S 00:12 0:00 /usr/bin/akonadi_mailfilter_agent --identifier akonadi_mailfilter_agent
student 1531 0.0 0.4 144376 36524 ? S 00:12 0:00 /usr/bin/akonadi_migration_agent --identifier akonadi_migration_agent
student 1532 0.0 0.7 317720 50360 ? S 00:12 0:00 /usr/bin/akonadi_newmailnotifier_agent --identifier akonadi_newmailnotifier_agent
student 1533 0.0 0.7 343160 63856 ? S 00:12 0:00 /usr/bin/akonadi_sendlater_agent --identifier akonadi_sendlater_agent
student 1601 0.0 0.3 130504 32776 ? S 00:12 0:00 /usr/bin/kuiserver5
root 1605 0.0 0.0 31532 7876 ? Ss 00:12 0:00 /usr/sbin/cupsd -l
root 1607 0.1 1.0 172724 88596 ? Ssl 00:12 0:06 /usr/libexec/packagekitd
root 1838 0.0 0.0 0 0 ? S 00:49 0:00 [kworker/3:1]
root 1845 0.0 0.0 0 0 ? S 00:50 0:00 [kworker/2:2]

```

```

root      1607  0.1  1.0 172724 88596 ?        Ssl  00:12  0:00 /usr/libexec/packagekitd
root      1838  0.0  0.0    0  0 ?        S    08:49  0:00 [kworker/3:1]
root      1845  0.0  0.0    0  0 ?        S    08:50  0:00 [kworker/2:2]
root      1939  0.0  0.0    0  0 ?        S    09:09  0:00 [kworker/u8:0]
root      1942  0.0  0.0    0  0 ?        S    09:10  0:00 [kworker/u8:3]
root      1952  0.0  0.0    0  0 ?        S    09:11  0:00 [kworker/0:2]
root      1960  0.0  0.0    0  0 ?        S    09:15  0:00 [kworker/u8:1]
student   2004  1.6  2.3 1321396 193748 ?        Sl   09:16  0:13 /usr/bin/amarok
student   2008  0.0  0.1 83180 15240 ?        Ss   09:16  0:00 kdeinit4: kdeinit4 Running...
student   2010  0.0  0.2 89312 19168 ?        S    09:16  0:00 kdeinit4: klauncher [kdeinit] --fd=9
student   2012  0.0  0.3 108896 27292 ?        S    09:16  0:00 kdeinit4: kded4 [kdeinit]
student   2014  0.0  0.0 12508 2708 ?        S    09:16  0:00 /usr/libexec/gam_server
student   2057  0.0  0.5 436024 45072 ?        Sl   09:17  0:00 /usr/bin/knotify4
student   2087  0.0  0.2 88256 22272 ?        S    09:17  0:00 /usr/libexec/kde4/kio_http_cache_cleaner
root      2114  0.0  0.0    0  0 ?        S    09:17  0:00 [kworker/1:0]
student   2121  0.3  0.6 172348 56672 ?        Rl   09:20  0:00 /usr/bin/konsole
student   2125  0.0  0.0 14580 3996 pts/1    Ss   09:20  0:00 /bin/bash
root      2158  0.0  0.0    0  0 ?        S    09:22  0:00 [kworker/1:1]
student   2161  0.0  0.0 16672 3616 pts/1    R+   09:23  0:00 ps -aux

[student@localhost ~]$ uname -m
i686
[student@localhost ~]$ uname -n
localhost.localdomain
[student@localhost ~]$ uname -r
4.11.8-300.fc26.i686PAE
[student@localhost ~]$ uname -s
linux
[student@localhost ~]$ uname -v
#1 SMP Thu Jun 29 20:38:21 UTC 2017
[student@localhost ~]$ uname -a
linux localhost.localdomain 4.11.8-300.fc26.i686PAE #1 SMP Thu Jun 29 20:38:21 UTC 2017 i686 i686 i386 GNU/Linux
[student@localhost ~]$ pwd
/home/student
[student@localhost ~]$ ls
Desktop  Documents  Downloads  filename.sh  gowtham  karthi79  'lab 2 05.txt'  Music  os.txt  Pictures  Public  stu  Templates  Videos  wx  wxcollege
[student@localhost ~]$ mv os.txt karthi79
[student@localhost ~]$ cat karthi79
cat: karthi79: Is a directory
[student@localhost ~]$ ls karthi79
os.txt
[student@localhost ~]$ cat os.txt
cat: os.txt: No such file or directory
[student@localhost ~]$ cd karthi79
[student@localhost karthi79]$ cat os.txt

```

```

linux localhost.localdomain 4.11.8-300.fc26.i686PAE #1 SMP Thu Jun 29 20:38:21 UTC 2017 i686 i686 i386 GNU/Linux
[student@localhost ~]$ pwd
/home/student
[student@localhost ~]$ ls
Desktop  Documents  Downloads  filename.sh  gowtham  karthi79  'lab 2 05.txt'  Music  os.txt  Pictures  Public  stu  Templates  Videos  wx  wxcollege
[student@localhost ~]$ mv os.txt karthi79
[student@localhost ~]$ cat karthi79
cat: karthi79: Is a directory
[student@localhost ~]$ ls karthi79
os.txt
[student@localhost ~]$ cat os.txt
cat: os.txt: No such file or directory
[student@localhost ~]$ cd karthi79
[student@localhost karthi79]$ cat os.txt
Hi hello, how are you?
Good Bye
[student@localhost karthi79]$ cd -
/home/student
[student@localhost ~]$ cat os.txt
cat: os.txt: No such file or directory
[student@localhost ~]$ cd karthi79
[student@localhost karthi79]$ wc os.txt
 2  7 32 os.txt
[student@localhost karthi79]$ cd -
/home/student
[student@localhost ~]$ top gowtham
top: unknown option 'g'
Usage:
  top -hv [-bchIOss -d secs -n max -uU user -p pid(s) -o field -w [cols]]
[student@localhost ~]$ head gowtham
r
e
c
c
o
l
e
g
e
[student@localhost ~]$ tail gowtham
e
t

```

```

o
l
l
e
g
e
[student@localhost ~]$ tail gowtham
e
t
h
a
n
d
a
l
a
m
[student@localhost ~]$ ping gowtham
ping: gowtham: Name or service not known
[student@localhost ~]$ cd karthi79
[student@localhost karthi79]$ ping os.txt
ping: os.txt: Name or service not known
[student@localhost karthi79]$ cd -
/home/student
[student@localhost ~]$ ifconfig
enp2s0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST>  mtu 1500
    inet 172.16.8.29  netmask 255.255.252.0  broadcast 172.16.11.255
    inet6 fe80::354c:ba27:ebcc:5d62  prefixlen 64  scopeid 0x20<link>
    ether f8:bc:12:90:45:7e  txqueuelen 1000  (Ethernet)
    RX packets 409135  bytes 342188533 (326.3 MiB)
    RX errors 0  dropped 109  overruns 0  frame 0
    TX packets 7862  bytes 474073 (462.9 KiB)
    TX errors 0  dropped 0  overruns 0  carrier 0  collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING>  mtu 65536
    inet 127.0.0.1  netmask 255.0.0.0
    inet6 ::1  prefixlen 128  scopeid 0x10<host>
    loop txqueuelen 1000  (local loopback)
    RX packets 0  bytes 0 (0.0 B)
    RX errors 0  dropped 0  overruns 0  frame 0
    TX packets 0  bytes 0 (0.0 B)
    TX errors 0  dropped 0  overruns 0  carrier 0  collisions 0
[student@localhost ~]$ cd karthi79

```

```

[student@localhost karthi79]$ cd -
/home/student
[student@localhost ~]$ ifconfig
enp2s0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST>  mtu 1500
    inet 172.16.8.29  netmask 255.255.252.0  broadcast 172.16.11.255
    inet6 fe80::354c:ba27:ebcc:5d62  prefixlen 64  scopeid 0x20<link>
    ether f8:bc:12:90:45:7e  txqueuelen 1000  (Ethernet)
    RX packets 409135  bytes 342188533 (326.3 MiB)
    RX errors 0  dropped 109  overruns 0  frame 0
    TX packets 7862  bytes 474073 (462.9 KiB)
    TX errors 0  dropped 0  overruns 0  carrier 0  collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING>  mtu 65536
    inet 127.0.0.1  netmask 255.0.0.0
    inet6 ::1  prefixlen 128  scopeid 0x10<host>
    loop txqueuelen 1000  (local loopback)
    RX packets 0  bytes 0 (0.0 B)
    RX errors 0  dropped 0  overruns 0  frame 0
    TX packets 0  bytes 0 (0.0 B)
    TX errors 0  dropped 0  overruns 0  carrier 0  collisions 0

[student@localhost ~]$ cd karthi79
[student@localhost karthi79]$ sort -r os.txt
Hi hello, how are you?
Good Bye
[student@localhost karthi79]$ sort -n os.txt
Good Bye
Hi hello, how are you?
[student@localhost karthi79]$ sort -m os.txt
Hi hello, how are you?
Good Bye
[student@localhost karthi79]$ grep "h" os.txt
bash: grep: command not found
[student@localhost karthi79]$ grep "h" os.txt
Hi hello, how are you?
[student@localhost karthi79]$ tail os.txt
Hi hello, how are you?
Good Bye
[student@localhost karthi79]$ who;date
student pts/0      2025-01-25 08:12 (:0)
student pts/1      2025-01-25 09:20 (:0)
sat Jan 25 09:31:14 IST 2025
[student@localhost karthi79]$ who&&date

```

```

inet 172.16.0.29 netmask 255.255.252.0 broadcast 172.16.11.255
inet6 fe80::354c:ba27:ebcc:5d62 prefixlen 64 scopeid 0x20<link>
ether fa:bc:12:58:45:7e txqueuelen 1000 (Ethernet)
RX packets 409135 bytes 342188533 (326.3 MiB)
RX errors 0 dropped 109 overruns 0 frame 0
TX packets 7862 bytes 474073 (462.9 KiB)
TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
inet 127.0.0.1 netmask 255.0.0.0
inet6 ::1 prefixlen 128 scopeid 0x10<host>
loop txqueuelen 1000 (local loopback)
RX packets 0 bytes 0 (0.0 B)
RX errors 0 dropped 0 overruns 0 frame 0
TX packets 0 bytes 0 (0.0 B)
TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

[student@localhost ~]$ cd karthi79
[student@localhost karthi79]$ sort -r os.txt
Hi hello, how are you?
Good Bye
[student@localhost karthi79]$ sort -n os.txt
Good Bye
Hi hello, how are you?
[student@localhost karthi79]$ sort -m os.txt
Hi hello, how are you?
Good Bye
[student@localhost karthi79]$ grep "h" os.txt
bash: grep: command not found
[student@localhost karthi79]$ grep "h" os.txt
Hi hello, how are you?
[student@localhost karthi79]$ tail os.txt
Hi hello, how are you?
Good Bye
[student@localhost karthi79]$ who;date
student pts/0 2025-01-25 08:12 (:0)
student pts/1 2025-01-25 09:20 (:0)
Sat Jan 25 09:31:14 IST 2025
[student@localhost karthi79]$ who&&date
student pts/0 2025-01-25 08:12 (:0)
student pts/1 2025-01-25 09:20 (:0)
Sat Jan 25 09:31:31 IST 2025
[student@localhost karthi79]$

```

RESULT:

Thus, the program of basic Linux commands has been executed and the output has been verified.
 2116231801033

CS23431

Ex. No: 2a
Date: 28/1/25

Shell Script

AIM:

To write a Shell script to display a basic calculator.

PROGRAM:

```
#!/bin/bash

while true; do
    echo "=====
    echo "  Basic Calculator"
    echo "=====
    echo "1. Addition"
    echo "2. Subtraction"
    echo "3. Multiplication"
    echo "4. Division"
    echo "5. Exit"
    echo -n "Choose an option (1-5): "
    read choice

    if [[ $choice -eq 5 ]]; then
        echo "Exiting Calculator. Goodbye!"
        exit 0
    fi

    echo -n "Enter first number: "
    read num1
    echo -n "Enter second number: "
    read num2

    case $choice in
        1) result=$((num1 + num2))
            echo "Result: $num1 + $num2 = $result"
            ;;
        2) result=$((num1 - num2))
            echo "Result: $num1 - $num2 = $result"
            ;;
        3) result=$((num1 * num2))
            echo "Result: $num1 * $num2 = $result"
            ;;
```


```

4) if [[ $num2 -eq 0 ]]; then
    echo "Error: Division by zero is not allowed!"
else

    result=$(awk "BEGIN {print $num1 / $num2}")
    echo "Result: $num1 / $num2 = $result"
fi
;;
*) echo "Invalid option! Please choose between 1-5."
;;
esac
echo "-----"
echo ""
done

```

OUTPUT:



```

File Edit Selection View Go Run Terminal Help
Basic Calculator
1. Addition
2. Subtraction
3. Multiplication
4. Division
5. Exit
Choose an option (1-5): 3
Enter first number: 5
Enter second number: 8
Result: 5 * 8 = 40
-----

Basic Calculator
1. Addition
2. Subtraction
3. Multiplication
4. Division
5. Exit
Choose an option (1-5): 2
Enter first number: 9
Enter second number: 5
Result: 9 - 5 = 4
-----

Basic Calculator
1. Addition
2. Subtraction
3. Multiplication
4. Division
5. Exit
Choose an option (1-5): 4
Enter first number: 5
Enter second number: 9
Result: 5 / 9 = 0.555556
-----

Basic Calculator
1. Addition
2. Subtraction
3. Multiplication
4. Division
5. Exit
Choose an option (1-5): 5

```

```
karthick.S@karthick42 MINGW64 ~
$ cd "/c:/Users/karthick.S/OneDrive/Documents/0s"
$ bash calc.sh
=====
Basic Calculator
=====
1. Addition
2. Subtraction
3. Multiplication
4. Division
5. Exit
Choose an option (1-5): 1
Enter first number: 5
Enter second number: 2
Result: 5 + 2 = 7
=====
Basic Calculator
=====
1. Addition
2. Subtraction
3. Multiplication
4. Division
5. Exit
Choose an option (1-5): 2
Enter first number: 5
Enter second number: 8
Result: 5 - 8 = -3
=====
Basic Calculator
=====
1. Addition
2. Subtraction
3. Multiplication
4. Division
5. Exit
Choose an option (1-5): 3
```

```
-----
Basic Calculator
-----
1. Addition
2. Subtraction
3. Multiplication
4. Division
5. Exit
Choose an option (1-5): 2
Enter first number: 9
Enter second number: 5
Result: 9 - 5 = 4
-----
Basic Calculator
-----
1. Addition
2. Subtraction
3. Multiplication
4. Division
5. Exit
Choose an option (1-5): 4
Enter first number: 5
Enter second number: 9
Result: 5 / 9 = 0.555556
-----
Basic Calculator
-----
1. Addition
2. Subtraction
3. Multiplication
4. Division
5. Exit
Choose an option (1-5): 5
Exiting Calculator. Goodbye!
karthick.S@karthick42 MINGW64 ~/OneDrive/Documents/0s
```


RESULT:

Thus, the basic calculator program was successfully implemented using shell scripting.

2116231801033

CS23431

Ex. No: 2b

Date: 28/2/25

Shell Script

AIM:

To write a Shellscrip to test given year is leap or not using conditional statement


PROGRAM:

```
#!/bin/bash

read -p "Enter year: " year

if (( year % 4 == 0 && year % 100 != 0 )) || (( year % 400 == 0 )); then
    echo "$year is a Leap Year"
else
    echo "$year is not a Leap Year"
fi
```

OUTPUT:



```
karthick.S@KarthickH2 MINGW64 ~/OneDrive/Documents/0s
$ bash leap.sh
Enter year: 2024
2024 is a Leap Year

karthick.S@KarthickH2 MINGW64 ~/OneDrive/Documents/0s
$ bash leap.sh
Enter year: 2000
2000 is a Leap Year

karthick.S@KarthickH2 MINGW64 ~/OneDrive/Documents/0s
$ bash leap.sh
Enter year: 2023
2023 is not a Leap Year

karthick.S@KarthickH2 MINGW64 ~/OneDrive/Documents/0s
$
```

RESULT:

Thus, the leap year program was successfully implemented using shell scripting.

Ex. No: 3a
Date: 8/2/25

Shell Script – Reverse of Digit

AIM:

To write a Shell script to reverse a given digit using looping statement.

PROGRAM:


```
#!/bin/bash

read -p "Enter a number: " num

reverse=0
while [ $num -gt 0 ]; do
    digit=$(( num % 10 ))
    reverse=$(( reverse * 10 + digit ))
    num=$(( num / 10 ))
done

echo "Reversed number: $reverse"
```

OUTPUT:

A screenshot of a terminal window with a dark background. The window title is "karthick.S@KarthickH2 MINGW64 ~". The terminal shows the following commands and output:
1. Command: `cd "/c/Users/karthick.S/OneDrive/Documents/Os"`
2. Command: `bash reverse.sh`
 Input: `Enter a number: 80`
 Output: `Reversed number: 8`
3. Command: `bash reverse.sh`
 Input: `Enter a number: 79`
 Output: `Reversed number: 97`
4. Command: `bash reverse.sh`
 Input: `Enter a number: 69`
 Output: `Reversed number: 96`
5. Command: `bash reverse.sh`
 Input: `Enter a number: 69`
 Output: `Reversed number: 96`
The terminal ends with a prompt `$`.

RESULT:

2116231801033

CS23431

The shell script to reverse a given digit is successfully implemented.

Ex. No: 3b

Date: 8/2/25

Shell Script – Fibonacci Series

AIM:

To write a Shell script to generate a Fibonacci series using a for loop.

PROGRAM:


```
#!/bin/bash

read -p "Enter the number of terms: " n
a=0
b=1

echo "Fibonacci Series:"
for (( i=0; i<n; i++ )); do
    echo -n "$a "
    temp=$((a + b))
    a=$b
    b=$temp
done

echo
```

OUTPUT

A screenshot of a terminal window with a dark background. The terminal shows the following commands and output: The user is at a prompt 'karthick.S@KarthickH2 MINGW64 ~'. They enter '\$ cd "/>

RESULT:

2116231801033

CS23431

The Shell Script to generate the Fibonacci series is successfully implemented.
Ex. No: 4a
Date: 13/2/25

EMPLOYEE AVERAGE PAY

AIM:

To find out the average pay of all employees whose salary is more than 6000 and no. of days worked is more than 4.

ALGORITHM:

1. Create a flat file emp.dat for employees with their name, salary per day and number of days worked and save it.
2. Create an awk script emp.awk
3. For each employee record do
 - a. If the Salary is greater than 6000 and number of days worked is more than 4, then print the name and salary earned
 - b. Compute total pay of employee
4. Print the total number of employees satisfying the criteria and their average pay.

PROGRAM:

```
#!/usr/bin/awk -f
```

```
BEGIN {  
    count = 0;  
    total_pay = 0;  
}  
  
{  
    salary = $2;  
    days = $3;  
  
    if (salary > 6000 && days > 4) {  
        pay = salary * days;  
        print "Employee:", $1, "Total Pay:", pay;  
        total_pay += pay;  
        count++;  
    }  
}  
  
END {  
    if (count > 0) {  
        avg_pay = total_pay / count;  
        print "\nTotal Employees:", count;  
        print "Total Pay:", total_pay;  
        print "Average Pay:", avg_pay;  
    } else {
```

```
    print "No employees satisfy the criteria.";
  }
}
```

INPUT:


John 7000 10

Alice 5000 12

Bob 8000 9

Mike 6500 6

OUTPUT:



```
karthick.S@karthickH2 MINGW64 ~
$ cd "/c:/Users/karthick.S/OneDrive/Documents/Os"
karthick.S@karthickH2 MINGW64 ~/OneDrive/Documents/Os
$ gawk -f emp.awk emp.dat
Employee: John Total Pay: 70000
Employee: Bob Total Pay: 72000
Employee: Mike Total Pay: 39000

Total Employees: 3
Total Pay: 181000
Average Pay: 60333.3
```

RESULT:

2116231801033

CS23431

To find the average salary whose salary is above 6000 is successfully implemented.
Ex. No: 4b
Date: 13/2/25

RESULTS OF EXAMINATION

AIM:

To print the pass/fail status of a student in a class.

ALGORITHM:

1. Read the data from file
2. Get a data from each column
3. Compare the all subject marks column
 - a. If marks less than 45 then print Fail
 - b. else print Pass


PROGRAM:

```
//marks.awk
#!/usr/bin/gawk -f
{
    name = $1;
    pass = 1;
    for (i = 2; i <= NF; i++) {
        if ($i < 45) {
            pass = 0;
            break;}
    }
    if(pass) {
        print name, "Pass";
    } else {
        print name, "Fail";}
}
```

INPUT:

```
//marks.dat
John 50 60 45 70 80
Alice 40 55 30 65 75
Bob 80 85 90 78 88
Mike 35 40 50 60 45
```


OUTPUT:



```
karthick.S@KarthickH2 MINGW64 ~
$ cd "/c/Users/karthick.S/OneDrive/Documents/Os"

karthick.S@KarthickH2 MINGW64 ~/OneDrive/Documents/Os
$ gawk -f marks.awk marks.dat
John Pass
Alice Fail
Bob Pass
Mike Fail

karthick.S@KarthickH2 MINGW64 ~/OneDrive/Documents/Os
$
```

RESULT:

To print the Pass/Fail Status of a student in a class is successfully implemented.

2116231801033

CS23431

Ex. No: 5

Date: 20/2/25

System Calls Programming

AIM:

To experiment system calls using fork(), execlp() and pid() functions.

ALGORITHM:

1. **Start**
2. **Include Header Files**
 - Include stdio.h for input/output functions
 - Include stdlib.h for general utility functions
3. **Variable Declaration**
 - Declare an integer variable pid to store the process ID returned by fork()
4. **Create a New Process**
 - Call the fork() function and assign its return value to pid
 - If fork() returns:
 - -1: Process creation failed
 - 0: This is the **child** process
 - A positive integer: This is the **parent** process
5. **Print Statement Executed by Both Processes**
 - Print: "THIS LINE EXECUTED TWICE"
6. **Check for Process Creation Failure**
 - If pid == -1:
 - Print: "CHILD PROCESS NOT CREATED"
 - Exit the program using exit(0)
7. **Child Process Execution Block**
 - If pid == 0:
 - Print:
 - "Process ID of child: " followed by getpid()
 - "Parent Process ID of child: " followed by getppid()
8. **Parent Process Execution Block**
 - If pid > 0:
 - Print:
 - "Process ID of parent: " followed by getpid()
 - "Parent's Parent Process ID: " followed by getppid()
9. **Final Print Statement (Executed by Both Processes)**
 - Print: objectives
IT CAN BE EXECUTED TWICE
10. **End**

PROGRAM:

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>

int main() {
    int pid;
    pid = fork();
    printf("This Line Executed Twice\n");


    if (pid < 0) {
        printf("Child Process Not Created\n");
        exit(1);
    }

    if (pid == 0) {
        printf("Child Process:\n");
        printf("Process ID: %d\n", getpid());
        printf("Parent Process ID: %d\n", getppid());
        execlp("/bin/ls", "ls", NULL);
        perror("execlp failed");
        exit(1);
    } else { // Parent process
        printf("Parent Process:\n");
        printf("Process ID: %d\n", getpid());
        printf("Parent's Parent Process ID: %d\n", getppid());
        printf("Child Process Completed\n");
    }

    printf("It can be executed twice\n");

    return 0;
}
```

OUTPUT:

A screenshot of a terminal window titled 'Input'. The terminal has a black background with white text. The output shows a parent process (ID: 44201) spawning a child process (ID: 44200). The child process prints 'This Line Executed Twice' and 'Child Process Completed'. The parent process prints 'Parent Process:' and 'Process ID: 44201'. The child process prints 'Child Process:' and 'Process ID: 44205'. The parent process prints 'Parent Process ID: 44201'. The terminal ends with '...Program finished with exit code 0' and 'Press ENTER to exit console.'.

```
Input
This Line Executed Twice
Parent Process:
Process ID: 44201
Parent's Parent Process ID: 44200
Child Process Completed
it can be executed twice
This Line Executed Twice
Child Process:
Process ID: 44205
Parent Process ID: 44201

...Program finished with exit code 0
Press ENTER to exit console.
```

RESULT:

To Program is implemented using fork(),execlp() and pid() Functions.

2116231801033

CS23431

Ex. No: 6a

Date: 20/2/25

FIRST COME FIRST SERVE

AIM:

To implement First-come First- serve (FCFS) scheduling technique

ALGORITHM:

1. Get the number of processes from the user.
2. Read the process name and burst time.
3. Calculate the total process time.
4. Calculate the total waiting time and total turnaround time for each process
5. Display the process name & burst time for each process.
6. Display the total waiting time, average waiting time, turnaround time.

PROGRAM:

```
#include <stdio.h>

int main() {
    int pid[15], bt[15], wt[15], n;
    float twt = 0, ttat = 0;

    printf("Enter the number of processes: ");
    scanf("%d", &n);

    printf("Enter process ID of all the processes:\n");
    for (int i = 0; i < n; i++) {
        scanf("%d", &pid[i]);
    }

    printf("Enter burst time of all the processes:\n");
    for (int i = 0; i < n; i++) {
        scanf("%d", &bt[i]);
    }

    wt[0] = 0;
    // Calculate waiting time for all other processes
    for (int i = 1; i < n; i++) {
        wt[i] = wt[i - 1] + bt[i - 1];
    }

    printf("\nProcess ID\tBurst Time\tWaiting Time\tTurnaround Time\n");

    for (int i = 0; i < n; i++) {
        int tat = bt[i] + wt[i];
        twt += wt[i];
    }
}
```

```

    ttat += tat;

    printf("%d\t%d\t%d\t%d\t%d\n", pid[i], bt[i], wt[i], tat);
}

printf("\nAverage waiting time = %.2f\n", twt / n);
printf("Average turnaround time = %.2f\n", ttat / n);

return 0;
}

```

OUTPUT:

```

karthick.9@karthick92 MINGW64 ~/OneDrive/Documents/0s
$ ./Ex-a.exe
bash: ./Ex-a.exe: No such file or directory

karthick.9@karthick92 MINGW64 ~/OneDrive/Documents/0s
$ ls
calc.sh*  emp.dat  Ex-6a.c  Ex-6b.c  Ex-6c.c  Ex-6d.c  fibo.sh*  marks.mk*  Outputs/
emp.mk*   Ex-5.c  Ex-6a.exe  Ex-6b.exe  Ex-6c.exe  Ex-6d.exe  leap.sh*  marks.dat  reverse.sh*

karthick.9@karthick92 MINGW64 ~/OneDrive/Documents/0s
$ ./Ex-6a.exe
Enter the number of processes: 3
Enter process id of all the processes: 1 2 3
Enter burst time of all the processes: 2 25 3
Process ID    burst time    waiting time    turnaround time
1             2             0              2
2             25            2              27
3             3             27             30
Avg. waiting time- 9.666667
Avg. turnaround time- 19.666666
karthick.9@karthick92 MINGW64 ~/OneDrive/Documents/0s
$

```

RESULT:

2116231801033

CS23431

The Program of first come first serve is successfully implemented.

Ex. No: 6b

Date: 20/2/25

SHORTEST JOB FIRST

AIM:

To implement the Shortest Job First (SJF) scheduling technique

ALGORITHM:

1. Declare the structure and its elements.
2. Get a number of processes as input from the user.
3. Read the process name, arrival time and burst time
4. Initialize waiting time, turnaround time & flag of read processes to zero.
5. Sort based on the burst time of all processes in ascending order.
6. Calculate the waiting time and turnaround time for each process.
7. Calculate the average waiting time and average turnaround time.
8. Display the results.

PROGRAM:

```
#include <stdio.h>
```

```
int main() {  
    int A[100][4]; // A[i][0]=PID, A[i][1]=BT, A[i][2]=WT, A[i][3]=TAT  
    int i, j, n, total = 0, index, temp;  
    float avg_wt, avg_tat;
```

```
    printf("Enter number of processes: ");  
    scanf("%d", &n);
```

```
    printf("Enter Burst Time:\n");  
    for (i = 0; i < n; i++) {  
        printf("P%d: ", i + 1);  
        scanf("%d", &A[i][1]);  
        A[i][0] = i + 1; // Assign process ID  
    }
```

```
    for (i = 0; i < n; i++) {  
        index = i;  
        for (j = i + 1; j < n; j++) {  
            if (A[j][1] < A[index][1])  
                index = j;  
        }
```

```
        temp = A[i][1];
```

2116231801033

CS23431

```

    A[i][1] = A[index][1];
    A[index][1] = temp;

    temp = A[i][0];
    A[i][0] = A[index][0];
    A[index][0] = temp;
}

A[0][2] = 0;
for (i = 1; i < n; i++) {
    A[i][2] = 0;
    for (j = 0; j < i; j++) {
        A[i][2] += A[j][1];
    }
    total += A[i][2];
}
avg_wt = (float) total / n;

total = 0;
printf("\nProcess\tBT\tWT\tTAT\n");
for (i = 0; i < n; i++) {
    A[i][3] = A[i][1] + A[i][2]; // TAT = BT + WT
    total += A[i][3];
    printf("P%d\t%d\t%d\t%d\n", A[i][0], A[i][1], A[i][2], A[i][3]);
}
avg_tat = (float) total / n;

printf("\nAverage Waiting Time = %.2f", avg_wt);
printf("\nAverage Turnaround Time = %.2f\n", avg_tat);

return 0;
}

```

OUTPUT:

```

karthick.S@karthickH2 MINGW64 ~
$ cd "/c:/Users/karthick.S/OneDrive/Documents/0s"
bash: $: command not found

karthick.S@karthickH2 MINGW64 ~
$ cd "/c:/Users/karthick.S/OneDrive/Documents/0s"

karthick.S@karthickH2 MINGW64 ~/OneDrive/Documents/0s
$ gcc Ex-6b.c -o Ex-6b.exe

karthick.S@karthickH2 MINGW64 ~/OneDrive/Documents/0s
$ ./Ex-6b.exe
Enter number of process: 4
Enter Burst Time:
P1: 2
P2: 5
P3: 7
P4: 1
P
BT    WT    TAT
P4    1    0    1
P1    2    1    3
P2    5    3    8
P3    7    8    15
Average Waiting Time= 3.000000
Average Turnaround Time= 6.250000
karthick.S@karthickH2 MINGW64 ~/OneDrive/Documents/0s
$

```


RESULT:

2116231801033

CS23431

The Program Shortest Job First is successfully implemented.

Ex. No: 6c

Date: 22/2/25

PRIORITY SCHEDULING

AIM:

To implement a priority scheduling technique

ALGORITHM:

1. Get the number of processes from the user.
2. Read the process name, burst time and priority of the process.
3. Sort based on burst time of all processes in ascending order based on priority
4. Calculate the total waiting time and total turnaround time for each process
5. Display the process name & burst time for each process.
6. Display the total waiting time, average waiting time, turnaround time.

PROGRAM:

```
#include <stdio.h>
#include <stdlib.h>

void swap(int *a, int *b) {
    int temp = *a;
    *a = *b;
    *b = temp;
}

int main() {
    int n;
    printf("Enter number of processes: ");
    scanf("%d", &n);

    int *burst = (int*)malloc(n * sizeof(int));
    int *priority = (int*)malloc(n * sizeof(int));
    int *pid = (int*)malloc(n * sizeof(int));
    int total_wait = 0, total_turnaround = 0;

    for (int i = 0; i < n; i++) {
        printf("Enter Burst Time and Priority for Process %d: ", i + 1);
        scanf("%d %d", &burst[i], &priority[i]);
        pid[i] = i + 1;
    }

    for (int i = 0; i < n - 1; i++) {
        for (int j = i + 1; j < n; j++) {
            if (priority[j] > priority[i]) {
                swap(&priority[i], &priority[j]);
                swap(&burst[i], &burst[j]);
                swap(&pid[i], &pid[j]);
            }
        }
    }
```

```

    }
}

int wait_time = 0;
printf("\nProcess   Burst Time   Wait Time   Turnaround Time\n");

for (int i = 0; i < n; i++) {
    int turnaround_time = wait_time + burst[i];
    total_wait += wait_time;
    total_turnaround += turnaround_time;

    printf("P%d      %d      %d      %d\n", pid[i], burst[i], wait_time, turnaround_time);

    wait_time += burst[i];
}


printf("\nAverage Waiting Time: %.2f\n", (float)total_wait / n);
printf("Average Turnaround Time: %.2f\n", (float)total_turnaround / n);

free(burst);
free(priority);
free(pid);

return 0;
}

```

OUTPUT:



```

karthick.s@karthickid: ~/OneDrive/Documents/0s
$ cd "/c:/Users/karthick.s/OneDrive/Documents/0s/"
karthick.s@karthickid: ~/OneDrive/Documents/0s
$ gcc Dx-6c.c -o Dx-6c.exe
karthick.s@karthickid: ~/OneDrive/Documents/0s
$ ./Dx-6c.exe
Enter number of processes: 4
Enter Burst Time and Priority for Process 1: 5 2
Enter Burst Time and Priority for Process 2: 3 1
Enter Burst Time and Priority for Process 3: 8 3
Enter Burst Time and Priority for Process 4: 2 4

Process   Burst Time   Wait Time   Turnaround Time
P4        2           0           2
P3        8           2          10
P1        5          10          15
P2        3          15          18

Average Waiting Time: 6.75
Average Turnaround Time: 11.25
karthick.s@karthickid: ~/OneDrive/Documents/0s
$

```

RESULT:

The Program of Priority scheduling is successfully implemented.

Ex. No: 6d

Date: 22/2/25

ROUND ROBIN SCHEDULING

AIM:

To implement the round-robin (RR) scheduling technique

ALGORITHM:

1. Declare the structure and its elements.
2. Get a number of processes and Time quantum as input from the user.
3. Read the process name, arrival time and burst time
4. Create an array rem_bt[] to keep track of the remaining burst time of processes which is initially copy of bt[] (burst times array)
5. Create another array wt[] to store waiting times of processes. Initialize this array as 0.
6. Initialize time : t = 0
7. Keep traversing all processes while all processes are not done. Do the following for i'th process if it is not done yet.
 - a- If rem_bt[i] > quantum
 - (i) t = t + quantum
 - (ii) bt_rem[i] -= quantum;
 - b- Else // Last cycle for this process
 - (i) t = t + bt_rem[i];
 - (ii) wt[i] = t - bt[i]
 - (iii) bt_rem[i] = 0; // This process is over
8. Calculate the waiting time and turnaround time for each process.
9. Calculate the average waiting time and average turnaround time.
10. Display the results.

PROGRAM:

```
#include <stdio.h>
#include <stdlib.h>

int main() {
    int n, time_quantum;
    printf("Enter number of processes: ");
    scanf("%d", &n);

    int *arrival = (int*)malloc(n * sizeof(int));
    int *burst = (int*)malloc(n * sizeof(int));
    int *remaining = (int*)malloc(n * sizeof(int));
    int wait_time = 0, turnaround_time = 0, total = 0, x = n;

    for (int i = 0; i < n; i++) {
        printf("Enter arrival time and burst time for process %d: ", i + 1);
        2116231801033
```

```

scanf("%d %d", &arrival[i], &burst[i]);
remaining[i] = burst[i];
}

printf("Enter time quantum: ");
scanf("%d", &time_quantum); printf("\nProcess\tBurst\tTurnaround\tWaiting\n");

for (int i = 0; x != 0;) {
    if (remaining[i] > 0) {
        if (remaining[i] <= time_quantum) {
            total += remaining[i];
            remaining[i] = 0;
            x--;
            printf("P%d\t%d\t%d\t%d\n", i + 1, burst[i], total - arrival[i], total - arrival[i] - burst[i]);
            wait_time += total - arrival[i] - burst[i];
            turnaround_time += total - arrival[i];
        } else {
            remaining[i] -= time_quantum;
            total += time_quantum;
        }
    }
}

i = (i + 1) % n;
}

printf("\nAverage Waiting Time: %.2f", (float)wait_time / n);
printf("\nAverage Turnaround Time: %.2f\n", (float)turnaround_time / n);

free(arrival);
free(burst);
free(remaining);

return 0;
}

```

OUTPUT:

```

karthick.S@KarthickH2 MINGW64 ~
$ cd "/c:/Users/karthick.S/OneDrive/Documents/Os"
karthick.S@KarthickH2 MINGW64 ~/OneDrive/Documents/Os
$ ./Ex-6d.exe
Enter number of processes: 3
Enter arrival time and burst time for process 1: 0 4
Enter arrival time and burst time for process 2: 1 3
Enter arrival time and burst time for process 3: 2 5
Enter time quantum: 2

Process Burst   Turnaround   Waiting
P1      4           8            4
P2      3           8            5
P3      5          10            5

Average Waiting Time: 4.67
Average Turnaround Time: 8.67
karthick.S@KarthickH2 MINGW64 ~/OneDrive/Documents/Os
$

```

RESULT:

2116231801033

CS23431

The Program of Round Robin Scheduling is successfully implemented.

Ex. No: 7

Date: 27/2/25

IPC USING SHARED MEMORY

AIM:

To write a C program to do Inter-Process Communication (IPC) using shared memory between the sender process and the receiver process.

ALGORITHM:

sender

1. Set the size of the shared memory segment
2. Allocate the shared memory segment using shmget
3. Attach the shared memory segment using shmat
4. Write a string to the shared memory segment using sprintf
5. Set delay using sleep
6. Detach shared memory segment using shmdt

receiver

1. Set the size of the shared memory segment
2. Allocate the shared memory segment using shmget
3. Attach the shared memory segment using shmat
4. Print the shared memory contents sent by the sender process.
5. Detach shared memory segment using shmdt

PROGRAM:

SENDER

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <sys/ipc.h>
#include <sys/shm.h>
#include <unistd.h>

#define SHMSIZE 1024

typedef struct {
    int ready;
    char message[SHMSIZE];
} SharedMemory;
```

```

int main() {
    key_t key = ftok("sender.c", 65);
    int shmid;
    SharedMemory *shm;

    shmid = shmget(key, sizeof(SharedMemory), 0666 | IPC_CREAT);
    if (shmid == -1) {
        perror("shmget failed");
        exit(1);
    }

    shm = (SharedMemory *)shmat(shmid, NULL, 0);
    if (shm == (SharedMemory *)-1) {
        perror("shmat failed");
        exit(1);
    }

    printf("Sender: Enter a message to send to receiver: ");
    fgets(shm->message, SHMSIZE, stdin);

    shm->message[strcspn(shm->message, "\n")] = '\0';

    shm->ready = 1;

    sleep(5);

    if (shmdt(shm) == -1) {
        perror("shmdt failed");
        exit(1);
    }

    return 0;
}

```

RECEIVER

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <sys/ipc.h>
#include <sys/shm.h>
#include <unistd.h>

#define SHMSIZE 1024

typedef struct {
    int ready;
    char message[SHMSIZE];
} SharedMemory;

```



```

int main() {
    key_t key = ftok("sender.c", 65);
    int shmid;
    SharedMemory *shm;

    shmid = shmget(key, sizeof(SharedMemory), 0666 | IPC_CREAT);
    if (shmid == -1) {
        perror("shmget failed");
        exit(1);
    }

    shm = (SharedMemory *)shmat(shmid, NULL, 0);
    if (shm == (SharedMemory *)-1) {
        perror("shmat failed");
        exit(1);
    }

    while (shm->ready == 0) {
        sleep(1);
    }

    printf("Receiver: Message received from sender: %s\n", shm->message);

    if (shmdt(shm) == -1) {
        perror("shmdt failed");
        exit(1);
    }

    if (shmctl(shmid, IPC_RMID, NULL) == -1) {
        perror("shmctl failed");
        exit(1);
    }

    return 0;
}

```

OUTPUT:

The screenshot shows two terminal windows in Visual Studio Code. The left window, titled 'karthih2@karthickh2:/mnt/c/Users/karthick.S/OneDrive/Documents/231801079-4/Os\$', shows the execution of the sender program. It prompts the user to enter a message, and the user enters 'Hi hellooo!...'. The right window, titled 'karthih2@karthickh2:/mnt/c/Users/karthick.S/OneDrive/Documents/231801079-4/Os\$', shows the execution of the receiver program. It displays the message received from the sender: 'Hi hellooo!...'. The interface includes a menu bar (File, Edit, Selection, View, Go, Run, Terminal, Help) and a toolbar with icons for file operations and terminal management.

RESULT:

The IPC Program with Shared Memory is Successfully Implemented.

2116231801033

CS23431

Ex. No: 8

Date: 08/3/25

PRODUCER CONSUMER USING SEMAPHORES

AIM:

To write a program to implement solutions to producer consumer problem using semaphores.

ALGORITHM:

1. Initialize semaphore empty, full and mutex.
2. Create two threads- the producer thread and the consumer thread.
3. Wait for target thread termination.
4. Call sem_wait on empty semaphore followed by mutex semaphore before entry into critical section.
5. Produce/Consume the item in the critical section.
6. Call sem_post on mutex semaphore followed by full semaphore
7. before exiting the critical section.
8. Allow the other thread to enter its critical section.
9. Terminate after looping ten times in producer and consumer Threads each.

PROGRAM:

```
#include <stdio.h>
#include <stdlib.h>
#include <pthread.h>

int mutex = 1;
int full = 0;
int empty = 10, x = 0;

pthread_mutex_t lock;

void *producer(void *arg)
{
    pthread_mutex_lock(&lock);

    if (empty != 0) {
        --mutex;
        ++full;
        --empty;
        x++;
        printf("\nProducer produces item %d\n", x);
        ++mutex;
    } else {
        printf("Buffer is full!\n");
    }

    pthread_mutex_unlock(&lock);
}
```

2116231801033

CS23431

```

    return NULL;
}

void *consumer(void *arg)
{
    pthread_mutex_lock(&lock);

    if (full != 0) {
        --mutex;
        --full;
        ++empty;
        printf("\nConsumer consumes item %d\n", x);
        x--;
        ++mutex;
    } else {
        printf("Buffer is empty!\n");
    }

    pthread_mutex_unlock(&lock);
    return NULL;
}

int main()
{
    int n, i;
    pthread_t prod_thread, cons_thread;

    pthread_mutex_init(&lock, NULL);

    printf("\n1. Press 1 for Producer"
           "\n2. Press 2 for Consumer"
           "\n3. Press 3 for Exit\n");

    for (i = 1; i > 0; i++) {
        printf("\nEnter your choice: ");
        scanf("%d", &n);

        switch (n) {
            case 1:
                if (mutex == 1 && empty != 0) {
                    pthread_create(&prod_thread, NULL, producer, NULL);
                    pthread_join(prod_thread, NULL);
                } else {
                    printf("Buffer is full!\n");
                }
                break;

            case 2:
                if (mutex == 1 && full != 0) {
                    pthread_create(&cons_thread, NULL, consumer, NULL);
                    pthread_join(cons_thread, NULL);
                } else {

```

```

        printf("Buffer is empty!\n");
    }
    break;

case 3:
    pthread_mutex_destroy(&lock);
    exit(0);
    break;
default:
    printf("Invalid choice! Please enter a valid option.\n");
}
}

return 0;
}

```

OUTPUT:

```

input
1. Press 1 for Producer
2. Press 2 for Consumer
3. Press 3 for Exit
Enter your choice: 1
Producer produces item 1
Enter your choice: 2
Consumer consumes item 1
Enter your choice: 2
Buffer is empty!
Enter your choice: 1
Producer produces item 1
Enter your choice: 1
Producer produces item 2
Enter your choice: 1
Producer produces item 3
Enter your choice: 1
Producer produces item 4
Enter your choice: 1
Buffer is full!
Enter your choice:

```

RESULT:

The Producer Consumer Program using Semaphore is Successfully Implemented.

Ex. No.: 9

Date: 27/3/25

DEADLOCK AVOIDANCE

AIM:

To find out a safe sequence using Banker's algorithm for deadlock avoidance.

ALGORITHM:

1. Initialize work=available and finish[i]=false for all values of i
2. Find an i such that both:
finish[i]=false and Needi<= work
3. If no such i exists go to step 6
4. Compute work=work+allocationi
5. Assign finish[i] to true and go to step 2
6. If finish[i]==true for all i, then print safe sequence
7. Else print there is no safe sequence.

PROGRAM:

```
#include <stdio.h>
#include <stdbool.h>

#define MAX 10

void findSafeSequence(int n, int m, int available[], int max[][MAX], int allocation[][MAX]) {
    int work[MAX], finish[MAX] = {0}, safeSeq[MAX], need[MAX][MAX];
    for (int i = 0; i < m; i++) work[i] = available[i];
    for (int i = 0; i < n; i++)
        for (int j = 0; j < m; j++)
            need[i][j] = max[i][j] - allocation[i][j];

    int count = 0;
    while (count < n) {
        bool found = false;
        for (int i = 0; i < n; i++) {
            if (!finish[i]) {
                bool canAllocate = true;
                for (int j = 0; j < m; j++)
                    if (need[i][j] > work[j]) { canAllocate = false; break; }
                if (canAllocate) {
                    for (int j = 0; j < m; j++) work[j] += allocation[i][j];
                    safeSeq[count++] = i;
                    finish[i] = 1;
                    found = true;
                }
            }
        }
    }
}
```

```

    }
    if (!found) { printf("No safe sequence.\n"); return; }
}
printf("Safe sequence: ");
for (int i = 0; i < n; i++) printf("P%d ", safeSeq[i]);
printf("\n");
}

int main() {
    int n, m, available[MAX], max[MAX][MAX], allocation[MAX][MAX];

    printf("Enter processes and resources: ");
    scanf("%d %d", &n, &m);
    while (getchar() != '\n');

    printf("Enter available resources: ");
    for (int i = 0; i < m; i++) scanf("%d", &available[i]);
    while (getchar() != '\n');

    printf("Enter Max matrix: \n");
    for (int i = 0; i < n; i++)
        for (int j = 0; j < m; j++) scanf("%d", &max[i][j]);
    while (getchar() != '\n');

    printf("Enter Allocation matrix: \n");
    for (int i = 0; i < n; i++)
        for (int j = 0; j < m; j++) scanf("%d", &allocation[i][j]);
    while (getchar() != '\n');

    findSafeSequence(n, m, available, max, allocation);
    return 0;
}

```

OUTPUT:

```

karthick.S@karthick02 MINGW64 ~/OneDrive/Documents/231801079-4/0s
$ gcc Ex-9.c -o Ex-9_new
karthick.S@karthick02 MINGW64 ~/OneDrive/Documents/231801079-4/0s
$ ./Ex-9
Enter processes and resources: 5 3
Enter available resources: 3 3 2
Enter Max matrix: 7 5 3
3 2 2
9 0 2
2 2 2
4 3 3
Enter Allocation matrix: 0 1 0
2 0 0
3 0 2
2 1 1
0 0 2
Safe sequence: P1 P3 P4 P0 P2
karthick.S@karthick02 MINGW64 ~/OneDrive/Documents/231801079-4/0s
$

```

RESULT:

2116231801033

CS23431

The Safe Sequence is found using Banker's Algorithm for Deadlock Avoidance.

Ex. No: 10a

Date: 29/3/25

BEST FIT

AIM:

To implement Best Fit memory allocation technique using Python.

ALGORITHM:

1. Input memory blocks and processes with sizes
2. Initialize all memory blocks as free.
3. Start by picking each process and find the minimum block size that can be assigned to current process
4. If found then assign it to the current process.
5. If not found then leave that process and keep checking the further processes.

PROGRAM:

```
def best_fit(blocks, processes):
    allocation = [-1] * len(processes)

    for i in range(len(processes)):
        best_index = -1

        for j in range(len(blocks)):
            if blocks[j] >= processes[i]:
                if best_index == -1 or blocks[j] < blocks[best_index]:
                    best_index = j

        if best_index != -1:
            allocation[i] = best_index
            blocks[best_index] -= processes[i]


    print("\nProcess No.\tProcess Size\tBlock No.")
    for i in range(len(processes)):
        print(f"{i + 1}\t\t{processes[i]}\t\t{allocation[i] + 1 if allocation[i] != -1 else 'Not Allocated'}")

if __name__ == "__main__":
    num_blocks = int(input("Enter number of memory blocks: "))
    blocks = list(map(int, input(f"Enter sizes of {num_blocks} memory blocks (space-separated): ").split()))

    num_processes = int(input("\nEnter number of processes: "))
    processes = list(map(int, input(f"Enter sizes of {num_processes} processes (space-separated): ").split()))

    best_fit(blocks, processes)
```

OUTPUT:



```
karthick.S@KarthickH2 MINGW64 ~/OneDrive/Documents/231801079-4/Os
$ python Ex-10a.py
Enter number of memory blocks: 5
Enter sizes of 5 memory blocks (space-separated): 100 500 200 300 600

Enter number of processes: 4
Enter sizes of 4 processes (space-separated): 212 417 112 426

Process No.    Process Size    Block No.
1              212            4
2              417            2
3              112            3
4              426            5

karthick.S@KarthickH2 MINGW64 ~/OneDrive/Documents/231801079-4/Os
$
```

RESULT:

2116231801033

CS23431

Thus, the Best Fit Memory allocation technique is implemented successfully using Python.

Ex. No: 10b

Date: 29/3/25

FIRST FIT

AIM:

To write a C program for the implementation of memory allocation methods for a fixed partition using the first fit.

ALGORITHM:

1. Define the max as 25.
2. Declare the variable frag[max],b[max],f[max],i,j, nb,nf, temp, highest=0, bf[max],ff[max].
3. Get the number of blocks, files, size of the blocks using a for loop.
4. In for loop check bf[j]!=1, if so temp=b[j]-f[i]
5. Check the highest.

PROGRAM:

```
#include <stdio.h>
#define MAX 25

int main() {
    int frag[MAX], b[MAX], f[MAX], i, j, nb, nf, temp;
    static int bf[MAX], ff[MAX];

    printf("Enter the number of blocks: ");
    scanf("%d", &nb);

    printf("Enter the number of files: ");
    scanf("%d", &nf);

    printf("Enter the size of the blocks:\n");
    for (i = 0; i < nb; i++) {
        printf("Block %d: ", i + 1);
        scanf("%d", &b[i]);
    }

    printf("Enter the size of the files:\n");
    for (i = 0; i < nf; i++) {
        printf("File %d: ", i + 1);
        scanf("%d", &f[i]);
    }

    for (i = 0; i < nf; i++) {
        for (j = 0; j < nb; j++) {
```

```

        if (bf[j] != 1) {
            temp = b[j] - f[i];
            if (temp >= 0) {
                ff[i] = j;
                bf[j] = 1;
                frag[i] = temp;
                break;
            }
        }
    }
}

printf("\nFile No.\tFile Size\tBlock No.\tBlock Size\tFragment\n");
for (i = 0; i < nf; i++) {
    if (bf[ff[i]] == 1)
        printf("%d\t%d\t%d\t%d\t%d\n", i + 1, f[i], ff[i] + 1, b[ff[i]], frag[i]);
    else
        printf("%d\t%d\t\t\t\t\tNot Allocated\n", i + 1, f[i]);
}

return 0;
}

```

OUTPUT:

```

karthick.SaKarthickH2 MINGW64 ~/OneDrive/Documents/231801079-4/Os
$ gcc Ex-10b.c -o Ex-10b

karthick.SaKarthickH2 MINGW64 ~/OneDrive/Documents/231801079-4/Os
$ ./Ex-10b
Enter the number of blocks: 5
Enter the number of files: 4
Enter the size of the blocks:
Block 1: 100
Block 2: 500
Block 3: 200
Block 4: 300
Block 5: 600
Enter the size of the files:
File 1: 212
File 2: 417
File 3: 112
File 4: 426

File No.    File Size    Block No.    Block Size    Fragment
1           212          2            500           288
2           417          5            600           183
3           112          3            200           88
4           426          Not Allocated

```

RESULT:

Thus, the First Fit allocation technique is implemented successfully using C.

Ex. No: 11a

Date: 3/4/25

FIFO PAGE REPLACEMENT**AIM:**

To find out the number of page faults that occur using the First-in First-out (FIFO) page replacement technique.

ALGORITHM:

1. Declare the size with respect to page length
2. Check the need for replacement from the page to memory
3. Check the need for replacement from the old page to the new page in memory
4. Form a queue to hold all pages
5. Insert the page required memory into the queue
6. Check for bad replacement and page fault
7. Get the number of processes to be inserted
8. Display the values.

PROGRAM:

```
def fifo_page_replacement(pages, frame_size):
    frames = []
    page_faults = 0
    front = 0

    print("\nPage Replacement Process:")

    for page in pages:
        if page not in frames:
            if len(frames) < frame_size:
                frames.append(page)
            else:
                frames[front] = page
                front = (front + 1) % frame_size
            page_faults += 1
            print(f"Page {page} => {frames} *Page Fault*")
        else:
            print(f"Page {page} => {frames}")


    print(f"\nTotal Page Faults = {page_faults}")

if __name__ == "__main__":
    n = int(input("Enter the number of pages: "))
    pages = []
```

```
print("Enter the page numbers one by one:")
for i in range(n):
    page = int(input(f"Page {i+1}: "))
    pages.append(page)
frame_size = int(input("Enter the number of frames: "))

fifo_page_replacement(pages, frame_size)
```

OUTPUT:



The screenshot shows a terminal window with the following output:

```
karthick.S&karthickH2 MINGW64 ~/OneDrive/Documents/231801079-4/Os
$ python Ex-11a.py
Enter the number of pages: 5
Enter the page numbers one by one:
Page 1: 1
Page 2: 2
Page 3: 3
Page 4: 4
Page 5: 5
Enter the number of frames: 3

Page Replacement Process:
Page 1 => [1] *Page Fault*
Page 2 => [1, 2] *Page Fault*
Page 3 => [1, 2, 3] *Page Fault*
Page 4 => [4, 2, 3] *Page Fault*
Page 5 => [4, 5, 3] *Page Fault*

Total Page Faults = 5
```

RESULT:

2116231801033

CS23431

The Fifo Page Replacement is Successfully Implemented using Python.

Ex. No: 11b

Date: 5/4/25

LRU

AIM:

To write a C program to implement LRU page replacement algorithm.

ALGORITHM:

1. Start the process
2. Declare the size
3. Get the number of pages to be inserted
4. Get the value
5. Declare counter and stack
6. Select the least recently used page by counter value
7. Stack them according the selection.
8. Display the values
9. Stop the process

PROGRAM:

```
#include <stdio.h>

int main() {
    int pages[50], frames[10], counter[10];
    int n, frameSize, i, j, k, flag, least, time = 0, faults = 0;
    printf("Enter the number of frames: ");
    scanf("%d", &frameSize);

    printf("Enter the number of pages: ");
    scanf("%d", &n);

    printf("Enter the page reference string: ");
    for(i = 0; i < n; i++) {
        scanf("%d", &pages[i]);
    }

    for(i = 0; i < frameSize; i++) {
        frames[i] = -1;
        counter[i] = 0;
    }

    for(i = 0; i < n; i++) {
        flag = 0;

        for(j = 0; j < frameSize; j++) {
            if(frames[j] == pages[i]) {
                counter[j] = ++time;
                flag = 1;
            }
        }
    }
}
```

```

        break;
    }
}

if(flag == 0) {
    int pos = -1, min = 9999;


    for(j = 0; j < frameSize; j++) {
        if(frames[j] == -1) {
            pos = j;
            break;
        } else if(counter[j] < min) {
            min = counter[j];
            pos = j;
        }
    }

    frames[pos] = pages[i];
    counter[pos] = ++time;
    faults++;
}
printf("Frames after inserting %d: ", pages[i]);
for(k = 0; k < frameSize; k++) {
    if(frames[k] != -1)
        printf("%d ", frames[k]);
    else
        printf("- ");
}
printf("\n");
}

printf("\nTotal Page Faults: %d\n", faults);
return 0;
}

```

OUTPUT:



```

karthick.SaKarthickH2 MINGW64 ~/OneDrive/Documents/231801079-4/Os
$ ./Ex-11b
Enter the number of frames: 3
Enter the number of pages: 7
Enter the page reference string: 1 2 3 2 4 1 5
Frames after inserting 1: 1 -
Frames after inserting 2: 1 2 -
Frames after inserting 3: 1 2 3
Frames after inserting 2: 1 2 3
Frames after inserting 4: 4 2 3
Frames after inserting 1: 4 2 1
Frames after inserting 5: 4 5 1

Total Page Faults: 6

```


RESULT:

The LRU Program is Successfully Implemented using C.

Ex. No: 11c

Date: 5/4/25

Optimal

AIM:

To write a c program to implement the Optimal page replacement algorithm

ALGORITHM:

1. Start the process
2. Declare the size
3. Get the number of pages to be inserted
4. Get the value
5. Declare counter and stack
6. Select the least frequently used page by counter value.
7. Stack them according the selection.
8. Display the values
9. Stop the process

PROGRAM:

```
#include <stdio.h>
#include <stdlib.h>

int isInFrame(int frame[], int count, int page) {
    for (int i = 0; i < count; i++)
        if (frame[i] == page) return 1;
    return 0;
}

int predict(int pages[], int frame[], int n, int index, int count) {
    int farthest = index, res = -1;
    for (int i = 0; i < count; i++) {
        int j;
        for (j = index; j < n; j++) {
            if (frame[i] == pages[j]) {
                if (j > farthest) {
                    farthest = j;
                    res = i;
                }
                break;
            }
        }
        if (j == n) return i; // If page not found in future
    }
    return (res == -1) ? 0 : res;
}

int main() {
    int n, frameCount, pageFaults = 0, filled = 0;
```

```

printf("Enter number of pages: ");
scanf("%d", &n);
int* pages = malloc(n * sizeof(int));

printf("Enter the page numbers:\n");
for (int i = 0; i < n; i++)
    scanf("%d", &pages[i]);

printf("Enter number of frames: ");
scanf("%d", &frameCount);
int* frame = malloc(frameCount * sizeof(int));
for (int i = 0; i < frameCount; i++)
    frame[i] = -1;


for (int i = 0; i < n; i++) {
    if (!isInFrame(frame, frameCount, pages[i])) {
        if (filled < frameCount)
            frame[filled++] = pages[i];
        else
            frame[predict(pages, frame, n, i, frameCount)] = pages[i];
        pageFaults++;
    }

    printf("Frame: ");
    for (int j = 0; j < frameCount; j++)
        frame[j] == -1 ? printf("- ") : printf("%d ", frame[j]);
    printf("\n");
}

printf("\nTotal Page Faults = %d\n", pageFaults);
free(pages);
free(frame);
return 0;

```

OUTPUT:



```

karthick.S@karthickH2 MINGW64 ~/OneDrive/Documents/231801079-4/Os
$ gcc Ex-11c.c -o Ex-11c

karthick.S@karthickH2 MINGW64 ~/OneDrive/Documents/231801079-4/Os
$ ./Ex-11c
Enter number of pages: 7
Enter the page numbers:
1 2 3 2 4 1 5
Enter number of frames: 3
Frame: 1 - -
Frame: 1 2 -
Frame: 1 2 3
Frame: 1 2 3
Frame: 1 4 3
Frame: 1 4 3
Frame: 5 4 3

Total Page Faults = 5

```

RESULT:

The Optimal page replacement Program is Successfully Implemented using C.

Ex. No: 12

Date: 5/4/25

File Organization Technique- Single- and Two-level directory

AIM:

To implement File Organization Structures in C are

- a. Single Level Directory
- b. Two-Level Directory
- c. Hierarchical Directory Structure
- d. Directed Acyclic Graph Structure

A. SINGLE LEVEL DIRECTORY

ALGORITHM:

1. Start
2. Declare the number, names and size of the directories and file names. 3. Get the values for the declared variables.
4. Display the files that are available in the directories.
5. Stop.

PROGRAM:

```
#include <stdio.h>
#include <string.h>

struct File {
    char name[20];
};

int main() {
    int n, i;
    struct File files[10];

    printf("Enter the number of files: ");
    scanf("%d", &n);

    if (n <= 0 || n > 10) {
        printf("Please enter a valid number of files (1-10).\n");
        return 1;
    }

    for (i = 0; i < n; i++) {
        printf("Enter the file %d: ", i + 1);
        scanf("%s", files[i].name);
    }
```

```

printf("\n\nRoot Directory\n");
printf("\n");

for (i = 0; i < n; i++) {
    printf("|-- %s\n", files[i].name);
}

return 0;
}

```

OUTPUT:

```

File Edit Selection View ... ← → Os
PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS
karthick.S@KarthickH2 MINGW64 ~/OneDrive/Documents/231801079-4/0s
$ gcc Ex-12a.c -o Ex-12a
karthick.S@KarthickH2 MINGW64 ~/OneDrive/Documents/231801079-4/0s
$ ./Ex-12a
Enter the number of files: 4
Enter the file 1: A
Enter the file 2: B
Enter the file 3: Game
Enter the file 4: File123

Root Directory
|-- A
|-- B
|-- Game
|-- File123

```

B. TWO-LEVEL DIRECTORY STRUCTURE

ALGORITHM:

1. Start
2. Declare the number, names and size of the directories and subdirectories and file names.
3. Get the values for the declared variables.
4. Display the files that are available in the directories and subdirectories. 5. Stop.

PROGRAM:

```

#include <stdio.h>
#include <string.h>

struct File {
    char name[20];
};

struct SubDirectory {
    char name[20];
    struct File files[10];
    int fileCount;
};

```

```

struct Directory {
    char name[20];
    struct SubDirectory subDirs[10];
    int subDirCount;
};

int main() {
    struct Directory dir;
    int i, j;

    printf("Enter root directory name: ");
    scanf("%s", dir.name);

    printf("How many subdirectories in '%s'? ", dir.name);
    scanf("%d", &dir.subDirCount);

    for (i = 0; i < dir.subDirCount; i++) {
        printf("\nEnter name of subdirectory %d under '%s': ", i + 1, dir.name);
        scanf("%s", dir.subDirs[i].name);

        printf("How many files in '%s'? ", dir.subDirs[i].name);
        scanf("%d", &dir.subDirs[i].fileCount);

        for (j = 0; j < dir.subDirs[i].fileCount; j++) {
            printf("Enter file %d in '%s': ", j + 1, dir.subDirs[i].name);
            scanf("%s", dir.subDirs[i].files[j].name);
        }
    }

    printf("\nDirectory Structure:\n");
    printf("NULL\n");
    printf("|__ %s\n", dir.name);

    for (i = 0; i < dir.subDirCount; i++) {
        printf("    |__ %s\n", dir.subDirs[i].name);
        for (j = 0; j < dir.subDirs[i].fileCount; j++) {
            printf("        |__ %s\n", dir.subDirs[i].files[j].name);
        }
    }


    return 0;
}

```

OUTPUT:

2116231801033

CS23431



```
File Edit Selection View ... ← → Os
PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS
karthick.S@KarthickH2 MINGW64 ~/OneDrive/Documents/231801079-4/0s
$ gcc Ex-12b.c -o Ex-12b
karthick.S@KarthickH2 MINGW64 ~/OneDrive/Documents/231801079-4/0s
$ ./Ex-12b
Enter root directory name: Course
How many subdirectories in 'Course'? 1
Enter name of subdirectory 1 under 'Course': Notes
How many files in 'Notes'? 2
Enter file 1 in 'Notes': week1.pdf
Enter file 2 in 'Notes': week2.pdf
Directory Structure:
NULL
|__ Course
|   |__ Notes
|       |__ week1.pdf
|       |__ week2.pdf
```

RESULT:

The File Organization Technique-Single and Two-Level Directory Program is Successfully Implemented using C.